

**Hawa - Sliding Door Fitting, Junior 80/B-Pocket, set**

for 1-leaf wooden sliding doors, for door weight up to 80 kg (176 lbs.), without running track

Item no. 940.80.014

\$ 881.44

Per Set (Set) Suggested Retail Price

Item details

Min installation height

Number of doors per system max. 1

Number of doors 1

For door material wood

Model 80 B Pocket

Soft closing mechanism without soft and self closing mechanism, with track buffer on one side, with wall buffer on one side

For door weight ≤ 80 kgFor door width $\leq 1,250$ mm

Controller installation options Ceiling installation, Integrated ceiling installation, Wall pocket solution

For door thickness 35 – 80 mm

Adjustment facility Height adjustment ± 3 mm, Door height adjustable +3 mm, with integrated anti-twist protection horizontal adjusting distance in lengthways direction in bayonet mount ± 8 mm

For door thickness max. 1 3/16"

Door weight max. 176 lbs

Door width max.	27 9/16 - 59 1/16"
Load bearing capacity	176 lbs.
Max. door weight	176 lb
Area of application	For 1-leaf sliding doors for wall pocket installation
Suitable for	Wall pocket solution
For door height	≤4,000 mm
Running position	Top
Functionality	Subsequent disassembly of the running track without opening the wall is possible, the running gear and the soft and self closing mechanism can be removed, stopper position can be readjusted in wall pocket
Installation	Suspension with recessed support profile and integrated suspension carriage
Installation reference	Subsequent disassembly of the running track is possible without opening the wall Running gear and soft and self closing mechanism can be removed Stopper position in the wall pocket is readjustable
Door processing	With recess
Standard	Certified in compliance with EN 1527:2013



Additional information

Hawa-SoftMove 80 soft and self closing mechanism

Spring buffer for comfortable ejection of the door (optional)

The Hawa-SoftMove 80 soft and self closing mechanism cannot be used in combination with the spring buffer

Additional information

Subsequent disassembly of the running track without opening the wall is possible, the running gear and the soft and self closing mechanism can be removed, stopper position can be readjusted in wall pocket

Line drawings





