
Load Center, ReliaHome PCC1612

Catalog No.	PCC1612
Enclosure	NEMA 1 Indoor, Combination
Bus / main	125A copper bus, convertible main, 120/240, 1-ph 3-W, 22 kAIC
Spaces / circuits	16 / 32
Cover	Surface / flush
Ground kit	TGK12, TNLK20
Dimensions	20.38 x 15.36 x 3.79 in
Modifications	80A 2-pole main THHQL2180 + ReliaHome breaker base kit TQMH000F

Substitution / Deviation - engineer confirmation required

Sized to the 1'-4" x 1'-9" panel opening on drawing JN-GP1R-A11-07A, Section 01. 125A is the largest bus ABB offers in an enclosure fitting that opening (a 150A bus is 26 in high); capacity 32 circuits. The 80A 2-pole main is supplied as a base kit (TQMH000F) plus breaker (THHQL2180). Requires engineer confirmation.



Representative Image

Catalog No. PCC1612
Description: LD CTR CONV 125A 16/32 CU N1 GR PON UL
UPC No 783164692556
Home > Load Center & Meter Combos > Load Centers

ABB ReliaHome makes homes reliable, with ease. We designed our ReliaHome load centers to be installed as fast as possible – and reliable so your customers can leave a job with confidence. They work seamlessly with all our residential circuit breakers, optimizing your stock.

Descriptors

Category	Load Centers
GO Schedule	RV
Grouping	Single Phase - USA

Specifications

# Branch Circuit 250A	16
1" Space	16
1/2" Space	0
Amperage	125 A
Circuit Breaker Style	Plug-On Neutral
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	YES
Feed	Either
Input/Output Voltage	120/240V ac
Interrupt Rating	22kAIC
Interrupting Capacity Rating	22kAIC
Load Center Type	P-Series+ (PON)
Meter Socket Options: 200 Amp Main Breaker Installed	No
Meter Socket Options: High Amp Mode	None
NEMA Rating	NEMA 1
No of Circuits	32
Phase	1 Phase
Service & Voltage	1 Phase, 3 Wire, 120/240V ac
Wires	3 Wire

Classifications

UL/CUL Listing	UL
----------------	----

by ABB



Representative Image

Catalog No. THHQL2180
Description: THHQL 2P 120/240V 22K IC 80 AMP

UPC No 783164092059

Home > Circuit Breakers > Residential Circuit Breakers > Q Line

Q line circuit breakers are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications. The QL breakers are plug-in versions of the Q Line used for connection to load centers and lighting panels. All Q Line circuit breakers feature Quick-make / Quick-break mechanisms, common trip bars, and easy to spot trip indication to ensure safety and reliability. Q Line breakers are available in 1, 2, and 3 pole versions, can be ordered with auxiliary contact and shunt trip accessories, and can be ordered for use in HID applications. 2180 Amps 80 A

Descriptors

Category	Q Line
Product Line	Q-Line (Plug-In)
GO Schedule	R5


Specifications

Interrupting Capacity Rating	22 kAIC
Voltage	120/240 V
Trip Style	Non-Interchangeable
Frame Type	Q-Line
Amperage	80 A
System Voltage	120 Vac 120/240 Vac
Poles	2
Trip Function	LI
Continuous Current Rated	Standard
120 Vac Interrupting Rating	22 KAIC
120/240 Vac Interrupting Rating	22 KAIC
Suitable for Reverse Feed	Yes
Long Time	Fixed
Instantaneous	Fixed
Protective Relays	No
Current Metering	No
Special Markings	HACR
GSA Compliance	No

Classifications

UL File #	E11592
-----------	--------

by ABB



PRODUCT-DETAILS

TQMH000F**MAIN BKR BASE ONLY KIT 125A MAX****General Information**

Global Commercial Alias:	TQMH000F
Extended Product Type:	TQMH000F
Product ID:	1TQQ12000X0301
Catalog Description:	MAIN BKR BASE ONLY KIT 125A MAX
Long Description:	Q-line plug-in circuit interrupters are one-inch wide per pole, compact, thermal-magnetic devices designed for residential and commercial applications in ReliaHome™ load centers. These breakers feature quick-make / quick-break mechanisms and easy to spot trip indication to ensure safety and reliability. Thermal magnetic circuit interrupters provide protection against overloads and short circuits.
Display Name:	TQMH000F

Material Compliance

RoHS Information:	No declaration needed
REACH Information:	No declaration needed
Conflict Minerals Reporting Template (CMRT):	9AKK108468A3363
WEEE Category:	Product Not in WEEE Scope

Certificates and Declarations

Declaration of Conformity - CE:	No declaration needed
---------------------------------	-----------------------

Installation

Instructions and Manuals:	No document needed
---------------------------	--------------------

Popular Downloads

Data Sheet, Technical Information:	No document needed
------------------------------------	--------------------

External Classifications and Standards

ETIM 9:	EC000228 - Power circuit-breaker for trafo/generator/installation protection
ETIM 10:	EC000228 - Power circuit-breaker for trafo/generator/installation protection

Categories

Products > Low Voltage Products and Systems > NEMA Residential and Commercial Portfolio > Residential Breakers > MAIN CB