

Name: Toufic Hamadeh

68

The exam assumes 32-bit Linux machines. The exam has 5 pages. Make sure you have all the pages. Do not take any page(s) with you. Any missing page(s) will result in failure in the exam. This exam is closed book close notes. Do not exchange anything during the exam. No questions will be answered during the exam. If you are in doubt, briefly state your assumptions below, including typos if any. Questions 1 to 17 are worth 3 points each.

I have read and understood all of the instructions above. On my honor, I pledge that I have not violated the provisions of the NJIT Academic Honor Code.

Signature: Toufic Hamadeh

Date: 11/22/2013

27

1. The number of iterations using breadth-first search is typically smaller than that of depth-first search for the 15-Puzzle.
 (a) True (b) False (c) Cannot Determine
- C 2. The depth for a state-space search tree using depth-first search is typically smaller than that of breadth-first search for the 15-Puzzle.
 (a) True (b) False (c) Cannot Determine
3. The search strategy that picks using the smallest estimated remaining distance is called
 (a) depth-first (b) breadth-first (c) branch-bound (d) best-first (e) A*
4. The search strategy that combines the distance incurred and the estimated remaining distance is called
 (a) depth-first (b) breadth-first (c) branch-bound (d) best-first (e) A*
- A 5. What is the minimum number of 32-bit words to represent a 15-puzzle state? An example 15-Puzzle state is '1 2 3 4 | 5 6 7 8 | 9 10 11 12 | 13 14 15 0,' where '|' is a row delimiter.
 (a) 2 (b) 4 (c) 8 (d) 16 (e) None of the above

Assuming the 15-Puzzle is implemented using singly-linked lists with last node NULL terminated, answer questions 6-9.

6. Given m =number of nodes on successor, n =number of nodes on open, p =number of nodes on closed, the number of pointer assignment statements to merge a list of successor nodes with open for depth first search is:
 (a) $O(m)$ (b) $O(n)$ (c) $O(p)$ (d) $O(n)+O(m)$ (e) None of the above

7. Given m =number of nodes on successor, n =number of nodes on open, p =number of nodes on closed, what is the number of pointer assignment statements to merge a list of successor nodes with open for *breadth* first search?
 (a) $O(m)$ (b) $O(n)$ (c) $O(p)$ (d) $O(n)+O(m)$ (e) None of the above

8. Given m =number of nodes on successor, n =number of nodes on open, p =number of nodes on closed, what is the number of pointer assignment statements to merge a list of successor nodes with open for *best* first search, assuming the open list is kept in sorted order of heuristic value?
 (a) $O(m)$ (b) $O(n)$ (c) $O(p)$ (d) $O(n)+O(m)$ (e) None of the above

9. Given m =number of nodes on successor, n =number of nodes on open, p =number of nodes on closed, what is the number of pointer assignment statements to merge a list of successor nodes to open for A^* first search?
 (a) $O(m)$ (b) $O(n)$ (c) $O(p)$ (d) $O(n)+O(m)$ (e) None of the above

10. Name an open source program that converts an html file to xhtml.

~~tagsoop~~ firebug

11. What is the Python package that provides a function to convert xhtml file to DOM tree?

~~import re~~

~~tagsoop~~

XML

12. List DOM node type 1 to 4.

1 = element, 2 = attribute, 3 = text, 4 = cdata

13. List the DOM node types that contain text? List numbers.

1, 2, 3

14. What API is required for a Python program to execute mysql queries?

import MySQLdb

connect, cursor, execute

15. The name of the method that Python uses to connect to mysql server is:

conn = MySQLdb.connect(host=" ", user=" ", passwd=" ", db=" ")

16. The name of the method that Python uses to get access to mysql tables is:

x = conn.cursor()

17. The name of the method that Python uses to execute mysql queries is:

x.execute()

SQL command here

x.execute(""" INSERT INTO Table VALUES (%s) """, (100))

Problem 18 (Search - 25 points): In HW7, you wrote a C program that performs state-space search for the 15-Puzzle similar in principle to those used in game engines.

Write a filter function which returns a list of nodes that are not on the list pointed by hp. Assume nodes_same() exists, which compares two nodes and return 0 for false or 1 for true.

```
struct node {
    int loc[N+1][N];
    struct node *next;
} *start,*goal;
int flag;
struct node *initialize(),*expand(),*merge(),*filter();
```

```
void main(int argc,char **argv) {
    struct node *open,*closed,*succ,*copen;
    open=closed=succ=NULL;
    start=initialize(argc,argv);
    open=start;
    while (open) {
        copen=open;
        open=open->next;
        succ=expand(copen);
        succ=filter(open,succ);
        succ=filter(closed,succ);
        if (goal_found(succ,goal)) break;
        if (succ) open=merge(succ,open,flag);
        copen->next=closed;
        closed=copen;
    }
}
```

25

```
struct node *filter(struct node *hp,struct node *succ){
    struct node *tp
    tp = malloc(struct node *) malloc (sizeof (struct node *))
    while (hp != NULL) { tp=succ
        while (succ != NULL) {
            if (nodes_same(hp, succ) == 0) {
                tp = hp
                tp = tp->next
            }
            succ = succ->next
        }
        hp = hp->next
    }
    succ = tp
}
```


returns nodes not
~~present to hp~~
on list pointed
to by hp

nodes_same = 0
means the
nodes are
not the
same



```
return succ;
}
```


Problem 19 (Linked list - 24 points): Consider the most active page in DOM displayed by Firebug. Write a Python program to return a *list of lists* each of which contains six values: symbol, name, price, change, %change, and volume: (a) write a function, `get_text()`, to extract the text pointed by an element pointer, (b) write a wrapper function that uses `get_text()`.



■■■■

methods and properties

`elm.nodeType` -> returns an integer # 1=element, 2=attribute, 3=text, and 4=cdata

elm.data -> returns a string

elm.childNodes -> returns list

elm.attributes -> returns list

`elm.getElementsByTagName(tag)` -> returns list

`elm.getAttribute(atr)` -> returns a string


`elm.hasAttributes()` -> returns true (value) or false (None)

666666

(a) Write a recursive Python function `get_text(elm)` to extract all the text of a dom tree pointed by `elm`.

12

```
lst = []
if e.nodeType in (3,4):
    if (e.data != "/n"):
        lst.append(e.data)
else:
    lst2 = e.childNodes
    for x in lst2:
        lst = lst + get_text(x)
return lst
```



(b) Write a Python function to find a *list of lists* for the dom tree described in the previous page. Use `get_text(elm)` in part (a).

4

```
lst = []
l = get_text(elm)
or lst = []
for x in (len(l)):
    if x.nodeType in (3,4):
    lst = lst + x.childNodes
return lst
```

