Deephaven as an application framework: verified facts ledger

One source of truth for every claim in our docs, deck and code. Each entry says how we know it. **Verified** = observed by a test in this repo on Deephaven Community 42.6 (pip `deephaven-server`, native Windows, Java 17; earlier rungs also on the Docker image) or read in the installed 42.6 source. **Docs** = stated in Deephaven documentation, not tested here.

Scopes, applications and fields

#	Fact	Evidence
S1	`run_script` (Python client) and `runCode` (JS API) run in the worker's single global scope; a name defined by one call is visible to the next	Verified: `tests/probe_concepts.py`
S2	Application-mode scripts run in that same global scope (`globals() is __main__.__dict__` was True). An undeclared top-level table became a `scope` field. `global` is **not** needed in Community 42.6 Python (the docs still advise it)	Verified: `tests/probe_app.d/scoping.py`
S3	With the pip server, the launching script's `__main__` **is** the console scope: its own functions appear there, and a client's `run_script` could read **and modify** the host's module globals	Verified: `tests/probe_introspection.py`, `tests/embedded_thread_demo.py`
S4	Underscore-prefixed names are published as `scope` fields like any other; an underscore does not keep a table private	Verified: `tests/probe_concepts.py`
S5	A worker holds several applications: `scope` plus one per `*.app` file; a built-in app with no exports does not appear in the field list	Verified: `tests/probe_concepts.py`
S6	Two applications can each publish a field with the same name; each resolves to its own object	Verified: `tests/probe_concepts.py`
S7	Fields are any registered object type (tables, figures, deephaven.ui elements, partitioned/hierarchical tables, plugin objects)	Verified: field types listed by `ListFields`; plugin registration in server logs
S8	`ApplicationState` (`get_app_state()["name"] = obj`) publishes a field under the app's own id	Verified: `tests/probe_app.d/scoping.py`

Tickets and sharing

#	Fact	Evidence
T1	Ticket formats: scope `s/<name>`; application `a/<app id>/f/<field>`; export `e` + 4-byte number (5 bytes); shared `h` + random 16-byte id	Verified: `pydeephaven` 42.6 `ticket.py`; export ticket length measured
T2	An export lives until released or its session closes, and keeps its object alive meanwhile	Verified: `pydeephaven` source docstrings

#	Fact	Evidence
T3	`bind_table(name, table)` promotes a client export to a scope field that outlives the binding session	Verified: `tests/probe_concepts.py`
T4	A shared ticket dies when the **publishing** session closes; a copy another session fetched earlier also stops working	Verified: `tests/probe_concepts.py`
T5	URIs `dh+plain://host:port/scope/<name>` and `dh+plain://host:port/app/<id>/field/<name>` resolve via `deephaven.uri.resolve`; `local:///...` has no resolver. A resolved URI appears in the worker's graph as a Barrage source node, even when pointing at the same server	Verified: `tests/probe_concepts.py`, introspection report
T6	`pq://<PQ>/scope/<name>` and `remote_table` are Enterprise's cross-PQ forms; data is copied into the consumer	Docs

Runtime: clock, threads, contexts

#	Fact	Evidence
R1	The default update graph cycles every ~1 s (`target_cycle_ms` 1000); rows arriving between cycles are batched into the next one	Verified: rungs 1 and 4 (`examples/`), introspection report
R2	Rows pushed from Python waited up to ~1 s (650–1,000 ms) before a cycle picked them up	Verified: rung 4
R3	`merged_listen` delivers one callback per cycle across all watched tables, with `None` for tables that did not change; a table read inside the callback is consistent with that step	Verified: rung 4
R4	An exception in a listener stops it permanently while feeds keep flowing	Verified: rung 4
R5	Re-running setup code stacks listeners unless the old handle is stopped; background tasks that read lifecycle state from globals leak until the worker restarts	Verified: rungs 3 and 4
R6	Execution contexts are **per thread**. The thread that started the server holds the systemic context; on another thread, `get_exec_ctx()` returns a static-only context and creating a ticking table fails (`UpdateGraphConflictException`). Capture the context on the server's thread (or inside `run_script`) and pass it in	Verified: `tests/embedded_thread_demo.py`
R7	Server executors `serial` and `concurrent` exist; `submit_task("concurrent", fn)` ran Python work on a JVM thread	Verified: `tests/probe_runtime_features.py`
R8	A second, **event-driven** update graph can be built from Python. Tables built under a context bound to it (`withUpdateGraph`, `table_publisher(update_graph=...)`) do not move on their own: three pushes stayed invisible for 1.5 s, then one `requestRefresh()` delivered them as one checkpoint (`A: 600` = 100+200+300)	Verified: `tests/probe_event_driven_clock.py`

#	Fact	Evidence
R9	The embedded server can be started on a **non-main thread**; the host's asyncio loop kept running during startup but at about half speed (89 ticks of a 50 ms sleep in 9.4 s)	Verified: `tests/embedded_thread_demo.py`
R10	In-process (embedded) use works without a client: tables built from the host, a listener bridged into asyncio via `call_soon_threadsafe`	Verified: `tests/embedded_thread_demo.py`
R11	GIL contention is real: while the host burned CPU in pure Python, median listener lag rose from 36.6 ms to 74.8 ms (max 41 → 87 ms)	Verified: `tests/embedded_thread_demo.py`
R12	Only one server per process: a second `Server(...).start()` fails with "Cannot create more than one instance of the server"	Verified: `tests/embedded_thread_demo.py`
R13	The host process exited promptly once its main coroutine returned, with the server on a daemon thread	Verified: `tests/embedded_thread_demo.py`
R14	Hosting the server as a subprocess works: up in 10.9 s, logic deployed with `run_script`, read at our own checkpoints; on Windows `terminate()` is a hard kill (exit code 1)	Verified: `tests/host_service_demo.py`
R15	Multiple update graphs per worker, each bound to an execution context	Docs (event-driven case Verified, R8)

Graph, cost and introspection

#	Fact	Evidence
G1	Every table operation and listener is a performance entry; Python callbacks were the costliest nodes (~195 ms per interval each) against ~80 ms for a rolling `update_by` and 3–36 ms for other Java operations	Verified: `examples/05_introspection.py`, `examples/pretty_graph.py`
G2	The ancestors log records dependencies only for nodes created after it was first opened; sources (no ancestors) appear only in the update performance log	Verified
G3	`ancestor_svg` / `ancestor_image` need the Graphviz `dot` binary, absent from the stock Docker image	Verified
G4	`merged_listen` creates one internal "Python Wrapped Listener recorder" per watched table; joins create `leftTable:` / `rightTable:` helper nodes; `update_by` creates per-bucket nodes	Verified: introspection report
G5	Java threads that call into Python appear in `threading.enumerate()` as `java-...` entries	Verified
G6	`introspect/dh_introspect.py` + client run end to end: field registry, scope objects, graph with cost, inputs, listeners vs handles, unreachable nodes (client exports), Python threads	Verified: `tests/probe_introspection.py`

Platform and tooling

#	Fact	Evidence
P1	The pip server runs natively on Windows (docs say WSL 2 is required) given Java 17+ in `JAVA_HOME`, the JVM DLL folders on `PATH`, and relative web-storage directories (otherwise: `jimage.dll` crash; "Invalid path: /layouts")	Verified: `server/run_server.py`
P2	`pydeephaven` 42.6 breaks with `bitstring` 5; pin `bitstring<5`	Verified
P3	React route: pin `@deephaven/jsapi-types` ~41.11 with the 1.3x UI packages; shim `@paciolan/remote-module-loader` under Vite; `IrisGrid` takes no `dh` prop	Verified: `react-client/`
P4	deephaven.ui `use_row_data` returns pandas-typed values (longs as floats)	Verified
P5	Formulas recompute only when their input columns change	Verified: rung 3
P6	Ten Deephaven gRPC services (Session, Console, Table, Application, Object, InputTable, PartitionedTable, HierarchicalTable, Storage, Config) plus Arrow Flight carrying Barrage	Verified: `deephaven_core.proto` stubs

Extension points and replay

#	Fact	Evidence
X1	A user-compiled Java class on `Server(extra_classpath=[jar])` is callable from formulas by fully qualified name (`com.acme.Risk.dv01(Qty, Px, 7.5)`) or after `getQueryLibrary().importStatic(<Class>)`	Verified: `tests/probe_framework_constructs.py`
X2	`query_library.import_static("com.acme.Risk")` raised ClassNotFound for that jar although `jpy.get_type` loaded it	Verified: same
X3	Python functions work in formulas; float hints give a `double` column; no hints give a `PyObject` column; `int` / `np.int64` hints are rejected on native Windows (numpy reports int64 as `q`, Deephaven accepts `l`)	Verified: same, and `deephaven/_udf.py`
X4	`function_generated_table(fn, refresh_interval_ms=200)` ran 3 times in 1.5 s (paced by the ~1 s cycle)	Verified: same
X5	`ring_table(t, 5)` held exactly the last 5 rows; a keyed `input_table` upserts by key and deletes by key	Verified: same
X6	`TableReplayer` released rows by timestamp at wall-clock pace (20 rows over ~4 s) through unchanged graph code; `now()` stayed wall-clock time	Verified: same
X7	On an event-driven graph, `requestRefresh()` returned only after the step finished (200/200); 200 slices took 0.137 s	Verified: same
X8	One `build_engine(quotes, limits, desks)` ran live (5.76 s, 4 router calls) and as an event-driven backtest (0.46 s, 28 calls) on the same 900 quotes, with an identical final book and desk risk (33 orders each)	Verified: `examples/06_trading_engine.py`

#	Fact	Evidence
X9	Enterprise replay queries (`ReplayScript`) swap in a simulated clock (`today`, `timeTable`) and redirect `db.live_table` to history, with speed and sorted-replay settings	Docs
X10	Custom Java sources implement `StreamPublisher` and feed `StreamToBlinkTableAdapter`	Docs (Javadoc)
X11	On native Windows, `parquet.read` / `parquet.write` reject `C:\...` paths (URISyntaxException); `file:///` URIs work, including key=value partitioned directories	Verified: `tests/test_dhfw_community.py`
X12	The `dhfw` wrapper's Community emulations pass 12/12 checks (historical and user tables, live append, system-table logging, registered feeds, replay mode, input tables, remote_table and `pq://`, controller imports, ACL no-op, explicit unsupported calls). Its Enterprise forwarding is untested	Verified (Community only): same

Corrections to earlier claims

Earlier claim	Correction
App-mode scripts need `global` to reach the console scope	Not in Community 42.6 Python (S2)
An underscore keeps a name private	Underscore names are published (S4)
Export tickets look like `e/<n>`	`e` + 4 binary bytes (T1)
A shared ticket can outlive its publisher	It dies with the publishing session (T4)
One clock per worker	One by default; more can be created, including event-driven (R8, R15)
No built-in Solace or kdb connector	Enterprise has Solace streaming import (Docs); kdb still none known
Unknown whether PQ scripts can come from Git	Enterprise supports Git-sourced PQ scripts (Docs)
Native Windows unsupported	Works with three workarounds (P1)
`get_exec_ctx()` works on any thread	Only on a thread that already holds a real context (R6)

Unverified: open questions from the audit

An audit compared every artifact against this ledger. It flagged these claims, but the checks on them never ran. Treat each one as **open**: it may be overstated, imprecise or wrong. The **Status** column records any fix made since.

#	Claim (where)	Why it is in doubt	Status
U1	T4: a copy another session fetched earlier also stops working (ledger)	`fetch_table` may only re-reference the shared ticket, not make a copy; then the test shows one ticket dying, not a copy	Open
U2	R11: median listener lag rose from 36.6 to 74.8 ms under host CPU load (ledger, Anatomy, deck)	One run with only 4 idle and 6 busy callbacks; the busy window includes a 1.5 s drain. The direction is plausible, the size is not established	Open: re-run with more samples
U3	R9: the host loop ran at about half speed during startup (89 ticks in 9.4 s) (ledger, Anatomy)	No idle baseline; on Windows a 50 ms asyncio sleep often takes longer anyway	Open: measure a baseline
U4	R2 / Findings: latency is "bounded below by the cycle"; pushed rows wait ~1 s	`MaxBufferedMs` is the oldest row's wait. The cycle caps the wait from above; a row pushed just before a cycle waits almost nothing	Open: reword as "up to one cycle"
U5	S7: fields are any registered object type (ledger)	Only tables and a deephaven.ui element were seen in `ListFields`; figures, partitioned and plugin objects were not tested	Open
U6	G6 / Findings: "2 Python listeners matching 2 handles, using 34% of engine time"	The saved report says 46% (174 of 381 ms) and 4 active listeners	Open: quote the report
U7	Findings summary: each cycle is consistent across **all tables in the worker**; cadence is set per worker	True only for the default graph; tables on an event-driven graph keep their own steps (R8)	Open: same fix as in Concepts and Anatomy
U8	Findings: "a worker can add update graphs" marked Verified	Only the event-driven case is verified (R8); the general claim is Docs (R15)	Open
U9	Findings: "Three realistic shapes"	Four numbered shapes follow	Open
U10	Findings: process lifecycle ("CPython embedded through jpy...") marked Verified	No ledger entry; describes the Docker worker, not the pip server, where Python starts first	Open
U11	Findings: scheduled stops are hard stops; failover can run two copies	Enterprise behaviour stated with no Docs marker	Open: mark Docs or confirm
U12	Anatomy: only the script session and the server's thread hold the real context	The test checked one other thread; listeners on update threads also run under a context	Partly fixed (Anatomy reworded)
U13	T2: export lifetime "Verified" from pydeephaven docstrings	A docstring is documentation, not an observation	Open: test it or mark Docs
U14	G2, G3, G5, P2, P4 marked Verified with no test named	Evidence exists for some (G5 in the report), not recorded here	Open: name the evidence
U15	`e/7` and single-update-graph wording in Concepts; "two workarounds" in the README	Contradicted T1, R8 and P1	Fixed

Also open in the introspection tool (code, not claims):

- **Fixed:**
- `update_by` bucket nodes were not folded as internal
- client: cleanup now runs even when a step fails
- client: a stale report is no longer read
- client: the field filter keeps other apps' `dhi_*` fields
- client: printing on Windows no longer fails before the JSON is written
- client: help and docstring wording
- **Open:**
- **Nodes miscounted:** stopped listeners still count as reachable roots, and listeners without a description look "stacked".
- **Parentless ops listed as inputs:** an op or sink with no parents shows up under INPUTS.
- **Missing descriptions:** `merged_listen` handles report no description.
- **Some time tables misread:** a `time_table` with a start time is classified as an operation, not a source.
- **Port list too broad:** listening ports outside a container include the whole host.
- **Library list wrong in places:** on Python 3.9 every standard library shows as non-platform, and the pip server shows as non-platform too.
- **DataFrames:** pandas DataFrame fields are typed incorrectly, and underscore-named DataFrames are skipped.
- **No opt-out:** opening the performance logs can't be skipped.