Deephaven as an application framework

A tested study of Deephaven (Community 42.6, with Enterprise in view) as a framework for trading and risk applications, plus two thin layers that make it easier to build on:

- `dhapp/`: an application layer. Four roles (source, stage, action, surface), live/backtest/test modes, a location-aware table catalog, trading and risk recipes, storage recipes and automatic deephaven.ui dashboards.
- `dhfw/`: one API for both runtimes. You write against the Enterprise (Core+) API; it forwards on Enterprise and emulates on Community.

Start here:

You want	Read or run
The story and an index of everything	`LLM_ONBOARDING.md`
Every claim and how we know it	`VERIFIED_FACTS.md` (test, source or docs)
How the engine works and how to program it	`deliverables/2026-10-21/Building a Deephaven Application A Programmer's Guide.pdf`
How to build on `dhapp` / `dhfw`	`deliverables/2026-10-21/dhapp and dhfw Framework Reference.pdf`
A working app with a live dashboard	`server/run_server.py --app-dir examples/mm_app.d`, then http://localhost:10000/iframe/widget/?name=mm_dashboard
The tests	`examples/07_app_framework.py` (8/8), `tests/test_dhfw_community.py` (12/12)

Building an app with dhapp

```
from dhapp import App, Catalog, recipes, schemas
from dhapp.ui import dashboard

app = App("mm", Catalog({"desk_limits": {"pq": "RiskLimits", "table": "desk_limits", "plant":
"ny"}}))
app.source("quotes", schemas.QUOTES, history=load_quotes)   # pushed live; replayed in backtest
app.source("limits", catalog="desk_limits")                 # resolved by where the app runs

@app.stage
def orders(quotes):
    return recipes.fill_at_touch(recipes.target_to_orders(recipes.ema_cross(quotes)))

@app.action(on="orders", services=["broker"])               # supervised; failures land in
app.health
def route(rows, broker): broker.send(rows)
```


```
app.service("broker", live=OrderGateway(), sim=RecordingBroker())
app.surface("orders")
app.start("live")                                          # or "backtest" + app.run_history(), or
"test"
mm_dashboard = dashboard(app)
```

The full engine (`examples/mm_app.py`) gives identical results live and in backtest, equal to the hand-written `examples/06_trading_engine.py`. Environment variables (`DHFW_PLANT`, `DHFW_PQ`, `DHFW_PQ_MAP`, `DHFW_DATA_ROOT`, ...) choose the runtime bindings; the code does not change. The Framework Reference covers the API, deployment and a cookbook. Nothing has run on an Enterprise plant yet: the first step there is to run the two test suites.

The two-UI comparison: deephaven.ui vs. web-client-ui

The same small "market-making book monitor" is built twice on top of one Deephaven Community server (v42.6; Docker, or the pip `deephaven-server` run as a plain Python process).

	(1) deephaven.ui	**(2) React + @deephaven/***
URL	http://localhost:10000/iframe/widget/?name=book_dashboard	http://localhost:4010
Code	`server/app.d/ui_dashboard.py` (~190 lines of Python)	`react-client/src/*` (~350 lines of TS/TSX)
Web server	Deephaven itself (Jetty on :10000)	Vite on :4010, proxying to :10000
Where the UI logic runs	**On the server**, in Python	**In the browser**, in React



Both frontends talk to the **same live tables**. Change a desk limit in one and the other shows the breach within a tick.

Run it

Prereqs: Node 18+, and either Docker Desktop or Java 17+ (`JAVA_HOME`) for the pip server.

```
# Option A: Docker
docker compose up -d --build         # Deephaven on :10000 (first pull ~1.5 GB)
# Option B: no Docker -- the pip server as a plain Python process
py -3.12 -m venv .venv-server; .\.venv-server\Scripts\pip install -r server\requirements-server.txt
.\.venv-server\Scripts\python server\run_server.py
# Either way, the React app on :4010
cd react-client; npm install; npm run dev
```

The pip server is documented as Linux/macOS/WSL 2 only; `server/run_server.py` makes it run natively on Windows. It needs Java 17+ in `JAVA_HOME`, then applies the other two workarounds itself: JVM DLL folders on `PATH`, and relative web-storage directories. `server/setup_wsl.sh` and `server/start.sh` set it up inside WSL instead.

- (1): http://localhost:10000/iframe/widget/?name=book_dashboard (or the IDE at http://localhost:10000/ide/, under **Panels** → **book_dashboard**)
- (2): http://localhost:4010
- The scripts in `server/app.d` only run at server start, so after editing them restart the server (`docker compose up -d --force-recreate`, or rerun `run_server.py`).
- Auth is **anonymous**, which is fine on localhost only. For a login, replace `-DAuthHandlers=io.deephaven.auth.AnonymousAuthenticationHandler` in `START_OPTS` (`docker-compose.yml`) with `-Dauthentication.psk=<key>`, or run `run_server.py --psk <key>`. `AppBootstrap` in (2) will then show a login prompt.

What each one demonstrates

Feature	(1) deephaven.ui	(2) React + web-client-ui
Live KPI cards	`ui.use_row_data(book_summary)`	`table.setViewport()` + `EVENT_UPDATED` listener (`hooks.ts`)
Live grid	`ui.table(desk_risk, format_=[...])` with server-evaluated conditional formats and databars	`<IrisGrid>` from `@deephaven/iris-grid`. It's the same grid, but deephaven.ui's `format_` (number formats, conditional colors, databars) has no IrisGrid prop, so numbers get the grid's defaults. To match, format the table in Python (`format_columns`, which IrisGrid renders)
Write to server	`set_limit()`, a plain Python call	`table.inputTable()` → `addRow({Desk, Limit})`, with no server code
"Callback" on server	`ui.use_memo(lambda: run_stress(shock, desk), [shock, desk])`	`session.runCode("stress_xxx = run_stress(...)")` → `session.getTable()`
Cross-panel state	`ui.use_state` hoisted to `book_layout` (row click → desk)	React `useState` in `App`
Chart	`dx.line(...)`, one line	Not included. It would need `@deephaven/chart` + plotly wiring

Feature	(1) deephaven.ui	(2) React + web-client-ui
Layout	`ui.dashboard` (drag/dock/tabs for free)	Your own CSS grid, or `@deephaven/dashboard` + golden-layout (heavy)

Takeaways

deephaven.ui is the fastest way to a live, interactive app if your team writes Python. You get no build step, no client code, and Deephaven's grid, plots and docking layout for free. State is per-session automatically, so two users with different sliders don't interfere. The costs: - Every interaction is a server round trip, and rendering spends server CPU per connected user. - You're limited to the component set it ships (React Spectrum + DH widgets). For anything else you have to write a JS plugin. - The page shell (`/iframe/widget` , the IDE) belongs to Deephaven, so branding and routing are limited.

web-client-ui gives full control of the frontend: your own routing, design system, other data sources, and deploying separately from the data server. The costs: - Plumbing. The bootstrap chain is `ApiBootstrap → AppBootstrap → ClientBootstrap → Auth → Connection` , and you manage the lifecycles of tables, models and sessions (`close()` everything). - The packages are monorepo-first, so integration has sharp edges (see below). - "Calling Python" means `runCode` against a **shared global scope**. Each tab here writes to its own `stress_<id>` variable to avoid clobbering others, and those variables are never cleaned up. In production you'd want a proper RPC instead: a custom object-type plugin with a message stream (which is how deephaven.ui itself works), or input tables as a "request" channel.

A reasonable hybrid: put the business logic in Python as tables and functions (as here), use deephaven.ui for internal and analyst tools, and use the React path only for the one or two apps that need a fully custom frontend.

Gotchas hit while building this (and the fixes in the code)

1. **App-mode scope.** The Deephaven docs say application-mode variables are not in the console scope unless declared `global` , so our scripts declare them. Testing later showed this is unnecessary on Community 42.6 Python: the scripts run in the global scope (`globals() is __main__.__dict__`), and undeclared top-level names are published as fields too (`tests/probe_concepts.py`). The declarations are harmless.
2. `jsapi-types` **version.** The web-client-ui 1.3x packages depend on `@deephaven/jsapi-types` 41.x. Installing 42.x (matching the server) creates duplicate, incompatible types. Keep `~41.11` . The *runtime* API always comes from the server (`/jsapi/dh-core.js`), so this only affects types.
3. `@paciolan/remote-module-loader` **interop.** `@deephaven/app-utils` default-imports this CJS module and gets `TypeError: ... is not a function` under Vite. Fix: the alias shim in `react-client/src/shims/` and `vite.config.ts` .
4. **The IrisGrid README is stale.** `<IrisGrid dh={dh} …>` no longer type-checks. `dh` now comes from context, so the call is just `<IrisGrid model={model} />` .
5. `use_row_data` **returns pandas-typed values.** Long columns arrive as floats (`514.0`). Cast with `int()` .
6. **Single origin.** Proxy `/jsapi` , `/js-plugins` , `/arrow.*` and `/io.deephaven.*` (with websockets) from your web server to Deephaven. Then the browser only talks to :4010, and you avoid CORS.

Files

```
LLM_ONBOARDING.md                the story so far and an index of every file
VERIFIED_FACTS.md                every claim, with how we know it (test, source or docs)
dhapp/                           application layer: app, catalog, recipes, schemas, store, ui
dhfw/                            Enterprise API on both runtimes: db, remote, systable, controller,
acl
examples/mm_app.py               the trading engine on dhapp; 07_app_framework.py runs it 3 ways
examples/mm_app.d/               application-mode demo with the live mm_dashboard
deliverables/                    PDF documents and text extracts
deck/                            presentation deck and its generator
docker-compose.yml               Deephaven 42.6 (+ Graphviz), app mode, anonymous auth
server/run_server.py             the same server via pip, no Docker (native Windows ok)
server/app.d/book.app            application-mode manifest
server/app.d/introspection.py    opens the performance logs at boot (full graph ancestry)
server/app.d/business_logic.py   shared mock book: tables + run_stress/set_limit
server/app.d/ui_dashboard.py     approach (1)
react-client/vite.config.ts      approach (2) web server + proxy
react-client/src/main.tsx        bootstrap chain
react-client/src/hooks.ts        useNamedTable / useViewportRows / useIdeSession
react-client/src/LiveGrid.tsx    IrisGrid wrapper
react-client/src/App.tsx         panels
examples/                        the experiment ladder, introspection, graph renderer
introspect/                      dh_introspect.py (in-worker report) + its client
tests/                           probes behind the Verified marks (scopes, fields,
                                 tickets, runtime features, event-driven clock,
                                 embedded thread, subprocess hosting, extension
                                 points, dhfw)
tools/build_deliverables.py      builds the PDFs and text extracts
```

Docs used: deephaven.ui docs, JS API how-to, application mode, iframes, and the `embed-widget` package in web-client-ui.