

Moodle Launch Flow

Launch flow reference for Moodle-to-Pre-Quran access and routing.

Audience: Admins, SQA testers

Generated: 2026-06-28

Moodle Launch Flow

This repo keeps Moodle PHP source/reference files separate from the Bunny-hosted static frontend.

Production Request Path

- Moodle login validates the user session.

```
https://quraan.academy/login/index.php
```

- Main Moodle launcher creates a short-lived mtoken and redirects to the Bunny app shell.

```
src/moodle/local_hubredirect/issue.php  
-> https://app.quraan.academy/pre_quraan/app/index.html?mtoken=...
```

- Bunny app shell shows the learner dashboard and routes unit buttons.

```
src/app-shell/index.html  
-> dist/pre_quraan/app/index.html  
-> dist/pre_quraan/scripts/index_v030.html compatibility alias
```

- Unit requests go back through Moodle child launcher for access, signing, and token brokering.

```
https://quraan.academy/local/hubredirect/issue_child.php?goto=alphabet_listen
```

- Moodle child launcher resolves goto to a Bunny lesson path, adds short-lived launch data, and wraps managed lessons in an iframe.

Current Alphabet Listen route in the imported reference:

```
alphabet_listen  
-> /pre_quraan/scripts/pq_unit_alphabet_html_v0.0_match.html?managed=1&v=20260425_240
```

In the new repo build, the equivalent Bunny output is:

```
/pre_quraan/units/alphabet/index.html?managed=1
```

- The iframe wrapper sends Moodle data to the unit with postMessage.

```
type: PQ_TOKENS  
uid  
wstoken  
wsendpoint: https://quraan.academy/webservice/rest/server.php  
managed: 1
```

- The Alphabet unit loads static assets from Bunny and reads/writes progress through Moodle web services.

```
src/units/alphabet/  
src/shared/  
src/moodle/local_preQuran/services.php  
src/moodle/local_preQuran/externallib_v4.php
```

Local Development Path

Local preview intentionally bypasses Moodle for frontend work:

```
http://127.0.0.1:4173/pre_quraan/scripts/index_v030.html  
-> Alphabet Listen  
-> http://127.0.0.1:4173/pre_quraan/units/alphabet/index.html?managed=1
```

The local-only route is controlled in:

```
src/app-shell/js/app-config.js
```

The local-only access-gate exception is controlled in:

```
src/shared/js/patches/access-gate.js
```

Production still routes through Moodle because the local overrides only apply to localhost and 127.0.0.1.

Hosted Bunny testing shortcuts may also open protected unit pages when the referrer host is quraan.academy or one of its subdomains. Direct no-referrer unit opens remain blocked.

Imported Moodle Files

```
src/moodle/local_hubredirect/issue.php
src/moodle/local_hubredirect/issue_child.php
src/moodle/local_prequran/services.php
src/moodle/local_prequran/externallib_v4.php
src/moodle/local_prequran/lib.php
src/moodle/course_format_reference/index.php
```

Moodle Dashboard Redirect

local_prequran keeps learner-style accounts out of Moodle's generic /my/ dashboard. When local_prequran/redirect_moodle_dashboard is enabled:

```
site administrator -> stays on /my/
unknown account -> stays on /my/
student profile -> /local/hubredirect/issue.php
teacher profile -> /local/hubredirect/dashboard.php
parent/guardian -> /local/hubredirect/dashboard.php
```

This redirect is intentionally conservative so administrators keep full Moodle access while students land in the Bunny app launcher.

Deployment Boundaries

Bunny output comes from:

```
npm run build:bunny
dist/pre_quraan/
```

Moodle PHP files are not copied into dist/. They belong in the Moodle server/plugin environment, not Bunny static hosting.

Next Integration Step

Update the Moodle alphabet_listen route after Bunny deployment so it points to the repo-built unit path:

```
'alphabet_listen' => '/pre_quraan/units/alphabet/index.html?managed=1&v=...'
```

Do this only after the Bunny upload path is confirmed.

The app shell launcher route in `issue.php` should remain:

```
$appBase = 'https://app.quraan.academy';  
$appPath = '/pre_quraan/app/index.html';
```