Sr. No.	Item	Technical Queries & Requirements
1	**High Accuracy CNC Lathe Machine – PD300-36MC**	1. Does this machine incorporate any components manufactured in Taiwan? No. 100% made in Germany 2. As the PD-300 is the latest version, what advancements, improvements, or new technologies does it offer compared to the SPINNER SB-CNC? -High-Precision Integrated Motor Spindle in Synchronous Technology manufactured in-house with active spindle temperature control equipped with hydraulic hollow clamping cylinder for high clamping forces. -BMT45 turret system for particularly high change accuracy and rigidity. -High-Precision Glass Scale HEIDENHAIN for X- and Z-Axis. -Direct Measuring System in the spindle for high-precision repositioning of the C-Axes. 3. Provide positional and geometrical accuracy specifications of the axes, along with spindle run-out details, preferably supported by inspection reports of a recently supplied machine for reference. Positioning X and Z = 0,006mm Repeatability X and Z= 0,003mm Spindle runout = 0,001mm
2	**Spindle**	Provide the spindle manufacturer's name, model and country of origin. SPINNER - Germany
3	**BMT 45 Turret System**	Provide the manufacturer's name , model and country of origin of the BMT 45 turret system. SPINNER - Germany
4	**Lubrication**	Confirm whether a centralized automatic lubrication unit is available. If so, clarify whether it automatically lubricates the lead screws, axis slides, guide roller pads, and other relevant components. Yes. Guideways + Feedscrews.
5	**Hard Turning Package**	1. Provide the accuracy specifications of the high-precision glass scales for the X and Z axes. 0,001mm resolution 2. Provide the make/manufacturer and country of origin of the glass scales. Heidenhain - Germany
6	**Clamping Tools – S1**	Provide the complete range, catalogue, or list of collets compatible with the Mini Pull-Back 42 A5 collet chuck. 4mm to 42,0mm.
7	**Cooling Unit**	An A/C cooling unit must be installed for effective cooling of the electrical control cabinet. Yes. Standard
8	**Relays Data Server**	Provide a relay data server board with 2 GB memory, including PMC/CNC parameters, SRAM backup, and an RS-232 communication port. Available USB Interface
9	**Mist Extraction System**	An electrostatic precipitator (EP)-type mist extraction unit is required. Included – please refer quote
10	**Service Access**	Password protection for service access to the machine, including activities such as parameter editing and hardware module replacement, should preferably be disabled. If this is not possible, the relevant service password must be provided for future diagnosis, maintenance, and troubleshooting. Included – please refer quote

11	**Service and Other Manuals**	The OEM must provide the machine service manual for future troubleshooting and maintenance. Other relevant manuals, including programming, parameter, electrical diagrams, ladder diagrams, hydraulic, and pneumatic manuals, should also be provided in both hard-copy and soft-copy formats (CD/DVD or equivalent digital media). Yes. Standard
12	**Communication Software**	Provide the necessary communication software for programme transfer, DNC operation, and any other related communication or data-transfer requirements. Included – please refer quote
13	**Spares**	1. Provide a comprehensive list of recommended electrical, electronic, and mechanical spare parts, including drives, motors, door switches, sensors, and other critical components. SPARE-PARTS Package included 2. Provide **01 set of spare jaws** for the power chuck, Make: SMW Autoblok, Model: BH-D 165-46-3-A05. – See quote 3. Provide **01 spare draw tube adapter**, Part No. 154961. – See quote
14	**Pre-Shipment Inspection (PSI)**	Include pre-shipment inspection (PSI) for **04-05 engineers for 10 working days** at the OEM's factory. – Included – please refer quote