

Shandong Jinboli Lubrication Technology Co., Ltd.

MCET609 Microemulsion Cutting Fluid MSDS

1. Product Labeling

- Product Description: Water-soluble microemulsion cutting fluid
- Product Name: MCET609 Microemulsion Cutting Fluid
- Manufacturer: SHANDONG JINBOLI LUBRICATING TECHNOLOGY CO., LTD

2. Composition/Ingredients Data

base oil
emulsifier
extreme pressure agent
Aluminum protective agent
antioxidant
surface active agent
antirust
Synthetic additives
anti-scuff agent

3. Hazard Warning Signs

- Safety hazards:
When using mineral oil products and chemicals, it is sufficient to implement the personal protectivemeasures specified in clauses 7 and 8; no additional hazards arise.
- Information regarding special hazards to humans and the environment: This product may contaminate water sources; see Clause 12.
- classification system:
Based on technical literature and information provided by suppliers, the scope of this classification is broader.

4. Emergency First Aid Measures

- General requirements: None.
- Upon skin contact: This product does not irritate the skin.
- After eye contact: Open your eyes and rinse thoroughly with clean water for several minutes.
- After swallowing: Please contact your doctor.

5. Fire Protection Measures

- Applicable extinguishing agents:
Use carbon dioxide powder extinguishing agent or a spray hose; in cases of large fires, use a spray hose or ethanol-resistant foam extinguishing agent. Select the appropriate extinguishing agent based on the specific environmental conditions.
Fire suppression measures.
- Fire extinguishing agents unsuitable for use due to safety considerations: use high-flow water spray from a hose.
- Protective equipment: When using the fire extinguisher, please wear a suitable breathing apparatus.

Product Name: MCET609 Microemulsion Cutting Fluid

Shandong Jinboli Lubrication Technology Co., Ltd.

MCET609 Microemulsion Cutting Fluid MSDS

6. Emergency First Aid Measures

- Safety and security measures for relevant personnel:
Take care to prevent products from spilling or overflowing.
- Environmental protection measures:
Prevent this product from entering or spreading into the drainage system, floors, and groundwater.
Prevent spillage of this product (separate using a baffle).
Prevent this product from entering the ground or soil.
- Cleaning/Collection Measures:
Use liquid adhesives for absorption (sand, diatomaceous earth, acidic adhesives, common adhesives, sawdust).
- Additional information: Does not release harmful substances.

7. Use and Storage

- make use of:
Safety Usage: No special requirements.
Regarding explosion-proof and fire protection requirements: No special requirements apply.
keep in storage:
Requirements for warehouses and containers: No special requirements.
Regarding data stored in a standard storage device: None.
Additional information regarding storage conditions: None.
- Storage classification: Classified
according to the rules for non-flammable liquids: Blank.
- Storage Classification: Classified in
accordance with regulations for non-flammable liquids: Blank.

8. Explosion Control and Personnel Protection

- Additional information regarding the design of the technical system: No further data; refer to Clause 7.
- Components in the factory requiring monitoring that have critical thresholds:

CAS	Material Specification	No.%	Category	Data	Unit	%	CAS
	Material Specification	No.%	Category	Data	Unit		

This product contains no substances whose content requires monitoring during actual operation.
- Personal protective equipment
- General protective and health care measures
General protective measures during the handling of chemical and mineral oil products must be observed. Avoid prolonged skin contact.
Use a moisturizing cream to protect the skin.
Do not place fabrics contaminated by this product in your trouser pockets.
- Respiratory equipment: No requirements.
- Hand protection: protective gloves and moisturizing cream.
- Eye protection: Wear appropriate safety goggles when canning.

Product Name: MCET609 Microemulsion Cutting Fluid

Shandong Jinboli Lubrication Technology Co., Ltd.

MCET609 Microemulsion Cutting Fluid MSDS

9. Physicochemical Properties

- Form: Liquid
- Color: Light yellow
- Scent: Soft
- Flash point: 160 °C
- Auto-ignition point: This product does not ignite spontaneously.
- Explosion Hazard: This product does not explode.
- Solubility in water / Compatibility with water

10. Stability and Reactivity

- Thermal decomposition / Conditions to avoid: No thermal decomposition will occur when used according to the instructions.
- Adverse reactions: None.
- Hazardous product components: None.

11. Toxicological Data

- Acute toxicity: None.
- Primary irritant effects:
For the skin: None.
For the eyes: None.
- Allergic reactions: None.
- Additional toxicity data:
When used and handled in accordance with the applicable regulations, based on our experience and available information, this product poses no hazard.

12. Ecological Data

- Biotoxicity: None.
- In wastewater treatment plants: this product floats on the water surface.
- General Precautions:
This product shall not be discharged into groundwater, water bodies, or wastewater systems.

Product Name: MCET609 Microemulsion Cutting Fluid

Shandong Jinboli Lubrication Technology Co., Ltd.

MCET609 Microemulsion Cutting Fluid MSDS

13. Handling Precautions

- product:
propose:
Small quantities must be disposed of in accordance with government regulations. Products that have undergone pretreatment must comply with the applicable regulations for the handling of special hazardous materials when discharged, recycled, or incinerated. When storing used mineral oil products, identify the type of waste oil and comply with mixing procedures. Waste oil may only be transported by government-authorized collectors.
- Uncleaned packaging:
propose:
All contaminated containers shall be emptied and recycled following complete and proper cleaning cycles. Single-use small packaging materials must be disposed of in accordance with local regulations.

14. Transport Documentation

- Transportation/Additional Information:
It is defined as non-hazardous goods in accordance with the Guidelines for the Transport of Hazardous Goods.

15. General Information

- national regulation
Water hazard level: 1 (self-assessment): Slight hazard to water.

16. Other Materials

- availability:
All previous versions of this product are no longer valid.
The version marked with an asterisk (*) contains amended terms.

Shandong Jinboli Lubrication Technology Co., Ltd.

MCET609 Microemulsion Cutting Fluid MSDS

Shandong Muchun TechnologyDevelopment Co., Ltd.

Test Report

Date: September 17,2026

Product Name: MCET609 | **Batch No.:** PO202691742

Product Name:

MCET609 | Batch No.: PO202691742

project	qualitative index	experimental method
surface	Pale yellow, transparent	visualization
smell	Mild odor	olfactory sensation
Refractometer diopter	58±1	Handheld refractometer
Thread engagement torque at 5% concentration	110Ncm	TTTtester
pH value at 5% concentration	9.34	pH meter
PB value at 5% concentration	60KG	Four-ball testing apparatus
Corrosion resistance of cast iron at 5% concentration	Level 0	JBT9189-2016
Corrosivity of aluminum at 5% concentration according to national standards	Grade A	GB6144-2010
Foam of the 5% working solution	30min/1300ml	NFT60-185

signature:FHH

