

【Chemical Safety Data Sheet-SDS】

1. Chemicals and company logos

Chemical name	Turning oil
Suggested use	Suitable for mirror turning

Effective date	August 20, 2026
----------------	-----------------

2. Overview of risks

GHS hazard category	Harmless
GHS label elements	
Symbol	No matches
Warning words	No warning words
Hazard description	Physical hazards: According to GHS standards, it's not classified as a hazardous substance. Health hazard: According to GHS standards, it is not classified as a health hazard. Environmental hazard: According to GHS standards, it is not classified as an environmental hazard.
GHS precaution instructions	
Precautions	
Accident response	No precautionary language
Store safely	No precautionary language
Waste disposal	No precautionary language No precautionary language
Other harms that don't affect the classification	Not rated as flammable, but can burn
Main symptoms and emergency overview	Based on animal tests, there is no strong evidence that this product causes cancer. Normally, it won't harm your health, but too much contact may irritate your eyes, skin, or lungs. If not washed properly, it could block skin pores and cause oily acne, folliculitis, and other skin issues. Used oil might contain harmful impurities.

3. Ingredients/Composition info

Recipe instructions

This product is a mixture, mainly made up of base oil and petroleum additives.

Chemical name	CAS number or ID number	EC number	Content , wt%
base oil	Mixture	---	92-99
Additive	Mixture	---	1-8

4. First aid

General information

Using it under normal conditions shouldn't be a health risk.

Handling different

types of contact

Inhale

No need for emergency medical care. If you have symptoms like coughing or difficulty breathing, it's advisable to see a doctor.

Skin contact

No need for medical emergency. Remove contaminated clothing, wipe the affected areas clean, and wash with soap and water. Thoroughly clean clothes and shoes before reuse. See a doctor if necessary.

Eye contact

Eat

No medical emergency needed. Rinse with water for 15-20 minutes. Seek medical attention if necessary.

Unless a large amount is swallowed, medical emergency care is usually not needed. As a precaution, it's recommended to see a doctor.

Main symptoms

(acute/delayed effects)

Breathing in oil mist or vapour for a long time at high temperatures may cause inflammation in the respiratory system, long-term or repeated skin contact can cause irritation or skin inflammation, eye contact may cause slight irritation to the eyes, and eating a lot may lead to stomach inflammation, vomiting, and diarrhoea.

5. Fire safety measures

Especially dangerous

This product has a flash point above 205°C and is not classified as hazardous. It can catch fire if exposed to high heat, open flames, or strong oxidisers.

Ways to put out fires and fire extinguishers

Water or spray, foam extinguisher, carbon dioxide extinguisher, dry powder extinguisher. Sand is only suitable for small fires.

Harmful substances produced during burning

Incomplete combustion produces thick smoke, carbon monoxide, carbon dioxide, sulfur oxides, aldehydes, nitrogen oxides, phosphates, certain metal oxides and other decomposition products

Fire extinguishing agents that are not allowed

Don't spray water

Special protective gear for firefighters

You must wear a breathing apparatus when getting close to a fire in a confined space.

6 . Leak emergency handling

Avoid contact with any spilled or released substances. For guidance on personal protective equipment, see chapter 8 of the safety datasheet. For disposal information, refer to chapter 13 of the safety datasheet. Please follow all applicable local or national regulations.

Emergency response procedure	Cut off the fire source and contact the operators immediately, ensuring unrelated personnel evacuate quickly to a safe area and stay isolated. Try to stop the leak from spreading into sewers, drainage ditches, or water bodies. Follow the relevant fire safety procedures and refer to Chapter 8 of the safety technical manual. Avoid contact with skin and eyes.
Worker safety measures	Before the workers arrive on site, try to contain the spilled substance as much as possible. For small leaks, use sawdust, sand, soil, or other absorbents to collect the spill and place it in a sealed, leak-proof container for disposal; for large leaks, build a bund or dig a pit to collect it, ensuring it doesn't flow into sewers, rivers, water sources, or low-lying areas. Place the spilled substance in suitable containers for disposal. If the soil and plants are contaminated, report it to the relevant authorities.
Environmental protection steps	For waste disposal, check out Chapter 13 of the safety datasheet.
Ways to get rid of it	For large spills, use a vacuum pump to transfer it to a container. For small spills, use sawdust, sand, soil, oil absorbent cotton, or other absorbents to prevent spreading and put it into a sealed container for disposal. For land spills, take protective measures to cut off the pollution source and minimise contamination of surface water. For water spills, immediately use oil booms to prevent the oil from spreading, warn nearby boats, and use suitable dispersants if necessary. Serious spills that can't be handled should be reported to the local authorities.

7. Handling and storage

Handling operations	Avoid prolonged or repeated skin contact; wash thoroughly after contact. If there is a risk of inhaling vapor, spray or mist, use local exhaust ventilation. Handle gently to prevent damage to packaging and containers.
General precautions	
Safety handling tips	Operators must be specially trained and strictly follow operating procedures. Avoid contact with oxidants. Keep suitable fire-fighting and spill-response equipment on hand. Wear protective footwear when handling 200-liter drums. Empty containers may retain harmful residues.
Storage conditions	Keep containers tightly closed; do not store in open or unlabeled containers. Store in a cool, dry, well-ventilated place, away from strong oxidants, ignition sources, heat and flammable materials. Store at room temperature. Empty containers may still contain product residues; do not cut or weld them, and do not expose them to high heat or flame.

8. Exposure Controls / Personal Protection

Exposure limits Occupational exposure limits for synthetic oil

U. S. ACGIH:

STEL: 10 mg/m³ Form: oil mist

TWA: 5 mg/m³ Form: oil mist

China MAC: no established standard

Engineering controls	Provide exhaust ventilation or other engineering controls to make sure the concentration of relevant substances in the air stays below the standard limits.
Personal protective equipment	Personal protective equipment should meet the relevant national standards. For details, please check with your PPE supplier.
Respiratory protection	Under normal usage conditions, you don't need to wear respiratory protection. If engineering controls don't keep the oil mist concentration at a level that protects health, you should choose respiratory protection equipment that meets relevant regulations. For details, please consult the supplier of the respiratory protection equipment.
Hand protection	Wear oil-resistant, chemical-resistant protective gloves. Nitrile, neoprene or PVC gloves are recommended. Replace contaminated gloves promptly. Wash thoroughly with soap and water after use.
Eye protection	If there might be splashes, wear safety goggles.
Skin and body protection	Under normal use conditions, apart from regular work clothes, no special skin or body protection is needed. If there is a chance of splashing, please choose suitable, impermeable safety clothing and safety shoes according to the actual situation at the workplace, preferably made of nitrile rubber.

9. Physical and chemical properties

Appearance	Transparent liquid	Vapor pressure	No data
Smell	Odorless or slight odor	Vapor density	No data
pH value	Not applicable	Viscosity index	105
Initial boiling point	Not applicable	Solubility	Insoluble in water
Melting point	Not applicable	Octanol/water partition coefficient	Not applicable
Flashpoint	180°C (open cup, typical)	Auto-ignition temp.	No data
tipping point	-38°C (typical)	Decomposition temp.	No data
Explosion limit	No data	Kinematic viscosity	9.1 mm ² /s at 40°C

10. Stability and Reactivity

Stability	Stable
Possibility of hazardous reactions	Contact with strong oxidants
Conditions to avoid	Extreme temperatures, direct sunlight, contact with strong oxidants and ignition sources
Incompatible materials	Strong oxidants
Hazardous decomposition products	No hazardous decomposition products under normal storage conditions.

11. Toxicological Information

Acute toxicity	Low toxicity expected. LD50: >5 g/kg (rabbit, dermal); >5 g/kg (rat, oral). LC50>10 g/m3 (rat).
Skin irritation/corrosion	Mild irritation expected. Prolonged or repeated skin contact without proper cleaning may cause dermatitis.
Eye irritation/corrosion	Mild irritation expected.
Inhalation hazard	Inhalation of vapor or oil mist may cause mild irritation.
Respiratory or skin sensitization	Not expected to be a skin sensitizer.
Germ cell mutagenicity	No mutagenic hazard.
Carcinogenicity	No component present at concentrations above 0.1% is recognized as a carcinogen by ACGIH, IARC or the EC.
Reproductive toxicity	No expected hazard
STOT - single exposure	No expected hazard
Reproductive toxicity	
STOT - repeated exposure	No expected hazard
Additional information	Used oil contains harmful impurities accumulated during use; the viscosity and composition vary with the process. Handling may pose risks to health and the environment. Handle used oil carefully and avoid skin contact. In animal tests, prolonged contact with used engine oil caused skin cancer.

12. Ecological Information

Ecotoxicity	No data available.
Persistence and degradability	Not expected to be readily biodegradable.
Bioaccumulation potential	Contains components with bioaccumulation potential.
Mobility in soil	If it enters soil, it will be adsorbed onto soil particles and will not migrate.

13. Disposal Considerations

Residual waste	Recover or recycle whenever possible, or dispose of through a waste collector approved under the relevant regulations.
Disposal of containers	Dispose of through a waste collector approved under the relevant regulations, whenever possible.
Disposal precautions	Wear personal protective equipment. Prevent waste from contacting soil or entering drains. When transporting or storing waste, use conveyances, recovery units and treatment/storage equipment approved by the relevant authority.

14. Transport Information

This product is not classified as hazardous for transport by road, sea or air

UN number	Not applicable
UN proper shipping name	Not applicable
UN hazard class	Not applicable
Packing group	Not applicable
Marine pollutant	Not applicable

15. Regulatory Information

Under the relevant regulations in China, this product is not classified as a hazardous chemical.

National chemical safety regulations
Council, Mar 2, 2011)

Regulations on Safe Administration of Hazardous Chemicals (issued by the State

Provisions on the Safe Use of Chemicals in the Workplace ([1996] Ministry of Labor
Order No. 423) GB 6944: Classification and Code of Dangerous Goods

GB/T 16483: Content and Order of Sections of Safety Data Sheets

GB 13690: General Rules for Classification and Hazard Communication of Chemicals

GB 12268: List of Dangerous Goods

GB 15258: Rules for Preparation of Chemical Safety Labels

GBZ 2.1: Occupational Exposure Limits for Hazardous Factors in the Workplace -
Part 1: Chemical Hazardous Factors

These and other regulations set out corresponding requirements for the safe use,
production, storage, transport and handling of hazardous chemicals.

16. Other Information

Revision statement: Compiled in accordance with GB/T 16483-2008, Safety Data Sheets for Chemicals.

The information provided is based on our current knowledge of the data and describes the
product only with regard to health, safety and environmental requirements. We make no
warranty as to the specific characteristics of the product.