DNS1 live-response evidence

Supporting material for App Review Guideline 2.5.19

Submitted version: 1.1.0, build 6 (developer-confirmed). Review invitation code and test credentials are provided in App Review Information.

Live capture: 2026-10-27T09:24:18+08:00 to 2026-10-27T09:24:20+08:00 (UTC+08:00 / Asia/Shanghai).

Observed results

Measurement	Main DNS source	Independent BIN request
Transport/result	7 AAAA records	HTTP 200; 280 bytes
Decoded format	Comma-separated TCP list	JSON object
TCP nodes	4	4
HTTP service URLs	0	4 (HTTPS)

The TCP node sets matched exactly before redaction. The decrypted BIN contained tcp and http fields, with no additional top-level fields in this capture. All four input entries in each relevant array/list remained in the normalized output.

How this relates to the review findings

Remote lookup: DNS1 obtains backend endpoints associated with the invitation code. The remote values can change which server the app connects to.

Decoding: AAAA records carry fragments of a custom endpoint-list protocol. The fallback BIN carries encrypted endpoint JSON. This is more than ordinary hostname resolution. The parsed values supply TCP connections and optional API/file-transfer URLs.

Lookup credentials: DNS1DoHClient uses an account identifier, access key and a locally calculated signature to authenticate the DNS-service request. The secret value is not sent as a plaintext query parameter. It is distinct from the test user password.

Evidence boundary

This was a macOS command-line capture using current project functions, not a capture from the submitted IPA. It does not verify user login, messaging, ECDH reachability or device reconnection. The next pages contain actual normalized results with explicitly substituted addresses and ports.

Decoded results, redacted

These are normalized outputs from the live responses, not raw wire JSON. Placeholder values were substituted after successful parsing; they are not invented network results.

A. Main DNS source

Completed: 2026-10-27T09:24:18+08:00. Seven AAAA records reconstructed a comma-separated list of four TCP nodes. The http array below is an empty normalization field; it was not present in the original DNS text.


```
{
  "http": [],
  "tcp": [
    "host-1.example.invalid:40001",
    "host-2.example.invalid:40002",
    "host-3.example.invalid:40002",
    "host-4.example.invalid:40001"
  ]
}
```


B. Fallback BIN source - independently requested

Completed: 2026-10-27T09:24:20+08:00. HTTPS download returned HTTP 200 and 280 bytes. Decryption produced a JSON object with four tcp entries and four http entries.


```
{
  "http": [
    "https://host-1.example.invalid:40003",
    "https://host-2.example.invalid:40004",
    "https://host-3.example.invalid:40004",
    "https://host-4.example.invalid:40003"
  ],
  "tcp": [
    "host-1.example.invalid:40001",
    "host-2.example.invalid:40002",
    "host-3.example.invalid:40002",
    "host-4.example.invalid:40001"
  ]
}
```


Redaction key

Each original host maps consistently to host-N.example.invalid across both results. Each explicit port maps consistently to a synthetic number from 40001. Schemes, normalized entry order/counts and host/port equality relationships are retained. No HTTP path was present in these accepted URLs. Actual hosts, ports, the invitation code, credentials and signed request URLs are omitted.

Method and provenance

Capture procedure

1. Read the user-supplied review invitation code without saving it to a source file. Use DNS1DoHClient.records for the live main-domain query and DNS1Payload.records for production parsing.

2. Request the configured BIN separately over HTTPS and pass its bytes to DNS1Payload.bin and AesEncryptUtils. Compare the two unredacted TCP node sets in memory.

3. Inspect the original decoded formats in memory and cross-check the inspection output against the production parser. Apply deterministic per-capture redaction, then save normalized JSON. Raw payloads and the mapping are not retained.

The independent BIN request demonstrates the backup data source can return parseable data at capture time. It does not demonstrate that the app automatically fell back from DNS during this run.

Source identification

Local revision: 53cdc4bc34215fd9a466995c2b444f6ab1d770c8

The local project reports version 1.0 / build 1. The developer identifies the rejected submission as 1.1.0 / build 6. Archive-to-source correspondence has not been independently verified; this report does not equate the two builds.

ddlNew/Network/DNS1/DNS1Payload.swift

`9badd776a27de5b44782af69dcb438e3e7c3c15f560aa3c9a4685168736cc1c9`

ddlNew/Network/DNS1/DNS1DoHClient.swift

`75dbff669ebf9d8d9a63b83de11a25dc714284db52d14cc1151bce3c7ddb3dda`

ddlNew/Common/Crypto/AesEncryptUtils.swift

`09166ce85ba1fc8825e4b39ecd7810ad8d5ff0ba835e8885cf2c30c94131c8eb`

Tests/DNS1/DNS1ReviewCapture.swift

`9ad401529241120585d15f612cea2edaec62b6a599d6b2ed9cf7abbc77e28461`

Tests/DNS1/capture-review-response.sh

`c6351a709cacb9806b10cf4c1e4bbe765da89e33f06ddbbd34a723e11174d9f5`

Supporting files

05-DNS1-Sanitized-Live-Response.json provides machine-readable results, timestamps and hashes. 02-DNS1-Source-Appendix.txt provides the six selected production source files with line numbers and original-file hashes. The capture helper is developer tooling outside the app source folder.

What these results do and do not establish

This capture confirms that the selected live DNS/BIN responses decode to endpoint data. The current DNS1 parser consumes tcp/http endpoint fields and ignores unknown JSON fields. An absence of other fields in one sample is not a guarantee about future responses or all app components. No app-account login, message transmission, node probing, device reconnection or App Store submission was performed.