

Upgrade to PHP version 7.2.34, 7.3.23, 7.4.11 or later.

Risk Factor

Medium

Vulnerability Priority Rating (VPR)

2.5

CVSS v3.0 Base Score

6.5 (AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS v3.0 Temporal Score

5.7 (E:U/RL:O/RC:C)

CVSS Base Score

6.4 (AV:N/AC:L/Au:N/C:P/I:P/A:N)

CVSS Temporal Score

4.7 (E:U/RL:OF/RC:C)

STIG Severity

I

References

CVE	CVE-2020-7070
CVE	CVE-2020-7069
XREF	IAVA-2020-A-0445-S

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2020/10/09, Modification date: 2022/04/11

Ports

10.13.26.211 (TCP/80) Vulnerability State: Active

URL : http://ip-10-13-26-211.ec2.internal/ (7.3.21 under Server:
Apache/2.4.46 (Win64) PHP/7.3.21)
Installed version : 7.3.21
Fixed version : 7.3.23

10.13.30.105

Scan Information

Start time: 2024/01/05 17:50
End time: 2024/01/05 18:09

Host Information

DNS Name:ip-10-13-30-105.ec2.internal

OS:Microsoft Windows

Results Summary

Critical	High	Medium	Low	Info	Total
0	1	6	0	26	33

Results Details

/

10092 - FTP Server Detection

[-/+]

Synopsis

An FTP server is listening on a remote port.

Description

It is possible to obtain the banner of the remote FTP server by connecting to a remote port.

Solution

N/A

Risk Factor

None

References

XREF	IAVT-0001-T-0943
XREF	IAVT-0001-T-0030

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 1999/10/12, Modification date: 2023/08/17

Ports

10.13.30.105 (TCP/21) Vulnerability State: Active

The remote FTP banner is :

```
220-FileZilla Server version 0.8.1 beta
220-written by Tim Kosse (Tim.Kosse@gmx.de)
220 Please visit http://sourceforge.net/projects/filezilla
```

10107 - HTTP Server Type and Version

[-/+]

Synopsis

A web server is running on the remote host.

Description

This plugin attempts to determine the type and the version of the remote web server.

Solution

N/A

Risk Factor

None

References

XREF

IAVT-0001-T-0931

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2000/01/04, Modification date: 2020/10/30

Ports**10.13.30.105 (TCP/5985) Vulnerability State: Active**

The remote web server type is :

Microsoft-HTTPAPI/2.0

10287 - Traceroute Information

[-/+]

Synopsis

It was possible to obtain traceroute information.

Description

Makes a traceroute to the remote host.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 1999/11/27, Modification date: 2023/12/04

Ports**10.13.30.105 (UDP/0) Vulnerability State: Active**

For your information, here is the traceroute from 10.13.26.187 to 10.13.30.105 :

10.13.26.187
10.13.30.105

Hop Count: 1

Synopsis

This plugin displays the SSL certificate.

Description

This plugin connects to every SSL-related port and attempts to extract and dump the X.509 certificate.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2008/05/19, Modification date: 2021/02/03

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

Subject Name:

Common Name: EC2AMAZ-2T6H6FL

Issuer Name:

Common Name: EC2AMAZ-2T6H6FL

Serial Number: 7B 21 C7 C3 43 87 B3 A7 48 15 30 99 49 A5 8F 98

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Dec 26 18:49:04 2023 GMT

Not Valid After: Jun 26 18:49:04 2024 GMT

Public Key Info:

Algorithm: RSA Encryption

Key Length: 2048 bits

Public Key: 00 D5 32 49 E1 C3 B4 BB 35 7B 54 74 D4 2B FA 80 17 DC 82 07 37 F9 E5 5C 9D D2 72 F0 CA E2 74 E1 7D 03 8B 21 C1 35 12 0C 50 11 64 9C 71 33 D8 5C E9 C2 06 49 26 1B 45 12 D3 54 66 9F F3 2B E6 8F E2 44 06 AE EB B5 D3 AC 3D 8E E5 94 39 15 94 CD F7 94 B1 FD 05 11 88 E1 09 C2 1D 07 C6 A2 CE C1 E1 AC 54 F5 F6 CB 56 CC 93 2B DC AF C8 D6 D0 5B 20 87 17 E4 E3 3C 47 D7 5A 8B B0 A2 BB 39 53 28 2C EB 62 A5 15 3F E2 F1 83 3B 3C ED 2E 8C 37 4F 50 80 D7 2F 86 85 C0 2C 9A 89 89 6B CA B5 A0 8E 02 33 17 39 2A 35 D9 CD D1 4E C4 05 AE D7 79 29 29 7B 3C F2 80 B2 22 AE 0A CE 08 AE 39 68 CD E3 59 1C 75 06 0F 09 FD 82 AD AF 4C 1D 1B ED 20 57 CD 6B 18 67 57 45 CE CF 2E C0 BA 4F 64 17 E8 E7 85 EA F1 59 F8 BE D5 5E 00 51 46 61 C8 02 7A 40 2F 36 00 C1 88 B7 07 AF 7E 0D 96 63 5F 28 A5 2E 0D

Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 D2 E6 40 66 06 17 C4 6A A2 B2 30 15 88 83 CB 96 45 49 48

```

76 77 95 AD B0 7C C8 DB C0 15 26 95 B2 41 D2 51 B8 8F 31 77
36 FD FA D8 D8 4D 7F 18 32 A8 CC 73 F7 83 62 FD 1E AF 40 F2
A1 C4 A1 A5 D0 6E C5 CD FF 05 EC EA A4 75 97 62 5D 74 2D 8C
F2 46 A1 D7 E5 3F 06 07 D9 01 9E C4 BE 3A BE 95 91 F9 F2 81
C7 20 27 DD D1 21 C8 78 44 DB 3E 34 36 C6 06 CC EE 75 02 34
2A 8B A3 32 FD B1 94 67 96 62 0F 4C F1 77 07 FD 66 B2 6E DD
0E 3A B3 CA 07 39 B5 DA 94 D8 87 F5 1C D4 46 A2 D6 52 12 C3
33 C9 40 56 94 B6 52 89 41 EF A6 2B 0B BA F6 EC 58 0E 7D 08
17 0A 74 50 2B [...]

```

10940 - Remote Desktop Protocol Service Detection

[-/+]

Synopsis

The remote host has an remote desktop protocol service enabled.

Description

The Remote Desktop Protocol allows a user to remotely obtain a graphical login (and therefore act as a local user on the remote host).

If an attacker gains a valid login and password, this service could be used to gain further access on the remote host. An attacker may also use this service to mount a dictionary attack against the remote host to try to log in remotely.

Note that RDP (the Remote Desktop Protocol) is vulnerable to Man-in-the-middle attacks, making it easy for attackers to steal the credentials of legitimate users by impersonating the Windows server.

Solution

Disable the service if you do not use it, and do not allow this service to run across the Internet.

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2002/04/20, Modification date: 2023/08/21

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

11219 - Nessus SYN scanner

[-/+]

Synopsis

It is possible to determine which TCP ports are open.

Description

This plugin is a SYN 'half-open' port scanner. It shall be reasonably quick even against a firewalled target.

Note that SYN scans are less intrusive than TCP (full connect) scans against broken services, but they might cause problems for less robust firewalls and also leave unclosed connections on the remote target, if the network is loaded.

Solution

Protect your target with an IP filter.

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2009/02/04, Modification date: 2023/09/25

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

Port 3389/tcp was found to be open

10.13.30.105 (TCP/5985) Vulnerability State: Active

Port 5985/tcp was found to be open

10.13.30.105 (TCP/21) Vulnerability State: Active

Port 21/tcp was found to be open

11936 - OS Identification

[-/+]

Synopsis

It is possible to guess the remote operating system.

Description

Using a combination of remote probes (e.g., TCP/IP, SMB, HTTP, NTP, SNMP, etc.), it is possible to guess the name of the remote operating system in use. It is also possible sometimes to guess the version of the operating system.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2003/12/09, Modification date: 2023/11/08

Ports**10.13.30.105 (TCP/0) Vulnerability State: Active**

Remote operating system : Microsoft Windows
Confidence level : 70
Method : HTTP

Not all fingerprints could give a match. If you think some or all of the following could be used to identify the host's operating system, please email them to os-signatures@nessus.org. Be sure to include a brief description of the host itself, such as the actual operating system or product / model names.

HTTP:Server: Microsoft-HTTPAPI/2.0

SinFP:!:
P1:B11113:F0x12:W65392:00204ffff:M8961:
P2:B11113:F0x12:W65535:00204ffff010303080402080affffff44454144:M8961:
P3:B00000:F0x00:W0:00:M0
P4:190704_7_p=5985
SSLcert:!:i/CN:EC2AMAZ-2T6H6FLs/CN:EC2AMAZ-2T6H6FL
a5199f298a9547134cc5e841c54990f41e9ffb6b

The remote host is running Microsoft Windows

12053 - Host Fully Qualified Domain Name (FQDN) Resolution [-/+]

Synopsis

It was possible to resolve the name of the remote host.

Description

Nessus was able to resolve the fully qualified domain name (FQDN) of the remote host.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2004/02/11, Modification date: 2017/04/14

Ports

10.13.30.105 (TCP/0) Vulnerability State: Active

10.13.30.105 resolves as ip-10-13-30-105.ec2.internal.

17593 - FileZilla FTP Server Multiple DoS [-/+]

Synopsis

The remote FTP server has multiple denial of service vulnerabilities.

Description

The remote host is running a version of FileZilla server with the following denial of service vulnerabilities :

- Requesting a file containing the reserved name of a DOS device (e.g. CON, NUL, COM1, etc.) can cause the server to freeze.
- Downloading a file or directory listing with MODE Z enabled (zlib compression) can cause an infinite loop.

See Also

http://sourceforge.net/project/shownotes.php?release_id=314473

Solution

Upgrade to FileZilla Server 0.9.6 or later.

Risk Factor

High

Vulnerability Priority Rating (VPR)

3.6

CVSS Base Score

7.8 (AV:N/AC:L/Au:N/C:N/I:N/A:C)

CVSS Temporal Score

5.8 (E:U/RL:OF/RC:C)

References

CVE	CVE-2005-0851
CVE	CVE-2005-0850
BID	12865
XREF	SECUNIA-14664

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2005/03/22, Modification date: 2018/07/11

Ports

10.13.30.105 (TCP/21) Vulnerability State: Active

19506 - Nessus Scan Information

[-/+]

Synopsis

This plugin displays information about the Nessus scan.

Description

This plugin displays, for each tested host, information about the scan itself :

- The version of the plugin set.
- The type of scanner (Nessus or Nessus Home).
- The version of the Nessus Engine.
- The port scanner(s) used.
- The port range scanned.
- The ping round trip time
- Whether credentialed or third-party patch management checks are possible.
- Whether the display of superseded patches is enabled
- The date of the scan.
- The duration of the scan.
- The number of hosts scanned in parallel.
- The number of checks done in parallel.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2005/08/26, Modification date: 2023/07/31

Ports

10.13.30.105 (TCP/0) Vulnerability State: Active

Information about this scan :

Nessus version : 10.6.4
Nessus build : 20005
Plugin feed version : 202401051133
Scanner edition used : Nessus
Scanner OS : WINDOWS
Scanner distribution : win-x86-64
Scan type : Normal
Scan name : Grp2
Scan policy used : Basic Network Scan
Scanner IP : 10.13.26.187
Port scanner(s) : nessus_syn_scanner
Port range : default
Ping RTT : Unavailable
Thorough tests : no
Experimental tests : no
Plugin debugging enabled : no
Paranoia level : 1
Report verbosity : 1
Safe checks : yes
Optimize the test : yes
Credentialed checks : no
Patch management checks : None
Display superseded patches : yes (supersedence plugin launched)
CGI scanning : disabled
Web application tests : disabled
Max hosts : 30
Max checks : 4
Recv timeout : 5
Backports : None

Allow post-scan editing : Yes
Nessus Plugin Signature Checking : Enabled
Audit File Signature Checking : Disabled
Scan Start Date : 2024/1/5 17:51 UTC
Scan duration : 593 sec
Scan for malware : no

21643 - SSL Cipher Suites Supported

[+/-]

Synopsis

The remote service encrypts communications using SSL.

Description

This plugin detects which SSL ciphers are supported by the remote service for encrypting communications.

See Also

<https://www.openssl.org/docs/man1.0.2/man1/ciphers.html>
<http://www.nessus.org/u?e17ffced>

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2006/06/05, Modification date: 2023/07/10

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

Here is the list of SSL ciphers supported by the remote server :
Each group is reported per SSL Version.

SSL Version : TLSv12
Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name Code KEX Auth Encryption MAC

DES-CBC3-SHA 0x00, 0x0A RSA RSA 3DES-CBC(168) SHA1

High Strength Ciphers (>= 112-bit key)

Name Code KEX Auth Encryption MAC

DHE-RSA-AES128-SHA256 0x00, 0x9E DH RSA AES-GCM(128) SHA256
DHE-RSA-AES256-SHA384 0x00, 0x9F DH RSA AES-GCM(256) SHA384
ECDHE-RSA-AES128-SHA256 0xC0, 0x2F ECDH RSA AES-GCM(128) SHA256
ECDHE-RSA-AES256-SHA384 0xC0, 0x30 ECDH RSA AES-GCM(256) SHA384
RSA-AES128-SHA256 0x00, 0x9C RSA RSA AES-GCM(128) SHA256
RSA-AES256-SHA384 0x00, 0x9D RSA RSA AES-GCM(256) SHA384
ECDHE-RSA-AES128-SHA 0xC0, 0x13 ECDH RSA AES-CBC(128) SHA1
ECDHE-RSA-AES256-SHA 0xC0, 0x14 ECDH RSA AES-CBC(256) SHA1
AES128-SHA 0x00, 0x2F RSA RSA AES-CBC(128) SHA1

```
AES256-SHA 0x00, 0x35 RSA RSA AES-CBC(256) SHA1
ECDHE-RSA-AES128-SHA256 0xC0, 0x27 ECDH RSA AES-CBC(128) SHA256
ECDHE-RSA-AES256-SHA384 0xC0, 0x28 ECDH RSA AES-CBC(256) SHA384
RSA-AES128-SHA256 0x00, 0x3C RSA [...]
```

22964 - Service Detection

[-/+]

Synopsis

The remote service could be identified.

Description

Nessus was able to identify the remote service by its banner or by looking at the error message it sends when it receives an HTTP request.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2007/08/19, Modification date: 2023/07/10

Ports

10.13.30.105 (TCP/21) Vulnerability State: Active

An FTP server is running on this port.

10.13.30.105 (TCP/5985) Vulnerability State: Active

A web server is running on this port.

24260 - HyperText Transfer Protocol (HTTP) Information

[-/+]

Synopsis

Some information about the remote HTTP configuration can be extracted.

Description

This test gives some information about the remote HTTP protocol - the version used, whether HTTP Keep-Alive and HTTP pipelining are enabled, etc...

This test is informational only and does not denote any security problem.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2007/01/30, Modification date: 2019/11/22

Ports**10.13.30.105 (TCP/5985) Vulnerability State: Active**

Response Code : HTTP/1.1 404 Not Found

Protocol version : HTTP/1.1

SSL : no

Keep-Alive : no

Options allowed : (Not implemented)

Headers :

Content-Type: text/html; charset=us-ascii

Server: Microsoft-HTTPAPI/2.0

Date: Fri, 05 Jan 2024 17:55:10 GMT

Connection: close

Content-Length: 315

Response Body :

25220 - TCP/IP Timestamps Supported

[-/+]

Synopsis

The remote service implements TCP timestamps.

Description

The remote host implements TCP timestamps, as defined by RFC1323. A side effect of this feature is that the uptime of the remote host can sometimes be computed.

See Also

<http://www.ietf.org/rfc/rfc1323.txt>

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2007/05/16, Modification date: 2023/10/17

Ports**10.13.30.105 (TCP/0) Vulnerability State: Active**

33139 - WS-Management Server Detection

[-/+]

Synopsis

The remote web server is used for remote management.

Description

The remote web server supports the Web Services for Management (WS-Management) specification, a general web services protocol based on SOAP for managing systems, applications, and other such entities.

See Also

<https://www.dmtf.org/standards/ws-man>

<https://en.wikipedia.org/wiki/WS-Management>

Solution

Limit incoming traffic to this port if desired.

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2008/06/11, Modification date: 2021/05/19

Ports

10.13.30.105 (TCP/5985) Vulnerability State: Active

Here is some information about the WS-Management Server :

Product Vendor : Microsoft Corporation

Product Version : OS: 0.0.0 SP: 0.0 Stack: 3.0

42873 - SSL Medium Strength Cipher Suites Supported (SWEET32) [-/+]

Synopsis

The remote service supports the use of medium strength SSL ciphers.

Description

The remote host supports the use of SSL ciphers that offer medium strength encryption. Nessus regards medium strength as any encryption that uses key lengths at least 64 bits and less than 112 bits, or else that uses the 3DES encryption suite.

Note that it is considerably easier to circumvent medium strength encryption if the attacker is on the same physical network.

See Also

<https://www.openssl.org/blog/blog/2016/08/24/sweet32/>

<https://sweet32.info>

Solution

Reconfigure the affected application if possible to avoid use of medium strength ciphers.

Risk Factor

Medium

Vulnerability Priority Rating (VPR)

6.1

CVSS v3.0 Base Score

7.5 (AV:N/AC:L/PR:N/UI:N/S:U/C:H/I:N/A:N)

CVSS Base Score

5.0 (AV:N/AC:L/Au:N/C:P/I:N/A:N)

References

CVE

[CVE-2016-2183](#)**Exploitable with**

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2009/11/23, Modification date: 2021/02/03

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name Code KEX Auth Encryption MAC

DES-CBC3-SHA 0x00, 0x0A RSA RSA 3DES-CBC(168) SHA1

The fields above are :

```

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

```

45112 - FileZilla Server < 0.9.31 Denial of Service

[-/+]

Synopsis

The remote FTP server is prone to a denial of service attack.

Description

According to its banner, the version of FileZilla Server installed on the remote host is older than version 0.9.31. An unspecified vulnerability in the SSL code for such versions can be exploited by a remote attacker to trigger a denial of service condition.

See Alsohttp://sourceforge.net/project/shownotes.php?release_id=665428**Solution**

Upgrade to FileZilla Server version 0.9.31 or later.

Risk Factor

Medium

Vulnerability Priority Rating (VPR)

2.7

CVSS Base Score

5.0 (AV:N/AC:L/Au:N/C:N/I:N/A:P)

CVSS Temporal Score

3.7 (E:U/RL:OF/RC:C)

References

CVE	CVE-2009-0884
BID	34006
XREF	CWE-119
XREF	SECUNIA-34089

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2010/03/19, Modification date: 2018/07/11

Ports

10.13.30.105 (TCP/21) Vulnerability State: Active

The remote FileZilla server returned the following banner :

FileZilla Server version 0.8.1 beta

45410 - SSL Certificate 'commonName' Mismatch [-/+]

Synopsis

The 'commonName' (CN) attribute in the SSL certificate does not match the hostname.

Description

The service running on the remote host presents an SSL certificate for which the 'commonName' (CN) attribute does not match the hostname on which the service listens.

Solution

If the machine has several names, make sure that users connect to the service through the DNS hostname that matches the common name in the certificate.

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2010/04/03, Modification date: 2021/03/09

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

The host name known by Nessus is :

ip-10-13-30-105.ec2.internal

The Common Name in the certificate is :

ec2amaz-2t6h6f1

45590 - Common Platform Enumeration (CPE)

[-/+]

Synopsis

It was possible to enumerate CPE names that matched on the remote system.

Description

By using information obtained from a Nessus scan, this plugin reports CPE (Common Platform Enumeration) matches for various hardware and software products found on a host.

Note that if an official CPE is not available for the product, this plugin computes the best possible CPE based on the information available from the scan.

See Also

<http://cpe.mitre.org/>

<https://nvd.nist.gov/products/cpe>

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2010/04/21, Modification date: 2023/12/27

Ports**10.13.30.105 (TCP/0) Vulnerability State: Active**

The remote operating system matched the following CPE :

cpe:/o:microsoft:windows -> Microsoft Windows

51192 - SSL Certificate Cannot Be Trusted

[-/+]

Synopsis

The SSL certificate for this service cannot be trusted.

Description

The server's X.509 certificate cannot be trusted. This situation can occur in three different ways, in which the chain of trust can be broken, as stated below :

- First, the top of the certificate chain sent by the server might not be descended from a known public certificate authority. This can occur either when the top of the chain is an unrecognized, self-signed certificate, or when intermediate certificates are missing that would connect the top of the certificate chain to a known public certificate authority.
- Second, the certificate chain may contain a certificate that is not valid at the time of the scan. This can occur either when the scan occurs before one of the certificate's 'notBefore' dates, or after one of the certificate's 'notAfter' dates.
- Third, the certificate chain may contain a signature that either didn't match the certificate's information or could not be verified. Bad signatures can be fixed by getting the certificate with the bad signature to be re-signed by its issuer. Signatures that could not be verified are the result of the certificate's issuer using a signing algorithm that Nessus either does not support or does not recognize.

If the remote host is a public host in production, any break in the chain makes it more difficult for users to verify the authenticity and identity of the web server. This could make it easier to carry out man-in-the-middle attacks against the remote host.

See Also

<https://www.itu.int/rec/T-REC-X.509/en>

<https://en.wikipedia.org/wiki/X.509>

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS Base Score

6.4 (AV:N/AC:L/Au:N/C:P/I:P/A:N)

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2010/12/15, Modification date: 2020/04/27

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

The following certificate was at the top of the certificate chain sent by the remote host, but it is signed by an unknown certificate authority :

| -Subject : CN=EC2AMAZ-2T6H6FL
| -Issuer : CN=EC2AMAZ-2T6H6FL

54615 - Device Type

[-/+]

Synopsis

It is possible to guess the remote device type.

Description

Based on the remote operating system, it is possible to determine what the remote system type is (eg: a printer, router, general-purpose computer, etc).

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2011/05/23, Modification date: 2022/09/09

Ports

10.13.30.105 (TCP/0) Vulnerability State: Active

Remote device type : general-purpose
Confidence level : 70

57041 - SSL Perfect Forward Secrecy Cipher Suites Supported

[-/+]

Synopsis

The remote service supports the use of SSL Perfect Forward Secrecy ciphers, which maintain confidentiality even if the key is stolen.

Description

The remote host supports the use of SSL ciphers that offer Perfect Forward Secrecy (PFS) encryption. These cipher suites ensure that recorded SSL traffic cannot be broken at a future date if the server's private key is compromised.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

https://en.wikipedia.org/wiki/Diffie-Hellman_key_exchange

https://en.wikipedia.org/wiki/Perfect_forward_secrecy

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2011/12/07, Modification date: 2021/03/09

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

Here is the list of SSL PFS ciphers supported by the remote server :

High Strength Ciphers (>= 112-bit key)

Name Code KEX Auth Encryption MAC

```
-----
DHE-RSA-AES128-SHA256 0x00, 0x9E DH RSA AES-GCM(128) SHA256
DHE-RSA-AES256-SHA384 0x00, 0x9F DH RSA AES-GCM(256) SHA384
ECDHE-RSA-AES128-SHA256 0xC0, 0x2F ECDH RSA AES-GCM(128) SHA256
ECDHE-RSA-AES256-SHA384 0xC0, 0x30 ECDH RSA AES-GCM(256) SHA384
ECDHE-RSA-AES128-SHA 0xC0, 0x13 ECDH RSA AES-CBC(128) SHA1
ECDHE-RSA-AES256-SHA 0xC0, 0x14 ECDH RSA AES-CBC(256) SHA1
ECDHE-RSA-AES128-SHA256 0xC0, 0x27 ECDH RSA AES-CBC(128) SHA256
ECDHE-RSA-AES256-SHA384 0xC0, 0x28 ECDH RSA AES-CBC(256) SHA384
```

The fields above are :

```
{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}
```

57582 - SSL Self-Signed Certificate

[-/+]

Synopsis

The SSL certificate chain for this service ends in an unrecognized self-signed certificate.

Description

The X.509 certificate chain for this service is not signed by a recognized certificate authority. If the remote host is a public host in production, this nullifies the use of SSL as anyone could establish a man-in-the-middle attack against the remote host.

Note that this plugin does not check for certificate chains that end in a certificate that is not self-signed, but is signed by an unrecognized certificate authority.

Solution

Purchase or generate a proper SSL certificate for this service.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (AV:N/AC:L/PR:N/UI:N/S:U/C:L/I:L/A:N)

CVSS Base Score

6.4 (AV:N/AC:L/Au:N/C:P/I:P/A:N)

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2012/01/17, Modification date: 2022/06/14

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

The following certificate was found at the top of the certificate chain sent by the remote host, but is self-signed and was not found in the list of known certificate authorities :

| -Subject : CN=EC2AMAZ-2T6H6FL

64814 - Terminal Services Use SSL/TLS

[-/+]

Synopsis

The remote Terminal Services use SSL/TLS.

Description

The remote Terminal Services is configured to use SSL/TLS.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2013/02/22, Modification date: 2023/07/10

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

Subject Name:

Common Name: EC2AMAZ-2T6H6FL

Issuer Name:

Common Name: EC2AMAZ-2T6H6FL

Serial Number: 7B 21 C7 C3 43 87 B3 A7 48 15 30 99 49 A5 8F 98

Version: 3

Signature Algorithm: SHA-256 With RSA Encryption

Not Valid Before: Dec 26 18:49:04 2023 GMT

Not Valid After: Jun 26 18:49:04 2024 GMT

Public Key Info:

Algorithm: RSA Encryption

Key Length: 2048 bits

Public Key: 00 D5 32 49 E1 C3 B4 BB 35 7B 54 74 D4 2B FA 80 17 DC 82 07
37 F9 E5 5C 9D D2 72 F0 CA E2 74 E1 7D 03 8B 21 C1 35 12 0C
50 11 64 9C 71 33 D8 5C E9 C2 06 49 26 1B 45 12 D3 54 66 9F
F3 2B E6 8F E2 44 06 AE EB B5 D3 AC 3D 8E E5 94 39 15 94 CD
F7 94 B1 FD 05 11 88 E1 09 C2 1D 07 C6 A2 CE C1 E1 AC 54 F5
F6 CB 56 CC 93 2B DC AF C8 D6 D0 5B 20 87 17 E4 E3 3C 47 D7
5A 8B B0 A2 BB 39 53 28 2C EB 62 A5 15 3F E2 F1 83 3B 3C ED
2E 8C 37 4F 50 80 D7 2F 86 85 C0 2C 9A 89 89 6B CA B5 A0 8E
02 33 17 39 2A 35 D9 CD D1 4E C4 05 AE D7 79 29 29 7B 3C F2
80 B2 22 AE 0A CE 08 AE 39 68 CD E3 59 1C 75 06 0F 09 FD 82
AD AF 4C 1D 1B ED 20 57 CD 6B 18 67 57 45 CE CF 2E C0 BA 4F
64 17 E8 E7 85 EA F1 59 F8 BE D5 5E 00 51 46 61 C8 02 7A 40
2F 36 00 C1 88 B7 07 AF 7E 0D 96 63 5F 28 A5 2E 0D
Exponent: 01 00 01

Signature Length: 256 bytes / 2048 bits

Signature: 00 D2 E6 40 66 06 17 C4 6A A2 B2 30 15 88 83 CB 96 45 49 48
76 77 95 AD B0 7C C8 DB C0 15 26 95 B2 41 D2 51 B8 8F 31 77
36 FD FA D8 D8 4D 7F 18 32 A8 CC 73 F7 83 62 FD 1E AF 40 F2
A1 C4 A1 A5 D0 6E C5 CD FF 05 EC EA A4 75 97 62 5D 74 2D 8C
F2 46 A1 D7 E5 3F 06 07 D9 01 9E C4 BE 3A BE 95 91 F9 F2 81
C7 20 27 DD D1 21 C8 78 44 DB 3E 34 36 C6 06 CC EE 75 02 34
2A 8B A3 32 FD B1 94 67 96 62 0F 4C F1 77 07 FD 66 B2 6E DD
0E 3A B3 CA 07 39 B5 DA 94 D8 87 F5 1C D4 46 A2 D6 52 12 C3
33 C9 40 56 94 B6 52 89 41 EF A6 2B 0B BA F6 EC 58 0E 7D 08
17 0A 74 50 2B [...]

66334 - Patch Report

[-/+]

Synopsis

The remote host is missing several patches.

Description

The remote host is missing one or more security patches. This plugin lists the newest version of each patch to install to make sure the remote host is up-to-date.

Note: Because the 'Show missing patches that have been superseded' setting in your scan policy depends on this plugin, it will always run and cannot be disabled.

Solution

Install the patches listed below.

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2013/07/08, Modification date: 2024/01/02

Ports

10.13.30.105 (TCP/0) Vulnerability State: Active

. You need to take the following action :

[FileZilla Server < 0.9.31 Denial of Service (45112)]

+ Action to take : Upgrade to FileZilla Server version 0.9.31 or later.

70544 - SSL Cipher Block Chaining Cipher Suites Supported

[-/+]

Synopsis

The remote service supports the use of SSL Cipher Block Chaining ciphers, which combine previous blocks with subsequent ones.

Description

The remote host supports the use of SSL ciphers that operate in Cipher Block Chaining (CBC) mode. These cipher suites offer additional security over Electronic Codebook (ECB) mode, but have the potential to leak information if used improperly.

See Also

<https://www.openssl.org/docs/manmaster/man1/ciphers.html>

<http://www.nessus.org/u?cc4a822a>

<https://www.openssl.org/~bodo/tls-cbc.txt>

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2013/10/22, Modification date: 2021/02/03

Ports**10.13.30.105 (TCP/3389) Vulnerability State: Active**

Here is the list of SSL CBC ciphers supported by the remote server :

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name Code KEX Auth Encryption MAC

DES-CBC3-SHA 0x00, 0x0A RSA RSA 3DES-CBC(168) SHA1

High Strength Ciphers (>= 112-bit key)

Name Code KEX Auth Encryption MAC

ECDHE-RSA-AES128-SHA 0xC0, 0x13 ECDH RSA AES-CBC(128) SHA1
ECDHE-RSA-AES256-SHA 0xC0, 0x14 ECDH RSA AES-CBC(256) SHA1

```

AES128-SHA 0x00, 0x2F RSA RSA AES-CBC(128) SHA1
AES256-SHA 0x00, 0x35 RSA RSA AES-CBC(256) SHA1
ECDHE-RSA-AES128-SHA256 0xC0, 0x27 ECDH RSA AES-CBC(128) SHA256
ECDHE-RSA-AES256-SHA384 0xC0, 0x28 ECDH RSA AES-CBC(256) SHA384
RSA-AES128-SHA256 0x00, 0x3C RSA RSA AES-CBC(128) SHA256
RSA-AES256-SHA256 0x00, 0x3D RSA RSA AES-CBC(256) SHA256

```

The fields above are :

```

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

```

86420 - Ethernet MAC Addresses

[-/+]

Synopsis

This plugin gathers MAC addresses from various sources and consolidates them into a list.

Description

This plugin gathers MAC addresses discovered from both remote probing of the host (e.g. SNMP and Netbios) and from running local checks (e.g. ifconfig). It then consolidates the MAC addresses into a single, unique, and uniform list.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2015/10/16, Modification date: 2020/05/13

Ports

10.13.30.105 (TCP/0) Vulnerability State: Active

The following is a consolidated list of detected MAC addresses:

- 02:3E:49:80:3E:17

104743 - TLS Version 1.0 Protocol Detection

[-/+]

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.0. TLS 1.0 has a number of cryptographic design flaws. Modern implementations of TLS 1.0 mitigate these problems, but newer versions of TLS like 1.2 and 1.3 are designed against these flaws and should be used whenever possible.

As of March 31, 2020, Endpoints that aren't enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

PCI DSS v3.2 requires that TLS 1.0 be disabled entirely by June 30, 2018, except for POS POI terminals (and the SSL/TLS termination points to which they connect) that can be verified as not being susceptible to any known exploits.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

Solution

Enable support for TLS 1.2 and 1.3, and disable support for TLS 1.0.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS Base Score

6.1 (AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF

CWE-327

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2017/11/22, Modification date: 2023/04/19

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

TLSv1 is enabled and the server supports at least one cipher.

121010 - TLS Version 1.1 Protocol Detection

[-/+]

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://tools.ietf.org/html/draft-ietf-tls-oldversions-deprecate-00>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

None

References

XREF

CWE-327

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2019/01/08, Modification date: 2023/04/19

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

TLSv1.1 is enabled and the server supports at least one cipher.

136318 - TLS Version 1.2 Protocol Detection

[-/+]

Synopsis

The remote service encrypts traffic using a version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.2.

See Also

<https://tools.ietf.org/html/rfc5246>

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2020/05/04, Modification date: 2020/05/04

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

TLSv1.2 is enabled and the server supports at least one cipher.

156899 - SSL/TLS Recommended Cipher Suites

[-/+]

Synopsis

The remote host advertises discouraged SSL/TLS ciphers.

Description

The remote host has open SSL/TLS ports which advertise discouraged cipher suites. It is recommended to only enable support for the following cipher suites:

TLSv1.3:

- 0x13,0x01 TLS13_AES_128_GCM_SHA256
- 0x13,0x02 TLS13_AES_256_GCM_SHA384
- 0x13,0x03 TLS13_CHACHA20_POLY1305_SHA256

TLSv1.2:

- 0xC0,0x2B ECDHE-ECDSA-AES128-GCM-SHA256
- 0xC0,0x2F ECDHE-RSA-AES128-GCM-SHA256
- 0xC0,0x2C ECDHE-ECDSA-AES256-GCM-SHA384
- 0xC0,0x30 ECDHE-RSA-AES256-GCM-SHA384
- 0xCC,0xA9 ECDHE-ECDSA-CHACHA20-POLY1305
- 0xCC,0xA8 ECDHE-RSA-CHACHA20-POLY1305
- 0x00,0x9E DHE-RSA-AES128-GCM-SHA256
- 0x00,0x9F DHE-RSA-AES256-GCM-SHA384

This is the recommended configuration for the vast majority of services, as it is highly secure and compatible with nearly every client released in the last five (or more) years.

See Also

https://wiki.mozilla.org/Security/Server_Side_TLS

<https://ssl-config.mozilla.org/>

Solution

Only enable support for recommended cipher suites.

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2022/01/20, Modification date: 2023/07/10

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

The remote host has listening SSL/TLS ports which advertise the discouraged cipher suites outlined below:

Medium Strength Ciphers (> 64-bit and < 112-bit key, or 3DES)

Name Code KEX Auth Encryption MAC

DES-CBC3-SHA 0x00, 0x0A RSA RSA 3DES-CBC(168) SHA1

High Strength Ciphers (>= 112-bit key)

Name Code KEX Auth Encryption MAC

RSA-AES128-SHA256 0x00, 0x9C RSA RSA AES-GCM(128) SHA256
RSA-AES256-SHA384 0x00, 0x9D RSA RSA AES-GCM(256) SHA384
ECDHE-RSA-AES128-SHA 0xC0, 0x13 ECDH RSA AES-CBC(128) SHA1
ECDHE-RSA-AES256-SHA 0xC0, 0x14 ECDH RSA AES-CBC(256) SHA1
AES128-SHA 0x00, 0x2F RSA RSA AES-CBC(128) SHA1
AES256-SHA 0x00, 0x35 RSA RSA AES-CBC(256) SHA1
ECDHE-RSA-AES128-SHA256 0xC0, 0x27 ECDH RSA AES-CBC(128) SHA256
ECDHE-RSA-AES256-SHA384 0xC0, 0x28 ECDH RSA AES-CBC(256) SHA384
RSA-AES128-SHA256 0x00, 0x3C RSA RSA AES-CBC(128) SHA256
RSA-AES256-SHA256 0x00, 0x3D RSA RSA AES-CBC(256) SHA256

The fields above are :

{Tenable ciphername}
{Cipher ID code}
Kex={key exchange}
Auth={authentication}
Encrypt={symmetric encryption method}
MAC={message authentication code}
{export flag}

157288 - TLS Version 1.1 Protocol Deprecated

[-/+]

Synopsis

The remote service encrypts traffic using an older version of TLS.

Description

The remote service accepts connections encrypted using TLS 1.1. TLS 1.1 lacks support for current and recommended cipher suites. Ciphers that support encryption before MAC computation, and authenticated encryption modes such as GCM cannot be used with TLS 1.1

As of March 31, 2020, Endpoints that are not enabled for TLS 1.2 and higher will no longer function properly with major web browsers and major vendors.

See Also

<https://datatracker.ietf.org/doc/html/rfc8996>

<http://www.nessus.org/u?c8ae820d>

Solution

Enable support for TLS 1.2 and/or 1.3, and disable support for TLS 1.1.

Risk Factor

Medium

CVSS v3.0 Base Score

6.5 (AV:N/AC:H/PR:N/UI:N/S:U/C:H/I:L/A:N)

CVSS Base Score

6.1 (AV:N/AC:H/Au:N/C:C/I:P/A:N)

References

XREF CWE-327

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2022/04/04, Modification date: 2023/04/19

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

TLSv1.1 is enabled and the server supports at least one cipher.

56984 - SSL / TLS Versions Supported [-/+]

Synopsis

The remote service encrypts communications.

Description

This plugin detects which SSL and TLS versions are supported by the remote service for encrypting communications.

Solution

N/A

Risk Factor

None

Exploitable with

Metasploit, CANVAS, Core Impact

Plugin Information:

Publication date: 2011/12/01, Modification date: 2023/07/10

Ports

10.13.30.105 (TCP/3389) Vulnerability State: Active

This port supports TLSv1.0/TLSv1.1/TLSv1.2.

10.13.30.242

Scan Information

Start time: 2024/01/05 17:50