


Most Popular Coding Languages of 2016



By Ripal Ranpara

The 9 Most In-Demand Programming Languages


2017



8/22/2017



Job Trend



Per the indeed.com, percentage growth of Python is 500 times more than it's peer Languages.
<http://www.indeed.com/jobtrends?q=Perl%2C+.Net%2C+Python%2Cjava&l=&relative=1>

8/22/2017

By Ripal Ranpara

Job In Big Data space

| Skill | % of Big Data Jobs Mentioning This Skill Set (multiple responses allowed) | % Growth in Demand For This Skill Set Over the Previous Year |
|---------------------------|---------------------------------------------------------------------------------|--------------------------------------------------------------------|
| Java | 6.62% | 63.30% |
| Structured query language | 5.86% | 76.00% |
| Apache Hadoop | 5.45% | 49.10% |
| Software development | 4.70% | 60.30% |
| Linux | 4.10% | 76.60% |
| Python | 3.99% | 96.90% |
| NoSQL | 2.74% | 34.60% |
| Data warehousing | 2.73% | 68.80% |
| UNIX | 2.43% | 61.90% |
| Software as a Service | 2.38% | 54.10% |

Source: <http://www.forbes.com/sites/louiscolumbus/2014/12/29/where-big-data-jobs-will-be-in-2015/>

8/22/2017

By Ripal Ranpara

What is Scripting Language?

- A scripting language is a “wrapper” language that integrates OS functions.
- The interpreter is a layer of software logic between your code and the computer hardware on your machine.

Wiki Says:

- The “program” has an executable form that the computer can use directly to execute the instructions.
- The same program in its human-readable source code form, from which executable programs are derived (*e.g., compiled*)
- Python is scripting language, fast and dynamic.
- Python is called ‘scripting language’ because of its scalable interpreter, but actually it is much more than that

8/22/2017

By Ripal Ranpara

What is Python?

Python is a high-level programming language which is:


- **Interpreted:** Python is processed at runtime by the interpreter. (Next Slide)
- **Interactive:** You can use a Python prompt and interact with the interpreter directly to write your programs.
- **Object-Oriented:** Python supports Object-Oriented technique of programming.
- **Beginner's Language:** Python is a great language for the beginner-level programmers and supports the development of a wide range of applications.


Interpreters Versus Compilers

- The first thing that is important to understand about Python is that it is an interpreted language.
- There are two sorts of programming languages: interpreted ones and compiled ones. A compiled language is what you are probably used to if you have done any programming in the past. The
- process for a compiled language is as follows:

8/22/2017

By Ripal Ranpara

- 
- Create source file using text edit →
 - Use compiler to syntax check and convert source file into binary →
 - Use linker to turn binary files into executable format →
 - Run the resulting executable format file in the operating system.

- 
- The biggest difference between interpreted code and compiled code is that an interpreted application need not be “complete.”
 - You can test it in bits and pieces until you are satisfied with the results and put them all together later for the end user to use.

Python Features

- **Easy to learn, easy to read and easy to maintain.**
- **Portable:** It can run on various hardware platforms and has the same interface on all platforms.
- **Extendable:** You can add low-level modules to the Python interpreter.
- **Scalable:** Python provides a good structure and support for large programs.
- Python has support for an **interactive mode** of testing and debugging.
- Python has a broad standard **library** cross-platform.
- Everything in Python is an **object**: variables, functions, even code. Every object has an ID, a type, and a value.

```
>>> x=36
>>> id(x)
4297539008
>>> type(x)
<class 'int'>
```

8/22/2017

More Features ..

- Python provides interfaces to all major commercial **databases**.
- Python supports functional and structured programming methods as well as **OOP**.
- Python provides very high-level **dynamic** data types and supports dynamic type checking.
- Python supports **GUI** applications
- Python supports automatic **garbage collection**.
- Python can be easily **integrated** with C, C++, and Java.

Why Python

| | |
|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Easy to read | ✓ Python scripts have clear syntax, simple structure and very few protocols to remember before programming. |
| Easy to Maintain | ✓ Python code is easily to write and debug. Python's success is that its source code is fairly easy-to-maintain. |
| Portable | ✓ Python can run on a wide variety of Operating systems and platforms and providing the similar interface on all platforms. |
| Broad Standard Libraries | ✓ Python comes with many prebuilt libraries apx. 21K |
| High Level programming | ✓ Python is intended to make complex programming simpler. Python deals with memory addresses, garbage collection etc internally. |
| Interactive | ✓ Python provide an interactive shell to test the things before implementation. It provide the user the direct interface with Python. |
| Database Interfaces | ✓ Python provides interfaces to all major commercial databases. These interfaces are pretty easy to use. |
| GUI programming | ✓ Python supports GUI applications and has framework for Web. Interface to tkinter, WXPYthon, Django in Python make it . |

8/22/2017

History of Python

- Python was conceptualized by **Guido Van Rossum** in the late **1980s**.
- Rossum published the first version of Python code (0.9.0) in February **1991** at the CWI (Centrum Wiskunde & Informatica) in the Netherlands , Amsterdam.
- Python is derived from **ABC** programming language, which is a general-purpose programming language that had been developed at the CWI.
- Rossum chose the name "**Python**", since he was a big fan of Monty Python's Flying Circus.
- Python is now maintained by a core development team at the institute, although Rossum still holds a vital role in directing its progress.



https://en.wikipedia.org/wiki/Guido_van_Rossum#/media/File:Guido_van_Rossum_OSCON_2006.jpg
8/22/2017

Python Versions

Release dates for the major and minor versions:

✦ **Python 1.0** - January **1994**

- Python 1.5 - December 31, 1997
- Python 1.6 - September 5, 2000

✦ **Python 2.0** - October 16, **2000**

- Python 2.1 - April 17, 2001
- Python 2.2 - December 21, 2001
- Python 2.3 - July 29, 2003
- Python 2.4 - November 30, 2004
- Python 2.5 - September 19, 2006
- Python 2.6 - October 1, 2008
- Python 2.7 - July 3, 2010

8/22/2017

By Ripal Ranpara

Python Versions

Release dates for the major and minor versions:


✦ **Python 3.0** - December 3, **2008**

- Python 3.1 - June 27, 2009
- Python 3.2 - February 20, 2011
- Python 3.3 - September 29, 2012
- Python 3.4 - March 16, 2014
- Python 3.5 - September 13, 2015

8/22/2017

By Ripal Ranpara

Python time line



Key Changes in Python 3.0

- ★ Python 2's print statement has been replaced by the **print()** function.

Old: `print 'Hello, World!'`

New: `print('Hello, World!')`

- ★ There is only one integer type left, **int**.
- ★ Some methods such as map() and filter() return **iterator** objects in Python 3 instead of lists in Python 2.
- ★ In Python 3, a TypeError is raised as warning if we try to compare unorderable types. e.g. `1 < ''`, `0 > None` are **no** longer valid
- ★ Python 3 provides Unicode (**utf-8**) strings while Python 2 has ASCII str() types and separate unicode().
- ★ A new built-in string formatting method **format()** replaces the **%** string formatting operator.

Key Changes in Python 3.0

- ★ In Python 3, we should enclose the exception argument in parentheses.

Old: `raise IOError, "file error"`

New: `raise IOError("file error")`

- ★ In Python 3, we have to use the **as** keyword now in the handling of exceptions.

Old:

```
try:
    ...
except NameError, err:
    ...
```

New:

```
try:
    ...
except NameError as err:
    ...
```

- ★ The division of two integers returns a **float** instead of an integer. `"//"` can be used to have the "old" behavior.



Python Syntax

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Basic Syntax

- **Indentation** is used in Python to delimit blocks. The number of spaces is variable, but all statements within the same block must be indented the same amount.
- The header line for compound statements, such as if, while, def, and class should be terminated with a colon (:)
- The semicolon (;) is optional at the end of statement.

```
if True:
    print ("Answer")
    print ("True")
else:
    print ("Answer")
    print ("False") → Error!
```

- Printing to the Screen:
- Reading Keyboard Input:
- **Comments**

```
print ("Hello, Python!")
```


```
name = input("Enter your name: ")
```

- Single line:
- Multiple lines:

```
# This is a comment.
```

```
'''
print("We are in a comment")
print ("We are still in a comment")
'''
```

- Python files have extension **.py**



8/22/2017

By Ripal Ranpara

Variables

- Python is dynamically typed. You do not need to declare variables!
- The declaration happens automatically when you assign a value to a variable.
- Variables can change type, simply by assigning them a new value of a different type.
- Python allows you to assign a single value to several variables simultaneously.
- You can also assign multiple objects to multiple variables.

```
counter = 100      # An integer assignment
miles   = 1000.0   # A floating point
name    = "John"   # A string
z       = None     # A null value
```

```
x = 1
x = "string value"
```

```
a = b = c = 1
```

```
a, b, c = 1, 2, "john"
```



Python Data Types

By Ripal Ranpara

8/22/2017

Numbers

- Numbers are **Immutable** objects in Python that cannot change their values.
- There are three built-in data types for numbers in Python3:
 - Integer (int)
 - Floating-point numbers (float)
 - Complex numbers: *<real part> + <imaginary part>j* (not used much in Python programming)
- **Common Number Functions**

| Function | Description |
|-----------------|-----------------------------------------|
| int(x) | to convert x to an integer |
| float(x) | to convert x to a floating-point number |
| abs(x) | The absolute value of x |
| cmp(x,y) | -1 if x < y, 0 if x == y, or 1 if x > y |
| exp(x) | The exponential of x: e^x |
| log(x) | The natural logarithm of x, for $x > 0$ |
| pow(x,y) | The value of $x^{**}y$ |
| sqrt(x) | The square root of x for $x > 0$ |

8/22/2017

Strings

- Python Strings are **Immutable** objects that cannot change their values.

```
>>> str= "strings are immutable!"
>>> str[0]="S"
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: 'str' object does not support item assignment
```

- You can update an existing string by (re)assigning a variable to another string.
- Python *does not* support a character type; these are treated as strings of length one.
- Python accepts single ('), double (") and triple (""" or """) quotes to denote string literals.

```
name1 = "sample string"
name2 = 'another sample string'
name3 = """a multiline
string example"""
```

- String indexes starting at **0** in the beginning of the string and working their way from **-1** at the end.

| | | | | | |
|---|---|---|---|---|---|
| P | y | t | h | o | n |
| 0 | 1 | 2 | 3 | 4 | 5 |

| | | | | | |
|----|----|----|----|----|----|
| P | y | t | h | o | n |
| -6 | -5 | -4 | -3 | -2 | -1 |

8/22/2017

Strings

■ String Formatting

```
>>> num = 6
>>> str= "I have {} books!".format(num)
>>> print(str)
I have 6 books!
```

■ Common String Operators

Assume string variable **a** holds 'Hello' and variable **b** holds 'Python'

| Operator | Description | Example |
|----------|-------------------------------------------------------------------------------------------|---------------------------------------|
| + | Concatenation - Adds values on either side of the operator | a + b will give HelloPython |
| * | Repetition - Creates new strings, concatenating multiple copies of the same string | a*2 will give HelloHello |
| [] | Slice - Gives the character from the given index | a[1] will give e a[-1] will give o |
| [:] | Range Slice - Gives the characters from the given range | a[1:4] will give ell |
| in | Membership - Returns true if a character exists in the given string | 'H' in a will give True |

8/22/2017

By Ripal Ranpara

Strings

■ Common String Methods

| Method | Description |
|--------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| <code>str.count(sub, beg=0, end=len(str))</code> | Counts how many times sub occurs in string or in a substring of string if starting index beg and ending index end are given. |
| <code>str.isalpha()</code> | Returns True if string has at least 1 character and all characters are alphanumeric and False otherwise. |
| <code>str.isdigit()</code> | Returns True if string contains only digits and False otherwise. |
| <code>str.lower()</code> | Converts all uppercase letters in string to lowercase. |
| <code>str.upper()</code> | Converts lowercase letters in string to uppercase. |
| <code>str.replace(old, new)</code> | Replaces all occurrences of old in string with new. |
| <code>str.split(str=' ')</code> | Splits string according to delimiter str (space if not provided) and returns list of substrings. |
| <code>str.strip()</code> | Removes all leading and trailing whitespace of string. |
| <code>str.title()</code> | Returns "titlecased" version of string. |

■ Common String Functions

str(x) :to convert x to a string

len(string):gives the total length of the string

8/22/2017

Lists

- A list in Python is an **ordered** group of items or elements, and these list elements *don't have* to be of the same type.
- Python Lists are **mutable** objects that can change their values.
- A list contains items separated by *commas* and enclosed within *square brackets*.
- List indexes like strings starting at **0** in the beginning of the list and working their way from **-1** at the end.
- Similar to strings, Lists operations include **slicing** ([] and [:]) , **concatenation** (+), **repetition** (*), and **membership** (in).
- This example shows how to *access, update* and *delete* list elements:

```
>>> list = ['physics', 'chemistry', 1997, 2000, 2015]
>>> print (list[0])    → access
physics
>>> print (list[1:4])  → slice
['chemistry', 1997, 2000]
>>> list[2] = 1999     → update
>>> print (list[2])
1999
>>> del (list[4])      → delete
>>> print (list)
['physics', 'chemistry', 1999, 2000]
```

8/22/2017

By Ripal Ranpara

Lists

- Lists can have sublists as elements and these sublists may contain other sublists as well.

```
>>> person = ["Tahani", "Nasser"], ["Boulder", "CO"]
>>> first_name = person[0][0]
>>> city = person[1][0]
>>> print(first_name+" lives in "+ city)
Tahani lives in Boulder
```

- Common List Functions

| Function | Description |
|---------------------------|--------------------------------------------|
| cmp (list1, list2) | Compares elements of both lists. |
| len (list) | Gives the total length of the list. |
| max (list) | Returns item from the list with max value. |
| min (list) | Returns item from the list with min value. |
| list (tuple) | Converts a tuple into list. |

8/22/2017

Lists

■ Common List Methods

| Method | Description |
|--------------------------------------|----------------------------------------------------|
| <code>list.append(obj)</code> | Appends object obj to list |
| <code>list.insert(index, obj)</code> | Inserts object obj into list at offset index |
| <code>list.count(obj)</code> | Returns count of how many times obj occurs in list |
| <code>list.index(obj)</code> | Returns the lowest index in list that obj appears |
| <code>list.remove(obj)</code> | Removes object obj from list |
| <code>list.reverse()</code> | Reverses objects of list in place |
| <code>list.sort()</code> | Sorts objects of list in place |

■ List Comprehensions

Each list comprehension consists of an **expression** followed by a **for** clause.

```
>>> a = [1, 2, 3]
>>> [x ** 2 for x in a] → List comprehension
[1, 4, 9]
>>> z = [x + 1 for x in [x ** 2 for x in a]]
>>> z
[2, 5, 10]
```

8/22/2017

By Ripal Ranpara

Python Reserved Words

A keyword is one that means something to the language. In other words, you can't use a reserved word as the name of a variable, a function, a class, or a module. All the Python keywords contain lowercase letters only.

| | | |
|-----------------|----------------|---------------|
| and | exec | not |
| assert | finally | or |
| break | for | pass |
| class | from | print |
| continue | global | raise |
| def | if | return |
| del | import | try |
| elif | in | while |
| else | is | with |
| except | lambda | yield |

8/22/2017

By Ripal Ranpara

Tuples

- Python Tuples are **Immutable** objects that cannot be changed once they have been created.
- A tuple contains items separated by *commas* and enclosed in *parentheses* instead of square brackets.

```
>>> t = ("tuples", "are", "immutable")
>>> t[0] → access
'tuples'
>>> t[0]="assignments to elements are not possible"
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
TypeError: 'tuple' object does not support item assignment → No update
```

- You can update an existing tuple by (re)assigning a variable to another tuple.
- Tuples are **faster** than lists and **protect** your data against accidental changes to these data.
- The rules for tuple **indices** are the same as for lists and they have the same **operations, functions** as well.
- To write a tuple containing a single value, you have to include a *comma*, even though there is only one value. e.g. `t = (3,)`

8/22/2017

By Ripal Ranpara

Hash Table


- Hashing is a technique that is used to uniquely identify a specific object from a group of similar objects.

Assume that you have an object and you want to assign a key to it to make searching easy.

To store the key/value pair, you can use a simple array like a data structure where keys (integers) can be used directly as an index to store values.

However, in cases where the keys are large and cannot be used directly as an index, you should use *hashing*.

By Ripal Ranpara



8/22/2017

Dictionary

- Python's dictionaries are kind of hash table type which consist of **key-value** pairs of **unordered** elements.
 - **Keys** : must be immutable data types ,usually numbers or strings.
 - **Values** : can be any arbitrary Python object.
- Python Dictionaries are **mutable** objects that can change their values.
- A dictionary is enclosed by *curly braces* (`{ }`), the items are separated by *commas*, and each key is separated from its value by a *colon* (`:`).
- Dictionary's values can be assigned and accessed using square braces (`[]`) with a key to obtain its value.

Dictionary

- This example shows how to *access*, *update* and *delete* dictionary elements:

```
dict = {'Name': 'Jood', 'Age': 9, 'Grade': '5th'}
# Access Dictionary
print ("dict['Name']: ", dict['Name'])
print ("dict['Age']: ", dict['Age'])
print(dict.keys())           #list of dict's keys
print(dict.values())         #list of dict's values
print(dict.items())          #list of dict's tuple pairs

# Update Dictionary
dict['Age'] = 10              # update existing entry
dict['School'] = "Fireside Elementary School" # Add new entry

print ("dict['Age']: ", dict['Age'])
print ("dict['School']: ", dict['School'])

# Delete Dictionary
del dict['Name']             # remove entry with key 'Name'
print (dict)
dict.clear()                 # remove all entries in dict
print (dict)
del dict                     # delete entire dictionary
print (dict)
```

- The output:

```
dict['Name']: Jood
dict['Age']: 9
dict_keys(['Name', 'Grade', 'Age'])
dict_values(['Jood', '5th', 9])
dict_items([('Name', 'Jood'), ('Grade', '5th'), ('Age', 9)])
dict['Age']: 10
dict['School']: Fireside Elementary School
{'School': 'Fireside Elementary School', 'Grade': '5th', 'Age': 10}
{}
<class 'dict'>
```

8/22/2017

Dictionary

■ Common Dictionary Functions

- **cmp(dict1, dict2)** : compares elements of both dict.
- **len(dict)** : gives the total number of (key, value) pairs in the dictionary.

■ Common Dictionary Methods

| Method | Description |
|--------------------------------------|--------------------------------------------------------------------|
| dict. keys() | Returns list of dict's keys |
| dict. values() | Returns list of <i>dict</i> 's values |
| dict. items() | Returns a list of <i>dict</i> 's (key, value) tuple pairs |
| dict. get (key, default=None) | For key, returns value or default if key not in dict |
| dict. has_key (key) | Returns <i>True</i> if key in <i>dict</i> , <i>False</i> otherwise |
| dict. update (dict2) | Adds <i>dict2</i> 's key-values pairs to <i>dict</i> |
| dict. clear () | Removes all elements of <i>dict</i> |

8/22/2017



Python Control Structures

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Conditionals

- In Python, **True** and **False** are Boolean objects of class '**bool**' and they are **immutable**.
- Python assumes any **non-zero** and **non-null** values as **True**, otherwise it is **False** value.
- Python *does not* provide switch or case statements as in other languages.
- **Syntax:**

if Statement

```
if expression:  
    statement(s)
```

if..else Statement

```
if expression:  
    statement(s)  
else:  
    statement(s)
```

if..elif..else Statement

```
if expression1:  
    statement(s)  
elif expression2:  
    statement(s)  
elif expression3:  
    statement(s)  
else:  
    statement(s)
```

- **Example:**

```
x = int(input("Please enter an integer: "))  
if x < 0:  
    x = 0  
    print('Negative changed to zero')  
elif x == 0:  
    print('Zero')  
elif x == 1:  
    print('Single')  
else:  
    print('More')
```

8/22/2017

Conditionals

■ Using the conditional expression

Another type of conditional structure in Python, which is very convenient and easy to read.

```
a, b = 4, 5  
  
if a < b:  
    x = 'smaller'  
else:  
    x = 'bigger'  
  
print (x)
```



```
x = 'smaller' if a < b else 'bigger'
```

Loops

■ The For Loop

```
# First Example
for letter in 'Python':
    print ('Current Letter :', letter)

# Second Example
fruits = ['banana', 'apple', 'mango']
for fruit in fruits:
    print ('Current fruit :', fruit)

# Third Example (Iterating by Sequence Index)
food = ['pizza', 'steak', 'rice']
for index in range(len( food )):      # range(3) iterates between 0 to 2
    print ('Current food :', food[index])
```

```
Current Letter : P
Current Letter : y
Current Letter : t
Current Letter : h
Current Letter : o
Current Letter : n
Current fruit : banana
Current fruit : apple
Current fruit : mango
Current food : pizza
Current food : steak
Current food : rice
```

■ The while Loop

```
count = 0
while (count < 5):
    print ('The count is:', count)
    count = count + 1
```

```
The count is: 0
The count is: 1
The count is: 2
The count is: 3
The count is: 4
```

8/22/2017

Loops

Loop Control Statements

- **break** :Terminates the loop statement and transfers execution to the statement immediately following the loop.

```
for letter in 'Python':  
    if letter == 'h':  
        break  
    print ('Current Letter :', letter)
```

```
Current Letter : P  
Current Letter : y  
Current Letter : t
```

- **continue** :Causes the loop to skip the remainder of its body and immediately retest its condition prior to reiterating.

```
for letter in 'Python':  
    if letter == 'h':  
        continue  
    print ('Current Letter :', letter)
```

```
Current Letter : P  
Current Letter : y  
Current Letter : t  
Current Letter : o  
Current Letter : n
```

- **pass** :Used when a statement is required syntactically but you do not want any command or code to execute.

```
for letter in 'Python':  
    if letter == 'h':  
        pass  
    print ('This is pass block')  
    print ('Current Letter :', letter)
```

```
Current Letter : P  
Current Letter : y  
Current Letter : t  
This is pass block  
Current Letter : h  
Current Letter : o  
Current Letter : n
```

8/22/2017



Python Functions

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Functions

A function is a block of organized, reusable code that is used to perform a **single, related action**. Functions provide better modularity for your application and a high degree of code reusing.

Defining a Function

- Function blocks begin with the **keyword `def`** followed by the function name and parentheses (`)`).
- Any input parameters or **arguments** should be placed **within these parentheses**. You can also define parameters inside these parentheses.
- The first statement of a function can be an optional statement - the documentation string of the function or *docstring*.
- The code block within every function starts with a **colon (`:`)** and is indented.
- The statement **`return [expression]`** exits a function, optionally passing back an expression to the caller. A return statement with no arguments is the same as `return None`.

Functions

■ Function Syntax

```
def functionname( parameters ):  
    "function_docstring"  
    function_statements  
    return [expression]
```

```
def printme( str ):  
    "This prints a passed string into this function"  
    print str  
    return
```

■ Function Arguments

You can call a function by using any of the following types of arguments:

- **Required arguments:** the arguments passed to the function in correct positional order.
- **Keyword arguments:** the function call identifies the arguments by the parameter names.
- **Default arguments:** the argument has a default value in the function declaration used when the value is not provided in the function call.

```
def func( name, age ):  
    ....  
    func("Alex", 50)
```

```
def func( name, age ):  
    ....  
    func( age=50, name="Alex" )
```

```
def func( name, age = 35 ):  
    ...  
    func( "Alex" )
```

Functions

- **Variable-length arguments:** This is used when you need to process unspecified additional arguments. An asterisk (*) is placed before the variable name in the function declaration.

```
def printinfo( arg1, *vartuple ):  
    print ("Output is: ")  
    print (arg1)  
    for var in vartuple:  
        print (var)  
    return  
  
printinfo( 5 )  
printinfo( 10, 20, 30 )
```

```
Output is:  
5  
Output is:  
10  
20  
30
```



Python File Handling

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

File Handling

- **File opening** `fileObject = open(file_name [, access_mode][, buffering])`

Common access modes:

- “**r**” opens a file for reading only.
- “**w**” opens a file for writing only. Overwrites the file if the file exists. Otherwise, it creates a new file.
- “**a**” opens a file for appending. If the file does not exist, it creates a new file for writing.

- **Closing a file** `fileObject.close()`

The `close()` method flushes any unwritten information and closes the file object.

File Handling

■ Reading a file `fileObject.read([count])`

- The ***read()*** method reads the whole file at once.
- The ***readline()*** method reads one line each time from the file.
- The ***readlines()*** method reads all lines from the file in a list.

■ Writing in a file `fileObject.write(string)`

The write() method writes any string to an open file.



Python Exception Handling

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Exception Handling

- Common Exceptions in Python:

NameError - TypeError - IndexError - KeyError - Exception

- Exception Handling Syntax:

```
try:
    statements to be inside try clause
    statement2
    statement3
    ...
except ExceptionName:
    statements to be evaluated in case of ExceptionName happens
```

- An empty except statement can catch any exception.
- **finally** clause: always executed before finishing try statements.

```
try:
    fobj = open("hello.txt", "w")
    res = 12 / 0
except ZeroDivisionError:
    print("We have an error in division")
finally:
    fobj.close()
    print("Closing the file object.")
```



We have an error in division
Closing the file object.

8/22/2017

| EXCEPTION NAME | DESCRIPTION |
|--------------------|-----------------------------------------------------------------------------|
| Exception | Base class for all exceptions |
| StopIteration | Raised when the next() method of an iterator does not point to any object. |
| SystemExit | Raised by the sys.exit() function. |
| StandardError | Base class for all built-in exceptions except StopIteration and SystemExit. |
| ArithmeticError | Base class for all errors that occur for numeric calculation. |
| OverflowError | Raised when a calculation exceeds maximum limit for a numeric type. |
| FloatingPointError | Raised when a floating point calculation fails. |
| ZeroDivisionError | Raised when division or modulo by zero takes place for all numeric types. |
| AssertionError | Raised in case of failure of the Assert statement. |

By Ripal Ranpara

8/22/2017

| | |
|-------------------|---------------------------------------------------------------------------------------------------------------|
| AttributeError | Raised in case of failure of attribute reference or assignment. |
| EOFError | Raised when there is no input from either the raw_input() or input() function and the end of file is reached. |
| ImportError | Raised when an import statement fails. |
| KeyboardInterrupt | Raised when the user interrupts program execution, usually by pressing Ctrl+c. |
| LookupError | Base class for all lookup errors. |
| IndexError | Raised when an index is not found in a sequence. |
| KeyError | Raised when the specified key is not found in the dictionary. |
| NameError | Raised when an identifier is not found in the local or global namespace. |
| UnboundLocalError | Raised when trying to access a local variable in a function or method but no value has been assigned to it. |
| EnvironmentError | Base class for all exceptions that occur outside the Python environment. |

| | |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IOError IOError | Raised when an input/ output operation fails, such as the print statement or the open() function when trying to open a file that does not exist. Raised for operating system-related errors. |
| SyntaxError IndentationError | Raised when there is an error in Python syntax. Raised when indentation is not specified properly. |
| SystemError | Raised when the interpreter finds an internal problem, but when this error is encountered the Python interpreter does not exit. |
| SystemExit | Raised when Python interpreter is quit by using the sys.exit() function. If not handled in the code, causes the interpreter to exit. |
| TypeError | Raised when an operation or function is attempted that is invalid for the specified data type. |
| ValueError | Raised when the built-in function for a data type has the valid type of arguments, but the arguments have invalid values specified. |
| RuntimeError | Raised when a generated error does not fall into any category. |
| NotImplementedError | Raised when an abstract method that needs to be implemented in an inherited class is not actually implemented. |



Python Modules

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Modules

- A module is a file consisting of Python code that can define functions, classes and variables.
- A module allows you to organize your code by grouping related code which makes the code easier to understand and use.
- You can use any Python source file as a module by executing an *import* statement

```
import module1[, module2[,... moduleN]
```

- Python's *from* statement lets you import **specific** attributes from a module into the current namespace.

```
from modname import name1[, name2[, ... nameN]]
```

- *import ** statement can be used to import **all** names from a module into the current namespace

```
from modname import *
```

8/22/2017

By Ripal Ranpara



Python Object Oriented

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Python Classes

```
class Employee:
    'Common base class for all employees'
    empCount = 0                                → Class variable

    def __init__(self, name, salary):           → Class constructor
        self.name = name
        self.salary = salary
        Employee.empCount += 1

    def displayCount(self):
        print ("Total Employee %d" % Employee.empCount)

    def displayEmployee(self):
        print ("Name : ", self.name, ", Salary: ", self.salary)

"This would create first object of Employee class"
emp1 = Employee("Zara", 2000)
"This would create second object of Employee class"
emp2 = Employee("Manni", 5000)
emp1.displayEmployee()
emp2.displayEmployee()
print ("Total Employee %d" % Employee.empCount)
```

Output →

| |
|-----------------------------|
| Name : Zara , Salary: 2000 |
| Name : Manni , Salary: 5000 |
| Total Employee 2 |

8/22/2017

By Ripal Ranpara

Python Classes

■ Built-in class functions

- **getattr(obj, name[, default])** : to access the attribute of object.
- **hasattr(obj,name)** : to check if an attribute exists or not.
- **setattr(obj,name,value)** : to set an attribute. If attribute does not exist, then it would be created.
- **delattr(obj, name)** : to delete an attribute.

```
hasattr(emp1, 'age')    # Returns true if 'age' attribute exists
setattr(emp1, 'age', 8) # Set attribute 'age' at 8
getattr(emp1, 'age')    # Returns value of 'age' attribute
delattr(emp1, 'age')    # Delete attribute 'age'
```

- **Data Hiding** You need to name attributes with *a double underscore prefix*, and those attributes then are not be directly visible to outsiders.

```
self.__name = name
self.__salary = salary
```


Class Inheritance

```
class Person:

    def __init__(self, name):
        self.name = name

    def get_details(self):
        "Returns a string containing name of the person"
        return self.name

class Student(Person):

    def __init__(self, name, branch, year):
        Person.__init__(self, name)
        self.branch = branch
        self.year = year


    def get_details(self):
        "Returns a string containing student's details."
        return "%s studies %s and is in %s year." % (self.name, self.branch, self.year)

person1 = Person('Alex')
student1 = Student('Jake', 'CSE', 2015)

print(person1.get_details())
print(student1.get_details())
```

```
Alex
Jake studies CSE and is in 2015 year.
```

8/22/2017



Python vs. Java

Code Examples

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Python vs. Java

■ Hello World

Java

```
public class Main {  
    public static void main(String[] args) {  
        System.out.println("hello world");  
    }  
}
```

Python

```
print ("hello world")
```

■ String Operations

Java

```
public static void main(String[] args) {  
    String test = "compare Java with Python";  
    for(String a : test.split(" "))  
        System.out.print(a);  
}
```

Python

```
a="compare Python with Java"  
print (a.split())
```

Python vs. Java

■ Collections

Java

```
import java.util.ArrayList;

public class Main {
    public static void main(String[] args) {
        ArrayList<String> al = new ArrayList<String>();
        al.add("a");
        al.add("b");
        al.add("c");
        System.out.println(al);
    }
}
```

Python

```
aList = []
aList.append("a")
aList.append("b")
aList.append("c")
print (aList)
```

8/22/2017

By Ripal Ranpara

Python vs. Java

■ Class and Inheritance

Java

```
class Animal{
    private String name;
    public Animal(String name){
        this.name = name;
    }
    public void saySomething(){
        System.out.println("I am " + name);
    }
}

class Dog extends Animal{
    public Dog(String name) {
        super(name);
    }
    public void saySomething(){
        System.out.println("I can bark");
    }
}

public class Main {
    public static void main(String[] args) {
        Dog dog = new Dog("Chiwawa");
        dog.saySomething();
    }
}
```

Python

```
class Animal():
    def __init__(self, name):
        self.name = name

    def saySomething(self):
        print ("I am " + self.name)

class Dog(Animal):
    def saySomething(self):
        print ("I am " + self.name \
              + ", and I can bark")

dog = Dog("Chiwawa")
dog.saySomething()
```

→ I am Chiwawa, and I can bark

8/22/2017



Python Useful Tools

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Useful Tools

■ Python IDEs

- Vim
- Eclipse with PyDev
- Sublime Text
- Emacs
- Komodo Edit
- PyCharm

8/22/2017

By Ripal Ranpara

Useful Tools

■ Python Web Frameworks

- Django
- Flask
- Pylons
- Pyramid
- TurboGears
- Web2py

8/22/2017

By Ripal Ranpara



Who Uses Python?

By Ripal Ranpara

8/22/2017

By Tahani Almanie | CSCI 5448

Organizations Use Python

- **Web Development** :Google, Yahoo
- **Games** :Battlefield 2, Crystal Space
- **Graphics** :Walt Disney Feature Animation, Blender 3D
- **Science** :National Weather Service, NASA, Applied Maths
- **Software Development** :Nokia, Red Hat, IBM
- **Education** :University of California-Irvine, SchoolTool
- **Government** :The USA Central Intelligence Agency (CIA)