



Java Foundations

7-5


Object Interaction and Encapsulation



Objectives

This lesson covers the following objectives:

- Understand object interaction in greater detail
- Use the `private` modifier to define class variables
- Understand the purpose of getter methods
- Understand the purpose of setter methods



Topics

- Object Interaction
- Access Modifiers
- Getters and Setters
- Encapsulation Assistance from NetBeans

Creating a
Class


Instantiating
Objects

Constructors

Overloading
Methods

Object
Interaction and
Encapsulation


Static
Variables
and
Methods



Section 7

Object Interaction

- Section 2 introduced the idea of object interaction.
 - No prescribed sequence for how object must interact.
- This lesson explores how to program interactions.



What Is Object Interaction?

- An object reference is a memory address.
 - A reference directs one object to another.
 - A reference allows one object to interact with another.
- Objects interact by ...
 - Accessing another object's fields.
 - Calling another object's methods.
- If the main method instantiates every object ...
 - The main method contains every object reference.
 - The main method can access every objects' fields and methods.

Example Program

- Consider a program that models `Prisoner`, `Cell`, and `Guard` objects.
- The main method may look like this:


```
public class PrisonTest{  
    public static void main(String[] args){  
  
        Prison p01 = new Prisoner();  
        Cell c01 = new Cell();  
        Guard g01 = new Guard();  
  
        p01.name = "Bubba";  
        c01.name = "A1";  
        g01.name = "Boss Man";  
  
    }  
}
```

Object references

Interactions


Interactions from the Main Method

- The main method contains all the object references.
- Therefore, the main method controls all interactions in this system.



Interactions Between Objects

- However, sometimes you'll want a program where objects interact with each other.
- To do this, objects must know about each other.
 - One object must know a reference to the other object.



How Do Objects Know About Each Other?

- Object references must be shared:
 - One object may contain another object as a field.
 - One object's method may accept another object as an argument.
- For example:
 - A way to describe a `Prisoner` is by their `Cell` number.
 - It could be argued that a `Cell` is a property of a `Prisoner` object.
 - The `Prisoner` class would contain a `Cell` field.



Exercise 1, Part 1

- Continue editing the `PrisonTest` project.
 - A version of this program is provided for you.
- Create a `Cell` class that includes the following:
 - String `name` of the cell.
 - Boolean describing whether the door is open.
 - Two-argument constructor that sets both fields.
- Modify the `Prisoner` class so that it:
 - Includes a `Cell` field.
 - Sets the `Cell` field based on a constructor parameter.
 - Prints the cell's `name` as part of the `display()` method.




Exercise 1, Part 2

- Write an `openDoor()` method in the `Prisoner` class.
 - Access and modify the corresponding field in the `Cell` object so that:
 - If the door is closed, open it.
 - If the door is open, close it.
 - Print whether the door opens or closes.
- From the main method:
 - Instantiate a `Cell` and a `Prisoner` object.
 - Call the prisoner's `display()` method once.
 - Call the `openDoor()` method a few times.

Oops!

The guards are panicking!

- Your program allows prisoners to access their cell doors.
- Considering Bubba's plans for revenge, this type of interaction should not be allowed!



Think About Potential Object Interactions

- Consider which objects **must** know about each other.
 - Some objects have no business modifying another's fields.
 - Try to minimize their knowledge of each other ...
 - This prevents unwanted results and make code less complicated.
- Consider which direction the interactions might occur and which objects should be properties of each other.
 - Should a `Prisoner` have a `Cell` property?
 - Should a `Cell` have a `Prisoner` property?
 - Or should neither know about each other?

Think About How to Distribute Behaviors

- Cells are designed to open and close.
 - Someone must have access to perform these interactions.
 - Prisoners should not be capable of this behavior.
 - Guards should be capable of this behavior.
- Deciding how to distribute behaviors between objects is an important challenge of object-oriented programming.
 - But don't worry. You already have experience doing this.
 - A major goal of Java Puzzle Ball was to create situations where players needed to think carefully about distributing behaviors between different object types.

Topics

- Object Interaction
- Access Modifiers
- Getters and Setters
- Encapsulation Assistance from NetBeans

Creating a
Class


Instantiating
Objects

Constructors

Overloading
Methods

Object
Interaction and
Encapsulation

Static
Variables
and
Methods



Section 7

Introducing **Encapsulation**

- Sometimes objects must know about each other.
- Encapsulation provides techniques for limiting one class's visibility of another.
- It's possible to restrict which fields and methods other classes can see.
- Special methods can be written to decide how data should be accessed and modified.
- Access and visibility should be limited as much as possible.

Access Modifiers

- The `public` keyword is one of several access modifiers.
- Access modifiers limit the visibility of fields and methods between classes.

```
public class Cell {  
    //Fields  
    public String name;  
    public boolean isOpen;  
  
    //Constructor  
    public Cell(String name, boolean isOpen){  
        this.name = name;  
        this.isOpen = isOpen;  
    }  
}
```

Access Modifier Details

- `public`: Visible to any class.
 - It's the least secure.
 - Methods are typically public.
- Package: Visible to the current package.
 - There's no keyword for this level of access.
- `private`: Visible only to the current class.
 - It's the most secure.
 - Fields are typically private.



Exercise 2

- Continue editing the `PrisonTest` project.
- Modify the `Cell` class:
 - Change its fields to `private`.
 - Save the file.
- Does NetBeans have any complaints?
 - What are the complaints?
 - Where do they occur?

The Effects of Private Data

- The following private fields can't be accessed outside the `Cell` class:
 - `isOpen`
 - `name`
- Even the main method can't access this data.
- It's good that prisoners can't open their cell doors.
- It's bad that prisoners don't know the names of their cells.
 - The next topic discusses how to address this issue.

Topics

- Object Interaction
- Access Modifiers
- Getters and Setters
- Encapsulation Assistance from NetBeans

Creating a
Class


Instantiating
Objects

Constructors

Overloading
Methods

Object
Interaction and
Encapsulation

Static
Variables
and
Methods



Section 7

Introducing **Getter Methods**

- When a field is inaccessible, it can't be:
 - Read
 - Modified
- However, in many cases it's desirable for one class to at least know the value of another class's fields.
 - A prisoner should at least know their cell name.
 - This requires a prisoner to read the value of a `Cell`'s `name` field.
- Getter methods provide a solution.

Getter Methods

- Getters are also called **accessors**.
- Getters are public.
- Getters usually accept no arguments.
- Getters return the value of a particular variable.
 - Most private variables require a getter method.

```
public class Cell {  
    ...  
    public String getName(){  
        return name;  
    }  
    public boolean getIsOpen(){  
        return isOpen;  
    }  
}
```


Introducing **Setter Methods**

- In other cases, it's desirable for one class to modify another class's field.
- However, this must be done safely.
- For example:
 - A guard should be able to open a door, but a prisoner should not.
 - A bank account balance should not drop below zero.
- Setter methods provide a solution.

Setter Methods

- Setters are also called **mutators**.
- Setters are usually public.
- Setters usually accept arguments.
- Setters are void type methods.

```
public class Cell {  
    ...  
    public void setName(String name){  
        this.name = name;  
    }  
    public void setIsOpen(boolean isOpen){  
        this.isOpen = isOpen;  
    }  
}
```

Designing Setters

- Be careful when you write setters like those shown on the previous slide.
 - Prisoners would again have access to their doors.
- Sometimes a little thought needs to go into designing a setter method.
 - A security door may ask for a security code.
 - Banking software may check whether a withdrawal amount would result in a balance less than zero or if the withdrawal amount is negative.



Exercise 3, Part 1

- Continue editing the `PrisonTest` project.
- Modify the `Cell` class so that ...
 - Getters exist for the `name` and `isOpen` fields.
 - There's a private 4-digit security code field. It's initialized from the constructor and has no getter method.
 - There's a setter for opening/closing the door, and it does the following:
 - Accepts a security code as an argument.
 - Prints if the code is incorrect.
 - If the code is correct and the door is closed, opens it.
 - If the code is correct and the door is open, closes it.
 - Prints if the door is opened or closed.





Exercise 3, Part 2

- Modify the `Prisoner` class so that ...
 - The `display()` method prints the cell name.
 - The `openDoor()` method is removed.
- Modify the main method so that ...
 - The `Cell` is instantiated properly.
 - The prisoner no longer tries to open the cell door.
 - It tests a cell class's ability to open and close its door.
 - Try supplying both correct and incorrect security codes.

Continuing to Develop This Software

- Currently, the main method tests a `Cell` door's ability to open and close based on a security code.
- Testing allows us to confirm that this feature is implemented properly.
 - If the feature doesn't work, it should be fixed.
 - If the feature does work, it's safe to include this feature as part of another feature.
- A possible next step would be to develop a `Guard` class with a method for inputting a security code.
 - Ultimately a guard, not the main method, would be responsible for inputting a security code.

The Role of the Main Method

- Some programs are driven by physical objects.
- Some programs are driven by buttons.
- In this exercise, the main method models actions that would drive the program.
 - Calling `bubba.openDoor()` models a prisoner trying to open their cell door.
 - Calling `cellA1.setIsOpen(1234)` models a person who entered a security code.

Topics

- Object Interaction
- Access Modifiers
- Getters and Setters
- Encapsulation Assistance from NetBeans

Creating a
Class


Instantiating
Objects

Constructors

Overloading
Methods

Object
Interaction and
Encapsulation

Static
Variables
and
Methods



Section 7



Exercise 4

- Continue editing the `PrisonTest` project.
- Encapsulate the `Prisoner` class.
 - Make its fields `private`.
 - Provide getters and setters for every field.


That Exercise Wasn't Fun!

- Was Exercise 4 tedious and did it make you groan?
- Some programmers prefer the control of encapsulating fields themselves.
- Other programmers would rather have NetBeans do the work for them.
 - There's a shortcut.
 - NetBeans can encapsulate fields for you.



NetBeans Encapsulation Trick

1. Highlight the fields that you want to encapsulate.




```
3 public class Prisoner {  
4     //Fields  
5     public String name;  
6     public double height;  
7     public int sentence;  
8     public Cell cell;  
9 }
```

2. Right-click and select **Refactor >> Encapsulate Fields**.

NetBeans Encapsulation Trick

3. Adjust the settings as you like.
4. Click **Refactor**.



3) We recommend these settings.

Summary of Encapsulation

- Encapsulation offers techniques for limiting the visibility of a class.
- Access and visibility should be limited as much as possible.
- Most fields should be `private`.
- Provide getter methods to return the value of fields.
- Provide setter methods to safely modify fields.

Summary

In this lesson, you should have learned how to:

- Understand object interaction in greater detail
- Use the `private` modifier to define class variables
- Understand the purpose of getter methods
- Understand the purpose of setter methods

