



Java Foundations

7-3

Constructors



ORACLE ACADEMY

Copyright © 2014, Oracle and/or its affiliates. All rights reserved.

2

Objectives


This lesson covers the following objectives:

- Understand default values
- Crash the program with a `null` reference
- Understand the default constructor
- Write a constructor that accepts arguments
- Initialize fields with a constructor
- Use `this` as an object reference



Topics

- Default Values
- Using Methods to Set Fields
- Constructors
- The `this` Keyword



Remember the Prisoner Class

- It may have looked like this code.
- It contains fields and methods.

```
public class Prisoner {  
    //Fields  
    public String name;  
    public double height;  
    public int sentence;  
  
    //Methods  
    public void think(){  
        System.out.println("I'll have my revenge.");  
    }  
}
```


Fields Are Variables

- Variables hold values.
- The values can be accessed.
- Code may need to access variables to ...
 - Make calculations
 - Check current values
 - Change a value
- What might happen if a field is accessed before it's assigned a value?



Exercise 1

- Continue editing with the `PrisonTest` project.
 - A version of this program is provided for you.
- Investigate what happens when fields are accessed before they're assigned values.
 - Instantiate a `Prisoner`.
 - Try printing the value of each field.




Accessing Uninitialized Fields

- If fields aren't initialized, they take on a **default value**.
- Java provides the following default values:

Data Type	Default Value
<code>boolean</code>	<code>false</code>
<code>int</code>	<code>0</code>
<code>double</code>	<code>0.0</code>
<code>String</code>	<code>null</code>
Any Object type	<code>null</code>

Null Object References

- Objects can have a `null` value.
- A null object points to an empty location in memory
- If an Object has another Object as a field (such as a `String`), its default value is `null`.



Accessing Null Objects Is Dangerous

- What if a null object contains a field or method that needs to be accessed?
 - This causes the program to crash!
 - The specific error is a `NullPointerException`.


```
public static void main(String[] args) {  
    String test = null;  
    System.out.println(test.length());  
}
```

The Importance of Initializing Fields

- It's always good to minimize the chances that your program will crash.
- And sometimes, Java's default values aren't desirable.
- The remaining topics in this lesson examine helpful alternatives for initializing fields.

Topics

- Default Values
- Using Methods to Set Fields
- Constructors
- The `this` Keyword



ORACLE ACADEMY

JFo 7-3
Creating a Class

Copyright © 2017, Oracle and/or its affiliates. All rights reserved.

12

Setting Prisoner Fields

- Currently, we need a line of code to set each field.
- Four lines are required for each Prisoner object.

```
public class PrisonTest {  
    public static void main(String[] args){  
        Prisoner p01 = new Prisoner();  
        Prisoner p02 = new Prisoner();  
  
        p01.name = "Bubba";  
        p01.height = 2.08;  
        p01.sentence = 4;  
  
        p02.name = "Twitch";  
        p02.height = 1.73;  
        p02.sentence = 3;  
    }  
}
```

Methods Make Code More Efficient

- If you find yourself repeating similar lines of code ...
 - Programming can become tedious.
 - It may be possible to do the same work in fewer lines.
 - Try to write that code as part of a method instead.

```
p01.name = "Bubba";  
p01.height = 2.08;  
p01.sentence = 4;  
  
p02.name = "Twitch";  
p02.height = 1.73;  
p02.sentence = 3;
```

} First occurrence

} Repeated



Exercise 2

- Continue editing with the `PrisonTest` project.
- Can fields be set more efficiently?
 - Add a `setFields()` method to the `Prisoner` class.
 - This method should take three arguments, which are used to set the values for every field.
 - Replace code in the main method with calls to this method.



Variable: p01
Name: Bubba
Height: 6'10" (2.08m)
Sentence: 4 years



Variable: p02
Name: Twitch
Height: 5'8" (1.73m)
Sentence: 3 years

Writing a Method to Set Fields

Your solution may have looked something like this:

```
public class Prisoner {  
    public String name;  
    public double height;  
    public int sentence;  
  
    public void setFields(String n, double h, int s){  
        name = n;  
        height = h;  
        sentence = s;  
    }  
}
```



Setting Prisoner Fields

- Two lines are required for each `Prisoner` object.
- But it's possible to do the same work in even fewer lines!

```
public class PrisonTest {  
    public static void main(String[] args) {  
        Prisoner p01 = new Prisoner();  
        Prisoner p02 = new Prisoner();  
  
        p01.setFields("Bubba", 2.08, 4);  
        p02.setFields("Twitch", 1.73, 3);  
    }  
}
```

Topics

- Default Values
- Using Methods to Set Fields
- **Constructors**
- The `this` Keyword



Calling a Constructor

- A **constructor** is a special method.
- Its goal is to “construct” an object by setting the initial field values.
- An object’s constructor is called once.
 - This occurs during instantiation.
 - And is never called again.
- We’ve been calling constructors this whole time.

Constructor method call

```
Prisoner p01 = new Prisoner();
```

The Default Constructor

- Java automatically provides a constructor for every class.
- It's never explicitly written in a class.
- This is called the **default constructor**.
- It's considered a **zero-argument constructor**.

Accepts zero
arguments



```
Prisoner p01 = new Prisoner();
```

Writing a Constructor Method

- You can replace the default constructor with a constructor that you wrote yourself.
- Constructors are written like any other method, except:
 - They have no return type (not even `void`).
 - They're named the same as the class.

```
//Constructor  
public Prisoner() {  
    System.out.println("This is a constructor");  
}
```



Exercise 3, Part 1

- Continue editing with the `PrisonTest` project.
- Copy the constructor into the `Prisoner` class.
 - Run the program.
 - Observe how the code in this method is executed when `Prisoner` objects are instantiated.

```
//Constructor  
public Prisoner() {  
    System.out.println("This is a constructor");  
}
```



Exercise 3, Part 2

- How could you modify this constructor so that it sets every field in the class?
 - Use your understanding of methods to find a solution. Remember, constructors are methods.
 - Remove the `setFields()` method. Your solution should make this method redundant.
- NetBeans will complain in the main method:
 - How could these issues be fixed?
 - Run the program after you have a solution.

You May Have Noticed ...

- Constructors can be written so that they accept arguments that set initial field values.
- When you write your own constructor, the default constructor is no longer available.
- Code becomes more useful and requires fewer lines.
 - The next few slides illustrate this increased efficiency.

```
//Constructor
public Prisoner(String n, double h, int s){
    name = n;
    height = h;
    sentence = s;
}
```


Setting Fields Without a Constructor

4 lines are required for each `Prisoner` object.

```
public class PrisonTest {  
    public static void main(String[] args){  
        Prisoner p01 = new Prisoner();  
        Prisoner p02 = new Prisoner();  
  
        p01.name = "Bubba";  
        p01.height = 2.08;  
        p01.sentence = 4;  
  
        p02.name = "Twitch";  
        p02.height = 1.73;  
        p02.sentence = 3;  
    }  
}
```

Setting Fields with a Method

2 lines are required for each `Prisoner` object.

```
public class PrisonTest {  
    public static void main(String[] args){  
        Prisoner p01 = new Prisoner();  
        Prisoner p02 = new Prisoner();  
  
        p01.setFields("Bubba", 2.08, 4);  
        p02.setFields("Twitch", 1.73, 3);  
    }  
}
```


Setting Fields with a Constructor

1 line is required for each `Prisoner` object.

```
public class PrisonTest {  
    public static void main(String[] args){  
        Prisoner p01 = new Prisoner("Bubba", 2.08, 4);  
        Prisoner p02 = new Prisoner("Twitch", 1.73, 3);  
    }  
}
```

Topics

- Default Values
- Using Methods to Set Fields
- Constructors
- The `this` Keyword



ORACLE ACADEMY

JF07-3
Creating a Class

Copyright © 2017, Oracle and/or its affiliates. All rights reserved.

28

Naming Parameters

- Single-character variable names are commonly used ...
 - If the variable has a very limited scope
 - If there aren't a lot of variables to keep track of
 - For testing purposes
- But earlier in this course, we encouraged giving variables a descriptive names.
 - This helps avoid confusion.
 - Definitely follow this convention for fields.
 - Some developers like to apply this convention to method parameters.

Naming Parameters the Same as Fields

- This is also a common practice, especially with constructors.
 - It's clearer what your parameters refer to.
 - But this creates scope complications.
- In the following code, is the `name` **field** or **parameter** printed?

```
public class Prisoner {  
    public String name;  
  
    public setName(String name) {  
        System.out.println(name);  
    }  
}
```

Which Version of `name` Is Printed?

- The **parameter** is printed.
 - Variables within the most local scope take priority.
 - In other words, the variables within the most recent scope.
- Can the **field** still be accessed?
 - Yes! Fields exist within the scope of their class methods.
 - But more syntax is required to access to them.

```
public class Prisoner {  
    public String name;  
  
    public setName(String name) {  
        System.out.println(name);  
    }  
}
```

The `this` Keyword

- `this` is a reference to the current object.
 - You can treat it like any other object reference.
 - Which means you can use the dot operator (`.`).
- `this.name` accesses the Prisoner's field.
- `this.setName()` accesses the Prisoner's method.

```
public class Prisoner {  
    public String name;  
  
    public setName(String name){  
        this.name = name;  
    }  
}
```




Exercise 4

- Modify the `Prisoner` constructor.
 - Change the parameters of this method so that each parameter's name matches the name of a field.
 - Set each field's value by using the `this` keyword.

Summary of Constructors

- Are special methods in a class
- Named the same as the class
- Have no return type (not even void)
- Called only once during object instantiation
- May accept arguments
- Used to set initial values of fields
- If you don't write your own constructor, Java provides a default zero-argument constructor

Summary

In this lesson, you should have learned how to:

- Understand default values
- Crash the program with a `null` reference
- Understand the default constructor
- Write a constructor that accepts arguments
- Initialize fields with a constructor
- Use `this` as an object reference



