

Phys499A Report

Thomas Belvin

October 2023

0.1 Introduction

The goal is to assess the viability of using wires to detect gravitational particles by measuring the force applied at the end of a wire due to a wave generated by an inciting particle.

If the particle is moving sufficiently at a sufficiently fast speed, v , the interaction can be approximated by the particle moving along a straight track in relation to the wire. I then define the coordinate system such that the wire lies on the $\hat{\mathbf{z}}$ axes and the distance of closest approach between the wire and the particle track, b , is centered at $z = 0$.

$$r_x = b \cos(\phi) + tv \sin(\theta) \sin(\phi) \quad (1)$$

$$r_y = b \sin(\phi) - tv \sin(\theta) \cos(\phi) \quad (2)$$

$$r_z = tv \cos(\theta) - z_{\text{wire}} \quad (3)$$

where \mathbf{r} is the vector from a point on the wire, z_{wire} to the particle, ϕ is the angle between the $\hat{\mathbf{x}}$ axes and the track at $z = 0$, and θ is the angle between track and the $\hat{\mathbf{z}}$ axes.

The force the particle applies on a small piece of the wire is

$$\mathbf{F} = \frac{GM\partial m}{\mathbf{r}^2} \hat{\mathbf{r}} \quad (4)$$

where M is the mass of the inciting particle, ∂m is the mass of a small segment of the wire, and \mathbf{r} is the vector between the inciting particle and the segment of wire.

Since the particle is moving quick enough that it can be approximated as moving in a straight line in relation to the wire, it is safe to assume that it will apply and impulse to the wire. Taking \mathbf{F} from (4) and integrating from negative infinity to infinity with time gives

$$I_x = \frac{2GM\partial m(b \cos(\phi) + z_{\text{wire}} \sin(\theta) \cos(\theta) \sin(\phi))}{v(b^2 - z_{\text{wire}}^2 \cos^2(\theta) + z_{\text{wire}}^2)} \quad (5)$$

$$I_y = \frac{2GM\partial m(b \sin(\phi) - z_{\text{wire}} \sin(\theta) \cos(\theta) \cos(\phi))}{v(b^2 - z_{\text{wire}}^2 \cos^2(\theta) + z_{\text{wire}}^2)} \quad (6)$$

$$I_z = -\frac{2GM\partial m z_{\text{wire}} \sin^2(\theta)}{v(b^2 - z_{\text{wire}}^2 \cos^2(\theta) + z_{\text{wire}}^2)} \quad (7)$$

0.2 Simple Example