

Highlights

**ABC multi-criteria classification with analytical hierarchy process:
how to force consistency of pairwise comparisons matrix**

Tatiana Balbi Fraga, Ítalo Ruan Barbosa de Aquino, Regilda da Costa e
Silva Menêzes

- generative method for forcing consistency ;
- multi-product p-batch processing time maximization (MPBPTM) problem definition;
- linear integer programming model for the MPBPTM problem;
- exact optimization method for solving the MPBPTM problem.

ABC multi-criteria classification with analytical hierarchy process: how to force consistency of pairwise comparisons matrix

Tatiana Balbi Fraga^{a,*}, Ítalo Ruan Barbosa de Aquino^a, Regilda da Costa e Silva Menêzes^a

^aAgreste Academic Center - Federal University of Pernambuco, Avenida Marielle Franco, Nova Caruaru, Caruaru, 55014-900, PE, Brazil

Abstract

Multicriteria classification is usually very important to the decision-making in manufacturing management process. For such classification, the attribution of weights to the criteria strongly influences the coherence of the results found. Saaty's Analytic Hierarchy Process (AHP) is an important method for assigning weights to multiple criteria. AHP's logic is not complicated at all but, since matrices of pairwise comparisons of criteria are usually generated manually and based only on some employee know-how, there is a huge complexity on generating a consistent pairwise matrix. Especially when many criteria are used. This paper presents a constructive algorithm that can be used to adjust inconsistent matrices, forcing such matrices to have a better consistency rate. We tested this algorithm by applying the AHP method, for

*corresponding author

Email addresses: `tatiana.balbi@ufpe.br` (Tatiana Balbi Fraga),
`italo_ruan@hotmail.com` (Ítalo Ruan Barbosa de Aquino),
`regilda.smenezes@ufpe.br` (Regilda da Costa e Silva Menêzes)

ABC multicriteria classification, to companies in two sectors. As a result we observed that the algorithm can adjust the pairwise matrices in just a few seconds, avoiding the manual work that would be done in weeks, therefore showing that it is an important resource for applying the AHP method.

Keywords: multi-product batch, processing time maximization, mathematical model, analytical solution, COPSolver, LINGO

1. Introduction

2. Algorithms for forcing matrix consistency

Algorithm 1 function *consistencyRate()*

Require: $[a_{ij}]_{i,j=1}^n, RI[x]_{x=1}^{10}$
 $\lambda_{max} = mainEigenvalue([a_{ij}]_{i,j=1}^n)$ ¹
 $CI = (\lambda_{max} - n)/(n - 1)$
 $CR \leftarrow CI/RI[n]$
return CR

2.1. Constructive algorithm

2.2. Iterative algorithm

3. Tests and results

4. Conclusions and suggestions for future works

In this paper we presented ...

Algorithm 2 function *constructivelyForceConsistency* ($[a_{ij}]_{i,j=1}^n$)

Require: $[a_{ij}]_{i,j=1}^n$

Ensure: $\text{consistencyRate}([a_{ij}]_{i,j=1}^n) \leq 0.1$

$CR = \text{consistencyRate}([a_{ij}]_{i,j=1}^n)$

if $CR \leq 0.1$ **then**

return $[a_{ij}]_{i,j=1}^n$

else

for $3 \leq k \leq n$ **do**

$([a_{ij}]_{i,j=1}^k, CR) \leftarrow \text{forceConsistency}([a_{ij}]_{i,j=1}^k)$

if $CR \leq 0.1$ **then**

break for

end if

end for

end if

return $([a_{ij}]_{i,j=1}^n, CR)$

5. CRediT authorship contribution statement

T.B. Fraga: Conceptualization, Project administration, Supervision, Software, Methodology, Validation, Formal analysis, Writing – original draft, Writing – review & editing. Í.R.B. Aquino: Data curation. R.C.S. Menêzes: Data curation.

6. Acknowledgments

We are enormously grateful to Coordenação de Aperfeiçoamento de Pessoal de Nível Superior (CAPES) and to Conselho Nacional de Desenvolvimento Científico e Tecnológico (CNPq) for the financial support provided to our projects. We also thank LINDO systems team for the LINGO software license, without which this work would not have been possible and the to the

Algorithm 3 function *forceConsistency* ($[a_{ij}]_{i,j=1}^k$)

Require: $[a_{ij}]_{i,j=1}^n \mid \text{consistencyRate}([a_{ij}]_{i,j=1}^{n-1}) \leq 0.1$

Ensure: $\text{consistencyRate}([a_{ij}]_{i,j=1}^n) \leq 0.1$

$CR \leftarrow \text{consistencyRate}([a_{ij}]_{i,j=1}^n)$

for $j \leq n - 2$ **do**

for $j + 1 \leq k \leq n - 1$ **do**

$g \leftarrow 0$

$s \leftarrow 0$

if $a_{nj} > a_{nk}$ and $a_{jk} \leq 1$ **then**

$g \leftarrow j$

$s \leftarrow k$

else if $a_{nj} < a_{nk}$ and $a_{jk} \geq 1$ **then**

$g \leftarrow k$

$s \leftarrow j$

end if

if $g \neq 0$ **then**

$([a_{ij}]_{i,j=1}^n, CR) \leftarrow \text{reduce}([a_{ij}]_{i,j=1}^n, g, s)$

if $CR \geq 0.1$ **then**

$([a_{ij}]_{i,j=1}^n, CR) \leftarrow \text{encrease}([a_{ij}]_{i,j=1}^n, g, s)$

end if

end if

if $CR \leq 0.1$ **then**

break for

end if

end for

if $CR \leq 0.1$ **then**

break for

end if

end for

return $([a_{ij}]_{i,j=1}^n, CR)$

Algorithm 4 function $reduce([a_{ij}]_{i,j=1}^n, g, s)$

Require: $g, s < n; [a_{ij}]_{i,j=1}^n$

```

while  $a_{ng} > a_{ns}$  do
   $a_{ng} \leftarrow a_{ng}^{--}$ 
   $a_{gn} \leftarrow a_{gn}^{++}$ 
   $aux_{CR} = consistencyRate([a_{ij}]_{i,j=1}^n)$ 
  if  $aux_{CR} < CR$  then
     $CR = aux_{CR}$ 
    if  $CR \leq 0.1$  then
      break
    end if
  else
     $a_{ng} \leftarrow a_{ng}^{++}$ 
     $a_{gn} \leftarrow a_{gn}^{--}$ 
    break
  end if
end while
return  $([a_{ij}]_{i,j=1}^n, CR)$ 

```

owner of the company in the plastics sector, who allowed us to learn about his company's production process. Finally, we would like to thank Pró-reitoria de Extensão e Cultura da UFPE (PROExC) and the Research Director of Propesqi (Pró-reitoria de Pesquisa e Inovação da UFPE) for their support and recognition of our work, and dear Professors Antônio José da Silva Neto and João Flávio Vieira de Vasconcellos from IPRJ/UERJ, who contributed significantly to the formation of essential skills for the development of our projects. We also thank my co-worker Marcos Luiz Henrique, for having helped by evaluating the mathematical model and solution method proposed in this paper.

Algorithm 5 function *encrease* ($[a_{ij}]_{i,j=1}^n, g, s$)

Require: $g, s < n; [a_{ij}]_{i,j=1}^n$

while $a_{ng} > a_{ns}$ **do**

$a_{ns} \leftarrow a_{ns}^{++}$

$a_{sn} \leftarrow a_{sn}^{--}$

$aux_{CR} = consistencyRate([a_{ij}]_{i,j=1}^n)$

if $aux_{CR} < CR$ **then**

$CR = aux_{CR}$

if $CR \leq 0.1$ **then**

break

end if

else

$a_{ns} \leftarrow a_{ns}^{--}$

$a_{sn} \leftarrow a_{sn}^{++}$

break

end if

end while

return ($[b_{ij}]_{i,j=1}^n, CR$)

Algorithm 6 function a_{ij}^{++}

Require: $a_{ij} \mid a_{ij} \in \{1/9, 1/7, 1/5, 1/3, 1, 3, 5, 7, 9\}$

if $a_{ij} \geq 1$ and $a_{ij} \neq 9$ **then**

$a_{ij} \leftarrow a_{ij} + 2$

else if $a_{ij} < 1$ **then**

$a_{ij} \leftarrow 1/(1/a_{ij} - 2)$

end if

return a_{ij}

Algorithm 7 function a_{ij}^{--}

Require: $a_{ij} \mid a_{ij} \in \{1/9, 1/7, 1/5, 1/3, 1, 3, 5, 7, 9\}$

if $a_{ij} \geq 3$ **then**

$a_{ij} \leftarrow b_{ij} - 2$

else if $a_{ij} \leq 1$ and $a_{ij} \neq 1/9$ **then**

$a_{ij} \leftarrow 1/(1/a_{ij} + 2)$

end if

return a_{ij}

Algorithm 8 function iterativelyForcingConsistency()

Require: $M[a_{ij}]_{i,j=1}^n$ **Ensure:** $\text{consistencyRate}([b_{ij}]_{i,j=1}^n) \leq 0.1$ **return** $M[b_{ij}]_{i,j=1}^n$

References

- Eilon. (1985). Multi-product batch production on a single machine - A problem revisited. *OMEGA Int. J. of Mgmt Sci.*, Vol. 13 (5), pp. 453–468.
- Fowler, J.W. and Mönch, L. (2022). A survey of scheduling with parallel batch (p-batch) processing. *European Journal of Operational Research*, Vol. 298, pp. 1–24.
- Fraga, T.B. (2023). COPSolver: open source software for solving combinatorial optimization and other decision problems - library for solving the multi-product p-batch processing time maximization problem *Software Impacts*, invited paper, in press.
- Fumero Y., Moreno M. S., Corsano, G., Montagna, J. M. (2016). A multi-product batch plant design model incorporating production planning and scheduling decisions under a multiperiod scenario. *Applied Mathematical Modelling*, Vol. 40, pp. 3498–3515.
- He, Y., Hui, C-W. (2008). A rule-based genetic algorithm for the scheduling of single-stage multi-product batch plants with parallel units. *Computers and Chemical Engineering*, Vol. 32, pp. 3067–3083.

- Kashan, A. H., and Ozturk, O. (2022). Improved MILP formulation equipped with valid inequalities for scheduling a batch processing machine with non-identical job sizes. *Omega*, Vol. 112, pp. 102673.
- Kim, M., Jung, J. H. and Lee, I. (1996). Intelligent scheduling and monitoring for multi-product networked batch processes. *Computers chem. Engn*, Vol. 20 (Suppl.), pp. 1149–1154.
- Li, C., Wang, F., Gupta, J.N.D., Chung, T. (2022). Scheduling identical parallel batch processing machines involving incompatible families with different job sizes and capacity constraints. *Computers & Industrial Engineering*, Vol. 169, pp. 108115.
- Liu, G., Li, F., Yang, X., and Qiu. S. (2020). The multi-stage multi-product batch-sizing problem in the steel industry. *Applied Mathematics and Computation*, Vol. 369, 124830.
- Méndez, C.A., Henning, G.P., Cerdá, J. (2000). Optimal scheduling of batch plants satisfying multiple product orders with different due-dates. *Computers and Chemical Engineering*, Vol. 24, pp. 2223–2245.
- Méndez, C.A., Cerdá, J. (2003). Dynamic scheduling in multiproduct batch plants. *Computers and Chemical Engineering*, Vol. 27, pp. 1247–1259.
- OMEGA Journal. (1993). Single Machine Multi-product Batch Scheduling: Testing Several Solution Methods. *OMEGA Int. J. of Mgmt Sci.*, Vol. 21 (6), pp. 709–711.

- Petkov, S. B., and Maranas, C. D. (1998). Design of Single-Product Campaign Batch Plants under Demand Uncertainty. *AIChE Journal*, Vol. 44 (4), pp. 896–911.
- Ravemark, D. E., and Rippin, D. W. T. (1998). Optimal design of a multi-product batch plant. *Computers chem. Engng*, Vol. 22 (1-2), pp. 177–183.
- Shi, B., Qian, X., Sun, S., Yan, L. (2017). Rule-based scheduling of multi-stage multi-product batch plants with parallel units. *Chinese Journal of Chemical Engineering*, in press.