

# obsidian-mcp-router — quick reference

v0.82.0 · multi-vault Obsidian MCP server, shipped by its Claude Code plugin — one install = everything (51 slash commands · 50 MCP tools · 47 skills)

[github.com/tboome33/obsidian-mcp-router](https://github.com/tboome33/obsidian-mcp-router)

---

## The router in 30 seconds

---

A single MCP process that knows **all your Obsidian vaults** (local + remote). Each tool takes a `vault` parameter (or uses the default). No more registering one MCP server per vault.

- **One plugin install = everything:** the Claude Code plugin ships *and launches* the server — declared in its root `.mcp.json` (key `router`, via `${CLAUDE_PLUGIN_ROOT}`). A manual `~/.claude.json` entry is the dev alternative; keeping both runs **two** server processes with duplicated tools ( `mcp__obsidian-router__*` vs `mcp__plugin_obsidian-router_router__*` )
- **Local + remote vaults** treated identically — drop URL + API key into the config, done
- **Cross-vault:** `vault: "*"`  auto-fans-out across every vault
- **Lock mode:** restrict the session to a single vault (safety, focus) · **Auto-enrichment:** Claude suggests wiki saves at 3 natural moments, 4 modes ( `ClaudeAsk` / `Hybrid` / `FullAuto` / `off` )
- **Conversion toolbox:** PDF / DOCX / XLSX / PPTX / image (OCR) / audio / YouTube / webpage / git repo → markdown; opt-in **Docling** high-fidelity PDF + `pdf_to_images` (the model sees a PDF page); **BM25 relevance filter** strips off-topic blocks before synthesis
- **Knowledge graph:** typed graph JSON + reading tours + neighbors + shortest link path; export as `llms.txt` or **OKF bundle** (Google's Open Knowledge Format v0.1, with one of the ecosystem's first validators)
- **Wiki analysis:** `find_boundary_pages` ranks heavily-linked-but-thin "frontier" pages; `find_twin_pages` finds quasi-duplicate pairs by cosine over the Smart Connections vectors, with a threshold derived from *your* vault's own distribution — and works on remote vaults too (bridge  $\geq 0.9.0$  serves the vector store)
- **Click-to-open:** clickable links in chat via the bridge's `GET /open/<path>` route; `open_in_obsidian` does the same server-side (no browser — ideal for Claude Desktop). The link survives losing the vault's disk ( `insecurePort` declarable in the config, exported only on explicit `--with-click-to-open` ), and a one-click `GET /ping?v=<vault>` self-test proves *which* vault answers on a port
- **Vault-creation wizard:** `plan_vault` → adjust → `provision_vault`, defaults-first (happy path = 1 interaction)
- **Multi-tenant mode** (opt-in): scope an instance by env vars — vault whitelist, read-only, per-user write audit — for MCPHub/proxy deployments
- **10 hooks:** 2 come active with the plugin for every installer (hot-cache load + decisions recall); the other 8 (session auto-journal, wiki autocommit, link linter, doc-drift checker, update check, hot-cache guard...) are opt-in via `node scripts/setup-vault.mjs --install-hooks`

## How the pieces fit — the dependency chain

```
Obsidian ← Local REST API (community plugin) ← BRIDGE (mcp-router-bridge)
  ↑ HTTP per vault (port + apiKey from the Local REST API plugin)
MCP SERVER (obsidian-mcp-router) – Node ≥ 20.18.1 process on the PC
  ↑ MCP over stdio, spawned by Claude Code
CLAUDE CODE PLUGIN (obsidian-router) – commands + skills + agents + hooks
  · the plugin SHIPS and LAUNCHES the server itself
```

- **Bridge** — runs *inside* Obsidian; registers extra routes on Local REST API's HTTP server (`/search/smart`, `/templates/execute`, `/open/*`, `/ping`, `PUT /vault-cas/*` ≥ 0.7.0 — atomic `ifMatch` writes —, `GET /smart-env/sources` ≥ 0.9.0 — serves the Smart Connections vector store, a dot-directory the REST API itself won't serve, so `find_twin_pages` works on remote vaults —, presence heartbeat). **Optional per vault:** without it, core file CRUD still works (plain Local REST API routes), but smart search, Templater execution, click-to-open links, atomic conditional writes and remote twin-page analysis don't (`ifMatch` then degrades to a checked non-atomic fallback). Updates itself via BRAT from GitHub releases.
- **MCP server** — Node process spawned by Claude Code. Requires the **Local REST API** plugin in every vault (mandatory) and its registry at `~/.claude/obsidian-mcp-router/config.json` (maintained by `setup-vault.mjs`); the bridge is optional per vault (see above).
- **Claude Code plugin** — its commands and skills orchestrate the server's MCP tools; two hooks (hot-cache load, decisions recall) read vault files directly from disk.

**The plugin ships the server** — installing (or updating) the plugin installs (or updates) the server in the same move; fresh installs self-heal `node_modules` via a zero-dependency `bin/` bootstrapper. No `~/.claude.json` entry needed — that path remains for dev checkouts only (`claude --plugin-dir <checkout>` replaces the installed plugin for a session).

## Vault setup

1. Have Node.js ≥ 20.18.1. Conversion backends are opt-in (no npm `postinstall`): `npm run install-markitdown` (needs Python 3.10+ on `PATH`), `npm run install-docling` — until installed, the conversion tools stay listed and return an actionable install hint
2. **Easiest path:** `/obsidian-router:meta-attach-vault` — interactive wizard that attaches a vault to a workspace (common case), bootstraps a standalone vault, or registers a remote one. Provisions plugins + scaffolds the wiki + binds `.env` + conventions picker.
3. CLI alternative:

```
npm run setup-vault -- "C:\VAULTS\MyVault"
```

⇒ installs/configures **Local REST API** + bridge plugins, writes `.env`, allocates a unique port, adds to the registry. The 2 base hooks come active with the plugin; the 8 extra hooks are opt-in via `node scripts/setup-vault.mjs --install-hooks`.

4. Optional for `search_smart`: **Smart Connections** + **obsidian-mcp-router-bridge** · for Templater: **Templater**

5. Verify: `/obsidian-router:meta-status` or just say "*diagnose the router*"

## Configuration — environment variables (workspace `.env`)

|                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|-----------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| VAULT_PATH                                                                                                            | Path of the current vault. Auto-detection: if it matches a registered vault, that vault becomes the default. Written by <code>setup-vault.mjs</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| OBSIDIAN_ROUTER_DEFAULT_VAULT                                                                                         | Explicit override of the default vault for this process. Wins over <code>VAULT_PATH</code> and over <code>config.defaultVault</code> . Also the workspace↔vault binding used by the wiki-query-first hooks.                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| OBSIDIAN_ROUTER_LOCKED                                                                                                | Locks the router to one vault for the session. Any tool call to another vault throws. Set via <code>/obsidian-router:lock &lt;vault&gt; --persist</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| OBSIDIAN_ROUTER_AUTO_ENRICH                                                                                           | Wiki auto-enrichment mode: <code>ClaudeAsk</code> (default)   <code>Hybrid</code>   <code>FullAuto</code>   <code>off</code> . Set via <code>/obsidian-router:auto-mode &lt;Mode&gt; --persist</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| OBSIDIAN_ROUTER_ALLOWED_VAULTS                                                                                        | Multi-tenant: comma-separated whitelist of vaults this instance sees. Others are skipped.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| OBSIDIAN_ROUTER_READONLY                                                                                              | Multi-tenant: truthy ( <code>1</code> / <code>true</code> / <code>yes</code> / <code>on</code> ) hides the <b>15</b> write tools — <code>write_file</code> , <code>append_to_file</code> , <code>patch_file</code> , <code>set_frontmatter</code> , <code>merge_frontmatter</code> , <code>move_file</code> , <code>delete_file</code> , <code>execute_template</code> , <code>download_page_assets</code> , <code>build_wiki_graph</code> , <code>provision_vault</code> , <code>write_bundle</code> , <code>record_source</code> , <code>refresh_okf_projections</code> , <code>build_search_index</code> — filtered from <code>ListTools</code> AND refused at call time. |
| OBSIDIAN_ROUTER_USER_ID                                                                                               | Multi-tenant: audit trail — every successful write appends an attributed line to the vault's <code>wiki-meta/journal.md</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| VAULT_<NAME>                                                                                                          | A whole vault defined in one env var (JSON: <code>name</code> , <code>baseUrl</code> , <code>apiKey</code> ...) — dashboard-editable on MCPHub deployments.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| OBSIDIAN_ROUTER_NO_WATCH                                                                                              | Disables hot-reload of the config file (useful for debugging).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| OBSIDIAN_ROUTER_NO_HOT_CACHE_LOAD<br>• ...NO_DECISIONS_RECALL • ...<br>NO_WIKI_AUTOCOMMIT • ...<br>NO_SESSION_JOURNAL | Per-hook opt-outs: disable the hot-cache load, decisions recall, wiki autocommit and session journal hooks respectively. All accept <code>1</code> / <code>true</code> / <code>yes</code> / <code>on</code> .                                                                                                                                                                                                                                                                                                                                                                                                                                                                |

## Important files — where things live

|                                                        |                                                                                                             |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| <code>~/.claude/obsidian-mcp-router/config.json</code> | Main router config (vaults, port registry, defaultVault, disabledVaults, remoteVaults). Hot-reload enabled. |
|--------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|

|                                                                        |                                                                                                                                                                                                                                                                                                                                                                                             |
|------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>~/.claude.json</code>                                            | Manual/dev setup only: a hand-registered server entry pointing to a checkout. The plugin declares its server in its own root <code>.mcp.json</code> (key <code>router</code> , <code>\${CLAUDE_PLUGIN_ROOT}</code> ); a hand-registered entry <i>plus</i> the plugin = two processes with duplicated tools (dev machines may keep both deliberately).                                       |
| <code>~/.claude/settings.json</code>                                   | The 8 opt-in hooks land here via <code>setup-vault.mjs --install-hooks</code> (the 2 base hooks ship active in the plugin's <code>hooks/hooks.json</code> — 10 hooks total). The plugin itself is enabled <b>per-workspace</b> via <code>&lt;workspace&gt;/.claude/settings.json</code> — 51 commands + 47 skills ≈ 10k context tokens, only load them where you use Obsidian.              |
| <code>&lt;workspace&gt;/.env</code>                                    | Environment variables for the current workspace (above). Auto-loaded at router boot.                                                                                                                                                                                                                                                                                                        |
| <code>&lt;vault&gt;/CLAUDE.md</code>                                   | Vault wiki consigne — loaded by Claude Code into context. Includes the auto-enrichment consigne (4 modes) + installed conventions.                                                                                                                                                                                                                                                          |
| <code>&lt;vault&gt;/wiki-meta/{catalog,journal,hot,overview}.md</code> | Karpathy LLM-wiki scaffolds (catalog, append-only journal, hot cache, overview) — under <code>wiki-meta/</code> (user pages live under <code>wiki/</code> ). Named <code>catalog</code> / <code>journal</code> rather than <code>index</code> / <code>log</code> because OKF reserves those two basenames; the old names are still read. Scaffolded by <code>/obsidian-router:wiki</code> . |
| <code>&lt;vault&gt;/wiki-meta/Sessions/</code>                         | Per-session detail journals (auto-written by the <code>session-auto-journal</code> hook; <code>journal.md</code> stays a thin index).                                                                                                                                                                                                                                                       |
| <code>obsidian-mcp-router/docs/</code>                                 | <code>auto-enrichment.md</code> (4 modes + 4 placement channels), <code>features/</code> (13 prose feature pages), <code>architecture.md</code> , this PDF (EN + FR).                                                                                                                                                                                                                       |

# 51 slash commands /obsidian-router:<name> · auto-trigger on natural language

(EN + FR)

 17 MCP wrappers — one per core vault tool

Categories: discover · read · write · manage · template · convert

| COMMAND                 | EFFECT                                                           | TRIGGER PHRASE (EN/FR)                                         |
|-------------------------|------------------------------------------------------------------|----------------------------------------------------------------|
| discover-list-vaults    | List vaults (online/latency/lock state)                          | "list my vaults" / "liste mes vaults"                          |
| discover-list-files     | List files in a vault directory                                  | "list files in Sessions" / "liste les fichiers de X"           |
| read-get                | Read a file (markdown + frontmatter)                             | "show me X" / "montre-moi X"                                   |
| read-search             | Plain-text (substring) search                                    | "grep for <text>" / "trouve <texte>"                           |
| read-search-smart       | Semantic search (Smart Connections)                              | "find notes about X" / "trouve mes notes sur X"                |
| read-frontmatter        | Read frontmatter (object or one key)                             | "metadata of X" / "quel est le statut de X"                    |
| write-create-or-replace | PUT — create or replace a file                                   | "save this as X.md" / "crée une note X"                        |
| write-append            | POST — append to a file                                          | "append to my journal" / "ajoute à X"                          |
| write-patch             | Surgical PATCH (heading/block/frontmatter)                       | "edit X section in Y" / "édite la section X dans Y"            |
| write-frontmatter-set   | Set one frontmatter key                                          | "tag this with X" / "passe le statut de X à closed"            |
| write-frontmatter-merge | Set multiple keys in sequence                                    | "on X set status=closed outcome=tp1"                           |
| write-bundle            | Multi-file bundle — all-or-nothing apply with journaled rollback | "write these 4 pages atomically" / "écris ces pages d'un bloc" |
| manage-move             | Move or rename a file                                            | "move X to Y" / "renomme X en Y"                               |

|                         |                                                               |                                                      |
|-------------------------|---------------------------------------------------------------|------------------------------------------------------|
| manage-delete           | Delete a file (2-step confirm guard)                          | "delete X" then "yes confirm=true"                   |
| template-execute        | Execute a Templater template                                  | "run X template" / "rends Templates/X.md avec arg=v" |
| pdf-to-markdown         | Local PDF → markdown (MarkItDown, fast plain-text)            | "convert this PDF to markdown" / "convertis ce PDF"  |
| pdf-to-markdown-docling | High-fidelity PDF → markdown (Docling, tables/layout, opt-in) | "convert with docling" / "conversion haute fidélité" |

### 3 router-state commands (lock + auto-enrichment)

| COMMAND   | EFFECT                                                                  | TRIGGER PHRASE (EN/FR)                           |
|-----------|-------------------------------------------------------------------------|--------------------------------------------------|
| lock      | Restrict the session to one vault (volatile or <code>--persist</code> ) | "I only want to work on X" / "verrouille sur X"  |
| unlock    | Lift the lock, restore multi-vault routing                              | "unlock vaults" / "déverrouille les vaults"      |
| auto-mode | Set the auto-enrichment mode (ClaudeAsk / Hybrid / FullAuto / off)      | "switch to Hybrid mode" / "passe en mode Hybrid" |

### 7 conversational helpers (setup + diagnostic)

| COMMAND            | EFFECT                                                                                                                      | TRIGGER PHRASE (EN/FR)                                            |
|--------------------|-----------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------|
| meta-setup         | Manual/dev install (clone + npm link + <code>~/ .claude.json</code> entry) — normal installs get the server from the plugin | "setup obsidian-mcp-router" / "installe le router"                |
| meta-attach-vault  | Wizard — attach a vault to a workspace (common), standalone, or remote                                                      | "attach a vault to this workspace" / "connecte mon vault distant" |
| meta-status        | Health-check every vault with fix hints                                                                                     | "are my vaults reachable" / "diagnostique le router"              |
| meta-sync-template | Propagate the reference vault's plugins/snippets/docs to vaults (picker)                                                    | "sync the template to all vaults" / "synchronise le template"     |
| sync-from-github   | Update one vault or the whole fleet straight from the GitHub skeleton (plugins, themes,                                     | "sync my vaults from github" / "mets à jour depuis GitHub"        |

snippets, docs) — no local dev  
repo needed

|                             |                                                                          |                                                         |
|-----------------------------|--------------------------------------------------------------------------|---------------------------------------------------------|
| meta-audit-bridge-readiness | Audit click-to-open readiness (bridge, REST API, HTTP, live /open probe) | "is click-to-open ready" / "audite le bridge"           |
| conventions                 | Install/remove/status/propagate CLAUDE.md conventions cross-vaults       | "install source-type on X" / "installe la convention X" |



## 24 knowledge-management commands (Karpathy-style LLM-wiki)

| COMMAND              | EFFECT                                                                                                                                                                          | TRIGGER PHRASE (EN/FR)                                    |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------|
| wiki                 | Scaffold the wiki in a vault (index, log, hot, overview)                                                                                                                        | "set up a wiki" / "scaffold un wiki"                      |
| wiki-ingest          | Ingest a source → entity/concept pages + cross-refs                                                                                                                             | "absorb this article" / "ingère cette URL"                |
| wiki-query           | 3-tier RAG over the wiki (no web)                                                                                                                                               | "what does my wiki say about X" / "d'après mes notes ..." |
| wiki-lint            | Health check (orphans, dead links, index drift)                                                                                                                                 | "audit my wiki" / "lint le wiki"                          |
| wiki-fold            | Idempotent log rollup under wiki/folds/                                                                                                                                         | "fold the log" / "compacte le journal"                    |
| hot-compact          | Compact an oversized hot.md back to its cache contract (verified backup first)                                                                                                  | "compact the hot cache" / "compacte le hot"               |
| save                 | File the conversation as a typed wiki note (session/decision/ADR/...)                                                                                                           | "save this" / "sauvegarde ça"                             |
| decision-consolidate | Compress a settled decision page to its essentials; move the full deliberation history to a verified archive note                                                               | "consolidate this decision" / "consolide cette décision"  |
| autoresearch         | Autonomous web→synth→file loop                                                                                                                                                  | "research X online" / "fais une recherche web sur X"      |
| canvas               | Create/edit Obsidian .canvas files                                                                                                                                              | "create a canvas for X" / "crée un canvas pour X"         |
| defuddle             | Strip noise from web pages before ingestion                                                                                                                                     | "defuddle <url>" / "nettoie cette page"                   |
| obsidian-bases       | Create/edit Obsidian .base files (database views)                                                                                                                               | "create a base for X" / "crée une base pour X"            |
| wiki-graph           | Build the typed knowledge-graph JSON → <code>wiki-meta/graph/</code> + an <code>.understand-anything/</code> copy for the Understand-Anything dashboard (deterministic, no LLM) | "build the wiki graph" / "construis le graphe"            |

|                      |                                                                                                                                                            |                                                                |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------|
| wiki-tour            | Ordered pedagogical reading tour from the link topology                                                                                                    | "give me a tour of this vault" / "par où je commence"          |
| wiki-neighbors       | One page's neighbors — links out, backlinks, or both                                                                                                       | "what links to X" / "voisins de X"                             |
| wiki-path            | Shortest link chain between two pages                                                                                                                      | "how is X connected to Y" / "quel rapport entre X et Y"        |
| wiki-export          | Export the vault as llms.txt / llms-full.txt or an OKF bundle                                                                                              | "export the wiki as llms.txt" / "exporte le wiki"              |
| okf-export           | Export a wiki subset as a shareable OKF v0.1 bundle (conformance self-checked)                                                                             | "export this folder as an OKF bundle" / "publie en bundle OKF" |
| okf-projections      | Regenerate the generated OKF navigation in wiki/ (root + per-directory index.md, newest-first log.md); auto-refreshed after writes; --check = drift report | "refresh the OKF projections" / "régénère les index du wiki"   |
| okf-check            | Validate any OKF bundle against the v0.1 conformance rules                                                                                                 | "validate this OKF bundle" / "ce bundle est-il conforme ?"     |
| wiki-refresh-digests | Regenerate per-page digest sidecars (concepts/claims/keywords)                                                                                             | "refresh the digests" / "rafraîchis les digests"               |
| build-search-index   | Build/refresh the local BM25 search index (plugin-free search tier, idempotent)                                                                            | "build the search index" / "construis l'index de recherche"    |
| wiki-boundary        | Rank heavily-linked-but-thin "frontier" pages worth writing next                                                                                           | "what should I write next" / "pages frontière du wiki"         |
| who-is-speaking      | Identify the family member in a shared vault, lock routing per member                                                                                      | "who is speaking" / "c'est Karine"                             |

## The 50 MCP tools — what Claude actually calls under the hood

---

|                                                                                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-----------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>list_vaults · list_files</code>                                                                                 | <b>Discovery.</b> Vault catalog with online status + latency (call first); directory listing.                                                                                                                                                                                                                                                                                                                        |
| <code>get_file · search · search_smart · get_frontmatter</code>                                                       | <b>Reads.</b> Full file (returns <code>contentSha256</code> — the <code>ifMatch</code> token); substring search; semantic search (Smart Connections embeddings, cosine scores); typed frontmatter. <code>vault: "*" = cross-vault fan-out.</code>                                                                                                                                                                    |
| <code>write_file · append_to_file · patch_file · delete_file · set_frontmatter · merge_frontmatter · move_file</code> | <b>Writes &amp; file management.</b> Create/replace; append; surgical patch by heading/block/frontmatter; guarded delete ( <code>confirm: true</code> ); one or many frontmatter keys; move/rename. <code>ifMatch</code> : replay <code>get_file</code> 's <code>contentSha256</code> and the write is refused (409) if the file changed since you read it — atomic with bridge ≥ 0.7.0, checked fallback otherwise. |
| <code>execute_template</code>                                                                                         | <b>Templater.</b> Render a template, optionally write the result; args via <code>tp.mcpTools.prompt("key")</code> .                                                                                                                                                                                                                                                                                                  |
| <code>lock_vault · unlock_vaults · set_auto_enrich_mode</code>                                                        | <b>Router state.</b> Single-vault isolation; auto-enrichment mode switch.                                                                                                                                                                                                                                                                                                                                            |
| <code>plan_vault · provision_vault</code>                                                                             | <b>Vault provisioning.</b> Read-only plan (defaults + questionnaire + warnings) → one-call creation (plugins, port, API key, wiki scaffold, registry). Local-only.                                                                                                                                                                                                                                                   |
| <code>pdf/docx/xlsx/pptx/image/audio_to_markdown</code>                                                               | <b>Local conversion</b> (Markdown — opt-in via <code>npm run install-markitdown</code> ; the tools stay listed and return an install hint when the backend is missing). Office/PDF/image OCR/audio transcription → markdown text; chain with <code>write_file</code> .                                                                                                                                               |
| <code>pdf_to_markdown_docling · pdf_to_images</code>                                                                  | <b>High-fidelity PDF</b> (opt-in Docling): layout + table-structure recognition. <code>pdf_to_images</code> renders pages to PNG so the model can see them (capped pages/bytes).                                                                                                                                                                                                                                     |
| <code>youtube/bing_search/webpage_to_markdown · git_repo_to_markdown</code>                                           | <b>Remote conversion.</b> URL → markdown (SSRF-guarded); YouTube transcripts; git repo → single markdown bundle (repomix, optional Tree-sitter compression). <code>webpage_to_markdown</code> accepts <code>relevanceQuery</code> (BM25).                                                                                                                                                                            |

|                                                                                                                                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>filter_relevant_blocks</code>                                                                                                                          | <b>Relevance filter.</b> Deterministic BM25 second pass over markdown you already have — drops off-topic blocks, keeps frontmatter/headings, multiple no-op safety nets. No fetch, no LLM.                                                                                                                                                                                                                                                                                    |
| <code>extract_page_metadata</code> · <code>propose_linked_sources</code> · <code>download_page_assets</code>                                                 | <b>Web ingestion support.</b> Deterministic page metadata (JSON-LD/OpenGraph); scored link-following candidates; image download into the vault.                                                                                                                                                                                                                                                                                                                               |
| <code>get_wiki_context_pack</code> · <code>build_wiki_graph</code> · <code>build_wiki_tour</code> · <code>get_page_neighbors</code> · <code>wiki_path</code> | <b>Context &amp; graph.</b> Structured context envelope for external agents; typed knowledge graph; reading tours; per-page neighbors; shortest link path.                                                                                                                                                                                                                                                                                                                    |
| <code>find_boundary_pages</code> · <code>find_twin_pages</code>                                                                                              | <b>Wiki analysis.</b> Frontier pages worth writing next (linked a lot, say little); quasi-twin pairs by cosine over the Smart Connections vectors, threshold derived from the vault's own distribution, every pair carrying the evidence to dismiss it. Both answer <code>available: false</code> with a reason (never a fake "0 found") when they cannot look. <code>find_twin_pages</code> works on <b>remote vaults</b> too (bridge $\geq 0.9.0$ serves the vector store). |
| <code>write_bundle</code> · <code>refresh_okf_projections</code> · <code>build_search_index</code>                                                           | <b>Wiki maintenance.</b> Journaled multi-file bundle — all-or-nothing apply with rollback; regenerate the OKF navigation (per-directory <code>index.md</code> + newest-first <code>log.md</code> — generated files, never edit by hand); local BM25 search index (works on every vault, no plugin needed).                                                                                                                                                                    |
| <code>record_source</code> · <code>audit_sources</code>                                                                                                      | <b>Source ledger.</b> Record where ingested content came from (URL, hash, date); audit a vault's sources for drift and gaps.                                                                                                                                                                                                                                                                                                                                                  |
| <code>build_open_link</code> · <code>open_in_obsidian</code> · <code>get_view_link</code>                                                                    | <b>Navigation.</b> Ready-to-paste click-to-open links (path-verified against the vault; on a diskless vault the link is still built, flagged <code>pathVerified: false</code> ); server-side open (raise Obsidian window, optional heading anchor) — no browser round-trip; ephemeral browser view-link to a live GUI for remote deployments.                                                                                                                                 |

**Tips** · Type `/obsidian-router:` in Claude Code → autocomplete · Every command accepts a `vault` argument (wrappers fall back to the default) · `vault: "*" on search / search_smart` = cross-vault fan-out · Trigger phrases are indicative — Claude recognizes variants · Write results carry a ready-made `clickToOpenUrl` — one click opens the note in Obsidian · Full docs: `README.md`, `docs/features/` (13 pages), `docs/auto-enrichment.md` in the repo.