

obsidian-mcp-router — quick reference

v0.8.2 · multi-vault Obsidian MCP server + Claude Code plugin (30 slash commands)

github.com/tboome33/obsidian-mcp-router

The router in 30 seconds

A single MCP process that knows **all your Obsidian vaults** (local + remote). Each tool takes a `vault` parameter (or uses the default). No more registering one MCP server per vault.

- **One entry** in `~/.claude.json` → all vaults visible everywhere (Code + Desktop)
- **Local + remote vaults** treated identically — drop URL + API key into the config, done
- **Cross-vault:** `vault: "*"` auto-fans-out across every vault
- **Lock mode:** restrict the session to a single vault (safety, focus)
- **Auto-enrichment** (v0.8.2): Claude proactively suggests wiki saves at 3 moments (validation / result / topic switch)

Vault setup

1. Have Node.js $\geq 20.18.1$
2. Install the **Local REST API** plugin in the Obsidian vault (community plugins)
3. Optional for `search_smart` : **Smart Connections** + **obsidian-mcp-router-bridge** (from GitHub)
4. Optional for Templater: **Templater** (community plugins)
5. Auto-bootstrap the vault:

```
npm run setup-vault -- "C:\VAULTS\MyVault"
```

⇒ writes `.env` with `VAULT_PATH` , `OBSIDIAN_API_KEY` , `OBSIDIAN_BASE_URL` ; allocates a unique port; adds to the registry.

6. Verify: `/obsidian-router:meta-status` or just say "*diagnose the router*"

Configuration — environment variables (workspace `.env`)

<code>VAULT_PATH</code>	Path of the current vault. Auto-detection: if it matches a registered vault, that vault becomes the default. Written by <code>setup-vault.mjs</code> .
<code>OBSIDIAN_ROUTER_DEFAULT_VAULT</code>	Explicit override of the default vault for this process. Wins over <code>VAULT_PATH</code> and over <code>config.defaultVault</code> .
<code>OBSIDIAN_ROUTER_LOCKED</code>	Locks the router to one vault for the session. Any tool call to another vault throws. Set via <code>/obsidian-router:lock <vault> --persist</code> .
<code>OBSIDIAN_ROUTER_AUTO_ENRICH</code>	Wiki auto-enrichment mode: <code>ClaudeAsk</code> (default) <code>Hybrid</code> <code>FullAuto</code> <code>off</code> . Set via <code>/obsidian-router:auto-mode <Mode> --persist</code> .
<code>OBSIDIAN_ROUTER_NO_WATCH</code>	Disables hot-reload of the config file (useful for debugging).

Important files — where things live

<code>~/.claude/obsidian-mcp-router/config.json</code>	Main router config (vaults, port registry, vault names, <code>defaultVault</code> , <code>disabledVaults</code> , <code>remoteVaults</code>). Hot-reload enabled.
<code>~/.claude.json</code>	Claude Code/Desktop config. Must contain the <code>mcpServers.obsidian-router</code> entry pointing to the <code>obsidian-mcp-router</code> binary.
<code>~/.claude/settings.json</code>	Activates the plugin (<code>extraKnownMarketplaces</code> + <code>enabledPlugins</code>) and optional hooks (<code>SessionStart</code> , <code>PostCompact</code> , <code>Stop</code>).
<code><workspace>/ .env</code>	Environment variables for the current workspace (above). Auto-loaded at router boot.
<code><vault>/CLAUDE.md</code>	Vault wiki consigne — loaded by Claude Code into context. Includes the auto-enrichment consigne (4 modes) since v0.8.2.
<code><vault>/{index,log,hot,overview}.md</code>	Karpathy LLM-wiki structure (catalog, journal, hot cache, overview). Scaffolded by <code>/obsidian-router:wiki</code> .
<code>obsidian-mcp-router/templates/wiki/CLAUDE.md</code>	Canonical template for the vault <code>CLAUDE.md</code> — cloned into every new vault scaffold.
<code>obsidian-mcp-router/docs/auto-enrichment.md</code>	Full auto-enrichment guide EN+FR: 4 modes (use cases) + 4 placement channels.

30 slash commands /obsidian-router:<name> · auto-trigger on natural language

(EN + FR)

 14 MCP wrappers — one per router tool

Categories: discover · read · write · manage · template

COMMAND	EFFECT	TRIGGER PHRASE (EN/FR)
discover-list-vaults	List vaults (online/latency/lock state)	"list my vaults" / "liste mes vaults"
discover-list-files	List files in a vault directory	"list files in Sessions" / "liste les fichiers de X"
read-get	Read a file (markdown + frontmatter)	"show me X" / "montre-moi X"
read-search	Plain-text (substring) search	"grep for <text>" / "trouve <texte>"
read-search-smart	Semantic search (Smart Connections)	"find notes about X" / "trouve mes notes sur X"
read-frontmatter	Read frontmatter (object or one key)	"metadata of X" / "quel est le statut de X"
write-create-or-replace	PUT — create or replace a file	"save this as X.md" / "crée une note X"
write-append	POST — append to a file	"append to my journal" / "ajoute à X"
write-patch	Surgical PATCH (heading/block/frontmatter)	"edit X section in Y" / "édite la section X dans Y"
write-frontmatter-set	Set one frontmatter key	"tag this with X" / "passe le statut de X à closed"
write-frontmatter-merge	Set multiple keys in sequence	"on X set status=closed outcome=tp1"
manage-move	Move or rename a file	"move X to Y" / "renomme X en Y"
manage-delete	Delete a file (2-step confirm guard)	"delete X" then "yes confirm=true"
template-execute	Execute a Templater template	"run X template" / "rends Templates/X.md avec arg=v"

3 router-state commands (lock + auto-enrichment)

COMMAND	EFFECT	TRIGGER PHRASE (EN/FR)
lock	Restrict the session to one vault (volatile or <code>--persist</code>)	"I only want to work on X" / "verrouille sur X"
unlock	Lift the lock, restore multi-vault routing	"unlock vaults" / "déverrouille les vaults"
auto-mode	Set the auto-enrichment mode (ClaudeAsk / Hybrid / FullAuto / off)	"switch to Hybrid mode" / "passe en mode Hybrid"

3 conversational helpers (setup + diagnostic)

COMMAND	EFFECT	TRIGGER PHRASE (EN/FR)
meta-setup	Bootstrap the router on a fresh machine	"setup obsidian-mcp-router" / "installe le router"
meta-add-vault	Interactive vault-add flow (local or remote)	"connect my remote vault" / "ajoute un vault"
meta-status	Health-check every vault with fix hints	"are my vaults reachable" / "diagnostique le router"

10 knowledge-management commands (Karpathy-style LLM-wiki)

COMMAND	EFFECT	TRIGGER PHRASE (EN/FR)
wiki	Scaffold wiki/ in a vault (index, log, hot, overview)	"set up a wiki" / "scaffold un wiki"
wiki-ingest	Ingest a source → entity/concept pages + cross-refs	"absorb this article" / "ingère cette URL"
wiki-query	3-tier RAG over the wiki (no web)	"what does my wiki say about X" / "d'après mes notes ..."
wiki-lint	Health check (orphans, dead links, index drift)	"audit my wiki" / "lint le wiki"
wiki-fold	Idempotent log rollup under wiki/folds/	"fold the log" / "compacte le journal"
save	File the conversation as a typed wiki note (session/decision/ADR/...)	"save this" / "sauvegarde ça"
autoresearch	Autonomous web→synth→file loop	"research X online" / "fais une recherche web sur X"
canvas	Create/edit Obsidian .canvas files	"create a canvas for X" / "crée un canvas pour X"
defuddle	Strip noise from web pages before ingestion	"defuddle <url>" / "nettoie cette page"
obsidian-bases	Create/edit Obsidian .base files (database)	"create a base for X" / "crée une base pour X"

Tips · Type `/obsidian-router:` in Claude Code → autocomplete · Every command accepts a `vault` argument (wrappers fall back to the default) · `vault: "*" on read-search` and `read-search-smart` = cross-vault fan-out · Trigger phrases are indicative — Claude recognizes variants · The `meta-*` commands plus `save` / `autoresearch` / `wiki*` invoke skills, the others are direct MCP wrappers · Full docs: `docs/auto-enrichment.md` and `README.md` in the repo.