

Oldcastle Building Envelope®

1-866-Oldcastle (653-2278) - www.obe.com


RELIANCE™-TC TYPE I (STD. HORIZONTALS & TC VERTICALS) 2-1/2" X 6" W/ 1" TYPICAL INFILL

(Drawing numbers---i.e., H3501---used as CAD detail reference only)


| Elevation | | Corner Details | | |
|--|--|----------------|---------------------------------|--|
| | | V7515 | 90° Outside Corner - 2 Mullion | |
| Horizonta | Horizontal Details | | 90° Inside Corner - 2 Mullion | |
| H3501 | Head | V7521 | 90° Outside Corner | |
| H3504 | Sill | V7523 | 135° Outside Corner | |
| H3505 | Intermediate Horizontal | V7527 | 135° Inside Corner - 2 Mullion | |
| H3508 | Roll-Over Horizontal | V7570 | SSG 90° Outside Corner Option 1 | |
| H3509 | Roll-Under Horizontal | V7571 | SSG 90° Outside Corner Option 2 | |
| H3518 | Horizontal at Operable Window (Pocket Frame) | | | |
| H3519 Horizontal at Operable Window (Flat Frame) | | Misc. Details | | |
| | | H0042 | Steel Anchoring | |
| Vertical D | <u> Details</u> | H3421 | Shear Block Anchoring | |
| V7501 | Jamb | H7425 | 'F' & 'T' Anchoring | |
| V7502 | Typical Vertical | H7443 | Mullion Splicing | |
| V7505 | Heavy Vertical | H7446 | Spandrel Glazing Options | |
| V7509 | Vertical at Operable Window | H7448 | Vision Glazing Options | |
| V7552 | SSG Vertical | | - · | |

Note: Type II horizontals may be used in lieu of standard Reliance horizontals for improved thermal performance.


Table of Contents




Reliance™-TC Type I - Standard Horizontals and TC Verticals 2-1/2" x 6" w/ 1" Glazing - Elevation




Head at Vision - H3501




Reliance™ Curtain Wall Sill at Vision - H3504




Reliance™ Curtain Wall
Intermediate Horizontal at Vision - H3505





Reliance™ Curtain Wall
Roll-over Horizontal at Vision - H3508





Reliance™ Curtain Wall
Roll-under Horizontal at Vision - H3509














Reliance™-TC Type I Vertical at Operable Window - V7509




Reliance™-TC Type I SSG Vertical - V7552




Reliance[™]-TC Type I 90° Outside Corner - V7515





Reliance™-TC Type I 90° Inside Corner - V7517




90° Outside Corner - V7521









Reliance™-TC Type I SSG 90° Outside Corner w/ Cap - V7570



Reliance™-TC Type I SSG 90° Outside Corner - V7571





Standard Curtain Wall Steel Anchor - H0042



NOTE:

- 1. ANCHOR BOLT DESIGNED BY STRUCTURAL ENGINEER.
- 2. WWW-104-01 ALUM. ANCHOR MAXIMUM ALLOWABLE END REACTION IS 375 LBS. PER ANCHOR, I.E. 375 LBS. AT JAMB VERTICAL, 750 LBS. AT INTERMEDIATE VERTICAL.







| "F" ANCHOR CHART | | | |
|------------------|---------------|--|--|
| PART NO. | MULLION | | |
| WW-103-05 | WW-520/WW-538 | | |
| WW-103-06 | WW-420/WW-438 | | |
| WW-103-07 | WW-530/WW-531 | | |
| WW-103-08 | WW-430/WW-431 | | |

| "T" ANCHOR CHART | | | |
|------------------|---------------|--|--|
| PART NO. | MULLION | | |
| WW-102-02 | WW-504 | | |
| WW-102-04 | WW-404 | | |
| WW-102-08 | WW-520/WW-538 | | |
| WW-102-09 | WW-420/WW-438 | | |
| WW-102-10 | WW-530/WW-531 | | |
| WW-102-11 | WW-430/WW-431 | | |
| WW-102-13 | WW-234 | | |
| WW-102-14 | WW-233 | | |
| WW-102-22 | AW-270 | | |


NOTE:

1. ANCHOR BOLT SIZE AND LOCATION DETERMINED BY STRUCTURAL ENGINEER





90° OUTSIDE CORNER





| 6" SYSTEM DEPTH | | | | |
|-----------------|-------------|--------------|--|--|
| MULLION | REAR SPLICE | FRONT SPLICE | | |
| WW-420 | CW-90 | WW-203-01 | | |
| WW-430 | CW-542 | WW-203-01 | | |
| WW-431 | CW-542 | | | |
| WW-438 | CW-90 | | | |
| AW-270 | AW-129-01 | | | |
| WW-233 | WW-213-01 | | | |


| 7-1/4" SYSTEM DEPTH | | | | | |
|---------------------|-----------|--------------|--|--|--|
| MULLION REAR SPLICE | | FRONT SPLICE | | | |
| WW-520 | CW-66 | WW-203-01 | | | |
| WW-530 | CW-1496 | WW-203-01 | | | |
| WW-531 | CW-1496 | | | | |
| WW-538 | CW-66 | | | | |
| AW-270 | AW-129-01 | | | | |
| WW-234 | WW-214-01 | | | | |


REFERENCE INSTALLATION MANUAL FOR ADDITIONAL SPLICE INFO.

Reliance™-TC Type I Mullion Splice - H7443










| GLAZING CHART | | | | | |
|---------------------|--------------------|-----------------------------------|---|--|--|
| INFILL THICKNESS | INTERIOR GASKET | EXTERIOR GASKET (VERTICALS) | EXTERIOR GASKET (HORIZONTALS & CORNERS) | | |
| 3/16" | GP-103 | GP-133 | GP-118 | | |
| 1/4" | GP-103 | GP-113 | GP-103 | | |
| 5/16" | GP-103 | GP-128 | GP-117 | | |
| 3/8" | GP-117 | GP-128 | GP-117 | | |

NOTES:

- GP-110 SETTING BLOCK IS TYPICAL @ SPANDREL GLAZING U.N.O.
- 2. GLASS POCKET WIDTH WITH ADAPTOR = 3/4"

Reliance™-TC Type I Spandrel Glazing Options - H7446



Reliance™-TC Type I Vision Glazing Options - H7448