Python Programming

Python Classes/Objects

```
# Defining a class
class Person:
    def __init__ (self, name, age):
        self.name = name
        self.age = age

    def __str__ (self):
        return f"{self.name}({self.age})"

    def myfunc(self): # An object method
        print(f"Hello, my name is {self.name}")

# Creating an object
p1 = Person("John", 36)

# Accessing attributes and methods
print(p1)
p1.myfunc()
```

John(36) Hello, my name is John

Inheritance and Polymorphism

```
# Parent Class
class Person:
   def init (self, first name, last name):
       self.first name = first name
       self.last name = last name
   def full name(self):
       return f"{self.first name} {self.last name}"
   def greet(self):
       return f"Hello, my name is {self.full name()}."
# Child Class
class Student(Person):
   def init (self, first name, last name, student id):
       super(). init (first name, last name)
       self.student id = student id
   def student info(self):
       return f"ID: {self.student id}, Name: {self.full name()}"
# Another Child Class
class Teacher(Person):
   def init (self, first name, last name, subject):
       super(). init (first name, last name)
       self.subject = subject
   def teach(self):
       return f"{self.full name()} is teaching {self.subject}."
# Instantiate Parent and Child Classes
person = Person("Jane", "Smith")
print(person.greet())
student = Student("John", "Doe", "S12345")
print(student.greet())
print(student.student info()
teacher = Teacher("Emily", "Davis", "Mathematics")
print(teacher.greet())
print(teacher.teach())
```

Hello, my name is Jane Smith.
Hello, my name is John Doe.
ID: S12345, Name: John Doe
Hello, my name is Emily Davis.
Emily Davis is teaching Mathematics.

Iterators

```
class MyNumbers:
    def __iter__(self):
         self.a = 1
         return self
    def __next__(self):
    if self.a <= 5:</pre>
             x = self.a
             self.a += 1
             return x
         else:
             raise StopIteration
my_numbers = MyNumbers()
my_iter = iter(my_numbers)
for num in my_iter:
    print(num)
```

1 2 3

5

Date/Time

```
import datetime
# Getting the current date and time
current datetime = datetime.datetime.now()
print("Current date and time:", current datetime)
# Extracting specific parts of the date/time
print("Year:", current datetime.year)
print("Month:", current datetime.month)
print("Day:", current datetime.day)
print("Hour:", current datetime.hour)
print("Minute:", current datetime.minute)
print("Second:", current datetime.second)
# Creating a specific date
specific date = datetime.datetime(2023, 12, 25) # Year, Month, Day
print("Specific date:", specific date)
# Formatting the current date/time into a readable string
formatted date = current datetime.strftime("%Y-%m-%d %H:%M:%S")
print("Formatted date and time:", formatted date)
# Parsing a string into a datetime object
date string = "2024-12-28 15:45:10"
parsed date = datetime.datetime.strptime(date string, "%Y-%m-%d %H:%M:%S")
print("Parsed date:", parsed date)
# Using the date and time classes
current date = datetime.date.today()
print("Current date:", current date)
specific time = datetime.time(14, 30, 45) # Hour, Minute, Second
print("Specific time:", specific time)
# Calculating the difference between two dates
date1 = datetime.datetime(2024, 1, 1)
date2 = datetime.datetime(2023, 1, 1)
difference = date1 - date2
print("Difference in days:", difference.days)
```

Current date and time: 2024-12-28 15:59:54.884711

Year: 2024 Month: 12 Day: 28 Hour: 15 Minute: 59

Second: 54

Specific date: 2023-12-25 00:00:00 Formatted date and time: 2024-12-28 15:59:54

> Parsed date: 2024-12-28 15:45:10 Current date: 2024-12-28 Specific time: 14:30:45 Difference in days: 365

Python Math

```
import math
# Constants
print("Value of pi:", math.pi) # Value of pi
print("Value of e:", math.e) # Euler's number
# Mathematical functions
# Absolute value
x = -5
print("Absolute value of -5:", math.fabs(x))
# Rounding values
print("Round 5.67 to nearest integer:", round(5.67))
print("Round 5.67 down:", math.floor(5.67)) # Round down
print("Round 5.67 up:", math.ceil(5.67)) # Round up
# Power and square root
print("2 raised to the power of 3:", math.pow(2, 3))
print("Square root of 16:", math.sqrt(16))
# Trigonometric functions
# Converting degrees to radians
angle degrees = 90
angle radians = math.radians(angle degrees)
print(f"90 degrees in radians:", angle radians)
# Sine, cosine, and tangent
print("Sine of 90 degrees:", math.sin(math.radians(90))) # Sin of 90 degrees
print("Cosine of 0 degrees:", math.cos(math.radians(0))) # Cos of 0 degrees
print("Tangent of 45 degrees:", math.tan(math.radians(45))) # Tan of 45
degrees
# Inverse trigonometric functions
print("Inverse sine of 1:", math.asin(1)) # Inverse sine
print("Inverse cosine of 0:", math.acos(0)) # Inverse cosine
# Logarithmic functions
print("Natural log of e:", math.log(math.e)) # Natural logarithm (log base e)
print("Log base 10 of 100:", math.log10(100)) # Logarithm with base 10
# Factorial
print("Factorial of 5:", math.factorial(5)) # Factorial of 5
```

Value of pi: 3.141592653589793 Value of e: 2.718281828459045 Absolute value of -5: 5.0 Round 5.67 to nearest integer: 6 Round 5.67 down: 5

Round 5.67 down: 5 Round 5.67 up: 6

2 raised to the power of 3: 8.0

Square root of 16: 4.0

90 degrees in radians: 1.5707963267948966

Sine of 90 degrees: 1.0 Cosine of 0 degrees: 1.0

Inverse cosine of 0: 1.5707963267948966

Natural log of e: 1.0 Log base 10 of 100: 2.0 Factorial of 5: 120

Greatest common divisor of 36 and 60: 12
Hyperbolic sine of 1: 1.1752011936438014
Hyperbolic cosine of 1: 1.5430806348152437
Combinations of 5 items taken 3 at a time (C(5, 3)): 10

Permutations of 5 items taken 3 at a time (P(5, 3)): 60

```
# Greatest common divisor
a = 36
b = 60
print("Greatest common divisor of 36 and 60:", math.gcd(a, b)) # GCD of 36 and
60

# Hyperbolic functions
print("Hyperbolic sine of 1:", math.sinh(1))
print("Hyperbolic cosine of 1:", math.cosh(1))

# Combinations and permutations
n = 5
k = 3
print(f"Combinations of 5 items taken 3 at a time (C(5, 3)):", math.comb(n, k))
# Combinations
print(f"Permutations of 5 items taken 3 at a time (P(5, 3)):", math.perm(n, k))
# Permutations
```

User Input

```
# Getting user input using input() function
name = input("Enter your name: ")
print(f"Hello, {name}!")
# Getting numerical input and converting it to an integer
age = int(input("Enter your age: "))
print(f"You are {age} years old.")
# Getting numerical input and converting it to a float
height = float(input("Enter your height in meters: "))
print(f"Your height is {height} meters.")
# Handling multiple inputs in one line
x, y = input("Enter two numbers separated by a space: ").split()
x = int(x)
y = int(y)
print(f"You entered \{x\} and \{y\}. The sum is \{x + y\}.")
# Using input to interact with the program more dynamically
operation = input("Do you want to add or subtract? (Enter 'add' or 'subtract'):
").strip().lower()
if operation == "add":
  a = int(input("Enter the first number: "))
  b = int(input("Enter the second number: "))
  print(f"The sum is {a + b}.")
elif operation == "subtract":
  a = int(input("Enter the first number: "))
  b = int(input("Enter the second number: "))
  print(f"The difference is {a - b}.")
else:
  print("Invalid operation.")
```

Enter your name: Carter
Hello, Carter!
Enter your age: 35
You are 35 years old.
Enter your height in meters: 1.7
Your height is 1.7 meters.
Enter two numbers separated by a space: 1 2
You entered 1 and 2. The sum is 3.
Do you want to add or subtract? (Enter 'add' or 'subtract'): add
Enter the first number: 2
Enter the second number: 3

The sum is 5.

String Formatting

```
# Basic String Formatting with f-strings (Python 3.6+)
name = "Alice"
age = 30
greeting = f"Hello, my name is {name} and I am {age} years old."
print(greeting)
# String Formatting using the format() method
greeting2 = "Hello, my name is {} and I am {} years old.".format(name, age)
print(greeting2)
# Using positional and keyword arguments in the format() method
greeting3 = "Hello, my name is {0} and I am {1} years old. {0} is learning
Python.".format(name, age)
print(greeting3)
# Using keyword arguments in the format() method
greeting4 = "Hello, my name is {name} and I am {age} years
old.".format(name=name, age=age)
print(greeting4)
# Formatting numbers (e.g., decimals, integers)
pi = 3.141592653589793
formatted pi = f"The value of pi is approximately {pi:.2f}"
print(formatted pi)
# Padding and aligning strings with format()
text = "Hello"
aligned text = f"{text:>10}" # Right-align the text
print(aligned text)
aligned text2 = f"{text:<10}" # Left-align the text</pre>
print(aligned text2)
aligned text3 = f"{text:^10}" # Centre-align the text
print(aligned text3)
# Padding numbers with leading zeros
number = 42
formatted number = f"{number:05}"
print(formatted number)
# Using format() with numbers
number = 1234567
formatted number2 = "{:,}".format(number)
```

Hello, my name is Alice and I am 30 years old.
Hello, my name is Alice and I am 30 years old.
Hello, my name is Alice and I am 30 years old. Alice is
learning Python.
Hello, my name is Alice and I am 30 years old.
The value of pi is approximately 3.14

Hello Hello Hello 00042 1,234,567 45.00% The result of 5 + 10 is 15.

```
print(formatted_number2)

# Formatting percentages
value = 0.45
formatted_percentage = f"{value:.2%}" # 45.00%
print(formatted_percentage)

# Combining string formatting with expressions
x = 5
y = 10
result = f"The result of {x} + {y} is {x + y}."
print(result)
```