



Server-Side Languages

Todd Smith
tbsmith@fullsail.com

Welcome to SSL!

We will learn to build websites with PHP and Python.

Day 1



Server-Side Languages

About Me

Todd Smith

Course Director for SSL and ASL

tbsmith@fullsail.com | 407-679-0100 ext. 7937

Office Hours: <http://goo.gl/RBfas>

- Education:

- Bachelor's, Applied Discrete Mathematics, Auburn University, 2004
- Master's, Applied Mathematics, UCF, 2007
- PhD, Mathematics, UCF, 2011

- Programming Experience: Perl, PHP, Java for Android, Mathematica, Python, JQuery
- Work Experience: Web Developer, System Admin and Math Teacher

Day 1



Server-Side Languages

About SSL

- Why might this class be taught simultaneously with the database class?
- How far will we get in this class?
- Next month is ASL- what will we do there?

Day I



Server-Side Languages


Server-side vs. Client-side

Basics

- Client (web browser) sends requests to the server-side script
- Script's code and the data it accesses are all on the server
- The script makes html dynamically to reply to the browser

Advantages

- Databases remain secure
- Content is customized for the client
- Can take advantage of software on or computing power of the server



Day I



Server-Side Languages

Daily Calendar

Day 1

1. Server Configuration
2. Git Repository Setup
3. Includes
4. Views

Day 2

1. Controller Classes
2. Pretty URLs

Day 3

1. URL & Form Data
2. Validation

Day 4

1. Database Queries
2. Model Classes

Day 5

1. Hashing and Salting
2. PHP Sessions

Day 6

1. JSON
2. Services

Day 7

1. CodeIgniter
2. Django
3. Start 2-day projects

Day 8

1. Work on projects

Day 9

1. Present Projects
2. Review for Practical

Day 10

Practical Exam



Server-Side Languages

Screencasts

4% of your grade (like one lab)

You must make at least one.

They should demonstrate something you learned in class. Make your video instructive and useful for students in the next SSL class.

Day I



Server-Side Languages

SSL Rubric - <http://goo.gl/F0BFo>

Assignments	Points
Labs 1-7 and videos	32
Two-day project	28
Practical final	30
Professionalism	10

Day 1



Server-Side Languages

Rules

- During Lecture and Lab, no FB or anything else.
- Phones should be on silent mode (not vibrate).
- No food or drinks.
- 10 day course, max 8 hours unexcused, 16 excused.
- 15 minutes late = 2 hours
- Contact me if you will miss class.

Day 1



Server-Side Languages

Turning In Work

- All deadlines are final. No late work.
- Do not commit your videos! Instead, update a screencasts.txt file with a youtube link.
- Make a github.com account.
- Dump your database and website code inside the day# folder and tar it up as yourname-day#.tgz
- Push to <https://github.com/tbsmithFS/SSL1308>

Day 1



Server-Side Languages

Our Languages of Choice



- php.net
- widely supported
- open source
- more symbols



- python.org
- widely supported
- open source
- more english



Server-Side Languages

PHP and Python Scripts

PHP:

```
html can be here

<?php
phpinfo();
?>

and here
```

PHP scripts start with `<?php` and end with `?>`

Python:

```
#!/usr/bin/python

import cgi

cgi.test()
```

Python scripts start with a `#!` and the path to the Python interpreter, usually `/usr/bin/python`

Day 1




Server-Side Languages

PHP Scalar Variables and Output

All PHP variables start with a dollar sign.

The echo() function will output text to the browser.

```
<?php  
$dog = "Lucy";  
echo $dog;  
?>
```





Server-Side Languages

PHP Debugging Tip #1

If your variable is not behaving as expected, use the `var_dump()` function to see exactly what's inside it.

```
<?php  
$dog = "Lucy";  
var_dump($dog);  
?>
```

http://example.com/
example.com
Most Visited ▾ Getting Started
string(4) "Lucy"

Day 1




Server-Side Languages

Python Scalar Variables and Output

All Python variables are just letters.

The print function will output text to the browser.

```
#!/usr/bin/python  
dog = "Lucy"  
print "Content-type: text/html\n\n"  
print dog
```






Server-Side Languages

Python Scalar Variables and Output

All Python variables are just letters.

The print function will output text to the browser.

```
#!/usr/bin/python  
dog = "Lucy"  
print "Content-type: text/html\n\n"  
print dog
```






Server-Side Languages

PHP Arrays

Arrays can be built with the `array()` function and can be accessed with the square brackets.

```
<?php  
$shoppingList = array("Milk", "Eggs", "Cheese");  
echo $shoppingList[1];  
?>
```

Indexes start at 0



Day 1




Server-Side Languages

Python Lists

Lists can be built and accessed with square brackets.

```
#!/usr/bin/python  
print "Content-type: text/html\n\n"  
numbers = ['one', 'two', 'three']  
print numbers[1]
```



Indexes start at 0

Day 1




Server-Side Languages

PHP Associative Arrays

Associative arrays can be built with the `array()` function and the `=>` symbols, and can be accessed with square brackets.

```
<?php
$mall = array(
    "name" => "Mall at Millenia",
    "size" => 155000, // square feet
    "location" => "Orlando",
    "stores" => array(
        "Macys",
        "Hollister",
        "Apple",
        "Godiva"
    )
);

echo $mall['stores'][2];
?>
```





Server-Side Languages

PHP Debugging Tip #1 example

```
<?php
$things = array(
    'car' => array(
        'year' => 1995,
        'make' => 'Dodge',
        'model' => 'Viper'
    ),
    'house' => array(
        'location' => 'Florida',
        'price' => 105000,
    )
);
var_dump($things);
?>
```

```
1 array(2) {
2     ["car"]=>
3     array(3) {
4         ["year"]=>
5         int(1995)
6         ["make"]=>
7         string(5) "Dodge"
8         ["model"]=>
9         string(5) "Viper"
10    }
11    ["house"]=>
12    array(2) {
13        ["location"]=>
14        string(7) "Florida"
15        ["price"]=>
16        int(105000)
17    }
18 }
19
```



Server-Side Languages

Python Dictionaries


Dictionaries can be built with curly braces and colons.
The syntax is exactly the same as JSON.

```
#!/usr/bin/python

print "Content-type: text/html\n\n"

collection = {
    'cards': {
        'baseball': {
            'quantity': 5000,
            'value': 600, # dollars
        },
        'football': {
            'quantity': 200,
            'value': 120,
        }
    },
    'stamps': {
        'numBooks': 5,
        'value': 300,
    },
}

print collection['cards']['football']['value']
```



Day I



Server-Side Languages

PHP Includes/Imports

```
include "models/UserInterface.php";
```

Read about the PHP *include* and *require* functions:

http://www.w3schools.com/php/php_includes.asp

Day 1



Server-Side Languages

Python Includes/Imports

```
from models.Rectangle import Rectangle
```

Directory name

File name

Class name

Day 1



Server-Side Languages

PHP OOP

“Dog.php”

```
<?php
class Dog {

    public $name;
    public $age;
    private $dogID;

    public function setDogID($givenID) {
        // TO DO: check if the givenID is okay
        $this->dogID = $givenID;
    }

    public function getDogID() {
        return $this->dogID;
    }

    public static function getDogYears($peopleYears) {
        return $peopleYears * 7;
    }

}
?>
```

Day 1



Server-Side Languages

PHP OOP


```
<?php

require "Dog.php";

$myDog = new Dog();
$myDog->name = "Lucy";
$myDog->age = 6;
$myDog->setDogID(123);

echo "The dog named " . $myDog->name . " has ID:" . $myDog->getDogID();
echo "<br/>\n";
echo "10 human years is " . Dog::getDogYears(10) . " dog years.";
echo "<br/>\n";

?>
```



Day 1



Server-Side Languages

In-class assessment: PHP OOP

Make a class with private and public methods.

Include it in the index file and instantiate it.

Use its methods and get and set its values.

Day 1



Server-Side Languages

Python OOP

```
#!/usr/bin/python
```

“models/Rectangle.py”

```
class Rectangle:
```

```
    def getArea(self):  
        return self.width * self.height
```

```
    def isSquare(self):  
        return True if self.width == self.height else False
```

Day I



Server-Side Languages

Python OOP


```
#!/usr/bin/python

print "Content-type: text/html\n\n"

from models.Rectangle import Rectangle

rect = Rectangle()
rect.name = "Bob"
rect.height = 3
rect.width = 4

print "The rectangle {} has area {}".format(rect.name, rect.getArea())
```



Day I



Server-Side Languages

In-class assessment: Python OOP

Make a class with several methods.

Import it into the index file and instantiate it.

Use its methods and get and set its values.

Day 1



Server-Side Languages

PHP For Loops

```
<?php  
  
for ($i=0; $i<4; $i++) {  
    echo $i;  
}  
  
?>
```

A screenshot of a web browser window. The address bar shows 'http://example.com/'. Below the address bar, there is a search bar with 'example.com' entered. Underneath the search bar, there are two buttons: 'Most Visited' and 'Getting Started'. The main content area of the browser displays the output of the PHP code, which is the string '0123'.

Day 1



Server-Side Languages

Python For Loops

```
#!/usr/bin/python

print "Content-type: text/html\n\n"

for i in range(0, 4):
    print i
    print "<br/>"

friends = ['Joe', 'Jen', 'Jon', 'Jae']

for friend in friends:
    print "My friend is " + friend + ".<br/>"
```

The screenshot shows a web browser window with the address bar displaying 'http://example.com/'. The browser's address bar also shows 'example.com'. Below the address bar, there are navigation buttons (back, forward, home) and a search bar. The main content area of the browser displays the output of the Python script: a list of numbers 0, 1, 2, 3, followed by four lines of text: 'My friend is Joe.', 'My friend is Jen.', 'My friend is Jon.', and 'My friend is Jae.' Each line of text is on a new line, as indicated by the HTML line break tags in the code.



Server-Side Languages



Python File Handling

```
#!/usr/bin/python

print "Content-type: text/html\n\n"

file_handle = open("list.txt", "r")

for line in file_handle:
    print "This line reads: " + line + "<br/>"
```





Server-Side Languages

Python Templating

```
#!/usr/bin/python

from string import Template

print "Content-type: text/html\n\n"

file_handle = open("list.txt", "r")


data = {
    'list_name': 'Shopping',
    'fav_color': 'red',
    'fav_food': 'beans'
}

for line in file_handle:
    print Template(line).substitute(data)
```

My \$list_name list:

\$fav_color shoes
Shirt that matches \$fav_color shoes
Some \$fav_food

“list.txt”



Day I



Server-Side Languages

In-class assessment: Python Templating

Make a view with several template variables.

Create a dictionary with keys that match the variables.


Use the Template class to print the view to the browser.

Day 1



Server-Side Languages

MVC



Day I



Server-Side Languages

Basic Website Structure



header

nav

body

footer

Day 1



Server-Side Languages

Using a model and views

In-class assessment:

- Make a file in the models directory called `UserInterface.php`
- Define a class called `UserInterface`
- Define a public static method called `printHeader` that takes no arguments and prints “Content-type: text/html\n\n”
- Define a public static method called `getView` that will:
 - take two arguments: the file(view) to include, and an associative array
 - Include the view
 - Displays information from the array in the view
- Include the model in the `index.php` file
- Make a header, body, and footer view that uses information from the passed-in associative array
- In the index file, construct an associative array and pass it to the model for the header, body, and footer views

Day I



Server-Side Languages

Lab I: Make two simple websites

- One website will use PHP
- One website will use Python
- Make a favicon.ico
- Include a css folder with a different style for each site

Day I