



# Server-Side Languages

Todd Smith  
[tbsmith@fullsail.com](mailto:tbsmith@fullsail.com)

## Welcome to SSL Day 6!

Interacting with a JSON API

Day 6



# Server-Side Languages

## Overview

In this class we will connect to a JSON API and we will create our own JSON service

- Encoding and Decoding JSON
- Reading and Writing JSON
- Reading from a URL

Day 6



# Server-Side Languages

## What is JSON?

A structured way to encode data.

```
myObject = {  
  "first": "John",  
  "last": "Doe",  
  "age": 39,  
  "sex": "M",  
  "salary": 70000,  
  "registered": true,  
  "favorites": {  
    "color": "Blue",  
    "sport": "Soccer",  
    "food": "Spaghetti"  
  }  
}
```



# Server-Side Languages

What is decoded JSON?

In PHP, decoded JSON becomes an associative array.

In Python, decoded JSON becomes a dictionary.

Day 6



# Server-Side Languages

## JSON in PHP

```
json_encode($g
```

```
json_decode($
```

Day 6



# Server-Side Languages

## PHP - json\_encode

```
$d = array(  
    "name" => "Joe",  
    "grades" => array(  
        "math" => "A",  
        "science" => "B"  
    )  
);  
echo json_encode($d);
```

```
{"name": "Joe", "grades": {"math": "A", "science": "B"}}
```



# Server-Side Languages

## PHP - json\_decode

```
$j = '{"name":"Joe","grades":{"math":"A","science":"B"}}';  
var_dump(json_decode($j));
```

```
object(stdClass)#1 (2) {  
  ["name"]=>  
  string(3) "Joe"  
  ["grades"]=>  
  object(stdClass)#2 (2) {  
    ["math"]=>  
    string(1) "A"  
    ["science"]=>  
    string(1) "B"  
  }  
}
```

Day 6





# Server-Side Languages

## PHP - json\_decode

Drilling down and the missing entry error

```
$j = '{"name":"Joe","grades":{"math":"A","science":"B"}}';  
$o = json_decode($j);  
echo $o->name . " got an " . $o->grades->math . " in math.\n";  
echo "This doesn't exist: " . $o->nothing;
```

```
Joe got an A in math.  
PHP Notice: Undefined property: stdClass::$nothing in /Users/tbsmith/  
Sites/test2.php on line 9  
This doesn't exist:
```





# Server-Side Languages

## JSON in Python

```
import json
```

```
json.loads(
```

```
json.dumps(
```



# Server-Side Languages

## Python - json.dumps

```
>>> import json
>>> info = {'name': 'Joe',
...        'grades': {'math': 'A',
...                    'science': 'B'}}
>>> json.dumps(info)
'{"grades": {"science": "B", "math": "A"}, "name": "Joe"}'
```

The syntax of a python dictionary is exactly the same as that of a JSON object.

In this example, a dictionary called 'info' is made and converted into a JSON string.



# Server-Side Languages

## Python - json.loads

Drilling down and the missing entry error

JSON objects can be embedded in other JSON objects.

```
>>> import json
>>> info_string = '{"name":"lamp","price":{"retail":9.99,"sale":5.99}}'
>>> info = json.loads(info_string)
>>> info['name']
u'lamp'
>>> info['price']['regular']
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
KeyError: 'regular'
>>> info['price']['retail']
9.99
```

A KeyError is given when you ask for a non-existent key in a dictionary.

“Drill down” into a dictionary using sequential square brackets.

Day 6



# Server-Side Languages

## In-class Assessment

Try out the coding functions in both languages.

- Make an associative array with at least one embedded associative array.
- Print it out to the browser.

Day 6



# Server-Side Languages

## Reading from a URL in PHP

```
file_get_contents($url)
```

This function returns a string with the contents as you would see if you viewed the source of the website.

Day 6





# Server-Side Languages

## Reading from a URL in Python

```
import urllib2

response = urllib2.urlopen("http://www.cnn.com")
print "Content-type: text/html\n\n"
print response.read()
```

<http://docs.python.org/2/library/urllib2.html>

Day 6





# Server-Side Languages

## In-class Assessment

- Make the CNN script use a different website with a more complicated URL. Pass parameter values to the URL string with your code.

Day 6



# Server-Side Languages

Choose a public JSON API

Find a free JSON API that interests you.



[programmableweb.com](http://programmableweb.com)

Day 6



# Server-Side Languages

In-class assignment:  
Replicate this functionality  
in both languages

## Our JSON Service guide

- Call the URL: [http://day6.python.com/api/get\\_random\\_user](http://day6.python.com/api/get_random_user) to get one random user.
- Call the URL: <http://day6.python.com/api/search/searchField/searchTerm> to search the database (maximum one parameter)
  - Make sure the **searchField** is a single word: firstname, lastname, phone, city, state, or zip
  - Make sure the **searchTerm** is a single word.

## Read JSON from duckduckgo.com

Keyword:

This will search your example database and return results in JSON form

This will get results from the API of your choice in JSON form and decode them into styled HTML

Day 6



# Server-Side Languages

## Lab 7

To each of your websites, add one of these:

**JSON Service** - will respond to HTTP requests by getting information from your database and encoding it with JSON

**JSON Reader** - will decode JSON from someone else's service and display it and insert it into your database

Day 6