



File Status Lifecycle




```
$git clone <url> / $git init
```




Exemple of development
Straight arrows = pointers


```
$git clone <url> / $git init  
$git commit [-a]
```




```
$git clone <url> / $git init
$git commit [-a]
$git commit [-a]
```




```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing
```




```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing
```




```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing  
$git commit [-a]
```




```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing  
$git commit [-a]  
$git checkout master
```




```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing  
$git commit [-a]  
$git checkout master  
$git commit [-a]
```



```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing  
$git commit [-a]  
$git checkout master  
$git commit [-a]
```




`$git checkout 34ac2`

Detached HEAD!


ok for experimenting but it is not tidy...

```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing  
$git commit [-a]  
$git checkout master  
$git commit [-a]
```



```
$git checkout -b testing2 34ac2
```


```
$git clone <url> / $git init  
$git commit [-a]  
$git commit [-a]  
$git branch testing  
$git checkout testing  
$git commit [-a]  
$git checkout master  
$git commit [-a]
```



```
$git checkout -b testing2 34ac2  
$git commit [-a]
```

\$git reflog

276fg2b HEAD@{0}: commit: new file: bid3
34ac21a HEAD@{1}: checkout: moving from master to testing2
87ab20a HEAD@{2}: commit: new file: bid2
f30abf1 HEAD@{3}: checkout: moving from testing to master
c2b9e4f HEAD@{4}: commit: new file: bid2
f30abf1 HEAD@{5}: checkout: moving from master to testing
f30abf1 HEAD@{6}: commit: modified: bid
34ac21a HEAD@{7}: commit: modified: bid
98ca920 HEAD@{8}: commit (initial): new file: bid




\$git checkout -b testing2 34ac2
\$git commit [-a]

\$git reflog

276fg2b HEAD@{0}: commit: new file: bid3
34ac21a HEAD@{1}: checkout: moving from master to testing2
87ab20a HEAD@{2}: commit: new file: bid2
f30abf1 HEAD@{3}: checkout: moving from testing to master
c2b9e4f HEAD@{4}: commit: new file: bid2
f30abf1 HEAD@{5}: checkout: moving from master to testing
f30abf1 HEAD@{6}: commit: modified: bid
34ac21a HEAD@{7}: commit: modified: bid
98ca920 HEAD@{8}: commit (initial): new file: bid

\$git reset HEAD@{6}



\$git checkout -b testing2 34ac2
\$git commit [-a]

```
$git reflog
```

```
276fg2b HEAD@{0}: commit: new file: bid3
```

```
34ac21a HEAD@{1}: checkout: moving from master to testing2
```

```
87ab20a HEAD@{2}: commit: new file: bid2
```

```
f30abf1 HEAD@{3}: checkout: moving from testing to master
```

```
c2b9e4f HEAD@{4}: commit: new file: bid2
```


```
f30abf1 HEAD@{5}: checkout: moving from master to testing
```

```
f30abf1 HEAD@{6}: commit: modified: bid
```

```
34ac21a HEAD@{7}: commit: modified: bid
```

```
98ca920 HEAD@{8}: commit (initial): new file: bid
```

```
$git reset [<-->] HEAD@{6}
```



Jargon:

276fg is “unreachable”
can be removed
with `git gc` when it
expires out from the
reflog

```
$git checkout -b testing2 34ac2  
$git commit [-a]
```