```
def var t-transcnt as int no-undo.

def var cOption1 as char no-undo.
def var cOption2 as char no-undo.
def var cOption3 as char no-undo.
def var cOption4 as char no-undo.
def var cOption5 as char no-undo.
def var cOption6 as char no-undo.
def var cOption7 as char no-undo.
def var cOption8 as char no-undo.
def var cOption9 as char no-undo.
def var cOption10 as char no-undo.
def var cOption11 as char no-undo.
def var cOption12 as char no-undo.
def var cOption13 as char no-undo.
def var cOption14 as char no-undo.
def var cOption15 as char no-undo.
def var cOption16 as char no-undo.
def var cOption17 as char no-undo.
def var cOption18 as char no-undo.
def var cOption19 as char no-undo.


If t-transcnt = 0 then
Display "** No Records Found **"


define frame f-under
"--------------------------------------------------------------------------
---------------------------------------------------"
with width 132 no-box no-labels page-top.

define frame f-und220
"----------------------------------------------------------------------------------------------------------------------------------------------------------------------
-----------------------
---------------------------------------------------"
with width 220 no-box no-labels page-top.

//For SARR
using serviceinterface.server.AppserverLogic.shared.asutilityclass from propath.

def var v-dir      as char            no-undo.

Assign
```

```
v-dir   = asutilityclass:GetTenantDir().
```