




US 20160309246A1

(19) **United States**(12) **Patent Application Publication**  
**O’Keeffe**(10) **Pub. No.: US 2016/0309246 A1**(43) **Pub. Date: Oct. 20, 2016**(54) **SMART SPEAKER WITH  
MULTIFUNCTIONAL FACEPLATE AND  
LOCAL ENVIRONMENT SENSING**(71) Applicant: **James Thomas O’Keeffe**, Newark, CA  
(US)(72) Inventor: **James Thomas O’Keeffe**, Newark, CA  
(US)(21) Appl. No.: **15/193,012**(22) Filed: **Jun. 25, 2016****Related U.S. Application Data**(63) Continuation-in-part of application No. 14/918,586,  
filed on Oct. 21, 2015, now Pat. No. 9,406,456, which  
is a continuation of application No. 14/788,726, filed  
on Jun. 30, 2015, now Pat. No. 9,196,432.(60) Provisional application No. 62/054,389, filed on Sep.  
24, 2014.**Publication Classification**(51) **Int. Cl.**  
**H04R 1/02** (2006.01)  
**G06F 3/16** (2006.01)  
**H04R 29/00** (2006.01)(52) **U.S. Cl.**CPC ..... **H04R 1/023** (2013.01); **H04R 29/001**  
(2013.01); **G06F 3/162** (2013.01); **H04R**  
**2201/028** (2013.01); **H04R 2420/07** (2013.01)(57) **ABSTRACT**

In particular embodiments, a smart speaker includes a speaker, a housing with a speaker grille portion, a circuit board, and one or more indirect input sensors (e.g. an antenna or a proximity sensor). The grille can comprise a first plurality of openings. The circuit board can reside behind the grille and in front of the speaker (e.g. in the path of sound transmission from the speaker). The circuit board can be a substrate for the one or more indirect input sensors. The circuit board can further comprise a second plurality of openings, at least some of which align with at least some of the openings in the grille, thereby providing sound transmission through the circuit board, while providing improved access for the sensors to the local environment in the vicinity of the smart speaker. Several embodiments enable the region behind the speaker grille to accomplish the dual functions sensing the local environment and sound transmission. For example, an indirect input sensor may detect aspects of the local environment (e.g. hand gestures made by a user, or the location of a person) and activate one or more aspects of the smart speaker in response (e.g. illuminate a display).






FIG. 1




FIG. 2A




FIG. 2B





FIG. 3






FIG. 4B




FIG. 5B




FIG. 5A






FIG. 5C




FIG. 6

460






FIG. 7






FIG. 9




FIG. 10




FIG. 11




FIG. 12






FIG. 13




FIG. 14




FIG. 15






FIG. 16A








FIG. 17




FIG. 18






FIG. 19A




FIG. 19B




FIG. 19C




FIG. 20




FIG. 21

## SMART SPEAKER WITH MULTIFUNCTIONAL FACEPLATE AND LOCAL ENVIRONMENT SENSING

### CROSS-REFERENCE TO RELATED APPLICATIONS

**[0001]** This application is a continuation-in-part of application Ser. No. 14/918,586 filed on Oct. 21, 2015, which is a continuation of application Ser. No. 14/788,726, filed on Jun. 30, 2015, now U.S. Pat. No. 9,196,432 which claims the benefit of provisional patent application No. 62/054,389, filed on Sep. 24, 2014 by the present inventor.

### TECHNICAL FIELD

**[0002]** The present disclosure relates generally to systems and methods for combining audio capability and local environment sensing (e.g. voice detection, occupant location, gestures, and RF signals) in the grille portion of a smart speaker. In particular, the technology relates to a wireless speaker that provides means for both sound transmission and improved sensing of the local environment.

### BACKGROUND

**[0003]** The proliferation of consumer wireless electronics (e.g. smartphones, tablet PCs and laptops) has resulted in consumers increasingly carrying music collections with them. Speaker manufacturers have responded to this market trend by making smaller, more portable wireless speakers and wireless multi-room speakers (e.g., Bluetooth portable speakers and multi-room Wi-Fi speakers). As the form factor of wireless speakers shrinks, the proportion of the enclosure occupied by the speaker element (e.g. the speaker cone and electromagnetic driver) has increased.

**[0004]** In a related area, a new generation of smart speakers (e.g. the Amazon Echo from Amazon Inc. of Bellevue Wash. and the Google Home speaker from Google Inc. of Mountain View Calif.) are combining wireless music streaming with local environment sensing (e.g. voice and proximity detection) and automatic speech recognition (ASR). Smart speakers can act as an interface to the World Wide Web as well as an interface to home automation devices (e.g. providing control for smart thermostats and smart televisions). Enhanced sensing of the local environment is an active area of innovation for smart speakers. Examples include, sensing the location of people, identifying speech across a noisy room, or sensing the presence of smart building devices. The speaker element of a traditional speaker can pose several challenges to the goal of sensing the local environment. The speaker element can be large and can occupy much of the available space in the enclosure. In addition, the speaker element can cause electromagnetic interference.

**[0005]** In conclusion, insofar as I am aware, no speaker assembly previously disclosed has provided sound transmission while providing effective sensing of the local environment in the vicinity of the speaker assembly.

### SUMMARY

**[0006]** In one embodiment, a smart speaker has an environmental sensing faceplate subassembly located in the path of sound transmission from a speaker component, the subassembly being operable to provide both sound transmission and sensing of the local environment. In another embodi-

ments an environmental sensing faceplate subassembly comprises: a front surface with a grille, a circuit board places in the path of sound transmission from a speaker and an indirect sensor, wherein the circuit board comprises means that enable the indirect sensor to sense an aspect of the local environment (e.g. the room where the smart speaker resides) and wherein the circuit board has openings that align with the grille to promote improved sound transmission from the speaker.

**[0007]** In particular embodiments, a smart speaker includes a speaker, a housing with a speaker grille portion, a circuit board, and one or more indirect input sensors (e.g. an antenna or a proximity sensor). The grille can comprise a first plurality of openings. The circuit board can reside behind the grille and in front of the speaker (e.g. in the path of sound transmission from the speaker). The circuit board can be a substrate for the one or more indirect input sensors. The circuit board can further comprise a second plurality of openings, at least some of which align with at least some of the openings in the grille, thereby providing sound transmission through the circuit board, while providing improved access for the sensors to the local environment in the vicinity of the smart speaker. Several embodiments enable the region behind the speaker grille to accomplish the dual functions sensing the local environment and sound transmission. For example, an indirect input sensor may detect aspects of the local environment (e.g. hand gestures made by a user, or the location of a person) and activate one more aspects of the smart speaker in response (e.g. illuminate a display). In some embodiments the disclosed invention enables the system to detect when a person is proximal to the smart speaker and activate an aspect of the smart speaker.

**[0008]** The techniques described in this specification can be implemented to achieve the following exemplary advantages: The field of view of indirect input sensors can be improved by enabling them to be placed in close proximity to the speaker grille and in some cases in the path of sound transmission from the speaker to the grille. In a related advantage the indirect input sensors can benefit from direct line of site to the local environment in front of the speaker grille through the openings in the grille. In another advantage placement of the indirect input sensors forward of the speaker cone can provide a location with lower electromagnetic interference. In yet another advantage the plurality of openings in the circuit board(s) can act to improve the sensing by conditioning sensor signals from the local environment (e.g. collimating light to a narrow range of angles as it passes through the openings, attenuating particular sound or RF frequencies, forming via holes between two or more layers in circuit board, or forming part of an antenna).

### DRAWINGS

**[0009]** FIG. 1 is an exemplary diagram of the front faceplate of an electrical switch assembly with audio capability and means for a user to operate two switches in accordance with an aspect of the present disclosure.

**[0010]** FIGS. 2A and 2B is a disassembled view of an electrical switch assembly with audio capability, including a speaker, and a touch sensitive faceplate in accordance with an embodiment of the present invention.

**[0011]** FIG. 3 is a block diagram illustrating various components of an electrical switch assembly with audio capability in accordance with one embodiment of the present technology.

[0012] FIGS. 4A and 4B illustrates an exemplary front view of a faceplate with a touch sensitive speaker grille and two circuit boards in accordance with one embodiment of the present technology.

[0013] FIGS. 5A to 5C illustrates a finger interacting with a target sensor electrode and a neighboring sensor electrode in accordance with one embodiment of the present technology.

[0014] FIG. 6 illustrates an insulating electrical substrate with conductive electrodes designed in accordance with one embodiment of the present technology.

[0015] FIG. 7 illustrates various elements of an indicator light assembly including insulating electrical substrate with light emitting elements in accordance with one embodiment of the present technology.

[0016] FIGS. 8A and 8B illustrate exemplary front views of a faceplate with a speaker grille operable to sense direct user interaction in accordance with one embodiment of the present technology.

[0017] FIG. 9 illustrates an exemplary rear view of a faceplate with a touch sensitive speaker grille in accordance with one embodiment of the present technology.

[0018] FIG. 10 illustrates a disassembled view of an interactive speaker grille in accordance with an embodiment of the present invention.

[0019] FIG. 11 illustrates exemplary front views of a faceplate with a speaker grille and solid center section in accordance with one embodiment of the present technology.

[0020] FIG. 12 is a flow chart diagram that outlines the operation of an electrical switch assembly with audio capability in accordance with an aspect of the present disclosure.

[0021] FIG. 13 is a flow chart diagram that outlines the operation of an electrical switch assembly with audio capability and illuminated switch indication in accordance with an aspect of the present disclosure.

[0022] FIG. 14 is a flow chart diagram that outlines the operation of an interactive speaker grille with audio capability and illuminated grille regions in accordance with an aspect of the present disclosure.

[0023] FIG. 15 is a flow chart diagram that outlines the operations associated with integrating an electrical switch assembly with audio capability, including a touch sensitive speaker grille.

[0024] FIG. 16A illustrates a traditional arrangement of a speaker and a plurality of indirect input sensors.

[0025] FIG. 16B and 16C illustrate a speaker and an environmental sensing faceplate subassembly, in accordance with several embodiments of the present disclosure.

[0026] FIG. 17 illustrates a smart speaker according to an embodiment of the present disclosure.

[0027] FIG. 18 illustrates a disassembled view of a smart speaker including a plurality of indirect input sensors located on a circuit board in accordance with an embodiment of the present disclosure.

[0028] FIG. 19A, 19B and 19C illustrate exemplary placement of a circuit board with an indirect input sensor, wherein the circuit board is placed in the path of sound transmission from a speaker to the region in front of the speaker grille, in accordance with several embodiments of the present disclosure.

[0029] FIG. 20 illustrates a display on a circuit board in the path of sound transmission from a speaker to a region in front of a speaker grille, in accordance with an embodiment of the present disclosure.

[0030] FIG. 21 is a flow diagram that outlines the operations associated with integrating environmental sensing into a smart speaker in accordance with an embodiment of the present disclosure.

#### DETAILED DESCRIPTION—FIG. 1-FIG. 11

[0031] In the following detailed description, for purposes of explanation, numerous specific details are set forth to provide a thorough understanding of the various implementations of the present invention. Those of ordinary skill in the art will realize that these various implementations of the present invention are illustrative only and are not intended to be limiting in any way. Other implementations of the present invention will readily suggest themselves to such skilled persons having the benefit of this disclosure.

[0032] In addition, for clarity purposes, not all of the routine features of the implementations described herein are shown or described. One of ordinary skill in the art would readily appreciate that in the development of any such actual implementation, numerous implementation-specific decisions may be required to achieve specific design objectives. These design objectives will vary from one implementation to another and from one developer to another. Moreover, it will be appreciated that such a development effort might be complex and time-consuming but would nevertheless be a routine engineering undertaking for those of ordinary skill in the art having the benefit of this disclosure.

[0033] It is to be appreciated that while one or more implementations are described further herein in the context of a typical building based electrical switch assembly used in a residential home, such as single-family residential home, the scope of the present teachings is not so limited. More generally, electrical switches with audio capability according to one or more of the preferred implementations are applicable for a wide variety of buildings having one or more speakers including, without limitation, duplexes, townhomes, multi-unit apartment buildings, hotels, retail stores, office buildings and industrial buildings. Further it is to be appreciated that an electrical switch with audio capability according to the implementations disclosed could be implemented in ships and airplanes. Further, it is to be appreciated that while the terms user, customer, installer, homeowner, occupant, guest, tenant, landlord, repair person, and the like may be used to refer to the person or persons who are interacting with the speaker or other device or user interface in the context of one or more scenarios described herein, these references are by no means to be considered as limiting the scope of the present teachings with respect to the person or persons who are performing such actions.

[0034] FIG. 1 is a diagram illustrating the front view of an exemplary wall-mounted electrical switch assembly 100 in accordance with an embodiment of the present disclosure. The electrical switch assembly 100 is designed to reside in an electrical junction box (not shown in FIG. 1). FIG. 1 illustrates a 2-bay switch assembly. A touch sensitive faceplate 105 controls power to two wires 110a and 110b and thereby controls the operation of two lights 115a and 115b. Alternative implementations of this disclosure can include other sizes of electrical switch assembly optimized for different sizes of electrical junction box designed to serve different numbers of building-based electrical devices (e.g. Lights, switch operated electrical outlets or garbage disposals). For example, a single bay junction box is common in many bedrooms to accommodate a single light switch, while

other locations may have three or four bay junction boxes. Faceplate **105** contains a plurality of openings **120** that form a speaker grille **114**. A substantial portion of the faceplate **105** can be occupied by speaker grille **114** (e.g. 50-100% of the total area of the front surface of faceplate **105**). Grille **114** protects a speaker (not shown in FIG. 1) located behind the faceplate while enabling effective sound transmission through the openings **120**. The faceplate, and in particular speaker grille **114**, is touch-sensitive, thereby enabling a person **125** to touch portions of the speaker grille **114** to operate lights **115a** and **115b**. Speaker grille **114** combines a variety of functions including sound transmission, light switch control, speaker protection and user protection. Aspects of the present disclosure show how to implement touch sensor functionality, while providing sound transmission through a large number of openings in the grille **114**. The touch sensitive speaker grille **114** and faceplate **105** can register binary user commands (e.g. ON/OFF) as well as continuum user input commands (e.g. increase illumination with a dimmer). Elements **130a**, **130b** and **130c** are regions of the faceplate that illuminate in order to further facilitate a user **125** with visual feedback. For example elements **130a** and **130b** can show the present state of the electrical switches number 1 and number 2 (e.g. ON/OFF/dimmed). In one implementation elements **130a** and **130b** are two elongated lines of light indicating the position of two dimmer switches. The user **125** can touch the faceplate **105** and drag the illuminated indication regions **130a** and **130b** up or down to a desired location and controlling lights **115** in the process. Faceplate **105** designed in accordance with the present disclosure provides means for visual switch position indication and touch sensitive surfaces while facilitating sound transmission with a large speaker grille portion **114**. In some implementations the touch sensitive speaker grille **114** can provide improved access for sensors positioned behind the faceplate (e.g. passive Infrared, active infrared proximity sensors or temperature sensors) to measure the environment in the region in front of the faceplate **105**. In some implementations sensors located behind the touch-sensitive speaker grille can provide enhanced sensing of a person in the vicinity of the switch assembly and illuminate regions **130a**, **130b** and **130c** when a person is nearby. In the implementation illustrated in FIG. 1 electrical switch assembly **100**, receives wireless signals **135** and can play music or audio messages from a variety of wireless devices **140**, for example a smartphone **140a**, a tablet PC **140b** or a media server **140c**. The media server **140c** can be an internet gateway (e.g. a home broadband internet router) and transmit internet radio content to electrical switch assembly **100**.

[0035] FIGS. 2A and 2B are disassembled views of an electrical switch assembly including a speaker grille **214** that can sense direct user interaction (e.g. touch or pressure) in accordance with one implementation of the present disclosure. Switch assembly **100** contains a housing **210**. Housing **210** is a mechanical enclosure for components of electrical switch assembly **100**. In one implementation housing **210** provides electrical and mechanical separation for components in electrical switch assembly **100** from the contents (e.g. wires) in an electrical junction box **215**. Housing **210** can contain two or more electrical terminals **290** operable to be attached to building-based wiring. Building based wiring can include wiring within the walls of a building or carried in metallic or plastic tubing for the purpose of electrically connecting switches and service points in the building

Service points can include wall mounted electrical sockets, HVAC equipment, sprinkler components and lighting fixtures in ceilings and walls. Examples of terminals **290** include screw terminal (e.g. those found on many light switches) and wire pigtails (e.g. a length of wire protruding from the housing). Housing **210** may be sized to fit in an electrical junction box **215** of a particular size. For example the two-bay junction box illustrated in FIG. 1 is approximately 4 inches wide and can accommodate two standard electrical light switches. The exemplary housing **210** in FIG. 1 is approximately 4 inches wide and 4 inches high and is designed to fit inside the majority of two-bay electrical junction boxes. Housing **210** has forward facing surfaces **217a** and **217b**.

[0036] Housing **210** contains a speaker **205** operable to generate sound in the region of the assembly. Speaker **205** functions to emit sound through the grille portion **214** of faceplate **105**. Grille **214** and grille **114** are operable similar exemplary grilles with different shapes. Speaker **205** can be an electromagnetic type speaker with an external or internal electromagnet. In FIG. 2A speaker **205** is located centrally in housing **210** and can occupy the position traditionally occupied by one or more mechanical switches. In another aspect of several embodiments the speaker grille is designed to fulfill the function of the electrical switches, including dimmer switches, that would traditionally occupy the space where speaker **205** is placed. Speaker **205** can have mounting features securing it to the housing **210** and in some embodiments an air-tight seal is formed between speaker **205** and housing **210** that enables further audio quality enhancement. Speaker **205** can have a mounting flange **206** operable to secure the speaker to housing **210**. Mounting flange **206** can have a variety of shapes including square or circular. Speaker **205** has a speaker cone **207** operable to move in the positive and negative Z direction when the electromagnet in the speaker is energized. The cone has a forward facing surface operable to project sound in the Z direction. In one embodiment the electrical switch assembly is designed to fit inside a 1-bay electrical junction box with dimensions of approximately 2 inches in the Y direction of FIG. 2A and 4 inches in the direction of X in FIG. 2B. In this embodiment the assembly **100** could contain a 3W 4 ohm speaker with a speaker cone with a diameter of approximately 50 mm. In another embodiment the electrical switch assembly **100** is designed to fit inside a 2-bay electrical junction box with dimensions of approximately 4 inches in the Y direction of FIG. 2A and 4 inches in the positive X direction in FIG. 2B. In this embodiment assembly **100** can contain a larger speaker with a cone of diameter 76 mm. Speaker **205** could be model number 1-530-767-12 from Sony. Speaker **205** can have a similar design to the speaker component used in a portable Bluetooth or Wi-Fi enabled wireless speaker, for example Jawbone Jambox®. In some embodiments electrical switch assembly **100** can include two or more speakers. This is sometimes advantageous when more sound volume is required than can be provided by a single speaker.

[0037] Electrical switch assembly **100** can contain a faceplate **105** with a front surface including portions **212a** and **212b**. The front surface can include a large portion **212a** in the X-Y plane and can also include the edges of the faceplate **212b**. The front surface including portions **212a** and **212b** provide surface for the user to interact while at the same time faceplate **105** provides electrical isolation, between the user

and high voltage components in the switch assembly behind the faceplate. Faceplate **105** can be constructed from a variety of materials including plastics, glass or enamel covered metal or metal. Faceplate **105** can be flat with rounded edges as illustrated in FIG. 2A and FIG. 2B. In other embodiments faceplate **105** can have a curved structure that can provide increased mechanical stiffness, when the front of the faceplate is touched or pressed. Faceplate **105** can contain one or more ribs molded on the interior surfaces to further increase mechanical stiffness. Faceplate **105** can function to conceal the gaps between the enclosure **210** and the electrical junction box **215**. The faceplate provides an aesthetically pleasing front surface for the user to interact with while concealing gaps between paint or drywall interfaces and junction box **215**. FIG. 2B illustrates that faceplate **105** contains a plurality of openings **120** that form a speaker grille portion **214** of the faceplate. Openings **120** can have a variety of shapes including circular, diamond, or oval. Speaker grille **214** is designed to transmit sound into the air space in front of the faceplate in a manner so as to provide effective sound to a user in the vicinity of the electrical switch assembly. FIG. 11 illustrates that speaker grille can be disposed as a complex shape comprising a plurality of openings **120** surround one or more solid sections **1110**. A solid section **1110** could be a decorative surface for a manufacturer to place a logo, hold a button, hold a touch sensitive button or an illuminated element. In the context of this disclosure a speaker grille refers to a portion of the faceplate **105** comprising a plurality of openings operable to transmit sound from a speaker and would not include the solid section **1110** illustrated in FIG. 11. In some embodiment the grille comprises several small clusters of openings. In this case the grille can refer to the combined portions of the faceplate covered by the openings. In the absence of molded features, edges or material differences delineating the boundary of the speaker grille **214** portion of faceplate **105**, the grille portion can be considered to be bounded by straight lines joining the points on the perimeter of those openings that form the perimeter of a plurality of openings. Faceplate **105** contains one or more regions **240** wherein direct user input (e.g., touching, swiping or pressing) is operable to be sensed by one or more sensor electrodes **255**. For example regions **240a**, **240b** and **240c** in FIG. 2A are exemplary touch sensitive regions used to control the operation of two electrical switches. In one implementation user input region **240a** functions as a binary switch to turn off switch number **2**. While the exact mechanism for turning off switch number **2** in response to direct user input is detailed later, it can be appreciated that regions **240** are operable to initiate the process of controlling one or more electrical switches. For example the region **240c** is operable to receive direct user input and direct user input sensors **330** (in FIG. 3) behind the faceplate can initiate the turn on of switch number **2**. In another example a user input region **240b** of the faceplate **105** can function to act as analog switch, capable of controlling light **115a** to have a value within a range of switch values (e.g. from 0 to 100). Examples of analog switches include slider actuators, dimmer switches, rotary dial switches. Physical features on the faceplate can indicate the intended function of a region. For example in FIG. 2B switch number **1** and switch number **2** can be separated by a molded feature **225** delineating the boundary between the two switches on the common faceplate. Features **225** can also be deposited on the faceplate using other technologies

including printing, etching, painting, overlay or electroplating. User input regions can control a function that is variable and dynamically defined by a computer processor. Region **240d** illustrate an example of a region that could initiate a plurality of control functions in a speaker application for example changing the volume, selecting a song, playing or pausing music or selecting an input source. In one implementation the function of **240d** can be defined by the direction or gesture the user makes while touching the region. For example swiping up and down may control light switch functionality, while swiping from left to right may decrease sound volume of the speaker and right to left may increase sound volume. The differentiation of these functions can be provided by the sequence of sensors **330** (in FIG. 3) activated behind the front surface of region **240d**. The function of region **240d** can be based in part the prior sequence of regions **240** that the user has interacted with. Illuminated sections of the faceplate **130** can indicate the present functionality of region **240d**.

[0038] In the embodiment illustrated in FIG. 2B speaker grille **214** occupies a large portion of the faceplate **105**. In this context a large portion can range from 30-100% of the faceplate area. In one aspect of this disclosure user input regions **240** overlap with grille **214**. In some embodiments user input regions can be fully contained within the grille portion of the faceplate. Speaker grilles are common on most speakers, where they provide mechanical protection for the sensitive speaker components while providing a path for sound vibrations to be emitted.

[0039] Electrical switch faceplates are required to provide electrical insulation between a user and high voltage components (e.g. wires) inside the junction box. In one aspect of the present disclosure electrical switch assembly **100** has a speaker grille **214** made from an electrically insulating material, for example plastic, glass, glass filled plastic, or ceramic. In one embodiment shown in FIG. 2A and FIG. 2B the grille and the surrounding area of the faceplate are made from the same piece of plastic, with the grille comprising a plurality of openings **120** covering the center section of the faceplate. In other embodiments the grille may be different material from the rest of faceplate, for example a plastic grille with an insulated metallic faceplate. The openings can be a wide variety of shapes (e.g. circular, square or elongated slots). A speaker grille is a combination of openings **120** and solid portions between the openings. The arrangement of openings and solid portions often forms a pattern and enhances the aesthetic appeal of the speaker enclosure. The combination of openings **120** and solid support material is designed to achieve competing goals of blocking or filtering objects larger than the grille openings while enabling air and sound waves to pass through the grille. The grille is not a perfect sound transmitter. The solid portions of the grille attenuate or diminish several physical properties such as sound intensity, light intensity and air flow. Sound attenuation can be caused by sound reflected back towards the speaker as it attempts to pass through the grille.

[0040] FIG. 2A illustrates a circuit board **260** behind the faceplate **105** and placed in front of the speaker **205**. The circuit board has an insulating substrate **262** that functions to hold conductors **254** and sensor electrodes **255** operable to sense direct user input. Conductors **254** can function to carry signals to and from sensor electrodes and can have a large ratio of length to width (e.g. >100). Modern circuit board manufacturing technologies such as photolithography and



foil etching can produce conductor features **254** as narrow as 40 micrometers. Electrodes are operable to sense an aspect of a user (e.g., capacitive or resistance changes associated with a user touching the front surface of faceplate **105**). Electrodes can have a larger surface area and smaller aspect ratio than conductors on the same circuit board. Circuit board **260** has a plurality of openings (e.g. **220a** and **220b**). Openings **220a** and **220b** function to enable sound from the speaker **205** to pass through the substrate. Openings **220** are designed to align with openings **120** in the faceplate so as to not to add to the overall sound attenuation and reflection of the grille. In one implementation opening **220a** is larger than the corresponding opening **120a** in the faceplate and can be large enough to cover multiple holes in the front faceplate. In one implementation **220a** can be larger than the opening **120a** in the speaker grille. For example openings **220a** could be a slot encompassing two openings in the faceplate. In some embodiments circuit board **260** can be a rigid circuit board made from layers of fiberglass and epoxy with deposited conductors. In other implementations circuit board **260** is a flexible circuit board. The faceplate **105** with speaker grille **214** can be combined with one or more circuit boards **260** to form an interactive grille. The interactive grille enables the switch assembly to transmit sound while accomplishing the task of switch power to household items. The switching functionality is accomplished by splitting the switching task into two functions sensing and power switching. The interactive grille enables the sensing to take place on the sound transmitting grille while the power switching is accomplished by circuitry located away from the path of sound transmission. Examples of circuitry located away from the path of sound transmission include low voltage switches and high voltage switches located behind the speaker in enclosure **210**. One high voltage switch **280** is illustrated behind the speaker in FIG. 2A. In the context of this disclosure high voltage refers to voltages with magnitudes greater than 20 volts. Low voltage refers to voltages with magnitudes in the range 0-20 volts. Examples of high voltage switches include electromechanical relays, solid state relays and triacs. A triac is a fast solid state switch often used to implement dimmer switches in buildings. Grille **214** can be larger than the speaker cone **207** extend beyond the speaker in the X-Y plane, thereby providing the benefits of access to the surrounding air to additional sensors in the electrical switch assembly. The speaker cone **207** is defined by the inside perimeter of speaker flange **206**. For example a microphone **268** could be placed in the housing and behind the grille, whereby the interactive grille provides improved sound coupling and therefore improved sound sensing in the vicinity of switch assembly **100**. Similarly, a passive infrared sensor **269** can be placed behind the interactive grille to sense motion in the vicinity of the speaker. Openings in the grille provide enhanced motion sensitivity. In other embodiment some or all of the sensor electrodes **255** can be deposited directly onto the rear surface of the speaker grille using electroplating or conductive inks. It would be known to someone skilled in the art that conductors and electrodes can be deposited on 3-dimensional polymer parts using modern technologies such as Laser Direct Structuring (LDS) or Molded Interconnect Device MID technology.

**[0041]** Mounting features **256** on the housing **210** can be connected to corresponding mounting features **222** on the electrical junction box **215**. For example **256** can be an oblong opening in the housing **210** and feature **222** can be

a threaded hole. A screw could be used to connect **256** and **222**. This arrangement enables fine adjustment of the orientation of the housing. In some embodiments additional mounting features **257a-d** are operable to secure faceplate **105** to the housing **210**. In several embodiments mounting features **257a-d** are load sensors. This enables the faceplate to be attached to the housing in a manner enables the load sensors **257a-d** to generate sensor signals when the faceplate is touched or pressed. For example mounting features **257a-d** could be planar beam type load sensors such as those available from Omega Engineering INC, Stamford Conn. In some embodiments there may more or less load sensors than the four shown in FIG. 2A. In response to a user touching or swiping an area of the faceplate the timing and sequence of load sensors values can be used to determine the area touched and the motion pathway (e.g., swipe in the up direction or down direction)

**[0042]** FIG. 3 is a block diagram of an exemplary electrical switch assembly **100**, illustrating electrical components used to provide the two functions of sound transmission and electrical switching in accordance with one implementation of the disclosure. Wireless devices **140** can transmit wireless signals **135** to the electrical switch assembly **100**. Switch assembly **100** contains an antenna **305** to receive wireless signals **135**. Antenna **305** can be printed on a circuit board, a discrete stamped metal component or an electroplated feature on a surface. In one embodiment of the disclosure the antenna can be deposited or attached to a subassembly including faceplate **105**. On advantage of attaching or depositing the antenna on the faceplate is that placement of the antenna outside of the metal junction box can improve the antenna range and sensitivity. The antenna is operably coupled to a wireless receiver **306**. Receiver **306** can be operable to receive and demodulate a variety of common wireless audio protocols such as amplitude modulated (AM) or frequency modulated (FM) radio signals (e.g. 88.9-107.7 MHz), Bluetooth, Wi-Fi or Apple Airplay ®. Receiver **306** can be part of a transceiver module that also includes transmission capability. Receiver **306** transmits demodulated wireless messages **307** to a speaker processor **308**. The speaker process performs operations to convert the digital wireless messages into audio frequencies. These operations can include digital-to-analog conversion, amplification, equalization, error correction, echo cancellation, bass enhancement, or introducing a delay to one or more frequency components. Speaker process **308** and wireless receiver **306** can be integrated into a single module or microchip. For example a Bluetooth wireless speaker can have a single chip receiver and speaker processor. Electrical switch assembly **100** can include an audio amplifier **309**. Amplifier **309** operates to receive audio signals from the speaker processor, to increase the power of these signals and to transmit amplified audio signals **316** to the speaker **205**. Amplifier **309** can be a single chip amplifier or can comprise multiple discrete transistors. Amplifier **309** can be a class A, B, A/B C or D amplifier. Amplifier **309** transmits amplified signals to the speaker. Amplifier **309** can be for a PAM1803 Class D audio amplifier available from Diode INC, Plano Tex. The amplifier **309**, speaker processor **308**, and receiver **306** can be housed behind the speaker, away from the path of sound transmission.

**[0043]** Electrical switch assembly **100** contains a plurality of direct user input sensors **310**. Direct user input sensors operate to sense direct user interaction with user input

regions **240** of the faceplate **105**. Examples of direct user interaction include touching or pressing the faceplate. Examples of direct user input sensors include sensor electrodes **255**, **605a**, **605b** (shown in FIG. **6**) and a load sensors **257a-d**. Other examples of a direct user input sensor could be a membrane switch such as found on many modern appliances such as a washing machine or stove control panel. Direct user input sensors **310** can operate to sense direct user input based on a variety of standard technologies. Examples of direct user input technology are capacitive touch sensing, resistive touch sensing, surface acoustic wave touch sensing and pressure sensing. In surface acoustic wave touch sensing a surface acoustic wave is generated on the front surface of the faceplate by one or more transmitters. Aspects of the reflected signals (e.g. arrival time and intensity) are used to sense a user touching the faceplate surface. In response to direct user input, sensors **310** generate direct sensor signals **311a**. Direct sensor signals **311a** can be current, voltage, frequency or sound intensity changes associated with user input sensed by one or more direct user input sensors **310**. In some embodiments an electrical connector **315** provides two separable halves that enable electrical connections to be made between conductors **254** and one or more low voltage switches **320**. One half of electrical connector **315** may be disposed on a circuit board **260** and the other side may be disposed inside the housing **210**. When a person attaches circuit board **260** to the housing **210** electrical connector **315** can connect electrical signals between conductors **254** and circuitry in the housing.

[0044] In one embodiment of the present disclosure, electrical switch assembly **100** provides the two functions of sound transmission and electrical load control using touch sensitive switches. In this embodiment the grille **214** is a touch sensitive surface while the other circuitry required to accomplish electrical switching function is positioned away from the sound transmission path of one or more centrally located speakers. The exemplary electrical switch assembly **100** illustrated in FIG. **3** contains a low voltage switches **320**. Other implementations may contain multiple low voltage switches. The switch can be located in housing **210**. The switch can function to convert sensor signals **311a** and **311b** into low voltage switch output signals **322**. Low voltage switch **320** can comprise a microchip or microcontroller. Many modern microcontrollers can have dedicated circuitry designed to implement low voltage touch sensitive switches. For example the Texas Instruments MSP430 processor from and the MicroChip DSPic33 processor families have analog-to-digital circuitry operable to implement the functionality of the low voltage switch **320**. In some embodiments this circuitry enables conversion of direct user interaction with a surface (e.g. touching or pressing) into low voltage switch output signals **322**. In some embodiments sensor signals **311** can cause small changes in in the frequency of an oscillating circuit inside the low voltage switch **320**. The processor is operable to measure these frequency changes and control one or more low voltage switch output signals **322** based on frequency changes. This type of frequency measurement is often used to transduce sensor signals from capacitive touch sensors. Several electrodes can be sequentially connected to a frequency measurement circuit inside low voltage switch **320** and switch **320** can identify when the user touches one or more of a large number (e.g. >50) of distinct regions on the faceplate **105**. In other embodiments the low voltage switch **320** can include an analog-to-digital converter oper-

able to sense small changes in voltage from sensors and generate digital values corresponding to the magnitude of sensor signals **311**. A processor in the low voltage switch **320** can have a preset threshold for the change in magnitude or frequency that would correspond to a user touching the faceplate. When the low voltage switch **320** measures a change in frequency or magnitude sufficient to cross this threshold the state of an output pin on the low voltage switch can be changed. The change in state of the output pin can act as a low voltage switch output signal **322**. In other embodiments low voltage switch **320** can include one or more elements designed to increase the output power of a low voltage switch signal. This process is sometimes called “buffering” and can be performed for the purpose of controlling high voltage switches **323**. Examples of components that can perform buffering include power transistors and relays.

[0045] In some embodiments the low voltage switch **320** can accept a large number of sensor inputs **311** and can produce a large number of low voltage switch output signals **322**, where a large number is for example fifty or more. In this way the low voltage switch can transduce a plurality of sensor inputs into distinct switch output signals. In some embodiments this circuitry enables conversion of direct human interaction with a surface (e.g. touching or pressing) into output voltage signals. In other embodiments the low voltage switch can combine several sensor signals **311a** and **311b**, perform one or more calculations using a computer processor in the low voltage switch **320** and generate one or more low voltage switch output signals **322**. For example low voltage switch **320** can receive a direct sensor signal **311a** when a user touches the multifunctional grille **214** and second sensor signal **311b** from a motion sensor **269** when a person moves in front of the grille openings. Low voltage switch **320** can contain a processor that can combine direct sensor signals **311a** and indirect sensor signals **311b** and generate an output signal. In some embodiments the low voltage switch can perform timing calculations to determine when to generate an output signal. For example electrical switch assembly **100** can receive direct sensor signals **311a** from the region **240a** of the faceplate operable to turn off a light **115a**. About the same time low voltage switch **320** and can receive indirect sensor input **311b** indicating a person moving in the vicinity of the switch assembly **100**. In response to **311a** and **311b** low voltage switch **320** can delay the transition of signal **322** to an OFF state by a few seconds in order to provide light while the person leaves the vicinity. In the context of this disclosure an ON state can be considered as having a voltage with a magnitude that is greater than a sizeable portion (e.g. >20%) of a power supply voltage (e.g. 5V) used to operate a low voltage switch **320**. In the context of this disclosure an OFF state can be considered as having a voltage with a magnitude that is less than a sizeable portion (e.g. <20%) of a power supply voltage used to operate low voltage switch **320**. The power supply voltage can be measured relative to a reference voltage supplied to the low voltage switch, often defined as a ground voltage or 0V. Low voltage switch **320** can include circuitry to operate one or more illumination components **330**. Illumination components **330** can be LEDs or electroluminescent segments, incandescent bulbs or fluorescent bulbs. Illumination components **330** can be switch position indicator lights

operable to indicate to a user the output state of one or more high voltage switches **323** or low voltage switch output signals **322**.

[0046] In other embodiments electrical switch assembly can include one or more illumination components **330**. Illumination components **330** can be operable to illuminate portions **130** of faceplate **105** and can be located on a circuit board located behind the front surface **212** of the faceplate. Connector **315** can also provide a junction for low voltage switch output signals **322d** from a low voltage switch **320** to illumination components **330**. Low voltage switch **320** can operate illumination components **330** (e.g. switch position indicator lights) in response to sensor signals. For example in response to a user touching a region of the faceplate, low voltage switch **320** can operate illumination components **330** to illuminate sections of the faceplate **130a** and **130b** indicating the present state of each of two dimmer switches. In another example a passive infrared sensor (PIR) could sense a person in the vicinity of electrical switch assembly **100** and signal low voltage switch **320** to illuminate regions **130a** and **130b** of the faceplate corresponding to the present value of low voltage switch output signals **322a** and **322b** (indicating the dimmer output to switch number **1** and ON-OFF position of switch number **2** respectively).

[0047] Low voltage switch output signals **322** are operable to control high voltage switches **323** and other aspects of the electrical switch assembly **100**. Low voltage switch output signals **322** can be voltages in the range of minus **20** volts to plus **20** volts relative to ground in the junction box, the neutral wire or a local ground reference voltage supplied to both the low voltage switch **320** and the high voltage switch **323**. In one implementation low voltage switch output signal **322a** is a pulse width modulated signal (PWM) containing a series of pulses. Pulses contain two or more distinct voltage levels; a high state and a low state voltage. By varying the time proportions of high and low state voltage the PWM voltage waveform voltage switch output signal **322a** can control the dimmer switch **323a**. Other low voltage switch output signals **322b** can operate electromechanical relays **323b**. Signals **322b** can supply a current to an electromagnet inside relay **323b**, thereby creating a low resistance connection between wires **110b** and **110d**. In this context a connection with resistance <3 ohms can be considered a low resistance connection. Other low voltage switch output signals **322c** can be transmitted to the speaker circuitry. FIG. 3 illustrates low voltage switch output signals **322c** transmitted to the speaker processor **308**. For example illumination components **330** can be used to indicate the volume of speaker **205** as an illuminated section **130a** on faceplate **105**. Grille **214** can additionally provide an active region **240d**. In response to user interaction with **240d** direct input sensors **330** can generate sensor signals **311a** and cause low voltage switch **320** to signal speaker processor **308** to change the volume of the speaker. In another implementation low voltage switch output signal **322b** operates a solid state relay, in which the moving parts of an electromagnetic relay are replaced with power transistors.

[0048] Electrical switch assembly **100** can contain a variety of other components and circuits. For example switch assembly **100** can contain a rectifier or diode rectifier to convert high voltages to low voltages, a battery to power the speaker or low voltage switches, particularly during a power outage to the building where the switch assembly is located. Electrical switch assembly **100** can contain one or more

visual displays operable to be seen through faceplate **105**. In some alternative embodiments amplifier **309** can be contained within speaker processor **308**. In other embodiments speaker processor **308** and low voltage switch **320** can be combined in a general purpose processor that combines the ability to sense user input and generate sound signals using digital-to-analog conversion or pulse width modulation. An example of a processor that could combine the functionality of speaker processor **308** and low voltage switch **320** is the DSPic33 processor family from Microchip Incorporated. In one embodiment of electrical switch assembly **100**, the functionality of one or more touch sensitive regions **240** can be determined by the present state of one or more low voltage switch output signals **322a** or **322b**. For example when a user walks into a room where the lights are OFF, low voltage electrical switch **320** can identify that one or more low voltage output signals **322** correspond to the light being in the OFF position and can interpret signals **311a** from some or all touch regions **240** as indications to turn on the light. In this way the electrical switch assembly can identify direct user interaction and estimate the associated intent based on the output state of one or more electrical switches **323**. When a person enters a dark room they often reach for the light switch and use the tactile feel of the switch as user feedback. In one example electrical switch assembly could devote sensor signals **311a** from user interaction with some or all of the surface of the grille to the function of turning on a light in this scenario, thereby alleviating the user from the burden of touching a particular ON location (e.g. **240c**). In this example an indirect input sensor (e.g., a light level detector) located behind the speaker grille could supply sensor signals **311b** to a low voltage switch **320**, indicating the light level in the room and enabling the low voltage switch to interpret sensor signals **311a** from a larger number of direct user input sensors **310** as indication to operate a high voltage switch to turn on a light. In another example, indirect user input sensors **325** (e.g. a PIR sensor or proximity sensor) could sense a person who has entered a dark room and illuminate one or more regions **130** of faceplate **105**. The indirect sensor can benefit from placement behind the grille **214** with a large density of openings **120** that enhance motion signal intensity. In one aspect the electrical switch assembly can illuminate features **130** with increasing intensity as person gets closer to the faceplate (e.g. as they reach for the switch), thereby avoiding unnecessarily disturbing a person who is moving in the vicinity of the electrical switch assembly and does not intend to operate an aspect of the assembly. Dynamic intensity variation can be controlled in part by sensing a person with a plurality of different sensing technologies. For example a faceplate can glow with a low intensity when a person is sensed on a long range PIR sensor (e.g. with **10** meter range). The faceplate can glow with a higher intensity if the person is subsequently sensed by a shorter range proximity sensor (e.g. active infrared transceiver).

[0049] FIG. 4A illustrates several exemplary components of electrical switch assembly **100** designed to enhance audio performance while enabling electrical switch functionality in according with embodiments of this disclosure. Two circuit boards **260** and **460** are positioned behind the faceplate **105**. Circuit board **260** contains a plurality of openings **220** and circuit board **460** contains a plurality of openings **420**. It can be appreciated that the density and shape of openings in the grille **214** can be chosen to fulfill the

competing goals of sound transmission and mechanical performance (e.g. electrical isolation and speaker protection). By choosing the size and shape of openings 220 so as not to cover openings 120 with substrate material 262 the sound transmission properties of the faceplate 105 can be preserved. In particular by aligning one or more openings 220 and 420 with the grille openings 120 the sound transmission performance becomes determined primarily by speaker grille 214. In the context of this disclosure an opening 220 can be considered to “align” with an opening 120 when the placement of 220 is such that the area of the unobstructed opening formed by the overlaid combination of 120 and 220 when viewed along an axis is at least half the area of the corresponding opening 120. For example 220a and 120a are considered aligned in FIG. 2A because when assembled the area of opening 120a and the area of the opening when 120a and 220a are in an assembled state is essentially equal. Opening 220a is made larger than 120a to ensure that any small misalignment of circuit board 260 and faceplate 105 following assembly does not cause 220a to impede sound transmission from speaker 205. In another example openings 120b and 220b are considered aligned when the electrical switch is assembled. By aligning one or more openings in the faceplate 105 and circuit boards (e.g. 260 and 460) the present disclosure enables the circuit boards to add functionality to the grille while transmitting sound from the speaker. For example circuit boards 260 and 460 can provide mounting surfaces to hold touch sensor electrodes, indicator lights, and environmental sensors such as a temperature sensor 480. In one implementation a connector 315 is used to connect circuit board 460 to one or more low voltage switches 320. In the context of this disclosure the improved sound transmission as a result of aligning openings in the grille 214 and a circuit board can include, higher volume experienced in the region in front of the grille, decreased reverberation caused by reflected sound from grille 214 and the circuit board and improved audio clarity.

**[0050]** Circuit board 260 can be comprised of transparent conductors and a transparent substrate similar (e.g. clear plastic) to the touchscreens on tablet PCs. Transparent elements on circuit board 260 enable light illumination components 330 (e.g. light emitting diodes 470 and electroluminescent regions) on circuit board 460 to illuminate portions (e.g. sections 130) of the faceplate.

**[0051]** Conductive elements 255 can also be a transparent material such as indium tin oxide (ITO), antimony tin oxide or silver filled ink. In one implementation an interactive faceplate subassembly 485 is comprised of the faceplate 105 and circuit board 260. The interactive faceplate subassembly 485 can be attached to the other components of the electrical switch assembly by a user or installer. Interactive faceplate subassembly 485 enables the alignment of one or more openings 120 and openings 220 to be conducted in a controlled manufacturing environment. Interactive faceplate subassembly 485 further facilitates installation by enabling installation of other electrical switch assembly components (e.g., the speaker 205 and housing 210) into the junction box 215 prior to installation of the faceplate. This order of installation can help to avoid damaging sensitive sensor electrodes 255 in the interactive faceplate subassembly 485. In another implementation interactive faceplate subassembly 490 includes an additional circuit board 460 operable to illuminate features on the faceplate. Connector 315 can be

disposed on a pigtail or a portion of flexible PCB designed to facilitate connection between the two halves of the connector. Connector 315 could be comprised of exposed connector electrodes at the end of a flexible PCB pigtail. Connector 315 can connect with a corresponding connector in the housing 210, for example a zero insertion force connector (ZIF) such as those sold by TE Connectivity from Harrisburg Pa. In other implementations interactive faceplate subassembly 490 has plurality of connectors similar to 315. Using more than one connector 315 provides redundancy in case a connector pin becomes dirty or damaged. One or more of the connectors can implement a safety interlock, thereby ensuring that portions of the electrical switch assembly 100 are not energized with high voltages until faceplate subassembly is properly secured and the connector 315 is correctly mated. In one embodiment interactive faceplate subassembly 490 has four connectors similar to 315, with one located at each corner of the faceplate to provide a means to both attach and provide power to subassembly 490. Interactive faceplate subassembly 490 has several additional advantages. The subassembly can be provided in a variety of colors, shapes and sizes to fit aspects of the wall opening and the user's preferences. Similarly, the size and pattern of grille member 214 can be varied as well as the color of illuminated sections 130. In contrast the portion of electrical switch assembly 100 inside the junction box 215 can be standardized and offer less customization. FIG. 4B illustrates a crosssectional view of the speaker grille subassembly 490 including aligned openings. Speaker 205 is shown for reference.

**[0052]** FIG. 5A and FIG. 5B illustrate the basic operating principle of capacitive sensing. A number of standard technologies can be adapted to provide user input sensing in the presence of a large speaker 205 and pluralities of holes 120 220 and 420. These technologies include capacitive touch sensing (illustrated in FIG. 5A and 5B), and resistive touch sensing, surface acoustic wave touch sensing and load sensing. A finger 505 is placed over a layer of insulating material 510. A target electrode 515 is disposed behind layer 510. Electrode 515 has a background capacitive coupling to a ground electrode similar to 495. When a finger or other object directly interacts with the top surface of layer 510 the capacitance 525 is often increased. The increase in capacitance causes a temporary current to flow in a conductor such as 254 connecting the sensor electrode 255 to a low voltage switch 320. This current constitutes a direct sensor signal 311a. FIG. 5B also illustrates an advantage of the present design. When a finger touches a conventional capacitive touch sensor, over a target electrode 515, as illustrated in FIG. 5A there is an unintended signal generated at a neighboring electrode 530. It is desirable to reduce this cross-capacitance signal 535a and 535b. FIG. 5B illustrates a capacitive touch sensor in accordance with one implementation of this disclosure. There is an opening 540 in the insulating layer 510 between the target and neighboring electrodes. This opening can be opening 120 in the grille 214. This opening reduces the cross capacitance 535b between the finger 505 and the neighboring electrode 530. By reducing the undesirable cross-capacitance from 535a to 535b the present disclosure enables electrodes 515 and 530 to sense more accurately or be placed closer together. In the present disclosure a plurality of holes 120 in the faceplate 105 can cross-capacitance ( $C2 < C1$ ), thereby enabling improved special resolution of touch identification. Yet

another advantage of the present assembly is illustrated in FIG. 5C whereby the target capacitance 530 can be increased by extending target electrode 515 at least some of the way into opening 540. The extended section is illustrated as the shaded portion 517 of the target electrode in FIG. 5C. One way to implement this electrode extension is to increase the plating thickness of electrode 515 close to opening 540. Electrode 515 and 530 are examples of direct user input sensors 310.

[0053] FIG. 6 illustrates an exemplary electrode array designed to enable a touch sensitive speaker grille in accordance with one implementation of this disclosure. A variety of sensor electrodes including 255, 605a and 605b are patterned on insulating substrate 262. Sensor electrodes are operable to sense direct user interaction with a variety of regions 240 of faceplate 105. The exact layout of sensor electrodes and regions 240 will vary from one implementation to another. Electrode 255 is a discrete sensor electrode designed to identify direct user interaction with a binary input region of the speaker grille. 605a and 605b are electrodes designed to nest within one another such that a user's finger is sensed by 2 or more electrodes at most times. Region 610 includes 5 nested electrodes and is used to implement a slider touch function. When a user slides their finger up or down within the dimmer region 240b of the faceplate 105 and grille 214, multiple electrodes in the touch slider electrode region 610 sense the direct user input and send sensor signals 311a to the low voltage switch 320. The low voltage switch can interpolate the sensor signals and estimate the placement of the user's finger on the touch sensitive region of the faceplate and grille. Circuit board 260 includes a ground electrode 495 that acts as a reference for the other electrodes. Circuit board 260 has a plurality of openings 220 places in accordance with aspects of this disclosure so as to enhance sound transmission. The size and location of openings 220 are chosen to align with openings 120. Conductors and electrodes can be routed around openings 220 as illustrated at 625. In some cases one electrode can be connected to multiple conductors 254. The conductors can be routed in different paths around openings 220 to account for the presence of plurality of openings 220. A person of skill in the art would appreciate that a dense plurality of openings can be placed on substrate 260 and modern circuit board layout software is well suited to routing conductors and electrodes within the small portion of solid substrate 262 that can remain. Openings 420 and 220 can have a guard ring 630 around the opening, whereby the guard ring is a ring around the opening without electrode material (e.g. copper foil). Guard ring 630 can ensure that a user cannot see or touch the edge of an electrode.

[0054] FIG. 7 illustrates an exemplary circuit board 460 designed to illuminate regions 130 of the faceplate 105. Light can be generated on circuit board 460 using a variety of technologies including light emitting diodes (LEDs) or electroluminescence (EL). In the embodiment illustrated in FIG. 7 two emitting diodes 470 are electrically connected between two conductors 254a and 254b. Light emitting diodes 470 can be electrically connected to circuit board 460 while enabling a plurality of openings 420 to align with openings 120 in grille 214. In this manner the LEDs can be used to illuminate sections of the faceplate 105 while the circuit board 460 does not diminish the sound transmission performance of the electrical switch assembly. Section 710 of circuit board 460 encloses a region operable to produce

illumination by a process of electroluminescence. Electroluminescent materials light up when current passes through them. A variety of electroluminescent paint kits are available for circuit board applications, for example the Luxprint® Electroluminescent products from Dupont. Conductors 254c are deposited on substrate 460 to define the shape of the electroluminescent region. Conductors 254c can have close proximity (e.g. 100 micrometers) thereby enabling intricate conductor shapes to be illuminated. A dielectric layer 725 covers the conductors 254c. The dielectric layer has a high electrical resistance relative to the underlying conductor 254c. Dielectric layer 725 can comprise a high dielectric constant material such as barium titanate. The dielectric layer can alternatively be a solder mask material deposited on the circuit board 460. An electroluminescent material 730 covers the dielectric layer. Common electroluminescent materials include phosphor and zinc sulfide. One or more top electrodes 740 covers the electroluminescent layer 730. In this embodiment the top electrode is a transparent electrode such as ITO on a clear plastic film. Alternating voltage applied to electrodes 740 and 254c causes the overlapping regions of the electrodes 740 and 254c to be illuminated. In some embodiments electrode 740 is large and covers a substantial portion of the circuit board 460. The electroluminescent region 710 can be particularly useful for providing a user with visual feedback regarding the state of one or more analog 322a outputs from a low voltage switch 320. For example region 710 can illuminate a dimmer switch position on the faceplate, thereby guiding the user's finger to touch the region of the faceplate corresponding to the present dimmer location and raise or lower the light level by dragging their finger to a new location. Conductors 254c can be closely spaced and can be energized in sequence as the user moves their finger on the faceplate, thereby tracking the user's finger with illumination from the original dimmer position to the new dimmer level. Electroluminescence can produce complex light patterns, based on the shape of conductors 254c. Electroluminescent illuminated regions 710 produce enhanced line edge definition in comparison to LED technology. Conductors 254c can be patterned so as to circumvent the openings 420. In this manner the electroluminescent region 710 can be used to illuminate sections of the faceplate 105 while the circuit board 460 and openings 420 enhance the sound transmission performance of the speaker 205.

[0055] FIGS. 8A and 8B illustrate two additional embodiments of the faceplate 105 of electrical switch assembly 100. In FIG. 8A molded features on the faceplate can indicate touch sensitive areas of faceplate 105. The raised areas can occupy a large portion of the faceplate. The size and shape of openings 120 can be designed to enhance sound performance and switch functionality. In FIG. 8B a plurality of vertical slots 815a are disposed in a touch sensitive faceplate 105. The openings 815a can be designed to produce a characteristic sound and sequence of direct user input sensor signals 311a electrode when a user moves their finger in a vertical manner on the dimmer section of the touch sensitive faceplate 105. In another example, a pattern of horizontal slots 815b can be arranged to cover a sensor disposed behind the grille (e.g. a passive infrared sensor 269). In this case the openings can be optimized to provide more openings with less space between openings in order to enhance sensitivity of PIR 269 to motion.

[0056] FIG. 9 illustrates an exemplary rear view of a faceplate with a touch sensitive speaker grille in accordance with one embodiment of the present technology. In this embodiment electrodes 255 and conductors 254 are deposited directly onto the rear surface of the faceplate 105. Electrodes 255 and conductor 254 can be deposited using a variety of technologies including conductive ink or laser direct structuring LDS or selective plating. Electrodes 255 and conductors 254 are deposited on an interior surface 910 of faceplate 105. Surface 910 contains a plurality of openings 920a and 920b that align with openings 120a and 120b in the front surface of the faceplate, and thereby enhance sound transmission from a speaker that can be placed behind faceplate 105. An electronic component (e.g. an LED, thermistor or resistor) is attached to the faceplate and electrically connected to conductors 954a and 954b. This implementation enables one or more electronic components to be disposed on the rear surface of the faceplate while not impeding sound transmission from the speaker 205. One or more electronic components 930 could be used with electrodes 255 to implement an indicator light that is locally controlled by signals 311a generated at touch electrodes 255 and do not need to be processed by low voltage 320 in order to generate illumination control signals. Another advantage of the implementation illustrated in FIG. 9 is that alignment of the openings 120 in the faceplate and openings 920 in touch electrode substrate can be enabled by a single molding operation. In particular, the step of aligning a separate substrate (e.g., 260 in FIG. 2) is eliminated. Direct structuring technologies such as LDS are well suited to routing narrow (<100 micrometer) conductors 254 around a plurality of closely spaced openings 920.

#### Other Embodiments

[0057] FIG. 10 illustrates an interactive speaker grille in accordance with several aspects of the present disclosure. Interactive speaker grille 1005 is designed to transmit sound from a speaker 205, and contains portions that are touch sensitive and operable to illuminate distinct features on the speaker grille. Interactive grille 1005 comprises a faceplate 105 and three circuit boards 260, 1060 and 460 located behind the faceplate and in front of speaker 205.

[0058] Sound transmission is enhanced by aligning a plurality of openings on faceplate 105 and circuit boards 260, 460 and 1060. Faceplate 105 has a plurality of openings 120 that form a speaker grille 214. When assembled, opening 120a aligns with openings 220a 1020a and 420a and thereby promotes sound transmission from speaker 205 to the area in front of faceplate 105. It can be appreciated that a large number of the openings comprising speaker grille 214 can be aligned with similar openings on one or more circuit boards to promote sound transmission. The speaker grille 214 contains a plurality of regions 240 in which direct user interaction (e.g., touching or pressing) can be sensed by a plurality of electrodes 255 and 605 disposed behind faceplate. FIG. 10 illustrate four exemplary regions 240a, 240b, 240c and 240d wherein direct user input is operable to be sensed by one or more sensor electrodes 255, 605a and 605b on circuit board 260. For example direct use interaction (e.g., touching or pressing) with region 240c causes sensor electrode 255 to generate direct user input signals 311a. In another example region 240b of the faceplate 105 can function to as analog switch. The placement position of a user's finger within region 240b indicates a desired user

input value to a low voltage switch 320 within a range of switch values (e.g. from 0 to 100). Region 240d is an example of a multipurpose touch sensitive region of speaker grille 214. Area 240d can to control a variety of functions in a speaker application for example changing the volume, selecting a song, playing or pausing music or selecting an input source. The function of region 240d can be based in part the prior sequence of regions 240 that the user has interacted with. Illuminated sections of the faceplate, for example 130c) can indicate the present functionality of region 240d. Circuit board 260 contains a plurality of electrodes 255, and 605b operable to sense direct user interaction with speaker grille 214. Electrodes 254 carry direct sensor signals 311a to a low voltage switch 320. Electrodes 254 are routed around the plurality of openings 220.

[0059] Sections of the interactive grille 1005 can be illuminated by light generating components 470 (e.g. LEDs or organic LED) or electroluminescent sections 710 (illustrated in FIG. 7). Light generating components 470 and electroluminescent sections 710 can be placed on a circuit board 260 with touch electrodes or can be placed on additional circuit boards behind the touch sensor electrodes 255 and 605b. FIG. 10 illustrates an LED 470 on circuit board 460 and an electroluminescent section (shown as 710 on FIG. 7). The electroluminescent section 710 contains the electrodes 254c, dielectric layer 725 and electroluminescent layer 730 described previously in this disclosure. In the implementation of FIG. 10 the top electrode 740 is replaced by a plurality of electrodes 1010 disposed on a third circuit board 1060. This arrangement enables horizontal electrodes 254c and vertical electrode 1010 to be operated by signals 322d (illustrated in FIG. 3) from a low voltage switch 320 and thereby generate an illuminated region 130c on faceplate 105. Pixel 130c on faceplate 105 is above the region where the two electrodes cross. It can be appreciated that similar pixels of light can be generated at a large number of locations where a horizontal and vertical electrode pass over one another. It can be appreciated that the pixels can be disposed around the plurality of openings 120 and can form a variety of patterns operable to convey information to a user. In one implementation multiple illuminated pixels such as 130c can display the function of a multipurpose active region 240d for example displaying the volume of the speaker. In another example an array of pixels 1030 can display an equalizer, indicating the sound volume of particular frequency bands (e.g. 1000-2000Hz). Such equalizer displays are common on multispeaker music systems such as the Kenwood GE 100 and provide an aesthetic appealing graphical display for the user. A plurality illuminated regions 130c can also generate patterns operable to change shape or intensity in time with the beat of a song. It would be understood by a person of skill in the art that an array of pixels capable of illuminating individual portions of the speaker grille 214, disposed around a plurality of openings 420a and 420b can also be implemented by a plurality of discrete light emitting light elements 470, such as LEDs, organic LEDs, incandescent lamps or fluorescent lamps. Electrodes 1010 can be made from a transparent material (e.g. indium tin oxide (ITO), antimony tin oxide (ATO) or silver ink) and thereby enhance light transmission from electroluminescent layer 730 or discrete illumination devices 705. In FIG. 10 direct sensor signals 311a are transmitted to low voltage switch 320. Low voltage switch

output signals **322d** can be transmitted to electrodes **254a** and **254b** to control illumination of light emitting elements **470**. Light emitting elements **470** are examples of illumination components **330** in FIG. 3. Other low voltage switch output signals **322d** can be transmitted to electrodes **254c** and **1010** to control illumination of some or all of electroluminescent region **710** (illustrated in FIG. 7). In general a large number of low voltage switch output signals **322d** can be used to operate a plurality of illuminated components **330** (e.g. discrete light emitting elements **470** or electroluminescent region **710**) disposed around a plurality of sound transmitting openings **420a** and **420b**, thereby illuminating sections **130** of speaker grille **214**. Direct sensor signals **311a** can also be used by low voltage switch **320** to generate low voltage switch outputs **322c** operable to control aspects of a speaker processor **308**. For example a user's finger can touch region **240b** of the interactive speaker grille and cause sensors in slider region **610** (illustrated in FIG. 6) to send signals **311** to low voltage switch **320**. The switch can in turn use signals **311a** to generate low voltage switch output **322c** indicative of the position of the user's finger on the volume slider portion of the faceplate. Speaker processor **308** can use signals **322c** to control the magnitude of signals **316** to the speaker **205**. In one aspect of the present disclosure, low voltage switch **320** can also produce outputs **322d** operable to control illumination of the section of the faceplate behind **240d** thereby indicating to the user the volume control value. In FIG. 10 circuit board **260** and **1060** can be transparent and contain transparent conductors so as to facilitate illumination of distinct portions of the faceplate by illumination components **705** and **710** on circuit board **460**.

[0060] Interactive speaker grille **1005** can enable touch sensitive and illuminated regions of the speaker grille using one or more circuit boards disposed behind the grille have one or more openings that align with the openings forming the grille. FIG. 10 illustrates three circuit boards **260**, **460** and **1060** in part to illustrate the arrangement of components (e.g. LEDs and electrodes) on individual substrates. It can be appreciated the same touch sensing and illumination functionalities can be accomplished by combining the individual circuit boards **260**, **460** and **1060** into a variety of multiple-layer circuit boards. For example circuit boards **260** and **1060** can be two separate transparent circuit boards or can be combined into one transparent circuit board with touch electrodes **605a** and **255** disposed on the surface facing the interactive grille **214** and illumination electrodes **1010** disposed on the rear surface facing circuit board **460**. Electroluminescent region **710** can require intimate contact between electrodes **1010** and the electroluminescent (e.g., phosphor) layer **730**. This contact can be accomplished by bonding circuit board **1060** to board **460** in a manner similar to touch sensitive display fabrication. One or more connectors similar to **315** can connect circuit boards **260**, **460** and **1060**. A connector can also be used to connect circuit boards (e.g. **260** or **460**) to another circuit board positioned behind the X-Y plane formed by the flange **206** of the speaker **205**. Electrodes on boards **260**, **460** and **1060** can also be connected using wires and solder contacts.

The interactive speaker grille **1005** enables a large area of the speaker grille **214** to be functionalized as a control surface and a display surface. In one aspect the speaker grille **214** can be made from an electrically insulating material, thereby enabling the interactive speaker grille to identify user interaction with multiple distinct regions of the grille.

A dense plurality of openings **120** can facilitate effect sound transmission. Interactive speaker grille **1005** can devote a large region (e.g. region **240d**) to speaker controls. As wireless speakers have become more compact the surface area devoted to user controls has decreased. In contrast interactive speaker grille **1005** could devote the whole grille area to controls such as radio station selection, play, pause or skip to the next song. The touch sensitive capability and the illumination functionality can be combined to implement an interactive control. For example many of the speakers on the market do not have enough available area to provide a volume slider and therefore require the user to press a volume button multiple times to increment or decrement volume. This repeated button pushing is tedious and the user is often left without a visual indication of the volume level. Illumination components **330** and low voltage output signals **322c** can instead produce a visual pattern of illuminated sections **130c** on the interactive speaker grille that effectively indicate the present volume level. A user can use a corresponding touch sensitive region (e.g. **240c** or **240d**) to initiate volume change Touch functionality and illuminated components can be implemented on circuit boards with a dense plurality of openings arranged so as to enable sound impedance of the interactive speaker grille **1005** in FIG. 10 is determined primarily by the sound impedance of the grille member **214**.

[0061] In another embodiment electrical switch assembly **100** can be used to replace the functionality of a mechanical object (e.g., mechanical toggle switch) with which a user associates a characteristic sound (e.g., the "click" sound associated with a light switch or the chime associated with a doorbell). A speaker **205** disposed behind the touch sensitive speaker grille can produce the sound familiar to the user. This embodiment has the advantage that the user receives the sound from the area that is touched (i.e. the speaker grille) and not from another area away from the touch sensitive surface, which would have the potential to confuse a user. For example the electrical switch assembly **100** could produce a familiar click sound when a user touches an area of the grille operable to control an electrical switch. In another example the touch sensitive speaker grille could be used to guide a person towards a touch sensitive surface with audio feedback. For example a person with visual impairment could follow sound emanating from the touch sensitive speaker grille in order find the touch sensitive surface operable to control aspects of the speaker or electrical switches. The sound could vary to indicate that the user is getting closer or further from the interactive speaker grille.

#### Operation—FIG. 12-15

[0062] FIG. 12 is a block diagram illustrating the operation an electrical switch assembly with audio capability in accordance with one embodiment of the present technology. At block **1210** the speaker **205** receives audio signals **316** from amplifier **309**. At block **1220** speaker **205** emits sound waves through a pattern of openings in the speaker grille **214** and an aligned pattern of openings in one or more circuit boards (e.g., openings **220** in circuit board **260**). At block **1230** a user touches a region of the speaker grille portion **214** of the faceplate **105**, wherein the region is operable to be sensed by electrodes on circuit board **260** or functionalized surface **910** disposed behind the front surface of the faceplate. At block **1230** electrodes (e.g. **255**, **605a** and **605b**)



generate direct sensor signals **311a**. At block **1240** sensor signals **311a** are received by one or more low voltage switches **320**. At block **1240** the low voltage switch processes the signals; determine if the signals meet specific criteria (e.g. touch location, duration, sequence). At block **1250** electrical switch assembly **100** generates one or more low voltage switch output signals **322** and transmits these signals to one or more high voltage switches (e.g. dimmer **323a** or relay **323b**). At block **1260** one or more high voltage switches **323** operate to control the connection between one or more pairs building-based electrical wires. This operating sequence enables the functionality of a traditional electrical switch to be replicated using a combination of a low voltage switch and a high voltage switch, while devoting the space traditionally occupied by the mechanical switch to a large speaker centrally disposed in the switch housing and operable to project sound waves through a touch sensitive speaker grille.

**[0063]** FIG. **13** is a block diagram illustrating additional steps involved in the operation of some alternative embodiments of the electrical switch assembly.

At block **1305** electrical switch assembly can receive wireless signals **135** from a variety of wireless sources **140**. System **100** can use a wireless receiver **306**, speaker processor **308** and amplifier **309** to generate audio signals **316**. At block **1325** electrical switch assembly **100** can illuminate regions of the speaker grille using illumination components **330** disposed on a circuit board designed with a plurality of aligned openings, wherein the opening promote sound transmission. At block **1327** electrical switch assembly **100** can optionally guide the user to an active region of the speaker grille using one or more illuminated regions **130**. At block **1345** illumination components **330** can be controlled using low voltage switch output signals **322d** from the low voltage switch processor **320**.

**[0064]** FIG. **14** is a block diagram illustrating the operation an interactive speaker grille **1005** in accordance with one embodiment of the present technology. At block **1410** the speaker **205** receives audio signals **316** from amplifier **309**. At block **1420** speaker **205** emits sound waves through a plurality of openings in the speaker grille **214** and an aligned plurality of openings in one or more circuit boards (e.g., openings **220** in circuit board **260**). At block **1425** interactive speaker grille **1005** can illuminate regions of the speaker grille using illumination components **330** disposed on a circuit board designed with a plurality of aligned openings, wherein the openings promote sound transmission. At block **1430** a user touches a region of the speaker grille **214**, wherein the region is operable to be sensed by direct user input sensors **310** (e.g. sensor electrode **255**) on circuit board **260** or functionalized surface **910** disposed behind the front surface of the faceplate. At block **1427** interactive speaker grille **1005** can optionally guide the user to an active region of the speaker grille using one or more illuminated regions **130**. At block **1430** electrodes (e.g. **255**, **605a** and **605b**) generate direct sensor signals **311a**. At block **1440** sensor signals **311a** are received by one or more low voltage switches **320**. At block **1440** the low voltage switch processes the signals; determine if the signals meet specific criteria (e.g. touch location, duration, sequence). At block **1445** illumination components **330** can be controlled using low voltage switch output signals **322d** from the low voltage switch processor **320**. At block **1450** a low voltage switch **320** generates one or more low voltage switch output signals

**322c** and transmits these signals to a speaker processor **308**. At block **1460** speaker processor **308** controls an aspect of audio signals **316** sent to speaker **205**.

**[0065]** FIG. **15** is a block diagram outlining the operations associated with integrating audio capability into an electrical switch assembly **100** in accordance with several aspect of the present disclosure. At block **1510** the integration can involve providing a housing **210** including a forward facing portion **217**. At block **1520** the integration can involve providing a speaker **205** disposed inside the housing. At block **1530** the integration can involve providing a faceplate operable to be attached to the housing and to cover the speaker. At block **1540** the integration can involve providing a grille portion of the faceplate having a first plurality of openings for sound generated by the speaker to be transmitted to the region in front of the assembly. At block **1550** the integration can involve providing one or more sensors disposed behind the forward facing surface of the faceplate and operable to sense direct user interaction with one or more regions of the forward facing surface of the faceplate. At block **1560** the integration can involve incorporating a second plurality of openings into the sensor substrate. At block **1570** the integration can involve aligning at least one of the openings in the first and second plurality, so as to promote improved sound transmission through the sensor substrate. At block **1580** the integration can involve providing a low voltage switch operable to process direct sensor signals from one or more of the sensors. At block **1580** the integration can involve providing sensor placement such that one or more of the sensors are operable to sense direct user interaction with the grille portion of the faceplate.

### Smart Speakers

**[0066]** Recent advancements in building automation and multimedia (e.g. streaming video and audio) are inspiring media companies to extend wireless speakers to become bi-directional interfaces to smart building and the World Wide Web. Voice-activated wireless speakers enable a variety of new uses including controlling local building automation devices, appliances, issuing web-requests and accessing remote audio and music content. Many of these new uses rely on automatic speech recognition (ASR) and are enabled by arrays of microphones and voice-recognition algorithms to steer a high gain region or lobe (e.g. beam-forming) towards a person speaking in a room. Direct input sensors (e.g. buttons and touch sensitive regions) are common in most wireless speakers. A parallel area of development in smart speakers is the use of indirect sensors to sense voice commands, gestures, room-layout, person location, person identity and the presence of other smart devices in the local environment (e.g. in the same room or in the same building). Exemplary indirect sensors can include microphones, antenna arrays, LIDAR or gesture recognizing RADAR and cameras. Exemplary indirect input sensors can use a variety of technologies to sense the local environment including light detection, thermal detection, passive infrared detection, active infrared, ultrasound, sound and capacitive coupling.

**[0067]** One challenge is that indirect sensors compete for space with speaker elements in smart wireless speakers. The size of the speaker element (e.g. the speaker cone and driver) can impede the performance of indirect input sensors. For example, in FIG. **16A** a speaker **205** and two indirect sensors **1610a** and **1610b** (e.g. a motion sensor) are located on a



common substrate **1620**. Speaker **205** comprises a speaker cone **1625** and speaker driver **1630** (e.g. an electromagnet). Indirect sensor **16010a** has a total field of view **1640** comprising the set of all angles for which sensor **1610a** can transduce indirect input into indirect sensor signals (e.g. **311b** in FIG. 3). Speaker **205** obstructs a large portion (e.g. portion **1650**) of the total field of view **1640**. Indirect sensor **1610b** can augment the field of view **1640** but nevertheless the presence of speaker **205** considerably complicates sensing aspects of the local environment. In the case of FIG. **16A** placing the indirect sensors **1610a** and **1610b** behind the plane of the front of the speaker cone (i.e. out of the path of sound transmission) can improve sound quality but can impede sensor performance.

[0068] FIG. **16B** is a disassembled diagram of an alternative solution including an environmental-sensing faceplate subassembly **1660a** placed in the sound transmission path (e.g. in front) of speaker **205**. In the embodiment of FIG. **16B** environmental-sensing faceplate subassembly **1660a** includes faceplate **1605** with a front surface **1675**. A portion **214** of surface **1675** contains a first plurality of openings forming a speaker grille. Environmental-sensing faceplate subassembly further comprises an indirect sensor **325** and a circuit board **260**. Circuit board **260** can be a flat circuit board with an insulating substrate, a flexible printed circuit board, a molded 2-D or 3-D polymer substrate with attached conductive elements or plated conductive elements or a ceramic printed circuit board. Faceplate **1605** can be a portion of the outer housing or enclosure of a speaker assembly. Faceplate **1605** can be similar in design and function to faceplate **105**. Circuit board **260** comprises a second plurality of openings in a second surface **1680**. Several opening in the grille portion **214** of the front surface **1675** can align with corresponding openings in the circuit board (e.g. **120b** can align with **220b** in surface **1680**) and thereby promote sound transmission from speaker **205**. Other openings in grille portion **214** of front surface **1675** (e.g. **120a**) can align with one or more openings in circuit board **260** (e.g. opening **220a** in surface **1680**) and thereby enable indirect input sensor **325** to sense an aspect of the local environment.

[0069] In several embodiments an environmental-sensing faceplate subassembly comprises: an front surface with a first plurality of openings forming a grille, a circuit board places in the path of sound transmission from a speaker and an indirect sensor, wherein the circuit board comprises means that enable the indirect sensor to sense an aspect of the environment in the vicinity of the smart speaker and wherein the circuit board has a surface with openings that align with the grille to promote improved sound transmission from the speaker.

[0070] In another embodiment an environmental-sensing faceplate subassembly comprises: a front surface, contains a first plurality of openings forming a speaker grille, an indirect sensor disposed on a second surface behind the front surface with a second plurality of openings, and wherein at least one of the openings in the first and second plurality of openings are aligned, thereby promoting improved sound transmission from the speaker. For example the second surface can be the rear surface of faceplate **1605** or the housing of a speaker. The rear surface of faceplate **1605** can be functionalized with conductors and mounting pads for one or more indirect sensors using the plating techniques and molding techniques simpler to the faceplate in FIG. **9**.

In this way one embodiment of the environmental-sensing faceplate substrate can be a faceplate portion of a housing with a plurality of openings extending through a first and second surface on the faceplate such that opening in the first and second surfaces align in the direction of sound transmission. An indirect input sensor can be attached to the faceplate and can be encompassed by at least some of the plurality of openings.

[0071] FIG. **16C** illustrates an alternative environmental-sensing faceplate assembly **1660b** in which indirect input sensor **325** is located on circuit board **260**. Exemplary means by which circuit board **260** can enable indirect sensor **325** (e.g. a light level sensor) to sense the local environment can include: one or more openings (e.g. **220a** in FIG. **16B**) to facilitate access to the local environment, a mounting surface for indirect input sensor **325** or one or more electrical connectors (e.g. bond pads **1685**) on circuit board **260** to transport electrical signals associated with indirect input sensor **325** or conductors (e.g. **254**) to carry power to indirect input sensor **325** or carry sensor signals from indirect input sensor **325**.

[0072] In some embodiments of the environmental-sensing faceplate subassembly the indirect sensor can sense through the material of the faceplate. For example the faceplate **1605** can be made from a material that is transparent to the sensing technology, such as an optically transparent material or an RF transparent polymer. In other embodiments of the environmental-sensing faceplate subassembly the faceplate portion of the housing can be opaque or non-transmitting to the sensing technology. In such embodiments the environmental-sensing faceplate subassembly enables the indirect input sensor (e.g. **325**) to be aligned with one or more openings (e.g. **120a**) in the exterior surface of the faceplate (e.g. **120a** aligning with sensor **325** in FIG. **16C**).

[0073] Turning to FIG. **17**, a smart speaker **1700** can include a circuit board (e.g. curved circuit board **1705**) in the path of sound transmission from a speaker assembly **1710**. The combination of an array of openings and indirect input sensors on circuit board **1705** provides multiple uses for the space behind the large portion of the speaker housing **1720** often devoted to the speaker grille. The external surface **1730** of housing **1720** contains a first plurality of openings forming a speaker grille. The openings can be grouped to form several portions (e.g. **1715a** and **1715b**). Various groups of openings in the plurality of openings can accomplish a variety of different purposes. For examples, a subset of the opening in the grille can accomplish an aesthetic purpose (e.g. defining a shape with the pattern of openings) while another subset of the plurality of openings can serve a functional purpose (e.g. enabling environmental access for different sensors and speakers). In FIG. **17** a portion **1715a** of the speaker grille has openings designed to align with openings in circuit board **1705** and thereby promote sound transmission from speakers **205**. A second portion **1715b** of the speaker grille provides improved access for indirect input sensors **1725a**, **1725b** and **1725c** to the local environment (e.g. the region in front of surface **1730**).

[0074] FIG. **18** illustrates a disassembled view of smart speaker **1700** including two grille portions **1805a** and **1806b** of housing **1720**. In the assembled position several first opening (e.g. opening **120b**) in the grille portions of the housing align with second openings (e.g. **220b**) in the circuit board **1705** and thereby promote sound transmission illus-

trates by path **1810**. The first openings can be in the front (or exterior) surface **1807** of the grille portion **1805a** of housing **1720** and can align with second openings in a surface **1825** of circuit board **1705**. Circuit board **1705** contains a variety of indirect sensors (e.g. **1815** encompassed by a plurality of openings, the sensor array comprising **1725a**, **1725b**, **1725c**, patterned metallic feature **1840**, and **1850**). Indirect input sensor **1815** can be radar, or LIDAR operable to transmit an energy beam **1820** into the local environment and characterize the placement of objects based on the one or more aspects of reflections from the energy beam **1820** (e.g. time-of-flight, amplitude, phase, dispersion, waveform shape or distortion of the reflections from beam **1820**).

#### Gesture Recognition

[0075] One or more indirect sensors (e.g. **1815**) can recognize gestures made by a user and thereby control aspects of the smart speaker **1700**. For example, indirect input sensor **1815** can be the Soli 76 Ghz radar system-on-chip available from Infineon Inc. or Milpitas Calif. and can identify hand gestures made by a user **125**. If the radar were placed in a traditional location away from the path of sound transmission it could experience a large radar reflection from the speaker. In the FIG. **18** placement of the radar chip on circuit board **1705** in front of speaker **205** enables improved access to the local environment. In addition the portion of the housing **1805a** in front of indirect input sensor **1815** can be modified with openings or an RF transparent polymer to promote radar transmission. Due to the close placement to the housing **1720** only a small portion of housing **1720** need be modified to enhance the entire field of view of the indirect input sensor **1815**. Indirect input sensor **1815** can also be lidar operable to scan a laser beam through the grille or optically transparent portion of housing **1720**. One or more indirect sensors (e.g. **1815**) can be an LED or laser based lidar that performs ranging or gesture recognition based on illuminating some or all of the local environment with visible or infrared light.

[0076] Circuit board **1705** can contain one or more conductors **254**. Patterned conductors can form one or more antennas (e.g. patch antenna **1840**). The placement of circuit board **1705** between the sound generating elements and the grille enables an array of antennas (e.g. **1840**) to characterize the direction of incoming RF signals or the relative strength of incoming RF signals from different directions. A plurality of antennas can be placed in the path of sound transmission and utilize more space thereby improving the antenna gain. Indirect input sensor **1850** can be an active ultrasound sensor and can utilize a portion of the grille e.g. opening **120a** to transmit a signal **1860** into the local environment and sense or characterize the location of people (e.g. **1870**) or objects. Indirect sensors **1725a**, **1725b**, and **1725c** can be a beam-forming microphone array and utilize a portion of the speaker grille (e.g. portion **1715b** in FIG. **17** to identify the direction of speech. In one embodiment indirect input sensors can be mounted on an interior surface of housing **1720** in FIG. **17**. Housing **1720** can comprise the plurality of aligned openings on a first and second surface. In yet another embodiment one or more of the opening in the circuit board **1705** can form part of an indirect input sensor (e.g. part of an antenna) or can form part of a conductive path (e.g. a via hole for a conductor). For example one of the openings in the plurality of openings on the circuit board can be designed to

both align with an opening in the grille and can be a plated hole thereby forming part of conductive pathway for current on the circuit board.

[0077] FIG. **19A** illustrates an embodiment wherein a circuit board **260** with an indirect input sensor **325** is in the path of sound transmission **1940a** between a speaker **205** to the front surface **1730** of housing **1720**. In the embodiment of FIG. **19A** speaker **205** generates sound by vibrating in directions **1950** while circuit board **260** is perpendicular to the directions of vibration of the speaker and perpendicular to the direction of sound transmission **1940a**. Several openings in housing **1720** align with openings in circuit board **260** (e.g. openings **1910** and **1920**) such that the combined sound impedance of the aligned openings when viewed along the direction of sound transmission is substantially equal to the sound impedance of the grille openings alone. In the embodiment of FIG. **19A** speaker **205** generates sound by vibrating in direction **1950** while circuit board **260** is perpendicular to the direction of vibration of the speaker and perpendicular to the direction of sound transmission **1940a**.

[0078] FIG. **19B** and FIG. **19C** illustrate another embodiment, that is common with bass speakers wherein the path of sound transmission undergoes a direction change between generation in direction **1950** and passing through the grille. Nevertheless, circuit board **260** with an indirect sensor **325** is in the path of sound transmission **1940b** from speaker **205** to the front surface **1730** of housing **1720**.

[0079] FIG. **20** illustrates a related embodiment in which a circuit board **2010** with plurality of openings is positioned in the sound transmission path (e.g. in front of the cone) of a speaker **205**. The plurality of openings in the circuit substrate can encompass a display **2020** (e.g. an LCD or an organic LED display). The circuit board is positioned behind a faceplate **2030** that contains a first plurality of openings. Some of the first plurality of openings (e.g. opening **120b**) align with openings in the circuit board (e.g. opening **220b**), thereby promoting sound transmission from the speaker **205**. In a traditional display with speakers (e.g. a flat screen TV) the speakers can be mounted at the side of the display. The width of side-positioned speakers determines at least in part ability or effectiveness of the speaker to create low frequency sound waves (e.g. the ability to create deep bass sounds). In this way narrow speakers positioned on either side of the display often have a smaller frequency range than a larger speaker positioned behind the display (as illustrated in FIG. **20**). Hence one advantage of arrangement **2000** is to enable lower base tones using a larger speaker positioned behind the display. Circuit board **2010** and in particular the aligned openings (e.g. **120b** and **220b**) in the circuit board and the faceplate enable transmission of the speaker sound while displaying images. One area of application for the embodiment of FIG. **20** is locations where the area for a display is limited while sufficient depth is available to mount the speaker behind the display. Exemplary applications include appliances (e.g. smart thermostats), smart routers and smart light switches where a large (e.g. 4x4 inch) speaker can be mounted behind a display in a 2-bay electrical junction box.

[0080] FIG. **21** illustrates a method **2100** for integrating environmental sensing into a smart speaker. At step **2110** a speaker is provided. The speaker can be part of a speaker assembly such as speaker assembly **1710** in FIG. **17**. At step **2120** a housing is provided. The housing can comprise several attached parts (e.g. two halves of a clamshell molded

housing or a housing similar to **210** with a faceplate similar to **105** in FIG. 2). The housing is provided with a grille portion comprising a first plurality of openings. The grille portion can be a molded array of holes in a portion of the housing or a metal mesh component of the housing.

[0081] At step **2130** a circuit board is provided with a second plurality of openings. The circuit board can have at least one electronic component disposed on the circuit board. Exemplary electronic components that can be disposed on the circuit board include, an indirect input sensor, a wire, a conductive metallic trace, a resistor, a diode, a capacitor, an inductor, a microchip, a button or an LED. The at least one electronic component can be disposed on the circuit board by mechanically attaching it to the board (e.g. gluing, fastening or insert molding) or electronically connecting it to the circuit board (e.g. soldering, crimping or mating to a connector on the circuit board).

[0082] At step **2140** the circuit board is positioned in the housing such that at least one of the openings in the second plurality of openings aligns with one or more of the openings in the first plurality of openings, thereby promoting improved sound transmission from the speaker. The positioning at step **2140** can involve placing the circuit board within the housing, in the path of sound transmission.

[0083] At step **2150** one or more indirect input sensors are provided. At step **2160** means are provided on the circuit board to enable sensing of one or more aspects of the environment in the vicinity of a smart speaker by at least one or the one or more indirect input sensor. Exemplary means include electrical bond pads to attach the indirect input sensor on the circuit board or mechanical attachment (e.g. fastening) features on the circuit board to mechanically connect the direct input sensor to the circuit board. Other means on the circuit board to enabling sensing by the indirect sensor include one or more opening in the circuit board to enable the indirect input sensor to sense the region beyond the grille, wires or conductors disposed on the circuit board to provide power to the indirect input sensor or carry indirect input sensor signals from the indirect input sensor. Other means on the circuit board include conductors or components that act to gather or condition an input signal from the environment (e.g. antenna elements for a radar chip or a filter network, such as a frequency selective band-pass filter disposed on the circuit board).

1. A smart speaker comprising:

a housing;

a speaker located at least partially inside the housing; the speaker comprising a speaker cone and

an environmental sensing faceplate subassembly comprising:

a front surface, wherein a portion of the front surface contains a first plurality of openings forming a speaker grille;

an indirect input sensor operable to sense one or more aspects of the environment in the vicinity of the smart speaker; wherein the indirect input sensor is disposed behind the front surface of the environmental sensing faceplate subassembly on a second surface with a second plurality of openings, and wherein at least one of the openings in the second plurality of openings is aligned with one or more of the openings in the first plurality of openings, thereby promoting improved sound transmission from the speaker.

2. The smart speaker of claim **1** wherein a conductor connected to the indirect sensor is disposed on the second surface and wherein at least a portion of the conductor is encompassed by the second plurality of openings.

3. The smart speaker of claim **1** wherein the indirect sensor comprises one or more antenna elements disposed on the second surface and wherein at least one of the antenna elements is encompassed by at least some of the second plurality of openings.

4. The smart speaker of claim **1** wherein the indirect sensor comprises one or more antenna elements disposed on the second surface and wherein at least one of the antenna elements encompasses by at least some of the second plurality of openings.

5. The smart speaker of claim **1** wherein the indirect sensor is located on a circuit board, wherein the circuit board is located behind the front surface of the environment sensing

faceplate subassembly, wherein the circuit board contains the second plurality of openings, and

wherein the circuit board is in the path of sound transmission from the speaker cone to the grille.

6. The smart speaker of claim **5** wherein the circuit board covers at least a portion of the speaker, and wherein the circuit board is perpendicular to the direction of vibration of the speaker.

7. The smart speaker of claim **1** wherein at least one of the openings in the first plurality of openings facilitates the indirect sensor to sense in the vicinity of the smart speaker.

8. The smart speaker of claim **1** wherein the speaker grille is further defined as a region of the interactive faceplate subassembly encompassing at least some of the first plurality of openings and wherein the region is bounded by a polygon, the polygon comprising a plurality of straight line segments, wherein each straight line segment in the plurality of straight line segments touches the perimeter of at least two of the openings in the first plurality of openings.

9. The smart speaker of claim **1** further comprising:

one or more low voltage switches operable to receive direct sensor signals from the one or more of the direct user input sensors and wherein at least one of the low voltage switches generates a low voltage switch output signal in response to one or more direct user sensors sensing direct user interaction with the speaker grille.

10. The smart speaker of claim **1** wherein the indirect sensors are based on a technology from a group of technologies consisting of: radio frequency signals detection, sound sensing, radar detection, ultrasonic detection, reflected light detection, passive infrared detection.

11. A smart speaker with local environment sensing, comprising:

a speaker comprising a speaker cone;

a housing comprising:

an front surface;

a speaker grille having a first plurality of openings wherein the speaker grille substantially protects the speaker, promotes sound transmission from the speaker and provides for physical separation between the user and the speaker;

and one or more indirect sensors operable to sense one or more aspects of the environment in the vicinity of the smart speaker;

wherein the one or more indirect sensors are located on a first surface, wherein the first surface contains a

second plurality of openings and wherein at least one of the openings in the second plurality of openings aligns with an opening in the first plurality of openings, thereby improving sound transmission from the smart speaker.

**12.** The smart speaker of claim **11** further comprising: one or more regions of the housing through which the one or more indirect sensors sense one or more aspects of the environment in the vicinity of the smart speaker, and wherein at least one of the one or more regions of the front surface includes at least a portion of the speaker grille.

**13.** The smart speaker of claim **11** further comprising: a circuit board disposed behind the front surface of the housing, wherein at least a portion of the circuit board is in the path sound transmission from the speaker to the speaker grille, and wherein the circuit board contains the second plurality of openings and the one or more indirect sensors.

**14.** The method of claim **11** wherein at least one of the one or more indirect sensors is encompassed by at least some of the openings in the second plurality of openings.

**15.** The smart speaker of claim **11** further comprising a short range wireless receiver,  
one or more low voltage switches operable to generate at least one low voltage switch output signal based at least in part on sensing direct one or more aspects of the

environment in the vicinity of the smart speaker and wherein the low voltage switch output signal operates an aspect of the smart speaker.

**16.** The smart speaker of claim **11** wherein in the assembled state the number of openings from the first plurality of openings that align with openings from the second plurality of openings, is at least **50**.

**17.** A method of integrating environmental sensing into a smart speaker comprising:

providing a speaker;  
providing a housing, with a grille portion comprising a first plurality of openings;  
providing a circuit board, with at least one electronic component disposed on the circuit board, wherein the circuit board contain a second plurality of openings;  
positioning the circuit board in the housing such that at least one of the openings in the second plurality of openings aligns with one or more of the openings in the first plurality of openings, thereby promoting improved sound transmission from the speaker;  
providing one or more indirect input sensor; and  
providing on the circuit board means to enable sensing of one or more aspects of the local environment in the vicinity of the smart speaker by at least one or the one or more indirect input sensor.

\* \* \* \* \*