

Table of Contents

CMMC Level 1 Identification & Authentication (IA) Labs — Student Completion Guide

This guide provides step-by-step instructions for completing all 12 Identification & Authentication labs. Each lab presents a real-world identity management problem that you must find and fix using tools on the domain controller: Active Directory Users and Computers (ADUC), PowerShell, Task Scheduler, and file-based evidence artifacts.

Table of Contents

1. [Before You Begin](#)
 2. [How to Connect to the Lab Environment](#)
 3. [How to Open Your Tools](#)
 4. [Understanding Your Pod](#)
 5. [Key Paths and Locations](#)
 6. [Module 1: User Identification \(Labs M1-L1 – M1-L3\)](#)
 7. [Module 2: Non-Person Entity Identification \(Labs M2-L1 – M2-L3\)](#)
 8. [Module 3: User Authentication Management \(Labs M3-L1 – M3-L3\)](#)
 9. [Module 4: Defaults & Process Authentication \(Labs M4-L1 – M4-L3\)](#)
 10. [Quick Reference: Tools and Commands](#)
 11. [Tips and Common Mistakes](#)
 12. [Lab Completion Checklist](#)
-

Before You Begin

What You Need

- Your **Pod number** (your instructor will assign this, e.g., Pod01, Pod05, Pod12)
- Your **Guacamole login credentials** (your instructor will provide your username and password)
- The **lab password** your instructor gives you for creating new accounts
- A computer with a web browser (Chrome, Firefox, or Edge) — no special software needed

What You Will Be Doing

You will work on a **Windows Server domain controller** to identify and remediate identity and authentication problems. Unlike the Access Control labs (which focus on group membership), the IA labs use a wider range of tools:

- **Active Directory Users and Computers (ADUC)** — managing user accounts and properties
- **PowerShell** — exporting reports, changing password policy, inspecting scheduled tasks
- **Task Scheduler** — viewing and reconfiguring the account a scheduled task runs as
- **File Explorer / Notepad** — creating evidence files, CSV inventories, and remediation summaries

CMMC Context

These labs align with **CMMC Level 1 Identification & Authentication (IA)** requirements:

- **IA.L1-3.5.1** — Identify system users, processes acting on behalf of users, and devices
 - **IA.L1-3.5.2** — Authenticate (or verify) the identities of those users, processes, or devices as a prerequisite to allowing access
-

How to Connect to the Lab Environment

You will connect to the lab through **Apache Guacamole** — a web-based remote desktop gateway. There is nothing to install; everything runs in your web browser.

Step 1: Open the Guacamole Gateway

1. Open your web browser (Chrome, Firefox, or Edge)
2. Go to: <https://crc.guac.01.tcecur.com/#/>
3. You will see a login screen

Step 2: Log In with Your Student Credentials

1. Enter your **Username** — this matches your pod number:
 - Pod 01 → student01
 - Pod 05 → student05
 - Pod 12 → student12
 - *(and so on — the number matches your assigned pod)*
2. Enter your **Password** (provided by your instructor)
3. Click **Login**

Step 3: Connect to the Domain Controller

Connection Name

PODXX-DC

PODXX-WS01

1. Click on **PODXX-DC** (where XX is your pod number, e.g., **POD03-DC**)
2. The remote desktop session opens directly in your browser — no extra login is needed
3. Wait a few seconds for the Windows Server desktop to appear

Tip: Press **Ctrl+Alt+Shift** to open the Guacamole side menu (to return Home or switch connections).

Step 4: Check Your Lab Progress

Option 1: Click the "Check Your Progress — Pod XX" banner at the top of the Guacamole interface.

Option 2: Go directly to <https://training.status.tcecure.com/pod/XX> (replace XX with your pod number).

How to Open Your Tools

Active Directory Users and Computers (ADUC)

- On the server desktop, double-click the **Active Directory Users and Computers** shortcut.

Important — do not launch ADUC any other way. Your account administers your own pod only and is deliberately not an administrator of the shared domain controller. Launching ADUC from **Server Manager → Tools**, from `dsa.msc`, or from a blank MMC console makes Windows try to start it elevated and show a **User Account Control** prompt for an administrator username and password; your student account will always be rejected there. That is expected and does not mean your password is wrong — click **No** and use the desktop shortcut. If the shortcut is missing, press **Windows + R** and paste `cmd /c "set __COMPAT_LAYER=RunAsInvoker&& start "" mmc.exe dsa.msc"`.

PowerShell

1. Right-click the **Start** button → **Windows PowerShell**
2. *Alternative:* **Windows + R** → **powershell** → Enter

Run PowerShell normally — do **not** choose **Windows PowerShell (Admin)**. Every command in this guide works with your own delegated permissions, and (Admin) triggers the same UAC prompt described above.

Task Scheduler (needed for M2-L1)

1. **Windows + R** → `taskschd.msc` → Enter, or Server Manager → **Tools** → **Task Scheduler**

File Explorer

- **Windows + E**, or the folder icon on the taskbar
-

Understanding Your Pod

All pods share one domain (`acs-p01.local`), so **every object in your pod is prefixed with your pod prefix** to keep your work separate. If you are **Pod 03**, your prefix is **P03**:

Thing

Shared reception account

Terminated employee

Generic accounts

Backup task owner

Service accounts


Security group

Scheduled task

Evidence root

Critical: when you create an account, you must include your prefix (PXX-k.omalley, **not** k.omalley). The automated checker looks for the prefixed name.

Your OU Structure in ADUC



Tip: in ADUC use **Edit** → **Find** and search for your prefix (e.g. P03-) to list all of your pod's objects quickly.

Key Paths and Locations

All IA files live under C:\CyberLab\PodXX\ on the domain controller (replace XX with your pod number):

Path

C:\CyberLab\PodXX\
C:\CyberLab\PodXX\IA-Artifacts\
C:\CyberLab\PodXX\IA-Artifacts\Vault\
C:\CyberLab\PodXX\LabArtifacts\
C:\CyberLab\PodXX\LabArtifacts\Scripts\
C:\CyberLab\PodXX\LabArtifacts\Scans\
C:\CyberLab\PodXX_LAB_READY_IA-*.txt

Important: the automated verification checks these exact paths and file names, including your pod folder. Saving to C:\CyberLab\IA-Artifacts\ (without PodXX) will fail.

Module 1: User Identification

Module 1 is about making sure every person has a unique, individual, accounted-for identity — and that shared, zombie, and generic accounts are remediated.

Lab M1-L1 — Shared Reception Account

Difficulty: Beginner | **Time:** 20 minutes | **Type:** Hands-on (ADUC)

Scenario

The front desk uses one shared account, PXX-frontdesk, that multiple reception staff log into. Shared accounts break individual accountability. Two people use it: Karen O'Malley and a temporary agency worker.

Your Task

1. Disable the shared account
2. Create an individual account for each person
3. Write an evidence file

Steps

1. **Disable the shared account:**

- In ADUC, go to **acs-p01.local** → **Students** → **PodXX** → **Users** → **Staff**

- Right-click **PXX-frontdesk** → **Disable Account** → OK
- 2. **Create Karen O'Malley's account:**
 - Right-click the **Staff** OU → **New** → **User**
 - **First name:** Karen, **Last name:** OMalley
 - **User logon name:** PXX-k.omalley — the prefix is required
 - Click **Next**, enter the lab password, uncheck "*User must change password at next logon*", click **Next** → **Finish**
- 3. **Create the temporary worker's account** the same way, with logon name PXX-temp.agency01
- 4. **Write the evidence file:**
 - Open **Notepad** and write a short summary, for example:

IA M1-L1 Remediation
Date: 2026-06-10 Performed by: <your name>
 - Disabled shared account PXX-frontdesk
 - Created individual account PXX-k.omalley (Karen O'Malley)
 - Created individual account PXX-temp.agency01 (Temporary Agency Worker)
 - Save as **C:\CyberLab\PodXX\M1-L1.txt**

PowerShell alternative:

```
$p = "PXX"    # your prefix, e.g. P03  
Disable-ADAccount -Identity "$p-frontdesk"  
Get-ADUser -Identity "$p-frontdesk" | Select-Object SamAccountName,  
Enabled
```

Completion Criteria

- ☐ PXX-frontdesk exists and is **disabled**
- ☐ PXX-k.omalley exists
- ☐ PXX-temp.agency01 exists
- ☐ C:\CyberLab\PodXX\M1-L1.txt exists

Why This Matters

IA.L1-3.5.1 requires every system user to be individually identified. With a shared account there is no way to tell who did what.

Lab M1-L2 — Zombie Account (Terminated User Still Enabled)

Difficulty: Beginner | **Time:** 20 minutes | **Type:** Hands-on (ADUC)

Scenario

Tom Davis left the company, but PXX-tom.davis is still enabled, still in the Sales OU, and still a member of the Sales security group. That is a "zombie account".

Your Task

1. Disable the account
2. Remove its group memberships
3. Move it to the **Terminated** OU

Steps

1. **Find the account:** ADUC → **Students** → **PodXX** → **Resources** → **Departments** → **Sales** (or **Edit** → **Find** for PXX-tom.davis)
2. **Disable it:** double-click the account → **Account** tab → check "**Account is disabled**" → **Apply**
3. **Strip group memberships:** **Member Of** tab → select PXX-SG-ACS-Sales → **Remove** → **Yes** → remove any other groups (Domain Users cannot be removed) → **Apply** → **OK**
4. **Move it:** right-click PXX-tom.davis → **Move...** → **Students** → **PodXX** → **Users** → **Terminated** → **OK**

PowerShell alternative:

```
$p = "PXX"
Disable-ADAccount -Identity "$p-tom.davis"
Get-ADUser "$p-tom.davis" -Properties MemberOf | Select-Object -
ExpandProperty MemberOf |
    ForEach-Object { Remove-ADGroupMember -Identity $_ -Members "$p-
tom.davis" -Confirm:$false }
$ou = (Get-ADOrganizationalUnit -Filter "Name -eq 'Terminated'" -
SearchBase (Get-ADUser "$p-tom.davis").DistinguishedName.Split(', ', 2)
[1]).DistinguishedName
Move-ADObject -Identity (Get-ADUser "$p-tom.davis").DistinguishedName
-TargetPath $ou
```

(If the last two lines are awkward, just move the account in ADUC.)

Completion Criteria

- ☐ PXX-tom.davis is **disabled**
- ☐ No group memberships remain except Domain Users
- ☐ The account's location is inside the **Terminated** OU

Why This Matters

Former employees' credentials show up in password dumps. A disabled, stripped, relocated account removes that entry point and shows a controlled termination process.

Lab M1-L3 — Generic Accounts Present

Difficulty: Beginner | **Time:** 25 minutes | **Type:** Hands-on (ADUC) + CSV

Scenario

Three generic accounts exist in your pod: PXX-admin, PXX-user1, and PXX-test. None can be traced to a person, and there is no inventory of authorized users.

Your Task

1. Disable the three generic accounts
2. Create an authorized user inventory CSV

Steps

1. **Disable each generic account:** ADUC → **Students** → **PodXX** → **Users** → right-click each of PXX-admin, PXX-user1, PXX-test → **Disable Account**

PowerShell alternative:

```
$p = "PXX"
"$p-admin", "$p-user1", "$p-test" | ForEach-Object { Disable-ADAccount -Identity $_ }
```

2. **Create the inventory.** Open Notepad and enter something like:

```
Username,FullName,Department,Status,Justification
PXX-k.omalley,Karen OMalley,Reception,Active,Individual reception
account
PXX-temp.agency01,Temp Agency Worker,Reception,Active,Temporary
agency staff
PXX-tom.davis,Tom Davis,Sales,Disabled,Terminated employee
PXX-admin,Admin Account,N/A,Disabled,Generic account - no
individual owner
PXX-user1,User1 Account,N/A,Disabled,Generic account - no
individual owner
PXX-test,Test Account,N/A,Disabled,Generic account - no individual
owner
```

3. **Save as** C:\CyberLab\PodXX\IA-Artifacts\Authorized_User_Inventory.csv

- In the Notepad **Save as type** box choose **All Files (*.*)** so it does not become .csv.txt

Completion Criteria

- ☐ PXX-admin, PXX-user1, PXX-test are all disabled (or deleted)
- ☐ Authorized_User_Inventory.csv exists in your pod's IA-Artifacts folder and is not empty

Why This Matters

If "admin" does something malicious, nobody can say who that was. An authorized user inventory proves the organization knows and approves every account it has.

Module 2: Non-Person Entity Identification

Module 2 covers the identities that are not people — service accounts, automated processes, and devices. CMMC requires them to be identified and managed just like human users.

Lab M2-L1 — Scheduled Task Running as a Human Account

Difficulty: Intermediate | **Time:** 25 minutes | **Type:** Hands-on (ADUC + Task Scheduler)

Scenario

The nightly backup task **PodXX ACS Nightly Backup** runs under a real employee's account, PXX-s.jenkins. Automated jobs should run as dedicated service accounts: when Steve leaves, the backup breaks, and his credentials are needlessly exposed.

Your Task

1. Create a dedicated service account PXX-svc_backup
2. Reconfigure the task to run as it

Steps

1. **Create the service account:**
 - ADUC → **Students** → **PodXX** → **Users** → right-click → **New** → **User**
 - **Full name / logon name:** PXX-svc_backup
 - Click **Next**, enter a strong password, check "**Password never expires**", uncheck "*User must change password at next logon*" → **Next** → **Finish**
 - Double-click the account and add a **Description:** Service account for nightly backup automation

2. Point the task at the service account:

- Open **Task Scheduler (Windows + R → taskschd.msc)**
- Click **Task Scheduler Library** and find **PodXX ACS Nightly Backup**
- Right-click → **Properties** → **General** tab
- The "When running the task, use the following user account" field shows ACS-P01\PXX-s.jenkins
- Click **Change User or Group...**, type PXX-svc_backup, click **Check Names** → **OK**
- Click **OK** and enter the service account password when prompted

3. **Verify:** the task's **Run As / Author** column should now show the service account.

```
(Get-ScheduledTask -TaskName "PodXX ACS Nightly Backup").Principal.UserId
```

Completion Criteria

- ☐ PXX-svc_backup exists in Active Directory
- ☐ The task no longer runs as PXX-s.jenkins
- ☐ The task principal is the service account (its name must contain svc)

Why This Matters

IA.L1-3.5.1 covers "processes acting on behalf of users". A dedicated service account gives the automated process its own identity and its own accountability.

Lab M2-L2 — Rogue Device Artifact

Difficulty: Beginner | **Time:** 20 minutes | **Type:** CSV analysis

Scenario

A device scan detected MAC address AA-BB-CC-11-22-33, which is not in the authorized device list. You must record it as unauthorized and open a configuration record for investigation.

Your Task

1. Review the authorized device list and the rogue MAC file
2. Add the rogue device to the list, marked UNAUTHORIZED
3. Create a device configuration record CSV

Steps

1. **Review the evidence:**

- Open C:\CyberLab\PodXX\IA-Artifacts\Authorized_Device_List.csv — three authorized devices (DC, workstation, printer)
 - Open C:\CyberLab\PodXX\LabArtifacts\rogue_mac.txt — the detected MAC AA-BB-CC-11-22-33
2. **Add the rogue device** to the bottom of Authorized_Device_List.csv (open it in Notepad), keeping the existing columns:
- ```
UNKNOWN-DEVICE,AA-BB-CC-11-22-33,Unknown,UNAUTHORIZED,Unknown,2026-06-10
```

Save the file (do not delete the existing rows).

3. **Create the configuration record.** Open Notepad and enter:

```
MACAddress,DeviceName,Status,Location,Notes
AA-BB-CC-11-22-33,Unknown Device,UNAUTHORIZED,Network scan,Rogue
device detected - requires investigation
```

Save as C:\CyberLab\PodXX\IA-Artifacts\Device\_Config\_Record.csv (**All Files** type).

**Heads-up:** Lab **M4-L2** adds a second finding to this *same* Device\_Config\_Record.csv. When you get there, **append** to the file — do not overwrite it, or M2-L2 will stop passing.

### Completion Criteria

- ☐ Authorized\_Device\_List.csv contains AA-BB-CC-11-22-33 **and** the word UNAUTHORIZED
- ☐ Device\_Config\_Record.csv exists and is not empty

### Why This Matters

IA.L1-3.5.1 requires devices to be identified, not just users. An undocumented device on the network is an unmanaged entry point.

---

## Lab M2-L3 — Service Account Matrix Required

**Difficulty:** Beginner | **Time:** 25 minutes | **Type:** Hands-on (ADUC) + CSV

### Scenario

Three service accounts exist — PXX-svc\_backup, PXX-svc\_web, PXX-svc\_print — but their **Description** fields are empty, and there is no matrix documenting the non-person accounts.

### Your Task

1. Populate the Description field on all three accounts

## 2. Create a service account matrix CSV

### Steps

1. **Set the descriptions** in ADUC (**Students** → **PodXX** → **Users**) — double-click each account, fill **Description**, click OK:

- PXX-svc\_backup → Automated nightly backup service
- PXX-svc\_web → IIS web application pool identity
- PXX-svc\_print → Print spooler service account

### PowerShell alternative:

```
$p = "PXX"
Set-ADUser "$p-svc_backup" -Description "Automated nightly backup service"
Set-ADUser "$p-svc_web" -Description "IIS web application pool identity"
Set-ADUser "$p-svc_print" -Description "Print spooler service account"
```

2. **Create the matrix.** In Notepad:

```
AccountName,Description,Owner,Purpose>PasswordRotation,LastReview
PXX-svc_backup,Automated nightly backup service,IT Operations,Runs the nightly backup scheduled task,90 days,2026-04-01
PXX-svc_web,IIS web application pool identity,Web Team,Hosts internal web applications,90 days,2026-04-01
PXX-svc_print,Print spooler service account,IT Operations,Manages network print services,90 days,2026-04-01
```

Save as C:\CyberLab\PodXX\IA-Artifacts\Service\_Account\_Matrix.csv.

### Completion Criteria

- ☐ All three service accounts exist with a non-empty Description
- ☐ Service\_Account\_Matrix.csv exists and is not empty

**Note:** If PXX-svc\_web or PXX-svc\_print is missing, create it the same way you created PXX-svc\_backup in M2-L1.

### Why This Matters

An undocumented service account is an identity nobody owns. The matrix records what it does, who owns it, and when it was last reviewed — the basis of lifecycle management for non-person identities.

---

## Module 3: User Authentication Management

Module 3 is about how users prove who they are: password policy, documented review, and credential handling.

## Lab M3-L1 — Password Policy Report Missing

**Difficulty:** Beginner | **Time:** 15 minutes | **Type:** PowerShell + evidence

### Scenario

A domain password policy exists, but there is no exported report and no record that anyone reviewed it. Auditors need written evidence.

### Your Task

1. Export the current password policy to an HTML report
2. Write an evidence file describing your review

### Steps

1. **Export the policy** (PowerShell, replace PodXX):

```
Get-ADDefaultDomainPasswordPolicy |
 ConvertTo-Html -Title "Password Policy Report" |
 Out-File "C:\CyberLab\PodXX\IA-Artifacts\
PasswordPolicy_Report.html"
```

2. **Open and read it:**

```
Start-Process "C:\CyberLab\PodXX\IA-Artifacts\
PasswordPolicy_Report.html"
```

Note MinPasswordLength, ComplexityEnabled, LockoutThreshold, PasswordHistoryCount, MaxPasswordAge.

3. **Write the evidence file** in Notepad and save as C:\CyberLab\PodXX\M3-L1.txt:

```
IA M3-L1 Password Policy Review
Date: 2026-06-10 Reviewed by: <your name>
```

```
Current policy settings:
- Minimum password length: <value>
- Password complexity: <Enabled/Disabled>
- Lockout threshold: <value>
- Password history: <value>
- Maximum password age: <value> days
```

```
Assessment: policy exported and reviewed as required by CMMC IA.L1-
3.5.2.
```

### Completion Criteria

- ☐ PasswordPolicy\_Report.html exists in your pod's IA-Artifacts folder and is not empty
- ☐ C:\CyberLab\PodXX\M3-L1.txt exists

## Why This Matters

Having a policy is not enough — you must be able to show it exists and is reviewed. Missing documentation is one of the most common audit findings.

---

## Lab M3-L2 — Weak Password Policy

**Difficulty:** Intermediate | **Time:** 25 minutes | **Type:** Hands-on (PowerShell or GPO)

### Scenario

The domain password policy is dangerously weak: minimum length 6, complexity disabled, and no account lockout.

**Note:** the password policy is **domain-wide**, shared by every pod. Fixing it fixes it for everyone, and it is the one IA lab whose change is not isolated to your pod. Do not weaken it again after you have strengthened it.

### Required Settings

Setting

---

Minimum password length

Password complexity

Account lockout threshold

### Steps

#### Option A — PowerShell (recommended):

```
Set-ADDefaultDomainPasswordPolicy -Identity (Get-ADDomain).DNSRoot `
 -MinPasswordLength 12 `
 -ComplexityEnabled $true `
 -LockoutThreshold 10 `
 -PasswordHistoryCount 24 `
 -MaxPasswordAge (New-TimeSpan -Days 90) `
 -MinPasswordAge (New-TimeSpan -Days 1)
```

gpupdate /force

Get-ADDefaultDomainPasswordPolicy

#### Option B — Group Policy Management:

1. **Windows + R** → `gpmc.msc` → Enter
2. **Forest** → **Domains** → **acs-p01.local** → **Default Domain Policy** → right-click → **Edit**

3. **Computer Configuration → Policies → Windows Settings → Security Settings → Account Policies → Password Policy**
  - **Minimum password length** → 12
  - **Password must meet complexity requirements** → Enabled
4. **Account Lockout Policy → Account lockout threshold** → 10 invalid logon attempts
5. Close the editor and run `gpupdate /force`

### *Completion Criteria*

- ☐ `MinPasswordLength` is 12 or more
- ☐ `ComplexityEnabled` is True
- ☐ `LockoutThreshold` is 10 or more

### *Why This Matters*

A 6-character password with no complexity and no lockout can be brute-forced in seconds. IA.L1-3.5.2 requires authentication that actually resists common attacks.

---

## **Lab M3-L3 — User Must Change Password at Next Logon**

**Difficulty:** Beginner | **Time:** 15 minutes | **Type:** Hands-on (ADUC) + evidence

### *Scenario*

David Chen (PXX-d.chen) had his password reset by the helpdesk, but the "must change password at next logon" flag was never set — so he can keep using the temporary password forever, and whoever set it still knows it.

### *Your Task*

1. Set the must-change-password flag on PXX-d.chen
2. Write an incident evidence file

### *Steps*

1. **In ADUC: Students → PodXX → Users → Staff** → right-click PXX-d.chen → **Reset Password...** → enter a new temporary password → check **"User must change password at next logon"** → OK

### **PowerShell alternative:**

```
$p = "PXX"
Set-ADUser -Identity "$p-d.chen" -ChangePasswordAtLogon $true
Get-ADUser "$p-d.chen" -Properties pwdLastSet | Select-Object
SamAccountName, pwdLastSet # expect 0
```

2. **Verify** in the account's **Account** tab that the flag is set (or that `pwdLastSet` is 0)
3. **Write the evidence file** and save as `C:\CyberLab\PodXX\M3-L3.txt`:

IA M3-L3 Password Reset Incident  
Date: 2026-06-10    Remediated by: <your name>  
User: PXX-d.chen (David Chen)  
Issue: password was reset without "must change at next logon"  
Action: reset the password and enabled the must-change-at-next-logon flag  
Result: the user must set their own password at next sign-in

#### *Completion Criteria*

- ☐ PXX-d.chen has the must-change-password flag set (`pwdLastSet` = 0)
- ☐ `C:\CyberLab\PodXX\M3-L3.txt` exists

#### *Why This Matters*

A temporary password that is never changed is a shared secret between the user and whoever issued it — which defeats individual authentication.

---

## Module 4: Defaults & Process Authentication

Module 4 covers default credentials, hardcoded passwords, and undocumented authentication configuration — among the most commonly exploited weaknesses in real attacks.

### Lab M4-L1 — Default Credentials Not Addressed in the Hardening Standard

**Difficulty:** Beginner | **Time:** 20 minutes | **Type:** Document editing + evidence

#### *Scenario*

Your organization has a hardening standard (`Hardening_Standard.txt`), but it never requires default passwords to be changed on new equipment.

#### *Your Task*

1. Review the standard
2. Add a default-credentials clause
3. Write an evidence file

#### *Steps*

1. **Read** `C:\CyberLab\PodXX\IA-Artifacts\Hardening_Standard.txt` — it covers OS hardening, network security, accounts, logging, and physical security, and ends by admitting it is incomplete

2. **Append a section** in Notepad and save the file:

6. DEFAULT CREDENTIALS

- All default passwords on newly deployed hardware and software must be changed before the system is placed into production, including:
  - network equipment (routers, switches, firewalls), server OS default accounts, application default admin accounts, SNMP community strings, and database default credentials.
- Responsibility: IT Operations must verify default credentials are changed as part of the deployment checklist.
- Reference: CMMC IA.L1-3.5.2 - authenticate identities before granting access

The checker looks for wording that ties **default** to **password/credential** — keep those words in the text.

3. **Write the evidence file** and save as C:\CyberLab\PodXX\M4-L1.txt:

IA M4-L1 Hardening Standard Update  
Date: 2026-06-10 Updated by: <your name>  
Action: added a default credentials section to Hardening\_Standard.txt  
Location: C:\CyberLab\PodXX\IA-Artifacts\Hardening\_Standard.txt  
The standard now requires all default passwords to be changed before production deployment, per CMMC IA.L1-3.5.2.

### *Completion Criteria*

- ☐ Hardening\_Standard.txt contains a default password/credential requirement
- ☐ C:\CyberLab\PodXX\M4-L1.txt exists

### *Why This Matters*

Default credentials are the easiest way in. The Mirai botnet took over hundreds of thousands of devices using nothing else.

---

## **Lab M4-L2 — SNMP Community String Set to "public"**

**Difficulty:** Beginner | **Time:** 20 minutes | **Type:** Scan report analysis + CSV

### *Scenario*

A vulnerability scan flagged a network device using the default SNMP community string public — anyone on the network can read its configuration.

### *Your Task*

1. Review the scan report
2. Document the SNMP finding in the device configuration record
3. Add an SNMP clause to the hardening standard

### *Steps*

1. **Read the scan report:** C:\CyberLab\PodXX\LabArtifacts\Scans\openvas\_scan\_report.txt
  - The [HIGH] finding is SNMP community string public on **10.50.1.30 (PRINT-P01)**, port 161/udp
2. **Append the finding to C:\CyberLab\PodXX\IA-Artifacts\Device\_Config\_Record.csv.**

**Do not overwrite this file** — it still has to contain your M2-L2 rogue-device row (AA-BB-CC-11-22-33 / UNAUTHORIZED) or M2-L2 will fail. Open it in Notepad and add a line at the end, for example:  
10.50.1.30,PRINT-P01,SNMP community string is 'public' (HIGH) - change to a complex value and restrict SNMP,OPEN,Network scan,From openvas\_scan\_report.txt

Keeping both findings in one file is what the checker expects: the file must mention SNMP (M4-L2) **and** the rogue MAC marked UNAUTHORIZED must still be in Authorized\_Device\_List.csv (M2-L2).

3. **Add an SNMP clause** to Hardening\_Standard.txt (good practice, and it reinforces M4-L1):  
  
7. SNMP CONFIGURATION  
- Default SNMP community strings (public, private) must be changed on all network devices. Use SNMPv3 with authentication and encryption where supported. SNMP v1/v2c with default strings is a critical finding.

### *Completion Criteria*

- ☐ Device\_Config\_Record.csv mentions SNMP
- ☐ The M2-L2 rogue-device evidence is still intact

## Why This Matters

SNMP with public hands out interface details, routing tables, and sometimes credentials to anyone who asks. Documenting the finding is the first step of correcting it.

---

## Lab M4-L3 — Script Contains a Hardcoded Password

**Difficulty:** Intermediate | **Time:** 25 minutes | **Type:** Hands-on (file editing) + evidence

### Scenario

db\_connect.py connects to the inventory database using a hardcoded password (password123). Anything that touches that file — a repo, a backup, a file share — leaks the credential.

### Your Task

1. Replace the hardcoded password with a vault reference
2. Create a vault entries file
3. Write a remediation summary

### Steps

1. **Open** C:\CyberLab\PodXX\LabArtifacts\Scripts\db\_connect.py in Notepad and find:

```
DB_PASSWORD = "password123"
```

Change it to a vault reference and save:

```
DB_PASSWORD = "VAULT_REF:db_production_password"
```

The literal password123 must no longer appear anywhere in the file, and VAULT\_REF must appear.

2. **Create the vault entries file.** In Notepad:

```
VaultKey,Description,Owner,RotationSchedule,LastRotated
db_production_password,Production database connection
credential,DBA Team,90 days,2026-04-01
```

Save as C:\CyberLab\PodXX\IA-Artifacts\Vault\Vault\_Entries.txt

3. **Write the remediation summary** and save as C:\CyberLab\PodXX\M4-L3.txt:

```
IA M4-L3 Hardcoded Password Remediation
Date: 2026-06-10 Remediated by: <your name>
Finding: db_connect.py contained the hardcoded password
```

"password123"

Location: C:\CyberLab\PodXX\LabArtifacts\Scripts\db\_connect.py

Remediation:

1. Replaced the hardcoded password with VAULT\_REF:db\_production\_password
2. Documented the credential in IA-Artifacts\Vault\Vault\_Entries.txt
3. The password is now retrieved from the vault at runtime, not stored in code

Impact: eliminated credential exposure through script files.

### *Completion Criteria*

- ☐ db\_connect.py no longer contains password123
- ☐ db\_connect.py contains VAULT\_REF
- ☐ Vault\_Entries.txt exists in IA-Artifacts\Vault\ and is not empty
- ☐ C:\CyberLab\PodXX\M4-L3.txt exists

### *Why This Matters*

Hardcoded credentials are CWE-798, a top software weakness. They end up in version control, backups, and logs. A vault reference keeps the secret out of code and makes rotation possible.

---

## **Quick Reference: Tools and Commands**

### **PowerShell Commands Used in the IA Labs**

Command

---

Get-ADUser -Filter "SamAccountName -eq 'PXX-name'"

Disable-ADAccount -Identity "PXX-name"

New-ADUser -SamAccountName "PXX-name" -Name "PXX-name" ...

Set-ADUser -Identity "PXX-name" -Description "text"

Set-ADUser -Identity "PXX-name" -ChangePasswordAtLogon \$true

Get-ADDefaultDomainPasswordPolicy

Set-ADDefaultDomainPasswordPolicy

Get-ScheduledTask -TaskName "PodXX ACS Nightly Backup"

gpupdate /force

### **File Operations**

Task

---

Create a text file

Create a CSV file

Open a path quickly  
Check a file exists

## Keyboard Shortcuts

Shortcut

---

**Windows + R**

**Windows + E**

**Ctrl+Alt+Shift**

## Tips and Common Mistakes

### Do

- **Do** include your pod prefix (PXX-) in every account name you create
- **Do** save files to the exact paths shown, **including your PodXX folder**
- **Do** use the correct extensions (.txt, .csv, .html)
- **Do** re-open a saved file to confirm the content landed
- **Do** put a date and your name in evidence files

### Don't

- **Don't** save to C:\CyberLab\IA-Artifacts\ — it must be C:\CyberLab\PodXX\IA-Artifacts\
- **Don't** delete accounts when the lab says disable — they are different actions, and the checker looks for the disabled account
- **Don't** overwrite Device\_Config\_Record.csv in M4-L2 — append to it
- **Don't** modify objects outside your pod's OU or other students' objects
- **Don't** panic at red PowerShell text — read it, it usually names the problem

## Common Issues

Problem

---

"Access denied" when saving

Verification says an account was not found

Verification says a file was not found

Can't find a user in ADUC

PowerShell AD commands not recognized

Task Scheduler won't save the change

File saved as .txt instead of .csv

New password rejected as too weak

## Lab Completion Checklist

### Lab

---

M1-L1

M1-L2

M1-L3

M2-L1

M2-L2

M2-L3

M3-L1

M3-L2

M3-L3

M4-L1

M4-L2

M4-L3

**Evidence files you should end up with in C:\CyberLab\PodXX\:** M1-L1.txt, M3-L1.txt, M3-L3.txt, M4-L1.txt, M4-L3.txt

**Artifacts you should end up with in C:\CyberLab\PodXX\IA-Artifacts\:** Authorized\_User\_Inventory.csv, Authorized\_Device\_List.csv (updated), Device\_Config\_Record.csv, Service\_Account\_Matrix.csv, PasswordPolicy\_Report.html, Hardening\_Standard.txt (updated), Vault\ Vault\_Entries.txt

---

*This guide was created for the Digital Resilience Community Clinic (DRCC) Cyber Range. CMMC Level 1 — Identification & Authentication (IA) Module*