

Table of Contents

CMMC Level 1 System & Communications Protection (SC) Labs — Student Completion Guide

This guide provides step-by-step instructions for completing all 12 System & Communications Protection labs. Each lab presents a real-world network security challenge using the pfSense firewall — the same technology used by thousands of organizations to protect their networks.

Table of Contents

1. [Before You Begin](#)
 2. [How to Connect to the Lab Environment](#)
 3. [How to Access the pfSense Firewall](#)
 4. [How to Open Lab Artifacts](#)
 5. [Understanding Your Pod](#)
 6. [Module 1: Foundations of the Digital Perimeter \(Labs M1-L1 – M1-L3\)](#)
 7. [Module 2: External and Internal Boundaries \(Labs M2-L1 – M2-L3\)](#)
 8. [Module 3: Firewall Rules \(Labs M3-L1 – M3-L3\)](#)
 9. [Module 4: Monitoring and Validation \(Labs M4-L1 – M4-L3\)](#)
 10. [Quick Reference: pfSense Navigation](#)
 11. [Tips and Common Mistakes](#)
 12. [Lab Completion Checklist](#)
-

Before You Begin

What You Need

- Your **Pod number** (your instructor will assign this, e.g., Pod01, Pod05, Pod12)
- Your **Guacamole login credentials** (your instructor will provide your username and password)
- A computer with a web browser (Chrome, Firefox, or Edge) — no special software needed

What You Will Be Doing

In these labs you will use **pfSense** — an open-source firewall and router platform — to configure boundary protection, create deny-by-default policies, segment networks, audit firewall rules, and investigate logs. These are the same skills a network security analyst uses daily.

CMMC Context

These labs align with **CMMC Level 1 System & Communications Protection (SC)** requirements:

- **SC.L1-3.13.1** — Monitor, control, and protect communications at the external and internal boundaries of organizational systems

This single SC control covers boundary protection, firewall configuration, network segmentation, deny-by-default policies, and communications monitoring.

How to Connect to the Lab Environment

You will connect to the lab through **Apache Guacamole** — a web-based remote desktop gateway. There is nothing to install; everything runs in your web browser.

Step 1: Open the Guacamole Gateway

1. Open your web browser (Chrome, Firefox, or Edge)
2. Go to: <https://crc.guac.01.tcecure.com/#/>
3. You will see a login screen

Step 2: Log In with Your Student Credentials

1. Enter your **Username** — this matches your pod number:
 - Pod 01 → student01
 - Pod 02 → student02
 - Pod 05 → student05
 - Pod 12 → student12
 - *(and so on — the number matches your assigned pod)*
2. Enter your **Password** (provided by your instructor)
3. Click **Login**

Step 3: Connect to the Domain Controller

After logging in, you will see a list of available connections:

Connection Name

PODXX-DC

PODXX-GW

1. Click on **PODXX-DC** (where XX is your pod number, e.g., **POD03-DC**)
2. The remote desktop session will open in your browser
3. Wait for the Windows Server desktop to appear

Tip: To return to the Guacamole home screen, press **Ctrl+Alt+Shift** to open the side menu, then click **Home**.

How to Access the pfSense Firewall

Most SC labs require you to log into the pfSense firewall web interface. There are two ways:

Option A: Through Guacamole (Recommended)

1. From the Guacamole home screen, click **PODXX-GW**
2. This opens the pfSense web interface directly in your browser

Option B: From the Domain Controller

1. Connect to **PODXX-DC** via Guacamole
2. Open a web browser (Edge or Firefox)
3. Navigate to: **http://10.51.XX.1** (replace XX with your pod number)
 - Pod 01 → http://10.51.1.1
 - Pod 05 → http://10.51.5.1
 - Pod 12 → http://10.51.12.1

pfSense Login Credentials

Field

Username

Password

After logging in, you will see the pfSense Dashboard showing system status, interfaces, and traffic information.

How to Open Lab Artifacts

Lab artifacts (worksheets, instructions, evidence templates) are stored on the Domain Controller:

1. Connect to **PODXX-DC** via Guacamole
2. Open **File Explorer** (click the folder icon in the taskbar)
3. Navigate to: C:\CyberLab\PodXX\SC-Artifacts\
 - SC-M1-L1_* — Module 1, Lab 1 files
4. You will see files for each lab:

- SC-M1-L2_* — Module 1, Lab 2 files
- _LAB_READY_SC-M1-L1.txt — Marker indicating lab is seeded

Saving Your Work

After completing each lab, save your evidence to the same SC-Artifacts directory:

- Screenshots: Use **Snipping Tool** (Windows key → type "snipping") to capture your pfSense configuration
 - Text files: Save completed worksheets and reports
 - Always include your pod number in evidence file names
-

Understanding Your Pod

Each student has an isolated pod environment:

Your Pod (PodXX)

- PODXX-DC (Domain Controller)
 - Active Directory
 - Lab artifacts: C:\CyberLab\PodXX\SC-Artifacts\
 - Shared with AC, IA, SI labs
- PODXX-GW (Gateway/Firewall)
 - WAN Interface: Connected to external network
 - LAN Interface: 10.51.XX.1/24
 - Web UI: http://10.51.XX.1
 - SSH: admin@10.51.XX.1

Your firewall is completely isolated from other students' pods. You can make any configuration changes without affecting anyone else.

Module 1: Foundations of the Digital Perimeter

Lab M1-L1: Understanding Trust Boundaries

Difficulty: Beginner | **Time:** 20 minutes | **Type:** Document-based

Scenario

You are the new cybersecurity analyst at ACS Consulting, a small defense contractor. Your first task is to identify the trust boundaries in the company's network.

What You Need

- Artifact: SC-M1-L1_Boundary_Worksheet.txt
- Artifact: SC-M1-L1_Network_Topology.txt

- Access to pfSense Dashboard (<http://10.51.XX.1>)

Steps

1. **Open the Network Topology reference:**

- On PODXX-DC, navigate to C:\CyberLab\PodXX\SC-Artifacts\
- Open SC-M1-L1_Network_Topology.txt
- Review the network layout

2. **Log into pfSense to see the live configuration:**

- Open browser → <http://10.51.XX.1>
- Login: admin / pfsense
- Go to **Status** → **Dashboard** to see interfaces
- Go to **Status** → **Interfaces** for detailed network info

3. **Open the Boundary Worksheet:**

- Open SC-M1-L1_Boundary_Worksheet.txt
- Complete each task:

4. **Task 1 — Identify the External Boundary:**

- The external boundary is where your network meets the internet
- Look at the pfSense WAN interface — what separates your network from the outside?
- Answer: The firewall's WAN interface is the external boundary

5. **Task 2 — Identify the Internal Boundary:**

- Are there zones within the LAN?
- Is there a DMZ configured? (Check Interfaces)

6. **Task 3 — Mark Trusted vs Untrusted Assets:**

- Internet = Untrusted
- ISP Router = Untrusted
- Firewall = Boundary device (controls trust)
- DC01, Workstation, File Server = Trusted (inside the boundary)

7. **Task 4 — Locate where FCI should reside:**

- FCI (Federal Contract Information) should only exist in the trusted zone
- Behind the firewall, on protected servers

8. **Save your completed worksheet:**

Save as: C:\CyberLab\PodXX\SC-Artifacts\SC-M1-L1_Completed.txt

This exact file name is required (.txt, .csv, or .png is accepted) and it must contain at least 50 characters of content.

Why This Matters

CMMC SC.L1-3.13.1 requires organizations to identify and protect their system boundaries. Without knowing where your boundaries are, you cannot protect them.

Lab M1-L2: Deny By Default Firewall

Difficulty: Beginner | **Time:** 30 minutes | **Type:** Hands-on (pfSense)

Scenario

The pfSense firewall currently has an "Allow Any Any" rule — it permits ALL traffic through without restrictions. This is a critical security misconfiguration that violates CMMC deny-by-default requirements.

What You Need

- pfSense web UI (<http://10.51.XX.1>)
- Artifact: SC-M1-L2_Lab_Instructions.txt

Steps

1. **Log into pfSense:**
 - Open browser → <http://10.51.XX.1>
 - Login: admin / pfsense
2. **View the current (bad) rules:**
 - Navigate to **Firewall** → **Rules** → **LAN**
 - You should see rules including "INSECURE: Allow all traffic"
 - This means ANY device can send ANY traffic anywhere — no restrictions
3. **Understand the problem:**
 - With "Allow Any Any," a compromised workstation can reach every server
 - An attacker inside the network has unrestricted access
 - This violates CMMC's deny-by-default principle
4. **Delete the "Allow Any Any" rule:**
 - Check the box next to the "INSECURE: Allow all traffic" rule
 - Click the **Delete** button (trash can icon)
 - **Also delete** the "INSECURE: Allow all WAN traffic" rule
 - Click **Apply Changes** at the top
5. **Create specific allow rules (deny-by-default):**
 - Click the + **Add** button (down arrow, add to bottom)

- Create these rules one at a time:

Rule 1: Allow DNS

- Action: Pass
- Interface: LAN
- Protocol: TCP/UDP
- Source: LAN net
- Destination: Single host — 10.50.1.10
- Destination Port: DNS (53)
- Description: Allow DNS to DC01
- Click Save

Rule 2: Allow Web Traffic

- Action: Pass
- Interface: LAN
- Protocol: TCP
- Source: LAN net
- Destination: Any
- Destination Port: HTTP (80) and HTTPS (443)
- Description: Allow web browsing
- Click Save

Rule 3: Allow ICMP (Ping)

- Action: Pass
- Interface: LAN
- Protocol: ICMP
- Source: LAN net
- Destination: Any
- Description: Allow ping for troubleshooting
- Click Save

6. Verify the default deny is in place:

- pfSense automatically blocks anything not explicitly allowed
- Your rule list should now show ONLY:
 - i. Anti-lockout (Web UI access)
 - ii. Allow DNS to DC01
 - iii. Allow web browsing
 - iv. Allow ping
- Everything else is denied by default

7. Click Apply Changes

8. Test your configuration:

- Go to **Diagnostics → Ping**
- Ping 10.50.1.10 (DC01) — should succeed
- Go to **Status → System Logs → Firewall**
- Look for blocked traffic entries — these prove deny-by-default is working

9. Save evidence:

- Take a screenshot of your final rule list

Save as: C:\CyberLab\PodXX\SC-Artifacts\M1-L2_FinalRules.png

Hint: If you accidentally lock yourself out of the pfSense web UI, don't panic. The anti-lockout rule at the top prevents this. If it does happen, ask your instructor for help.

Why This Matters

"Deny by default" is the foundation of all network security. Instead of trying to block everything bad (impossible), you only allow what is specifically needed. This is required by CMMC SC.L1-3.13.1.

Lab M1-L3: Monitor, Control, Protect

Difficulty: Intermediate | **Time:** 30 minutes | **Type:** Hands-on (pfSense)

Scenario

A firewall has three core responsibilities: **Monitor** (observe and log traffic), **Control** (decide what traffic is allowed), and **Protect** (block harmful traffic). Your firewall has rules demonstrating all three. Your job is to identify which is which.

What You Need

- pfSense web UI (<http://10.51.XX.1>)
- Artifact: SC-M1-L3_Worksheet.txt

Steps

1. **Log into pfSense** and go to **Firewall → Rules → LAN**
2. **Review each rule and identify its responsibility:**

Rule Description

Web traffic (logging enabled)

DNS only to DC01

Block access to management network

Default Deny

3. Check the logs to see monitoring in action:

- Go to **Status → System Logs → Firewall**
- You should see log entries from rules that have logging enabled
- Each entry shows: time, interface, source IP, destination IP, action (pass/block)

4. Complete the worksheet:

- Open SC-M1-L3_Worksheet.txt on the DC
- For each task, identify the specific rule and explain how it demonstrates that responsibility
- Answer the analysis questions

5. Save evidence:

- Screenshot the firewall log showing all three types of entries
- Save as: C:\CyberLab\PodXX\SC-Artifacts\M1-L3_Worksheet_Complete.txt

Why This Matters

Understanding Monitor/Control/Protect helps you design complete security architectures. A firewall that only blocks (protects) but doesn't log (monitor) is blind to attacks. One that only logs but doesn't restrict (control) is useless.

Module 2: External and Internal Boundaries

Lab M2-L1: Draw the Organizational Boundary

Difficulty: Beginner | **Time:** 20 minutes | **Type:** Document-based

Scenario

Using your pod's live pfSense configuration, create a complete organizational boundary diagram showing all network zones, connections, and security boundaries.

Steps

1. Gather network information from pfSense:

- Log into pfSense (<http://10.51.XX.1>)
- Go to **Status → Interfaces** — note WAN and LAN details
- Go to **Firewall → Rules** — understand traffic flow
- Go to **Status → Dashboard** — see system overview

2. Open the boundary worksheet on the DC:

- SC-M2-L1_Boundary_Worksheet.txt

3. Draw your diagram including:

- ISP / Internet (external, untrusted)
- Your pod's firewall (boundary device)
- LAN network (internal, trusted)
- Each server/workstation with its role
- Mark each boundary line clearly

4. Save your completed diagram:

Save as: C:\CyberLab\PodXX\SC-Artifacts\SC-M2-L1_Completed.txt

This exact file name is required (.txt, .csv, or .png is accepted) and it must contain at least 50 characters of content.

Lab M2-L2: Secure the DMZ

Difficulty: Advanced | **Time:** 45 minutes | **Type:** Hands-on (pfSense)

Scenario

ACS Consulting's public web server is sitting on the internal LAN at 10.51.XX.50. This means external visitors accessing the web server can potentially reach internal resources like DC01. You must move the web server into a DMZ (Demilitarized Zone).

Steps

1. **Log into pfSense** and review the current (bad) configuration:
 - Go to **Firewall → Rules → WAN**
 - Note the rule allowing HTTP to an internal LAN IP — this is the problem
 - Go to **Firewall → NAT → Port Forward**
 - Note the NAT rule pointing to the LAN
2. **Create a DMZ interface:**
 - Go to **Interfaces → Assignments**
 - If you have an available interface, click **+ Add**
 - Rename the new interface to **DMZ**
 - Set the IP: 10.51.XX.200 with subnet /24
 - Enable the interface → Save → Apply
3. **Update firewall rules:**

DMZ rules:

 - Allow inbound HTTP/HTTPS from WAN to DMZ web server
 - **Block** all traffic from DMZ to LAN (critical — isolates the DMZ)

- Allow DMZ to respond to established connections

LAN rules:

- Allow LAN to manage DMZ (for administration)

4. Update NAT rules:

- Go to **Firewall → NAT → Port Forward**
- Change the target from the LAN IP to the new DMZ IP
- Save → Apply

5. Verify:

- ☐ Web server accessible from WAN through DMZ
- ☐ DMZ cannot ping or reach LAN resources
- ☐ LAN can still manage the DMZ
- ☐ DC01 is NOT accessible from DMZ

6. Save evidence:

Save as: C:\CyberLab\PodXX\SC-Artifacts\M2-L2_DMZ_Rules.png

Save as: C:\CyberLab\PodXX\SC-Artifacts\M2-L2_DMZ_Verification.txt

Hint: The key concept is that a DMZ is a "semi-trusted" zone. External users can reach the web server, but if the web server is compromised, the attacker cannot reach the internal LAN.

Lab M2-L3: Internal Segmentation with VLANs

Difficulty: Advanced | **Time:** 45 minutes | **Type:** Hands-on (pfSense)

Scenario

ACS Consulting has four departments on a flat network — HR, Finance, Engineering, and Guest WiFi. Any device can reach any other device. A guest on the WiFi can access HR file shares and Finance databases.

Steps

1. Review the segmentation plan:

- Open SC-M2-L3_Segmentation_Plan.txt on the DC
- Note the four required VLANs and their subnets

2. Create VLANs on pfSense:

- Go to **Interfaces → VLANs**
- Click **+ Add**:
 - Parent Interface: vtnet1 (LAN)
 - VLAN Tag: 10
 - Description: HR Department

- Repeat for:
 - VLAN 20 — Finance
 - VLAN 30 — Engineering
 - VLAN 40 — Guest WiFi

3. **Assign VLAN interfaces:**

- Go to **Interfaces → Assignments**
- Assign each VLAN as a new interface (OPT1 through OPT4)
- Rename them: HR, FINANCE, ENGINEERING, GUEST
- Set each interface IP (e.g., 10.51.XX.10.1/24 for HR)
- Enable each interface → Save → Apply

4. **Configure DHCP (optional):**

- Go to **Services → DHCP Server**
- Enable DHCP on each VLAN interface with appropriate ranges

5. **Create firewall rules for isolation:**

HR VLAN rules:

- Allow DNS to DC01 (10.50.1.10:53)
- Allow AD traffic to DC01
- Block traffic to Finance, Engineering, Guest
- Default deny

Finance VLAN rules:

- Allow DNS to DC01
- Allow HTTPS to accounting app
- Block traffic to HR, Engineering, Guest
- Default deny

Guest VLAN rules:

- Allow DNS (any DNS server)
- Allow HTTP/HTTPS to internet
- **Block ALL internal networks** (most important rule)
- Default deny

6. **Verify isolation:**

- From each VLAN, test connectivity:
 - ☐ Guest cannot reach HR
 - ☐ Guest cannot reach Finance
 - ☐ Engineering cannot reach Finance
 - ☐ All departments can reach DC01 for DNS
 - ☐ Guest can browse the internet

7. **Save evidence:**

Save as: C:\CyberLab\PodXX\SC-Artifacts\M2-L3_VLAN_Config.png
Save as: C:\CyberLab\PodXX\SC-Artifacts\M2-L3_Isolation_Test.txt

Why This Matters

Network segmentation limits the blast radius of a breach. If an attacker compromises a guest device, they cannot reach HR or Finance data. This is a core CMMC SC requirement.

Module 3: Firewall Rules

Lab M3-L1: Firewall Rule Audit

Difficulty: Intermediate | **Time:** 30 minutes | **Type:** Hands-on (pfSense)

Scenario

A previous administrator left messy, insecure firewall rules. You must audit every rule, identify issues, clean up the rule set, and verify everything still works.

Steps

1. **Log into pfSense** and go to **Firewall → Rules → LAN**
2. **Open the audit worksheet:**
 - On DC: SC-M3-L1_Audit_Worksheet.txt
3. **Audit each rule — identify the issue type:**

Issue Type

[A] Allow Any

[S] Shadowed

[D] Duplicate

[U] Unused

[O] OK

4. **Document each rule in the audit table**

5. **Clean up the rules:**

- Delete all [A] Allow Any rules
- Delete all [D] Duplicate rules
- Delete all [U] Unused rules
- Move [S] Shadowed rules above the rule blocking them, OR delete if unnecessary
- Keep [O] OK rules
- Click **Apply Changes**

6. Verify connectivity:

- DNS should still work
- Web browsing should still work
- Unauthorized traffic should be blocked

7. Save evidence:

Save as: C:\CyberLab\PodXX\SC-Artifacts\M3-L1_Audit_Complete.txt
Save as: C:\CyberLab\PodXX\SC-Artifacts\M3-L1_CleanRules.png

Lab M3-L2: Rule Ordering Challenge

Difficulty: Intermediate | **Time:** 25 minutes | **Type:** Hands-on (pfSense)

Scenario

The firewall has all the right rules, but they are in the wrong order. A "Block All" rule appears BEFORE the allow rules, so all legitimate traffic is being blocked.

Steps

1. **Log into pfSense** and go to **Firewall → Rules → LAN**
2. **Observe the problem:**
 - The "Default Deny" rule is near the top
 - All allow rules (DNS, web, RDP, ICMP) are below it
 - pfSense processes rules top-to-bottom — first match wins
 - Since "Block All" matches everything, the allow rules never fire
3. **Reorder the rules:**
 - Click and drag rules to reorder them (grab the three-line handle on the left)
 - Or select a rule and use the arrow buttons to move it
 - **Correct order:**
 - i. Anti-lockout (Web UI access) — keep first
 - ii. Allow DNS to DC01
 - iii. Allow Web traffic (80, 443)
 - iv. Allow RDP to DC01
 - v. Allow ICMP/Ping
 - vi. Default Deny — **must be LAST**
4. **Click Apply Changes**
5. **Verify everything works:**

- Go to **Diagnostics → Ping** — ping 10.50.1.10 (should succeed now)
- Go to **Status → System Logs → Firewall** — confirm traffic is flowing
- Check that the Default Deny is still catching unauthorized traffic

6. **Save evidence:**

Save as: C:\CyberLab\PodXX\SC-Artifacts\M3-L2_Reordered_Rules.png

Key Takeaway: In firewall administration, the ORDER of rules is as important as the rules themselves. A correctly written rule in the wrong position is useless.

Lab M3-L3: Least Privilege Access

Difficulty: Intermediate | **Time:** 25 minutes | **Type:** Hands-on (pfSense)

Scenario

The accounting application at 10.51.XX.100 only needs HTTPS (TCP 443). But the firewall allows FTP, SSH, Telnet, HTTP, MySQL, and an alternate HTTP port — all unnecessary and potentially dangerous.

Steps

1. **Log into pfSense** and go to **Firewall → Rules → LAN**
2. **Identify rules targeting the accounting server (10.51.XX.100):**
 - You should see 7 rules allowing different ports
 - Only ONE is needed: TCP 443 (HTTPS)
3. **Delete unnecessary port rules:**
 - Check the box next to each unnecessary rule:
 - ☐ Port 21 (FTP) — DELETE
 - ☐ Port 22 (SSH) — DELETE
 - ☐ Port 23 (Telnet) — DELETE (especially dangerous!)
 - ☐ Port 80 (HTTP) — DELETE (app uses HTTPS)
 - ☐ Port 443 (HTTPS) — **KEEP THIS**
 - ☐ Port 3306 (MySQL) — DELETE (app handles DB internally)
 - ☐ Port 8080 (Alt HTTP) — DELETE
 - Click Delete → Apply Changes
4. **Verify:**
 - The accounting app should still work on HTTPS
 - All other ports should be blocked (default deny catches them)

- Check **Status → System Logs → Firewall** for blocked traffic to confirm

5. **Save evidence:**

Save as: C:\CyberLab\PodXX\SC-Artifacts\M3-L3_LeastPrivilege_Rules.png

Why This Matters

Least privilege means giving only the minimum access needed. An application that only needs port 443 should not have ports 21, 22, 23, 80, 3306, and 8080 open. Each open port is an attack surface.

Module 4: Monitoring and Validation

Lab M4-L1: Firewall Log Investigation

Difficulty: Intermediate | **Time:** 30 minutes | **Type:** Hands-on (pfSense)

Scenario

Your firewall logs contain evidence of suspicious activity. As the security analyst, investigate the logs and document your findings.

Steps

1. **Log into pfSense** and go to **Status → System Logs → Firewall**
2. **Investigate the following categories:**

Port Scans:

- Look for blocked connections to ports 22 (SSH), 23 (Telnet), 3389 (RDP), 445 (SMB)
- Multiple connection attempts from the same IP = likely port scan
- Document: source IPs, ports targeted, timestamps

Blocked Malware Indicators:

- Look for blocked outbound connections to IRC ports (6660-6669)
- These could indicate malware trying to contact a command-and-control server
- Document: internal IPs making suspicious outbound connections

Denied Legitimate Traffic:

- Look for blocked traffic that should be allowed
- This might indicate missing firewall rules
- Document: what applications are affected

Suspicious Sources:

- Note any blocked traffic from unusual IP ranges
 - Document: IPs, patterns, recommended actions
3. **Open the investigation worksheet** on the DC:
 - SC-M4-L1_Investigation_Worksheet.txt
 - Answer each investigation question with evidence from the logs
 4. **Save evidence:**

Save as: C:\CyberLab\PodXX\SC-Artifacts\SC-M4-L1_Completed.txt

This exact file name is required (.txt or .csv) and it must contain at least 50 characters of content.
-

Lab M4-L2: Verify SC Compliance

Difficulty: Intermediate | **Time:** 35 minutes | **Type:** Hands-on (pfSense + DC)

Scenario

You are performing a simplified CMMC assessor walkthrough. Using the compliance checklist, verify that your pod's System & Communications Protection controls are properly implemented.

Steps

1. **Open the compliance checklist** on the DC:
 - SC-M4-L2_Compliance_Checklist.txt
2. **Work through each section:**

Boundary Protection:

- Log into pfSense → Status → Dashboard
- Screenshot the dashboard showing the firewall is operational
- Check Firewall → Rules for configured rules
- Check Status → System Logs for log entries

Firewall Configuration:

- Verify default deny policy exists (last rule)
- Verify no "Allow Any Any" rules
- List each allow rule and justify why it's needed

Logging:

- Verify logging is active on key rules
- Screenshot log entries

Segmentation:

- Check Interfaces → VLANs for network segmentation
- If not yet configured, document this as a finding

FCI Protection:

- Identify where FCI resides
- Document the firewall rules protecting it

3. For each checklist item:

- Check the box if compliant
- Take a screenshot as evidence
- Note any findings or non-compliance issues

4. Save evidence:

Save your completed checklist to: C:\CyberLab\PodXX\SC-Artifacts\
SC-M4-L2_Completed.txt

Save any screenshots to: C:\CyberLab\PodXX\SC-Artifacts\
M4-L2_Compliance_Evidence\

SC-M4-L2_Completed.txt (or .csv) is the file verification looks for,
and it must contain at least 50 characters of content. Screenshots
are supporting evidence only.

Lab M4-L3: Final Capstone

Difficulty: Expert | **Time:** 60 minutes | **Type:** Hands-on (pfSense + DC)

Scenario

ACS Consulting, a small defense contractor, has inherited a poorly configured network. The firewall allows all traffic, has no segmentation, no logging, and dangerous services are exposed to the internet. You must fix EVERYTHING.

This lab is the practical assessment for the entire SC module. You will use everything you have learned.

Steps

1. Log into pfSense and assess the damage:

- Go to **Firewall → Rules** — note the "Allow Any" rules
- Check WAN rules — note inbound Telnet exposure
- Check for VLANs — none configured
- Check logging — not enabled

2. TASK 1: Implement Deny-By-Default (15 min)

- Delete all "Allow Any" rules on LAN and WAN
- Create specific allow rules for required services

- Ensure default deny is last rule
 - *(Apply everything you learned in Lab M1-L2)*
3. **TASK 2: Secure the WAN** (10 min)
 - Remove the Telnet exposure (port 23 from WAN)
 - Block all inbound WAN traffic by default
 - Only allow necessary inbound services
 4. **TASK 3: Create Network Segmentation** (15 min)
 - Create at least 2 VLANs
 - Configure inter-VLAN rules
 - Isolate sensitive resources
 - *(Apply everything you learned in Lab M2-L3)*
 5. **TASK 4: Enable Logging** (5 min)
 - Enable logging on all block rules
 - Enable logging on critical allow rules
 - Verify logs appear in **Status → System Logs**
 6. **TASK 5: Verify Communications** (10 min)
 - Test DNS (ping DC01)
 - Test web browsing
 - Verify internal services accessible
 - Verify external attacks blocked
 7. **TASK 6: Produce Assessment Evidence** (5 min)
 - Screenshot final firewall rules
 - Screenshot VLAN configuration
 - Screenshot firewall logs
 - Complete the compliance checklist
 - Draw a network diagram with boundaries marked
 8. **Save all evidence:**

Save to: C:\CyberLab\PodXX\SC-Artifacts\M4-L3_Capstone\

Grading Criteria

All 6 tasks must be completed with evidence:

- ☐ No "Allow Any" rules, default deny in place
- ☐ WAN secured, no dangerous services exposed
- ☐ At least 2 VLANs configured with isolation rules
- ☐ Logging enabled and generating entries
- ☐ Required communications verified working
- ☐ All evidence screenshots saved

Quick Reference: pfSense Navigation

Task

View/edit firewall rules
Create a new rule
View firewall logs
View system dashboard
View interface status
Create VLANs
Assign interfaces
Configure NAT/port forwarding
Test connectivity (ping)
Configure DHCP
View ARP table
Backup configuration

pfSense Rule Tips

- **Rules are processed top to bottom** — first match wins
 - **Default deny is automatic** — anything not explicitly allowed is blocked
 - **Always click "Apply Changes"** after modifying rules
 - **Logging:** Click the information icon (i) on a rule to enable/disable logging
 - **Rule actions:** Pass = allow, Block = silently drop, Reject = drop with notification
-

Tips and Common Mistakes

Common Mistakes

Mistake

Forgetting to click "Apply Changes"
Creating rules on wrong interface
Deleting the anti-lockout rule
Rules in wrong order
Not saving evidence

Getting Unstuck

- **Locked out of web UI?** Contact your instructor — they can reset your firewall

- **Can't reach pfSense?** Make sure you're using the right IP:
http://10.51.XX.1
 - **Rules not taking effect?** Click "Apply Changes" — changes are not active until applied
 - **Lost your changes?** Go to **Diagnostics → Backup & Restore** to restore a previous config
-

Lab Completion Checklist

Use this checklist to track your progress:

Lab

M1-L1
M1-L2
M1-L3
M2-L1
M2-L2
M2-L3
M3-L1
M3-L2
M3-L3
M4-L1
M4-L2
M4-L3

After completing each lab:

1. Verify your evidence files are saved in C:\CyberLab\PodXX\SC-Artifacts\
 2. Check that your artifact files have your pod number in the file names
 3. Mark the lab as complete in this checklist
-

This guide was created for the Digital Resilience Community Clinic (DRCC) Cyber Range. CMMC Level 1 — System & Communications Protection (SC) Module