Study on tree-based methods. MATH 6380 project 2

Chenyang, DONG Tsz Cheung, LO Jiacheng, XIA

April 24, 2017

1 / 16

Outline

- Introduction
- 2 American Crime Dataset
- 3 Kaggle: Binray Drug
- Conclusion

Table of Contents

- Introduction
- 2 American Crime Dataset
- 3 Kaggle: Binray Drug
- Conclusion





Why did we choose tree-based methods?

• We went through several methods.



- We went through several methods.
- Tree-based methods are straight-forward and easy to implement.

- We went through several methods.
- Tree-based methods are straight-forward and easy to implement.
- There are yet many improvement methods.



- We went through several methods.
- Tree-based methods are straight-forward and easy to implement.
- There are yet many improvement methods.
- Studied the method on 3 datasets.



Table of Contents

- Introduction
- 2 American Crime Dataset
- 3 Kaggle: Binray Drug
- Conclusion

The dataset

This dataset and the preprocessing are the same as project 1.

The dataset

This dataset and the preprocessing are the same as project 1.

Goal for this dataset

Do straightforward analysis and compare with Lasso (PJ 1).

What we found

In terms of MSE, simple regression tree (0.11) slightly worse than Lasso (0.06); bagging, random forest and boosting even better (0.04, 0.02).

Visualize the results




Figure: Regression tree on crime data

Boosting and random forests




Figure: Importance from boosting




Figure: Importance from random forest

Table of Contents


- Introduction
- 2 American Crime Dataset
- 3 Kaggle: Binray Drug
- 4 Conclusion

Variable Importance

- The R randomForest package optionally produces 2 additional pieces of information. One is called Variable Importance, a measure of the importance of the predictor variables.
- It is based upon the mean decrease of accuracy in predictions on the out of bag samples when a given variable is excluded from the model.
- In this project, we define variables/predictors with %IncMSE > 0 as important variables, then select them as our predictors in our final model.

Importanct Variables in BinaryDrug

The necessary calculations are carried out tree by tree as the random forest is constructed. Our experience has been that even though the variable importance measures may vary from run to run, the ranking of the importances is quite stable.



A potential variable selection method?

- We have tried *LASSO* in this dataset. Bad.
- Somebody introduced p-value selection. Kaggle MSE=3.08. Good.
- Can we do better using variable importance?

some V.I related models

• V.I + MLR, Kaggle *MSE* = 3.26057



some V.I related models

- V.I + MLR, Kaggle MSE = 3.26057
- V.I + Random Forest with using all V.I, Kaggle MSE = 3.23067

some V.I related models

- V.I + MLR, Kaggle MSE = 3.26057
- V.I + Random Forest with using all V.I, Kaggle MSE = 3.23067
- So sad. And I don't know why.

However...

- What if we adapt a Random Forest with mtry slightly > # of V.I ?
- Say in this Kaggle Competition, # of V.I is 25, and we have tried mtry = 25 to 30, all giving us MSE lower than 3.10.
- (Maybe) this can be explained from that, using slightly more *mtry* in each iteration can have a higher chance covering all those V.I when building **Random Forest**.

Table of Contents

- Introduction
- 2 American Crime Dataset
- 3 Kaggle: Binray Drug
- Conclusion



To conclude our work in PJ2...

- Tree-based regression algos are suitable for these discrete-input, continous-output dataset
- As a metric, Variable Importance may not be useful for variable selection process.