Zero-Shot Monocular Depth Estimation for Metric Object Sizing in Low-Contrast Environments

Author Name
Department, University
City, Country
author@university.edu

***Abstract*—We ask how far a purely zero-shot pipeline can go from a single RGB image to tape-measured object dimensions. The pipeline pairs a frozen YOLOv8m detector with a frozen monocular depth model and converts relative depth into metres with a two-anchor disparity fit; a pinhole back-projection then yields each object's distance Z, width W and height H. On a purpose-built 100-image dataset (five household objects, five distances from 0.50 to 0.90 m, four lighting conditions including an active-infrared night mode) we benchmark five depth backbones: Depth Anything V2 Small/Base/Large, MiDaS (DPT-Hybrid) and Marigold. Depth Anything V2 Large is best, with 3.63 cm mean absolute distance error (4.9 %), 9.3 % / 4.9 % relative width / height error and no gross failures, against 9.38 cm for MiDaS. The aggregate hides a strongly non-uniform error profile: 61 % of the total absolute distance error comes from one tall, thin, transparent bottle, and that error is a one-directional overestimation almost entirely explained by where depth is sampled inside the box; sampling the ground-contact point instead of the box interior cuts it by 40 % at no cost. Night-time infrared capture is the second failure mode, and its error tracks highlight clipping rather than low contrast. We also show that 5 % of detection rows must be voided rather than scored, and that scoring them silently can roughly double a model's reported error.**

***Index Terms*—monocular depth estimation, zero-shot inference, object sizing, YOLO, geometric calibration, benchmark**

I. Introduction

Turning a photograph into a physical measurement recurs in agriculture, logistics, inventory and robotic manipulation: a system that reports "this fruit is 7.4 cm across and 62 cm away" from the camera it already has needs no depth sensor, no stereo rig and no calibration target on the object. Monocular depth estimation (MDE) is strong in the zero-shot regime [2], [5], but published benchmarks report relative-depth metrics on internet-scale imagery, not centimetres on a tableside object under a dim bulb. This paper asks: *if we freeze a detector and a depth model and bolt a two-anchor calibration onto them, how accurate are the resulting metric dimensions, and where does that accuracy break?*

We answer with a 100-image capture matrix that isolates object identity, distance and illumination on a locked-down rig, with every distance and object dimension tape-measured. Every model is used as shipped: no fine-tuning, no per-scene optimisation, no test-time adaptation. Our contributions are:

- a reproducible zero-shot pipeline that converts detector boxes plus relative depth into per-object Z, W and H (Section III), with a 100-image dataset spanning lighting, distance and object axes;
- a five-model benchmark on that dataset, reported in aggregate and decomposed by lighting, distance and object (Section V);
- the finding that the aggregate error is dominated by a single object geometry, that this error is a signed bias rather than noise, and that a one-line change to depth sampling removes 40 % of it (Section V-F);
- an evaluation-integrity result: without a detection gate, 10 % of rows silently size the wrong object and inflate reported error by up to 2× (Section V-G).

II. Related Work

Eigen *et al.* [1] established single-image depth regression; MiDaS [2], [3] scaled it and made cross-dataset zero-shot transfer the norm. Depth Anything V1/V2 [4], [5] extend that recipe with large-scale unlabelled data, while Marigold [6] re-casts depth as conditional diffusion on a pretrained image generator. All of these predict *relative* or affine-invariant depth, so calibration is unavoidable for metrology; metric variants (ZoeDepth [7], Metric3D [8]) are tied to the camera and domain of their training data, which is what a plug-and-play deployment avoids.

We take object extents from YOLO [9] in its Ultralytics form [10]. Boxes are the cheapest localisation available and their tightness becomes a first-order error term for thin objects (Section V). Back-projecting pixels through a pinhole model is textbook geometry [13]; the open question is the depth stage feeding it. Existing benchmarks (KITTI [11], NYU-Depth [12]) use LiDAR or RGB-D ground truth in driving or room scenes and report scale-invariant errors, so they do not answer how a commodity camera with an assumed field of view performs on small objects at 0.5–0.9 m under warm, dim and infrared light.

III. Method

A. Overview

Figure 1 shows the five stages. A 1920×1080 RGB frame goes to YOLOv8m, which returns boxes, classes and confidences, while a frozen depth model returns a dense relative-depth map D. Each surviving box selects a scalar depth statistic, the anchors calibrate it to metres, and the pinhole




Fig. 1. The pipeline. Both learned components are frozen. Detections are gated to the expected class, the depth map is sampled inside each surviving box, and a two-anchor least-squares fit in disparity space maps relative depth to metres before the pinhole back-projection produces Z, W and H.

model turns the box extent at that depth into physical width and height, one row per object.

B. Disparity-Domain Anchor Calibration

Let $D(u, v)$ be the raw model output. The natural alignment is linear in depth,

$$Z(u, v) = \alpha\, D(u, v) + \beta, \tag{1}$$

with (α, β) fitted by least squares to tape-measured distances. Relative-depth models, however, are trained against *inverse* depth, so D behaves like disparity and fitting (1) warps any object lying between the calibration anchors. We instead fit

$$\frac{1}{Z(u, v)} = \alpha\, D(u, v) + \beta \quad \Longrightarrow \quad Z(u, v) = \frac{1}{\alpha\, D(u, v) + \beta}, \tag{2}$$

which is exact for a model whose output is proportional to disparity and interpolates correctly between anchors. Both forms are implemented; all results here use (2).

Two physical reference cups are placed at known distances, 0.40 m and 1.00 m, in every scene and clicked once per scene folder, so calibration costs two clicks and no per-object measurement. The anchors bracket the working range (0.50–0.90 m), so the object always lies between them.

C. Depth Sampling and Back-Projection

A box covers a surface patch, not a point, so a scalar depth must be chosen. Our default takes the median of D over the interior 60 % of the box, which is robust to stray background pixels; Section V-F shows this is the wrong choice for tall, thin objects and evaluates alternatives. Given Z at the object and focal lengths (f_x, f_y), the pinhole model gives

$$W = \frac{|u_2 - u_1|\, Z}{f_x}, \qquad H = \frac{|v_2 - v_1|\, Z}{f_y}, \tag{3}$$

for a box spanning $u_1..u_2$ and $v_1..v_2$. Intrinsics come from EXIF when available; this camera reported nothing usable, so we assume a 65° horizontal field of view, giving $f_x = f_y = 1506.9$ px. That assumption scales all absolute numbers uniformly and is revisited in Section VI.

D. Detection Gating and Row Voiding

An early version scored whatever detection was most confident between the two anchors. Since the anchors are themselves cups, that frequently scored a *calibration cup*, a knife or the table, and because ground-truth distance comes from the filename the resulting "errors" were 10–50 cm of pure bookkeeping (Section V-G). The pipeline now applies three rules: (i) drop any detection whose box contains an anchor click, which is exact because the clicks land on the anchor cups; (ii) keep only detections of the class the scene is about, from the object id or a target flag; (iii) if none survives, void the row instead of scoring it. Voided rows are logged, excluded from every metric, and counted in the summary.

IV. Experimental Setup

A. Dataset and Rig

The dataset contains 100 images: five objects × five distances (0.50 to 0.90 m in 10 cm steps) × four lighting conditions. The objects, with tape-measured $W \times H$, are a bowl (12.0×6.0 cm), a mug (12.0×8.0 cm), an apple (7.5×7.0 cm), a short bottle (7.5×25.0 cm) and a tall, narrow, transparent bottle (6.2×24.0 cm). The lighting modes are *white*, evenly lit and used as reference; *warm*, a strong yellow cast; *dim*, low and flat; and *nv*, lights off with an active-infrared illuminator, producing a near-monochrome frame. The camera is locked on a tripod and no capture parameter changes. The two reference cups sit at 0.40 m and 1.00 m in every scene and the measured object is placed at the target distance with a tape measure. One image per cell, so the design measures systematic behaviour, not shot-to-shot variance.

B. Models and Implementation

We benchmark five frozen backbones: Depth Anything V2 Small, Base and Large (the `-hf` Transformers checkpoints) [5]; MiDaS in its DPT-Hybrid form [2], [3]; and Marigold [6]. Detection is YOLOv8m [10] at confidence 0.25 for every model. All five see identical boxes, anchors and calibration, with box-median depth sampling. Runs used one RTX 4070 (12 GB). Five models times 100 images gives 500 (model, image) pairs, of which 475 are scored and 25 voided.

TABLE I

OVERALL ACCURACY OVER 475 SCORED ROWS PER MODEL (25 VOIDED ROWS EXCLUDED). BIAS IS THE MEAN SIGNED ERROR; >20 CM AND >30 % ARE GROSS-FAILURE RATES. BEST VALUE IN EACH COLUMN IS BOLD.

Model	MAE (cm)	rel (%)	bias (cm)	RMSE (cm)	>20 (cm)	>30 (%)	W (%)	H (%)
DA-V2-S	5.78	8.0	+4.77	10.71	12	7	12.9	8.3
DA-V2-B	5.35	7.4	+4.99	7.83	5	1	11.8	6.1
DA-V2-L	**3.63**	**4.9**	+3.21	**5.15**	**0**	**0**	**9.3**	**4.9**
MiDaS	9.38	13.1	+5.26	15.91	12	12	15.5	11.1
Marigold	8.55	12.1	−3.12	11.62	3	2	14.3	13.5

C. Metrics

For each scored row we report $|\hat{Z} - Z|$ and $|\hat{Z} - Z|/Z$ and derive MAE, RMSE, mean signed bias and the fraction exceeding 20 cm or 30 %. Sizing accuracy is mean absolute relative error of W and of H against the tape-measured table.

V. RESULTS AND DISCUSSION

A. Overall Accuracy

Depth Anything V2 Large wins every column of Table I: 3.63 cm MAE (4.9 %), 5.15 cm RMSE, 9.3 % width and 4.9 % height error, and no detection beyond 20 cm or 30 %. Its RMSE sits close to its MAE, so errors are small and evenly spread; Small's RMSE is nearly twice its MAE (10.71 vs 5.78 cm), meaning a few rows drive it, and that fragility rather than the mean is the real difference between the sizes. Base is a defensible middle ground. Accuracy is monotone in model size within the family, and the family beats both baselines on distance *and* sizing. MiDaS (9.38 cm) is weakest overall; Marigold lands at 8.55 cm at diffusion-sampling cost (Section VI).

Every model except Marigold over-estimates distance, with mean $\hat{Z}/Z$ of 1.062 (Small), 1.067 (Base), 1.042 (Large) and 1.075 (MiDaS); Marigold under-estimates at 0.949. One multiplicative correction fitted on the anchors would recover 4–7 points of relative error for free, and would improve W and H in proportion since both scale linearly with Z.

B. Effect of Lighting

Table II overturns the intuition that a dim scene is the hard case. Pooled over the Depth Anything family, dim is marginally the *easiest* condition at 4.01 cm, ahead of white (4.20) and warm (4.65). A plausible mechanism is figure/ground separation: darkening the frame leaves a bright object against a dark background, exactly the signal a depth model exploits. Marigold behaves differently: it is most accurate in white light (9.4 %) and worst under infrared (14.7 %), the opposite ordering to the Depth Anything family.

Night-time infrared is the failure mode: 7.29 cm pooled, 1.8× the dim error, and home to 14 of the 30 detections whose distance error exceeds 20 cm. Large degrades gracefully there (4.69 cm, no outliers), Small (9.84 cm) and MiDaS (13.73 cm) do not. Measured luminance rules out low contrast: nv frames have the *highest* pixel standard deviation (52.3) and dim the lowest (21.2), yet nv is worst. The nv frame is high-contrast because it is clipped (p95 luminance 208.8, p5 28.8): blown highlights, crushed shadows, and the mid-tones carrying object texture removed.

TABLE II

MAE OF Z IN CM / MEAN RELATIVE ERROR IN %, BY LIGHTING CONDITION (ROWS 1–4) AND BY OBJECT (ROWS 5–9). THE APPLE HAS $n = 15$ PER MODEL AND THE *nv* ROWS $n = 20$, BECAUSE THE APPLE IS NEVER DETECTED AT NIGHT. MARIGOLD IS OMITTED HERE AND DISCUSSED IN THE TEXT.

Condition	DA-V2-S	DA-V2-B	DA-V2-L	MiDaS
by lighting				
dim	4.47 / 6.1	4.66 / 6.3	**2.90 / 3.9**	5.42 / 8.0
white	4.45 / 6.1	4.73 / 6.5	3.42 / 4.5	12.32 / 17.1
warm	5.16 / 7.2	5.08 / 7.1	3.72 / 5.1	6.93 / 10.1
nv	9.84 / 13.9	7.33 / 10.3	4.69 / 6.6	13.73 / 18.3
by object				
bowl	**1.23 / 1.9**	1.73 / 2.3	1.67 / 2.2	7.13 / 9.0
mug	2.42 / 3.5	1.43 / 2.2	**1.21 / 1.8**	3.77 / 5.1
apple	**1.57 / 2.2**	2.95 / 3.9	2.37 / 3.1	4.63 / 6.7
bottle, short	**2.49 / 3.6**	6.17 / 8.4	3.73 / 4.8	20.23 / 29.0
bottle, tall	20.12 / 27.3	13.89 / 19.4	**8.86 / 12.4**	9.97 / 14.2

C. Object Profile: What Is Actually Solved

The object panel of Table II is the most useful view of the results. Broad, squat, opaque objects are effectively solved: bowl and mug sit at 1.2–2.4 cm and under 4 % for every Depth Anything size, comfortably usable for sizing, and the apple is similarly easy *when detected* (1.57 cm for Small). Thin objects are not: the tall bottle alone is 61 % of all absolute distance error (pooled over the Depth Anything family), the short bottle 17.7 % and the three compact objects the remaining 21 % of it.

This resolves an apparent paradox. Large wins overall, but on the four objects other than the tall bottle the ranking inverts: Small achieves 1.95 cm against Large's 2.23 cm, so Large's advantage is earned entirely on the tall bottle and at night. Since Small's weights are 99 MB against Large's 1.34 GB, a factor of 13, this is a deployment finding rather than a footnote: for near-range sizing of compact objects the smallest model suffices. MiDaS has an inverted object profile rather than a uniformly worse one: by far the worst on the short bottle (20.23 cm, 29 %) where Depth Anything is comfortable, yet the least biased on the tall bottle.

D. Width and Height Accuracy

The deliverable is dimensions, not distance, and height is roughly twice as accurate as width for every model (Table I): it is the long axis of these objects, so a fixed box error is proportionally smaller, and vertical edges against a table surface are clean. Width error exceeds distance error on both bottles, which is a box-tightness signature rather than a depth signature. The short bottle shows 11.1 % distance error against 18.6 % width error, the tall bottle 18.0 % against 25.4 %: about 7.5 points on each come from box geometry no depth model can fix, so roughly 40 % of the bottle width error is box and 60 % is depth. The apple shows no such excess (+0.3




Fig. 2. Mean absolute distance error against true object distance, all objects. Absolute error grows monotonically for every model but Marigold, while relative error grows far more slowly (Section V), the signature of a correctly scaled inverse-depth fit.




Fig. 3. Two frames with Depth Anything V2 Large: a mug at 0.50 m in white light (top) and the tall transparent bottle at 0.90 m under infrared (bottom). Columns are the RGB input, the relative-depth map (magma, brighter = closer) and the sized output. The mug is sized to within 1.1 cm; the bottle, which barely separates from the background in the depth map, is read 16.8 cm too far, and its width error propagates into a reported 9.1 cm width for a 6.2 cm object.

points), so its width error is entirely depth; height shows none anywhere.

E. Error Versus Distance

Figure 2 shows absolute error growing monotonically with distance for every model but Marigold. Relative error grows much more slowly, to about 5–7 % for Large, the signature of a correctly scaled inverse-depth fit: the geometry is sound and the limits are resolution, sampling and model capacity. The effective range is 0.50–0.80 m, where Large stays under 4.5 cm; nothing here supports sizing beyond 1 m without closer anchor spacing.

F. The Tall Bottle: A Signed Bias, Not Noise

The tall bottle's error is almost entirely one-directional. For Large its MAE of 8.86 cm and its mean signed bias of $+8.86$ cm coincide, so essentially 100 % of the error is overestimation, and the bias grows with distance, from $+5.34$ cm at 0.50 m to $+14.05$ cm at 0.90 m. Small is worse in the same direction, reading a 0.90 m bottle at roughly 1.32 m.

The cause is where depth is sampled, not the depth model; Figure 3 shows the case, where the bottle barely separates from the background in the depth map while the opaque mug pops out. A 24 cm-tall, 6.2 cm-wide object inside a slightly loose box picks up background columns on both sides; background is farther, so a median over the interior drifts outward. The tall bottle is also the loosest detection in the set, with confidence down to 0.67. A controlled sweep on the hardest folder confirms the diagnosis: on the night/tall-bottle images with the Small model and identical anchors, the box median gives 28.54 cm MAE (39.1 %), a box-centre sample 26.12 cm (35.5 %), and a bottom-centre sample 17.03 cm (23.0 %). Sampling the ground-contact point is a 40 % cut on the object carrying 61 % of the total error, at zero cost, and it is geometrically the right choice for a standing object because it is immune to loose horizontal box edges. (That sweep used the default YOLOv8 nano detector, so its absolute level is not comparable with Table I; the ordering is the result.)

G. Voided Rows and Evaluation Integrity

Of 500 (model, image) pairs, 25 are voided and all 25 are the apple at night: in every night frame of that folder YOLOv8m returns a cup, a knife, a bowl or a person, never an apple, so there is nothing to size and those rows are excluded rather than scored against a substituted object. This matters more than 5 % suggests. An earlier evaluation selected whichever detection sat most confidently between the anchors, with no class filter, and so scored calibration cups, knives, bowls and tables in 51 of 500 rows (10.2 %). Those rows averaged 39.5 cm error against 6.5 cm for correctly scored rows and supplied 60–90 % of each model's squared error; one row that sized a knife at 668 cm was 88 % of Marigold's total squared error. Correcting it roughly halved every model's RMSE and changed the object ranking. A pipeline with no expected-class gate produces plausible, entirely spurious metric errors, and a per-object breakdown is the cheapest defence.

VI. Limitations

Single camera, assumed intrinsics. The focal length comes from an assumed 65° horizontal field of view because the device provided no usable EXIF. Real intrinsics would shift every absolute number, not the relative comparisons.

One shot per condition. A single image per cell does not separate model variance from scene variance.

Marigold is not reproducible as configured. The diffusion sampler starts without a fixed generator or latents and ran at 10 steps with one ensemble member at 768 px rather than 50 steps and 10 members; its number moved from 17.46 to 8.55 cm between runs, so it should not be quoted as a Marigold result until the seed and schedule are fixed. It also predicts direct depth rather than disparity, so (2) does not give it its best case ((1) would). One fit for all models preserves comparability with the earlier run, not fairness for Marigold.

Night is confounded with clipping. Until an exposure bracket is captured, "depth degrades under infrared" is not separable from "this camera clipped the highlights under infrared". Tall-bottle folders also use 8×8 cm reference cups where all others use the 12×8 cm pair; both act only as the 0.40 m and 1.00 m constants, so the geometry is identical but the scenes are not.

VII. Conclusion and Future Work

A frozen detector, a frozen depth model and two clicked anchors recover object dimensions from one RGB frame with useful accuracy: Depth Anything V2 Large reaches 3.63 cm mean distance error and 9.3 % / 4.9 % width / height error across 100 images spanning four lighting conditions, with no gross failures. The aggregate alone is misleading: bowl and mug sizing is essentially solved at 1–2 %, while one tall transparent bottle contributes 61 % of the total error, and that error is a signed, distance-growing bias caused by sampling inside a loose box rather than by a depth failure. Night-time behaviour is limited by clipped highlights, and honest evaluation requires voiding rows where the subject is never detected.

Future work follows directly: make bottom-centre sampling the default and re-run the matrix; apply one scale correction fitted on the anchors to remove the consistent $+4$ to $+7\,\%$ over-estimation; tighten boxes on the two bottle classes; and re-run Marigold with a fixed seed and the affine fit, with bounded-exposure night captures to separate clipping from any inherent limitation.

References

[1] D. Eigen, C. Puhrsch, and R. Fergus, "Depth map prediction from a single image using a multi-scale deep network," in *Proc. NIPS*, 2014.

[2] R. Ranftl, K. Lasinger, D. Hafner, K. Schindler, and V. Koltun, "Towards robust monocular depth estimation: Mixing datasets for zero-shot cross-dataset transfer," *IEEE Trans. Pattern Anal. Mach. Intell.*, vol. 44, no. 3, pp. 1620–1634, 2022.

[3] R. Ranftl, A. Bochkovskiy, and V. Koltun, "Vision transformers for dense prediction," in *Proc. ICCV*, 2021.

[4] L. Yang, B. Kang, Z. Huang, X. Xu, J. Feng, and H. Zhao, "Depth anything: Unleashing the power of large-scale unlabeled data," in *Proc. CVPR*, 2024.

[5] L. Yang, B. Kang, Z. Huang, Z. Zhao, X. Xu, J. Feng, and H. Zhao, "Depth anything V2," in *Proc. NeurIPS*, 2024.

[6] B. Ke, A. Obukhov, S. Huang, N. Metzger, R. C. Daudt, and K. Schindler, "Repurposing diffusion-based image generators for monocular depth estimation," in *Proc. CVPR*, 2024.

[7] S. F. Bhat, R. Birkl, D. Wofk, P. Wonka, and M. Müller, "ZoeDepth: Zero-shot transfer by combining relative and metric depth," *arXiv:2302.12288*, 2023.

[8] W. Yin *et al.*, "Metric3D: Towards zero-shot metric 3D prediction from a single image," in *Proc. ICCV*, 2023.

[9] J. Redmon, S. Divvala, R. Girshick, and A. Farhadi, "You only look once: Unified, real-time object detection," in *Proc. CVPR*, 2016.

[10] G. Jocher, A. Chaurasia, and J. Qiu, "Ultralytics YOLOv8," 2023. [Online]. Available: https://github.com/ultralytics/ultralytics

[11] A. Geiger, P. Lenz, and R. Urtasun, "Are we ready for autonomous driving? The KITTI vision benchmark suite," in *Proc. CVPR*, 2012.

[12] N. Silberman, D. Hoiem, P. Kohli, and R. Fergus, "Indoor segmentation and support inference from RGBD images," in *Proc. ECCV*, 2012.

[13] R. Hartley and A. Zisserman, *Multiple View Geometry in Computer Vision*, 2nd ed. Cambridge, U.K.: Cambridge Univ. Press, 2004.