

Test Points

151- Series









SPECIFICATIONS					
Material Bead:	Boro Silicate Sintered Glass				
Tag:	Phosphor Bronze BS 384 Solder Tinned				
-RC:	RoHS Compliant Part				

Glass Bead										
Coeff	Density	Viscosity Poise °C			L	.og (Ω (CM)	Dielectric Properties		
Term. Expn.	g/cc	14.6	13	7.6	TR	DC Re	sistivity	@1MHz @20°C		
X 10°6 / °C		10	10	10	100	250°C	350°C	Const	Loss Ang	
4.94	2.27	475	515	719	365	10.1	8.2	5.7	0.003	

Coefficient of expansion is quoted for the range of -50°C ~ +300°C.

Mouser			Dimensi	Board	Mounting	Center	Colors			
Stock No.	Α	В	С	D	Е	F	Thickness	Hole ø	to Center	001013
151-101-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	White
151-102-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Yellow
151-103-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Black
151-104-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Brown
151-105-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Blue
151-106-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Pink
151-107-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Red
151-108-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.109	.063"	.052"	.125"	Green
151-201-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	White
151-202-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Yellow
151-203-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Black
151-204-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Brown
151-205-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Blue
151-206-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Pink
151-207-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Red
151-208-RC	.120~.130	.051~.059	.087~.097	.042~.052	.020	.109	.063"	.040"	.100"	Green
151-301-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	White
151-302-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Yellow
151-303-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Black
151-304-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Brown
151-305-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Blue
151-306-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Pink
151-307-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Red
151-308-RC	.112~.122	.080~.085	.113~.123	.059~.069	.032	.141	.094"	.052"	.125"	Green

Date Last Revised: 9/19/05

Available from Mouser Electronics 1-800-346-6873 www.mouser.com

KC-300780

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Kobiconn:

<u>151-202-RC</u> <u>151-308-RC</u> <u>151-102-RC</u> <u>151-101-RC</u> <u>151-205-RC</u> <u>151-206-RC</u> <u>151-103-RC</u> <u>151-201-RC</u> <u>151-105-RC</u> <u>151-208-RC</u> <u>151-204-RC</u> <u>151-203-RC</u> <u>151-104-RC</u> <u>151-106-RC</u> <u>151-301-RC</u> <u>151-303-RC</u> <u>151-305-RC</u> <u>151-306-RC</u>