

# ICCS 313: Assignment 1

Tawan Chaeyklinthes u5980963

Date : 14 Sep 2018

---

## Problem 1

---

(a)  $3n^3 + 75n^2 + 8\log_2 n \in \mathcal{O}(n^3)$

Proof:

$$\begin{aligned} 3n^3 + 75n^2 + 8\log_2 n &\leq 3n^3 + 75n^3 + 8^3 && ; \text{ for } n \geq 1 \\ &\leq 90n^3 \end{aligned}$$

Therefor this is true when  $c = 5$  and  $n_0 = 1$ .

(b)  $1 + 3 + 5 + \dots + (2n - 1) \in \mathcal{O}(n^2)$

Proof: We know that  $1 + 2 + 3 + \dots + (2n - 1) = \sum_{i=1}^n (2i - 1)$ . Which can be written as:

$$\begin{aligned} \sum_{i=1}^n 2i - \sum_{i=1}^n 1 &= 2\left(\frac{n(n+1)}{2}\right) - n \\ &= n^2 + n - 2n \end{aligned}$$

Thus,

$$n^2 \leq n^2 \quad ; \text{ for } n \geq 1$$

So, this is true when  $c = 1$  and  $n_0 = 1$ .

(c)  $1 + 2 + 4 + 8 + \dots + 2n^2 \in \mathcal{O}(2^n)$

Proof: Let  $S(n) = 1 + 2 + 4 + 8 + \dots + 2n^2$ ,

$$\begin{aligned} S(n) &= 2^0 + 2^1 + 2^2 + \dots + 2^n \\ 2S(n) &= 2^1 + 2^2 + \dots + 2^n + 2^{n+1} \\ &= S(n) - 1 + 2^{n+1} \\ S(n) &= 2^{n+1} - 1 \\ &= 2(2^n) - 1 \end{aligned}$$

Thus,

$$2(2^n) - 1 \leq 2(2^n) \quad ; \text{ for } n \geq 1$$

So, this is true when  $c = 2$  and  $n_0 = 1$ .

---

(d)  $1 + \frac{1}{2} + \frac{1}{4} + \dots + \frac{1}{2^n} \in \mathcal{O}(1)$

Proof: Let  $S(n) = 1 + \frac{1}{2} + \frac{1}{4} + \dots + \frac{1}{2^n}$

$$\begin{aligned} S(n) &= \frac{1}{2^0} + \frac{1}{2^1} + \frac{1}{2^2} + \dots + \frac{1}{2^n} \\ \frac{S(n)}{2} &= \frac{1}{2^1} + \frac{1}{2^2} + \frac{1}{2^3} + \dots + \frac{1}{2^n} + \frac{1}{2^{n+1}} \\ &= S(n) - 1 + \frac{1}{2^{n+1}} \\ -S(n)\left(\frac{1}{2}\right) &= \frac{1}{2^{n+1}} - 1 \\ S(n) &= 2 - \frac{1}{2^n} \end{aligned}$$

Therefor, we can see that:

$$2 - \frac{1}{2^n} \leq 2(1) \quad ; \text{ for } n \geq 1$$

So, this is true when  $c = 2$  and  $n_0 = 1$ .

---

## Problem 2

---

(a) We need to show that all the elements in A remains in A after the loop.

(b) Loop-invariant: At the start of each iteration, in the sub-array  $A[j..n]$ ,  $A[j]$  is the smallest.

Initialized: At the start,  $j = n$  so the sub-array is  $A[n]$ . Since  $A[n]$  is the only element, it is the smallest.

Maintenance: Let  $k =$  iteration number. Suppose that  $A[j_k] < A[j - 1_k]$ , the value of  $A[j_k]$  and  $A[j - 1_k]$  will then be swapped. The value of  $A[j - 1_k]$  is now the smallest since  $A[j_k]$  was originally the smallest in  $A[j_k..n]$ . Therefore, in the next iteration, value of  $A[j_{k+1}]$  will be the smallest in  $A[j_{k+1}..n]$ . If  $A[j_k] > A[j - 1_k]$ , it means that  $A[j - 1_k]$  is now the smallest in  $A[j - 1_k..n]$ . There will be no swapping so in the next iteration,  $A[j_{k+1}]$  will be the smallest in  $A[j_{k+1}..n]$ . Thus, the invariant is maintained.

Termination: The for-loop will terminate at  $j = i$ . From the loop-invariant, this will give us a sub-array  $A[i..n]$  where  $A[i]$  is the smallest.

(c) Loop-invariant: At the start of each iteration, the sub-array  $A[1..i]$  is sorted

Initialized: At the start  $i = 1$ , the sub-array  $A[1]$  is already sorted.

Maintenance: Let  $i = k$  where  $k$  is an iteration of the for-loop. Using invariant from part (b), we know that  $A[k]$  is the smallest in  $A[k..n]$ . And with invariant from part (c), we know that  $A[1..k - 1]$  is already sorted. We also know that as the value of  $i$  increases, the length of final sub-array in inner-loop decreases. Therefore, we are sure that  $A[k - 1]$  must be the smallest value in  $A[k - 1, k, ..n]$  the iteration before. Thus, at the end of the iteration, we would have  $A[1..k]$  which is sorted.

---

Termination: The loop will terminate when  $i = n$ . With our invariant, this will give us a sub-array  $A[1...n]$  that is sorted. By observation, the sub-array is our array. Thus, the algorithm gives us a sorted array upon termination.

(d) The worst-case is when the array is sorted in descending order. The running-time would be :

$$\begin{aligned} T(n) &= \sum_{i=2}^{n-1} i \\ &\approx \frac{n(n+1)}{2} \\ &= \mathcal{O}(n^2) \end{aligned}$$

Which is the same as the worst-case running time for insertion sort.

---

### Problem 3

---

$$S(n) = 1^c + 2^c + 3^c + \dots + n^c$$

(a)  $S(n)$  is  $\mathcal{O}(n^c + 1)$

Proof:

$$1^c + 2^c + 3^c + \dots + n^c \leq n(n^c) \quad ; \text{ for } n \geq 1$$

So, this is true when constant =  $n$  and  $n_0 = 1$ .

(b)

Proof:

$$\begin{aligned} 1^c + 2^c + 3^c + \dots + n^c &\geq \left(\frac{n}{2}\right)^c + \dots + n^c && ; \text{ for } n \geq 1 \\ &\geq \left(\frac{n}{2}\right)\left(\frac{n}{2}\right)^c \\ &\geq \left(\frac{n}{2}\right)^{c+1} \\ &\geq \left(\frac{1}{2}\right)^{c+1} n^{c+1} \end{aligned}$$

So, this is true when constant =  $\left(\frac{1}{2}\right)^{c+1}$  and  $n \geq 1$ .

---

### Problem 4

---

(a) Observations:  $2 = 2$  bits,  $4 = 3$  bits,  $8 = 4$  bits,  $2^n = n + 1$  bits.

So the big-O is:  $\mathcal{O}(\log_2 n + 1) = \mathcal{O}(\log_2 n)$ .

(b) The number  $n$  is being divided by 2 for each loop. So the numbers of times that  $n$  has to be divided by 2 before reaching 1 is  $\log_2 n$  and the total iteration is  $\log_2 n + 1$ . Thus the big-O is  $\mathcal{O}(\log_2 n)$ .

---

(c) Each iteration that the code makes, the input size is reduced by half. So we can write the running time as follow:

$$\begin{aligned}
T(n) &= n^3 + \left(\frac{n}{2}\right)^3 + \left(\frac{n}{2^2}\right)^3 + \left(\frac{n}{2^3}\right)^3 + \dots + 1 \\
&= n^3 + \left(\frac{n^3}{8}\right) + \left(\frac{n^3}{8^2}\right) + \left(\frac{n^3}{8^3}\right) + \dots + 1 \\
\frac{T(n)}{8} &= \left(\frac{n^3}{8}\right) + \left(\frac{n^3}{8^2}\right) + \left(\frac{n^3}{8^3}\right) + \left(\frac{n^3}{8^4}\right) + \dots + 1 + \frac{1}{8} \\
&= T(n) - n^3 + \frac{1}{8} \\
\frac{7}{8}T(n) &= n^3 - \frac{1}{8} \\
T(n) &= \frac{8n^3}{7} - 7 \\
&= \mathcal{O}(n^3)
\end{aligned}$$

So the running time is  $\mathcal{O}(n^3)$ .

---

### Problem 5

---

(a) Function `foo()` takes in a sorted list, integers  $m$  and  $val$ . The function first search for an interval of size  $m + 1$  where the value  $val$  could be inside. If such interval is not found, function returns -1. Else, it would then search the interval one by one for the value  $val$ . If the value is found, function will return the index of the value, otherwise ,it returns -1.

(b) Lemma 1 : The first while-loop will terminate with the right interval (if exist) for  $m \geq 1$ .

Proof : When  $m \geq 1$ , first while-loop will terminate on 2 conditions. Firstly, the loop will break if an interval where  $alist[left] \leq val$  and  $alist[right] \geq val$  since there is a statement checking for this condition. Hence, this break will give us the correct interval and will terminate. If such interval doesn't exist, the value of  $left$  will keep increasing until  $left \geq length$  or  $alist[left] > val$ . This will then return -1 on line 10 which indicates that  $val$  doesn't exist in the array.

Lemma 2 : The second while-loop will return the index of  $val$  or -1.

Proof : In second while-loop, it will iterate over the range that we got from the first while-loop one element at a time. If the element is equal to  $val$  it will return that index, thus, returning the index of  $val$ . However, if  $val$  is not in the array, i will keep increasing till  $i > r$  or  $alist[i] > val$  which will terminate the while-loop and returns -1.

With this 2 lemmas, it can be seen that this code will return the right answer.

(c) The worst-case is when  $m = 1$  and the value to find is more than last index. This will give us a running time of:

$$T(n) = n = \mathcal{O}(n)$$

---

(d) The maximum number of comparison made in first-loop is  $\frac{n}{m}$  and the second loop is  $m$ . So to find the minimum we take the derivative of function:  $\frac{n}{m} + m$ .

$$\frac{d}{dm}\left(\frac{n}{m} + m\right) = \frac{-n}{m^2} + 1$$

To find the minimum, we let :  $\frac{d}{dm}\left(\frac{n}{m} + m\right) = 0$ :

$$\begin{aligned}\frac{-n}{m^2} + 1 &= 0 \\ \frac{n}{m^2} &= 1 \\ n &= m^2 \\ m &= \sqrt{n}\end{aligned}$$

Therefore, the  $m = \sqrt{n}$  for the minimum comparison.

---

### Problem 6

---

(a)  $\mathcal{O}(n^3)$

(b)  $\mathcal{O}(n \log n)$

(c)  $\mathcal{O}(3^n)$

(d)  $\mathcal{O}(n^3)$

(e)  $\mathcal{O}(n^4)$