

TECHNOLOGY
POWERS A LOW-CARBON
BETTER LIFE



科技 成就低碳美好生活

SPECIFICATION



Type 2 AC Charger

Product features

- 1. Personalized charging experience: users can set charging parameters according to their own needs via Bluetooth, such as charging time and notifications.
- 2. IP65, hassle-free use in all weather conditions.
- 3. Support remote upgrade and bug fixes.
- 4. The LCD screen enables users to operate it easily and friendly.



		Unit	ACS07-201W/202W	ACS11-201W/202W/203W	ACS22-201W/202W/203W	
AC Input	Input Voltage	V	230	380	380	
	Rated Current	A	32A	16A	32A	
	Frequency	Hz	50/60	50/60	50/60	
	Input Wiring	-	1-Phase, L/N/PE	3-Phase, L1/L2/L3/N/PE	3-Phase, L1/L2/L3/N/PE	
AC Output	Output Voltage	V	230	380	380	
	Output Current	A	32A	16A	32A	
	Rated Power	kW	7	11	22	
Configuration	Indicator	-	Green/Yellow/Red			
	RFID Reader	-	Yes			
	LCD Display	-	Optional			
	Electricity Metering	-	No	Optional	Optional	
	On-board Metering	-	Yes	Optional	Optional	
	Emergency Stop	-	No			
Communication	WIFI	-	Yes			
	OCPP	-	OCPP 1.6			
Protection	Input Protection	-	Surge protection			
	Output Protection	-	Ground protection, Over-temperature protection, Leakage protection, CP fault detection, Output current limiting protection			
	IP Rating	-	IP65			
Compliance	EMC	-	IEC 61851-21-2			
	Safety	-	IEC 61851-1			
	Certification	-	CE			
Mechanical	Package Dimension (W×D×H)	mm	520×350×355			
	Net Weight	kg	4	4.5	4.5	
	Gross Weight	kg	5	6.6	6.6	
	Charging Cable Length	m	5			
Environmental	Work Temperature	℃	-25 ~ +55	Relative Humidity	%	5 ~ 95
	Storage Temperature	℃	-40 ~ +85 ℃	Altitude	m	≤2000
RRP		-				

