WinFlex Web Single Sign-On

(Zinnia XML Format)
Version: 1.8

The goal of this document is to specify and explore the basic operations that are required to facilitate a vendor application requesting access to the WinFlex Web user interface and returning to the vendor user interface.

For WinFlex, this interface can be used to provide a method of creating users on the system as well as seamlessly logging them in and passing case data on future requests.

Calling WinFlex Web

For this version of the service, we will use the HTTPS POST method

- The protocol used. "https://" as a secure connection is required.
- The web page URL (ie; the web server name, domain and any other location). This can take the form of "www.winflexweb.com/wfw_sso_login.aspx".
- The parameter name is defined as "llXML=<xml-message>" (LLXML).
- Use an http POST request so the xml-message is not shown on the URL and a document of any length may be passed.

Based on the above information, we can create a complete form request using the following protocol, format and parameters:

Example:
"https://www.winflexweb.com/wfw_sso_login.aspx" with the parameter llXML=<xml-message>*

* This URL is subject to change. Contact Zinnia for the actual URL when implementing Single Sign-On.

The <xml-message> refers to the complete xml document that has been URL-encoded to allow it to be passed as a parameter value in an http post request. The primary nodes of <xml-message> are defined as follows:

- Global LL node
- Error node
- WinFlex node

The namespace used for the schema is "urn:lifelink-schema".

The WinFlex XML Document

LL node:
The LL XML node contains multiple objects that are used to fulfill a request. The full LL object is included in both the request and the response. Each request to the llXML web services requires a single LL object. The object includes:

- *LoginType* – The LoginType attribute tells the receiving application how to process the request for access. Enumerated value:
  - LL_NONE – Not used
  - WF_CARRIER – All carrier access should be performed under this login type
  - WF_AGENCY – All agency access should be performed under this login type
  - WF_3RDPARTY – Used for 3rd Party vendor access to WinFlex Web

- *UserName* – Each individual WinFlex user has a unique user name. The user name is not the actual WinFlex Web user name, but a unique ID representing the user in the calling system. During the course of the single sign-on process, the ID will be linked with a WinFlex Web account, either previously existing, or newly created.(required)

- *WFCompanyCode* – When calling WinFlex, this field is required to identify the company sending the request. Zinnia will assign this value.

- *WFCompanyPassword* – When calling WinFlex, this field is required in conjunction with the WFCompanyCode in order to validate the calling vendor. Assigned by Zinnia.

- *InterfaceType* – There are two main types of interfaces – with or without a user interface. The types of "GUI" and "NoGUI" will indicate whether the user will navigate through the Zinnia user interface or not. For the initial version of the LL XML Interface, the GUI version will take the user to Step 1 of the tool specified. In subsequent versions, the client software can specify a starting location for each tool. (required)

  With the non-GUI version, no user interface is displayed and the resulting output is returned in an xml format. If pdf or emf output is returned, the related xml node will indicate where to find the resulting output files (as urls).

- *OutputType* – (XML, PDF, XMLPDF, EMF, URL, XML_RAW) Various output types may be supported by the LLP XML interface in the future. (required)

  - NoGUI
    - XML - Returns all xml. No PDF link is included
    - PDF - Returns all xml. PDF link is included in specific product node
    - XMLPDF - Returns all xml information as well as a link to the PDF
    - EMF - Not supported at this time
    - URL - Not supported at this time
    - XML_RAW - Same as XML

  - GUI
    - XML - Posts XML to ReturnButton/PostAddress if exists.
    - PDF - Displays PDF if ReturnButton/ViewFirst is 1. Otherwise link is created in XML returned to ReturnButton/PostAddress if exists.
    - XMLPDF - Combination of XML and PDF
    - EMF - Not supported at this time
    - URL - ll.aspx returns the URL to be redirected to or empty string if error occurred
    - XML_RAW - Displays the full processed XML

- *Tool* –There are currently five Zinnia tools: VitalSigns, VitalTerm, VitalLTC, VitalUL, and WinFlex. Depending on the type of output requested, the vendor software may include up to one tool section for each LL tool. For *GUI* interface type, the user interface will start at the first tool specified. The remaining tools will be initialized with the specified information, but the user will be required to navigate to it. For the *PDF* output type, each tool will be processed in the order they are received. (required)

  - *Name –The tool name field should be "*WinFlex". (required)

Note: *For the first version of the xml interface, the StartLocation will be ignored. Users will automatically be routed to the first step of the tool. The information in the input xml may or may not populate more information than is shown on the first step of each tool.*

Example:

```
<LifeLink xmlns="urn:lifelink-schema">
      <LL LoginType="LL_NONE">
            <UserName>bobtest123</UserName>
            <LOLAKey>generatedkey</LOLAKey>
            <InterfaceType>GUI</InterfaceType>
            <OutputType>XML</OutputType>
            <Tool>
                  <Name>WinFlex</Name>
            </Tool>
            <Tool>
                  <Name>VS</Name>
                  <StartLocation>1</StartLocation>
            </Tool>
      </LL>
</LifeLink>
```

Client node:

The Client XML node contains the details about the insurance product client. The node includes:

- *Applicant – The primary applicant personal information*
  - *FirstName* – The firstname of the client.
  - *MiddleName* – The client's middle name or initial
  - *LastName* – The client's surname
  - *Birthdate* – mm/dd/yyyy formatted client's birthdate
  - *Age* – Current age of the client, used when the birthdate is not specified. May be interpreted as "AgeLast" for some tools. (required)
  - *AgeNearest* – Nearest age that may be used alternatively if a birthdate is not specified and a particular insurance product is sold based on the client's nearest age. (required)
  - *Sex* – Male or Female (required)
  - *MaritalStatus* – Single or Married
- *Spouse* – The personal information of the primary applicant's spouse
  - *FirstName* – The firstname of the client
  - *MiddleName* – The client's middle name or initial
  - *LastName* – The client's surname
  - *Birthdate* - mm/dd/yyyy formatted client's spouse's birthdate
  - *Age* – Current age of the client, used when the birthdate is not specified. May be interpreted as "AgeLast" for some tools.
  - *AgeNearest* – Nearest age that may be used alternatively if a birthdate is not specified and a particular insurance product is sold based on the client's nearest age.
  - *Sex* - Male or Female
- *StateOfIssue* – Two letter state abbreviation where the insurance policy is to be issued. (required)

Example:

```
<LifeLink xmlns="urn:lifelink-schema">
      <Client>
            <Applicant>
                  <FirstName>Haley</FirstName>
                  <MiddleInitial>J</MiddleInitial>
                  <LastName>Osment</LastName>
                  <Age>14</Age>
                  <AgeNearest>14</AgeNearest>
```

```
                <Sex>Male</Sex>
                <MaritalStatus>Single</MaritalStatus>
            </Applicant>
            <State>CA</State>
        </Client>
</LifeLink>
```

Error node:

The Error XML node allows Zinnia to report back to the vendor application with errors or warnings that may have occurred during the processing of a request. These errors refer to general errors about the Zinnia interface request. Errors that are specifically related to any particular Zinnia tool are included with the xml output for that tool.

- *Error* – Details about a single error. Multiple errors may be included.
  - *Type* – Defines the severity of the error. Possible values are Error, Warning, and Message, with Error defining a fatal error with no recovery and Message just providing information.
  - *Number* – Error numbers may be assigned and documented that help identify the errors. When reporting back to Zinnia, the error number may be a useful tool in identifying a problem.
  - *Description* – Text description of the error. The client application could display this text to the user or log in the application.
  - *Source* – LLP source component that raised the error.
  - *Method* – LLP method of the source that raised the error.

Example:

```
<LifeLink xmlns="urn:lifelink-schema">
        <Error>
            <Type>Error</Type>
            <Number>234</Number>
            <Description>
                No valid request information provided.
            </Description>
            <Source>clsLLInterface</Source>
            <Method>Initialize</Method>
        </Error>
</LifeLink>
```

WinFlex node:

The WinFlex XML node allows the vendor to create, login, and pass case data to the WinFlex Web System. The WinFlex node includes:

- *ReturnURL – (optional)* – Describes the URL to which WinFlex will return when processing is complete; A parameter of "xmlife" will be POSTED to this URL upon completion. See the XMLife implementation guide for more information.
- *XMLifeDoc* – (optional) – The XMLife payload to be used to create an illustration within WinFlex Web
- *Captive - (optional)* – Marks the user as a captive user within WinFlex Web. The user will be unable to request access to additional carriers/agencies. Values: True | False
- *Policy* – (optional) – Used to send additional information to WinFlex Web to be preloaded into the WinFlex Web applet
  - *Company* – (optional) - Describes the default company to be loaded into WinFlex Web.
    - *Code* – The WinFlex company code representing the company to preload.

        - *Product* – Describes the default product to be loaded into WinFlex Web.
            - *Code* – The WinFlex product code representing the product to preload.
            - *Concept* – Describes the default Concept to be loaded
                - *Code* – The WinFlex concept code representing the concept to preload.
    - *Insured* – (optional) – Information about a client to be pre-loaded into WinFlex Web
        - *FirstName*
        - *LastName*
        - *Age*
        - *Sex*
        - *BirthDate*
        - *State*
    - *Insured2* – (optional) – Information about an optional second insured to be pre-loaded in WinFlex
        - *FirstName*
        - *LastName*
        - *Age*
        - *Sex*
        - *BirthDate*
        - *State*
    - *Agent* – (optional) – Agent information to be pre-loaded into WinFlex Web
        - *FirstName*
        - *LastName*
        - *Company*
        - *Address1*
        - *Address2*
        - *Address3*
        - *City*
        - *State*
        - *Zip*
        - *Phone*
        - *Fax*
        - *Email*
        - *License*
    - *Premium* – (optional) – An optional premium to be pre-loaded into WinFlex Web
    - *FaceAmount* – (optional) – An optional Death Benefit to be pre-loaded into WinFlex Web
- *Profile* – (optional) – Profile information used to pre-populate the registration page upon new user registration. This may be sent every time, but will be ignored if the user is already registered. Available elements are:
    - FirstName
    - LastName
    - Initial
    - Credentials
    - CompanyName
    - Address1
    - Address2
    - City
    - State
    - Zip
    - Phone
    - Fax
    - Email

- *ClientId* – (optional) - DEPRECATED – The unique Client Id associated with an exported client. This can be used to load an existing client into the client editor interface that may have been exported to another system such as a CMS. All other preload data will be ignored when a ClientId is passed (i.e. Policy or Agent information).
- *ClientExportGUID* – (optional) – A unique ID representing a one or more exported clients that will be preloaded into the client editor. Similar to the ClientId, the associated clients will have been exported to another system such as a CMS. All other preload data will be ignored when a ClientId is passed (i.e. Policy or Agent information). The Profile node may still be used, and is required when auto-creating users.

Note regarding ClientId and ClientExportGUID. ClientId has been deprecated. After 11/01/2017, new implementations should use ClientExportGUID.

Example:

```
<LifeLink xmlns="urn:lifelink-schema">
      <WinFlex>
            <ReturnURL>http://www.someplace.com</ReturnURL>
            <XMLifeDoc>
                  <TXLife>
                  ::
                  ::
                  ::
                  </TXLife>
            </XMLifeDoc>
            <Captive>False</Captive>
            <Policy>
                  <Company>
                        <Code>DEMO</Code>
                        <Product>
                              <Code>DEMOUL</Code>
                        </Product>
                  </Company>
                  <Insured>
                        <FirstName>Mr</FirstName>
                        <LastName>Client</LastName>
                        <Age>45</Age>
                        <Sex>M</Sex>
                        <State>CA</State>
                  </Insured>
                  <Agent>
                        <FirstName>Sam</FirstName>
                        <LastName>Agent</LastName>
                        <Company>Some Company</Company>
                        <Address1>Some Street</Address1>
                        <City>Some City</City>
                        <State>UT</State>
                        <Zip>55555</Zip>
                        <Phone>555-555-5555</Phone>
                        <Fax>555-555-5556</Fax>
                        <Email>sam@somecompany.com</Email>
                        <License>1234567890</License>
                  </Agent>
                  <Premium>15000.00</Premium>
            </Policy>
            <Profile>
```

```
                <FirstName>Some</FirstName>
                <LastName>Person</LastName>
                <CompanyName>A Company</CompanyName>
                <Address1>100 Anywhere Ln</Address1>
                <City>Some City</City>
                <State>CA</State>
                <Zip>55555</Zip>
                <Phone>555-555-5555</Phone>
                <Email>someperson@acompany.com</Email>
            </Profile>
        </WinFlex>
</LifeLink>
```

Linking to WinFlex Web

The current link to WinFlex Web supports only the GUI Interface Type. Future versions will support the NOGUI Interface Type as well as various data return types (XML, PDF, etc.).

When linking to WinFlex Web, the following fields are required:

- LL node
  - LoginType (attribute)
  - UserName – The UserName node is not actually a "username" in the WinFlex Web schema, but a unique ID or name identifying the user in the **calling vendor's system.** This ID is used by WinFlex to link to the user's account in subsequent calls to WinFlex Web.
  - WFCompanyCode – This item is assigned by Zinnia and is unique to the carrier / agency.
  - WFCompanyPassword – This item is assigned by Zinnia. This will be a 20 digit alpha-numeric key that will be used in conjunction with the WFCompanyCode to authenticate that the request is coming from a "trusted source".
  - InterfaceType
  - Tool
    - Name

The WinFlex node is optional and is used for sending additional data to WinFlex Web upon startup. The **Policy** node is used to pre-poplulate values within the WinFlex Web applet. The **Profile** node may be used to pass profile information to be pre-populated upon registration. Both nodes are optional, but may be passed with every call. The Profile node is ignored if the user has already registered for WinFlex Web.

An example Zinnia XML document for use with WinFlex Web is shown below:

```
<LifeLink xmlns="urn:lifelink-schema">
      <LL LoginType="WF_AGENCY">
            <UserName>testuser</UserName>
            <WFCompanyCode>DEMO</WFCompanyCode>
            <WFCompanyPassword>aij4l2n5wm0o5dzu71gp</WFCompanyPassword>
            <InterfaceType>GUI</InterfaceType>
            <OutputType>URL</OutputType>
            <Tool>
                  <Name>WinFlex</Name>
            </Tool>
      </LL>
      <WinFlex>
            <Captive>False</Captive>
            <Policy>
                  <Company>
```

```
                        <Code>DEMO</Code>
                        <Product>
                              <Code>DEMOPROD</Code>
                              <Concept>
                                    <Code>LEDGER</Code>
                              </Concept>
                        </Product>
                  </Company>
                  <Insured>
                        <FirstName>Some</FirstName>
                        <LastName>Person</LastName>
                        <Age>29</Age>
                        <Sex>M</Sex>
                        <BirthDate>1974-05-15</BirthDate>
                  </Insured>
                  <!-- Insured 2 used for Survivorship products
                  <Insured2>
                        <FirstName/>
                        <LastName/>
                        <Age/>
                        <Sex/>
                        <BirthDate/>
                  </Insured2>
                  -->
                  <Agent>
                        <FirstName>Demo</FirstName>
                        <LastName>Agent</LastName>
                        <Company>Some Company</Company>
                        <Address1>Anywhere Street</Address1>
                        <Address2/>
                        <Address3/>
                        <Phone>555-555-5555</Phone>
                        <Fax>555-555-5556</Fax>
                        <Email>dagent@somecompany.com</Email>
                        <License>1234567890</License>
                  </Agent>
                  <Premium>5000.00</Premium>
                  <FaceAmount>0.0</FaceAmount>
            </Policy>
            <Profile>
                  <FirstName>Some</FirstName>
                  <LastName>Person</LastName>
                  <CompanyName>A Company</CompanyName>
                  <Address1>100 Anywhere Ln</Address1>
                  <City>Some City</City>
                  <State>CA</State>
                  <Zip>55555</Zip>
                  <Phone>555-555-5555</Phone>
                  <Email>someperson@acompany.com</Email>
            </Profile>
      </WinFlex>
</LifeLink>
```

The example shown above will log the user into the system (if he/she exists) and load WinFlex Web with the information provided in the WinFlex node. If the user does not exist, he/she will be prompted to complete the WinFlex Web registration process. The data in the Profile node will be used to pre-fill the

registration form. Upon receiving confirmation of registration and carrier/agency approval, subsequent attempts to log into WinFlex Web will be seamless from the vendor's application/website.

XMLife Requests

When making a request to WinFlex Web with the XMLifeDoc element populated, WinFlex will expect a valid XMLife Illustration request document to be populated into this field. If an XMLife result is expected, the calling system must pass a valid URL through the ReturnURL element located in the WinFlex node. Upon completion of processing, an XMLifeResult document will be generated and POSTED to the URL provided.

Preloading Client Information

The WinFlex Web SSO allows for the preloading of previously exported clients back into the UI. By passing a ClientExportGUID, the user will be sent directly to the client editor interface screen with the represented clients loaded. As previously noted, all other SSO nodes that aid in the preloading of information, such as the Policy and Agent nodes, are ignored. The profile node may still be used to further identify the user, or update user information. A sample SSO request that uses this method follows:

```
<LifeLink xmlns="urn:lifelink-schema">
      <LL LoginType="WF_AGENCY">
            <UserName>testuser</UserName>
            <WFCompanyCode>DEMO</WFCompanyCode>
            <WFCompanyPassword>TEST</WFCompanyPassword>
            <InterfaceType>GUI</InterfaceType>
            <OutputType>URL</OutputType>
            <Tool>
                  <Name>WinFlex</Name>
            </Tool>
      </LL>
      <WinFlex>
            <Profile>
                  <FirstName>Some</FirstName>
                  <LastName>Person</LastName>
                  <CompanyName>A Company</CompanyName>
                  <Address1>100 Anywhere Ln</Address1>
                  <City>Some City</City>
                  <State>CA</State>
                  <Zip>55555</Zip>
                  <Phone>555-555-5555</Phone>
                  <Email>someperson@acompany.com</Email>
            </Profile>
            <ClientExportGUID>F9168C5E-CEB2-4faa-B6BF-329BF39FA1E4
            </ClientExportGUID>
      </WinFlex>
</LifeLink>
```