

A Modal Approach to the Space Time Dynamics of Cognitive Biomarkers

T. Griffith

Defense

May 20, 2021

Outline

1. Introduction & Motivation
2. A Dynamic Systems View of Brain Waves
3. System Identification of Brain Wave Modes Using EEG
4. Modal Analysis of Brain Wave Dynamics
5. Adaptive Unknown Input Estimators
6. Reconstructing the Brain Wave Unknown Input
7. On the Observability of Matrix-Vector Dynamical Systems
8. Conclusions

Introduction & Motivation




Fig 1. A Wholistic View of Brain Waves

Recent modeling work, however, using large-scale dynamical models on the human connectome, suggests that cortical flow patterns are multistable and exhibit phase-transitions. To study such phenomena, a dynamic analysis in which no assumptions about stationarity are made, is required.

Hindriks, Rikkert, et al. "Latency analysis of resting-state BOLD-fMRI reveals traveling waves in visual cortex linking task-positive and task-negative networks." *Neuroimage* 200 (2019): 259-274.

A cannonical approach:

True brain wave plant

$$\begin{cases} \dot{x} = Ax + Bu + v_x \\ y = Cx \end{cases}$$

Modal brain wave plant

$$\begin{cases} \dot{\eta} = \Lambda\eta + V^{-1}Bu + V^{-1}v_x \\ y = CV\eta \end{cases}$$

where A , B , C , v_x , x , and u are **all unknown**.

This level of uncertainty is an unsolved problem

$$\text{Identify the plant: } \begin{cases} \dot{x}_m = A_m x_m \\ y_m = C x_m \end{cases},$$

Adaptive Unknown Input Brain Wave Estimator:

$$\begin{cases} \dot{\hat{x}} = (A_m + BL(t)C)\hat{x} + B\hat{u} + K_x e_y; \\ \hat{y} = C\hat{x}. \end{cases}$$


System Identification of Brain Wave Modes Using EEG

Identifying linear patterns

Identify the plant: $\begin{cases} \dot{x}_m = A_m x \\ y_m = C x_m \end{cases}$

$$O = \begin{bmatrix} C \\ CA \\ CA^2 \\ \vdots \\ CA^{s-1} \end{bmatrix} X_0$$

$$\hat{\Gamma} = US^{1/2} \quad \hat{X}_0 = S^{1/2}V^*$$




System Identification of Brain Wave Modes Using EEG

Identifying linear patterns

Identify the plant: $\begin{cases} \dot{x}_m = A_m x \\ y_m = C x_m \end{cases}$

$$O = \begin{bmatrix} C \\ CA \\ CA^2 \\ \vdots \\ CA^{s-1} \end{bmatrix} X_0$$

$$\hat{\Gamma} = US^{1/2} \quad \hat{X}_0 = S^{1/2}V^*$$



Analysis of Linear Brain Wave Modes










Table 1: Common OMA Brain Modes				
	Frequency	Damping [%]	Complexity [%]	Shape Correl.
Alpha Mode 1	4.34±0.03	8.20±1.20	11.47±17.59	0.97±0.016
Beta Mode 2	21.83±0.22	1.98±2.63	32.29±35.67	0.96±0.018
Gamma Mode 3	40.39±0.26	11.87±7.49	12.42±16.88	0.99±0.010
Gamma Mode 4	44.19±0.24	2.52±1.39	2.93±5.69	0.99±0.012





Unknown Input Estimators



aUIO Performance



Classification



Quantum Observability

$$\begin{aligned}
 \dot{\rho}(t) &= \sum_{k=1}^N p_k \dot{P}_k(t) \\
 &= -i[H\rho(t) - \rho(t)H] \\
 &= (-i)[H, \rho] \equiv (-i)L\rho \\
 y_i(t) &= \text{tr}(C_i \rho)
 \end{aligned}$$

$$y^{(k)}(0) = (C, A^k \rho_0)_{\text{tr}} = \underbrace{((A^*)^k C, \rho_0)_{\text{tr}}}_{\Theta_k}; \quad k = 0, 1, \dots, N^2 - 1$$

