

# Lab 6

## FIT Staff

### 6th week

#### 1 Topics

- Functions

#### 2 Reading Materials

In Russian

- <https://informatics.msk.ru/mod/book/view.php?id=563>
- <https://informatics.msk.ru/mod/book/view.php?id=563&chapterid=302>
- <https://informatics.msk.ru/mod/book/view.php?id=563&chapterid=304>

In English

- <http://www.cplusplus.com/doc/tutorial/functions/>

#### 3 Problem Set

## Problem A. 74446. A+B

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

You are given two integers  $a$  and  $b$ . Write function which will return single integer, sum of  $a$ ,  $b$ .

### Input

The only line of the input contains integers  $a$  and  $b$  ( $-100 \leq a, b \leq 100$ ).

### Output

Sum of  $a$  and  $b$ .

### Example

standard input	standard output
7 8	15

## Problem B. 74862. Difference between two arrays

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

You have two arrays  $a$  and  $b$ . Create a new array  $d$  which elements will  $d_i = |a_i - b_i|$ .

### Input

In first line given single integer  $n$ , ( $1 \leq n \leq 10000$ ) — size of array.

In second line given elements of  $a$ , ( $1 \leq a_i \leq 1000000$ ).

In third line given elements of  $b$ , ( $1 \leq b_i \leq 1000000$ ).

### Output

All elements of  $d$ .

### Examples

standard input	standard output
3 6 2 1 10 4 2	4 2 1
2 2 1 5 2	3 1
3 10 5 8 7 5 8	3 0 0
4 4 3 10 2 6 10 10 5	2 7 0 3
2 2 3 10 6	8 3

## Problem C. 74865. How many elements are same?

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

Given two array  $a$  and  $b$ . Find the count of equal elements of two arrays.

### Input

In first line given single integer  $n$ , ( $1 \leq n \leq 10000$ ) — size of array.

In second line given  $n$  elements of  $a$ , ( $1 \leq a_i \leq 1000000$ ).

In third line given  $n$  elements of  $b$ , ( $1 \leq b_i \leq 1000000$ ).

### Output

Single integer numbers of equal elements.

### Examples

standard input	standard output
6 4 3 1 2 4 1 3 1 1 5 4 4	5
1 3 5	0
2 1 4 2 4	1
5 2 2 2 4 2 5 2 5 3 4	2
3 4 1 1 1 3 5	1

### Note

In first sample number 4 in first array occurs 2 times 1 also 2 times and 3 one time. In sum will be 5.

## Problem D. 74449. Books

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

Each book in the library has own ID number. Alikhan wants to buy a book which has an ID number  $x$ . He wants to know has the library got this book? Let's help him.

### Input

In first line given single integer  $n$ , ( $1 \leq n \leq 10000$ ) — number of books in the library.

In second line given ID numbers of books  $a$ , ( $1 \leq a_i \leq 1000000$ ) .

In third line given elements of  $x$ , ( $1 \leq x \leq 1000000$ ).

### Output

If the library has this book print "Yes"otherwise "No".

### Examples

standard input	standard output
2 4 5 4	Yes
5 4 2 5 6 5 6	Yes
3 7 2 5 7	Yes
9 9 10 1 8 1 3 2 2 10 5	No
2 4 9 7	No

## Problem E. Hypotenuse

Input file:            `standard input`  
Output file:          `standard output`  
Time limit:           1 second  
Memory limit:        256 megabytes

Given two integers  $a$  and  $b$  – sides of triangle. You need to write a function that calculates the hypotenuse of the triangle.

### Input

Input contains two integers  $a$  and  $b$  ( $1 \leq a, b \leq 10^5$ ).

### Output

Output the hypotenuse of the triangle.

### Examples

standard input	standard output
3 4	5
4 6	7.211
3 7	7.616
1 3	3.162
7 8	10.63

### Note

Use `setprecision(4)` to output the answer. In order to use this function, you need to include `iomanip` library.

## Problem F. Valid string

Input file:            `standard input`  
Output file:         `standard output`  
Time limit:          1 second  
Memory limit:       256 megabytes

Given a string  $s$ . You need to write a function that validates the string. Valid string is the string that contains  $n$  or more digits.

### Input

Line contains string  $s$  ( $0 \leq s.length \leq 10^5$ ) and integer  $n$  ( $1 \leq n \leq 10^5$ ).

### Output

Print "YES"(without quotes) if the string is valid, otherwise "NO".

### Examples

standard input	standard output
som3thing4 2	YES
j4stc0d3it 5	NO
s4ys0om3thing 1	YES
w4k3up4y0u 6	NO
rem0veitnow 1	YES

## Problem G. Remove vowels

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

Given a string  $s$ . You have to write a function that removes all vowels from the string.

### Input

Line contains string  $s$  ( $0 \leq s.length \leq 10^5$ )

### Output

Output the string without vowel letters.

### Examples

standard input	standard output
S0mething is coming UP. So I need 2 go now.	S0mthng s cmng P. S nd 2 g nw.
I need to work hard to pass programming principles final exam.	nd t wrk hrd t pss prgrmmng prncpls fnl xm.
Alice looked at glance	lc lkd t glnc
Lorem Ipsum Dolor Sit Amet	Lrm psm Dlr St mt
1998 is the number that consists of 4 digits.	1998 s th nmbr tht cnssts f 4 dgts.

### Note

Assume that letter  $Y$  is consonant.



## Problem H. Valid number

Input file:            standard input  
Output file:           standard output  
Time limit:           1 second  
Memory limit:         256 megabytes

Given a number  $n$ . Write a function for checking if this number is valid. Valid number is the number that consists of even digits only.

### Input

Line contains  $n$  ( $1 \leq n \leq 10^{10}$ ).

### Output

If number is valid, print "Valid"(without quotes), otherwise "Not valid".

### Examples

standard input	standard output
1111	Not valid
2222	Valid
332	Not valid
442862	Valid
31312234	Not valid

## Problem I. Capital Even

Input file:            `standard input`  
Output file:          `standard output`  
Time limit:           `1 second`  
Memory limit:        `256 megabytes`

Given a string  $s$ . You need to write a function that takes the string and turn capital letters on even positions to lowercase letters.

### Input

Line contains string  $s$  without whitespaces. ( $1 \leq s.length \leq 10^5$ ).

### Output

Output the string after manipulations.

### Examples

standard input	standard output
<code>somestring</code>	<code>SoMeStRiNg</code>
<code>needtocode</code>	<code>NeEdToCoDe</code>
<code>codeislife</code>	<code>CoDeIsLiFe</code>
<code>codeislove</code>	<code>CoDeIsLoVe</code>
<code>nolifewithoutcoding</code>	<code>NoLiFeWiThOuTcOdInG</code>

## Problem J. Find the maximum

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

Write a function for finding the maximum of 4 numbers.

### Input

You are given 4 numbers  $n$  ( $-10^5 \leq n \leq 10^5$ ).

### Output

Output the maximum of 4 numbers.

### Examples

standard input	standard output
-10 4 5 3	5
-10 3 2 3	3
0 0 0 0	0
3 4 -1 -2	4
3 1 1 2	3

## Problem K. Find the sum of all digits

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

You are given a number  $n$ . Write a function for finding the sum of all digits of number  $n$ .

### Input

Input contains positive number  $n$  ( $0 \leq n \leq 10^8$ ).

### Output

Output the sum of all digits.

### Examples

standard input	standard output
11	2
1233	9
1000	1
2233	10
2231313	15

## Problem L. Valid string - 2

Input file:            `standard input`  
Output file:         `standard output`  
Time limit:          1 second  
Memory limit:       256 megabytes

Given a string  $s$ . You need to write a function that validates the string. Valid string is the string that contains  $n$  or more consequent digits.

### Input

Line contains string  $s$  ( $0 \leq s.length \leq 10^5$ ) and integer  $n$  ( $1 \leq n \leq 10^5$ ).

### Output

Print "Valid"(without quotes) if the string is valid, otherwise "Not valid".

### Examples

standard input	standard output
som3thing4 2	Not valid
j4stc0d3it 5	Not valid
s4ys0om3thing 1	Valid
w43kup4y0u 2	Valid
rem0veitnow 1	Valid

## Problem M. Reverse the array

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

You are given an array of  $n$  elements. Write a function for printing given array in reverse order.

### Input

The first line contains an integer  $n$  ( $1 \leq n \leq 10^5$ ). The second line contains  $n$  numbers  $i$  (elements of the array) ( $1 \leq i \leq 10^6$ ).

### Output

Output the array in reverse order.

### Examples

standard input	standard output
3 1 2 3	3 2 1
5 3 2 1 3 4	4 3 1 2 3
2 0 2	2 0
4 0 2 233 1	1 233 2 0
1 2	2

## Problem N. Array transpose

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

Given an array of  $n \times m$  elements. Write a function that transposes the array.

### Input

First line contains two integers  $n$  and  $m$  ( $1 \leq n, m \leq 10^3$ ). The next  $n$  lines contain  $m$  integers  $i$  ( $1 \leq i \leq 10^5$ ) each.

### Output

Output the transposed array.

### Examples

standard input	standard output
2 3 1 2 3 4 5 6	1 4 2 5 3 6
3 4 82 12 13 24 22 11 22 30 93 33 11 33	82 22 93 12 11 33 13 22 11 24 30 33
1 1 1	1
2 2 1 2 3 4	1 3 2 4
5 1 33 22 13 33 78	33 22 13 33 78

### Note

Transposed array - array obtained by switching columns with rows of the array.

## Problem O. 74861. Lucky ticket

Input file:        `standard input`  
Output file:      `standard output`  
Time limit:       1 second  
Memory limit:    256 megabytes

Do you use public transportation? Probably, you paid for the fare and received ticket with number. Lucky ticket is ticket with number, where sum of all numeral is divided by last numeral. For example, 754 is lucky, because the remainder of dividing  $7+5+4$  by 4 is 0. Write the function which check the number for luck.

### Input

In the first line of the input file there is a natural number  $n$ , ( $1 \leq n \leq 10000$ ) — ticket number.

### Output

If the ticket is lucky "Yes" otherwise "No".

### Example

standard input	standard output
123123	Yes



## Problem P. Positive number

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

Alisa hates negative numbers. Write the function which converts the number to positive.

### Input

In the first line of the input file there is a natural number  $n$ , ( $1 \leq n \leq 10000$ ) — number.

### Output

Output the positive number.

### Examples

standard input	standard output
1	1
-10	10
-15	15

## Problem Q. 74867. Percent of girls

Input file:            `standard input`  
Output file:          `standard output`  
Time limit:           1 second  
Memory limit:        256 megabytes

Director of school number 3 wants to congratulate all girls. That's why he need know what percentage of all pupils are girls? Let's help him.

### Input

In the first line of the input givens two integers  $n$  and  $m$  ( $1 \leq m \leq n \leq 1000$ ) — total number of pupils and number of girls.

### Output

Output percentage of girls with 1000 accuracy.

### Examples

standard input	standard output
100 20	20
50 20	40

## Problem R. 74447. ToUpper

Input file:           standard input  
Output file:         standard output  
Time limit:          1 second  
Memory limit:       256 megabytes

You are given one letter of English alphabet, write a function which will convert only lowercase letters to uppercase.

### Input

In first line of input given a character lower or upper case English letter.

### Output

Upper case English letter.

### Examples

standard input	standard output
a	A
b	B
c	C
d	D
E	E

## 4 Lab Contest

All given task are emplaced in automated checker system for **lab4**:

[http://acm.kbtu.kz/cgi-bin/new-client?contest\\_id=146](http://acm.kbtu.kz/cgi-bin/new-client?contest_id=146)

Feel free to submit your solutions without attempt count penalty.

## 5 Solutions

### Problem 73273

---

```
#include <iostream>
using namespace std;

bool isPrime(int x) { // boolean function

    for (int i = 2; i < x; ++ i) {
        if (x % i == 0) {
            return false;
        }
    }
    return true;
}

int main () {
    int x;
    cin >> x;
    if (isPrime(x)) {
        cout << "Yes";
    }
    else
        cout << "No";
    return 0;
}
```

---

### Problem 74447

---

```
#include <iostream>
using namespace std;

char toUpper(char a) { // takes one parametr English character
```

```

        if (a >= 'A' && a <= 'Z')
            return a;
        int x = a - 'a';
        return char (x + 'A');
        // returns char upper case English character
    }
int main () {
    char c;
    cin >> c;
    cout << toUpper(c);
    return 0;
}

```

---

### Problem 74450

---

```

#include <iostream>
using namespace std;

int module(int x) {
    if (x < 0)
        return x * -1;
    return x;
}

int main () {
    int x;
    cin >> x;
    cout << module(x);
    return 0;
}

```

---

### Problem 74632

---

```

#include <iostream>
#include <cmath>

using namespace std;

int sum_of_all_numbers(int x) {
    int ans = 0;

```

```

        while (x > 0) {
            ans += x % 10;
            x /= 10;
        }

        return ans;
    }

    int n;

    int main() {
        cin>>n;
        cout<<sum_of_all_numbers(n);

        return 0;
    }

```

---

#### Problem 74714

---

```

#include <iostream>

using namespace std;

int n, m, a[1000][1000];

void transpose(int x, int y) {
    for (int i = 0; i < y; i++) {
        for (int j = 0; j < x; j++) {
            cout<<a[j][i]<<" ";
        }
        cout<<endl;
    }
}

int main() {
    cin >> n >> m;
    for (int i = 0; i < n; i++) {
        for (int j = 0; j < m; j++) {
            cin>>a[i][j];
        }
    }
}

```

```

    }

    transpose(n, m);
    return 0;
}

```

---

### Problem 74718

---

```

#include <iostream>

using namespace std;

bool isValidString(string s, int n) {
    int counter = 0;
    for (int i = 0; i < s.size(); i++){
        char c = s[i];
        if (c >= '0' && c <= '9') counter++;
    }

    return counter >= n;
}

int n;
string s;

int main() {

    cin >> s >> n;
    if (isValidString(s, n)) {
        cout<< "YES";
    } else {
        cout<< "NO";
    }

    return 0;
}

```

---

### Problem 74803

---

```

#include <iostream>

```

```

using namespace std;

long long getRemainder(long long number, long long division) {
    return number % division;
}

bool isValidNumber(long long number) {
    while(number > 0) {
        if (!(getRemainder(number % 10, 2) == 0)) {
            return false;
        }
        number /= 10;
    }

    return true;
}

long long n;

int main() {

    cin>>n;
    bool check = isValidNumber(n);
    if (check) cout<<"Valid";
    else cout<<"Not valid";

    return 0;
}

```

---

### Problem 74861

---

```

#include <iostream>
using namespace std;

bool check(int x) {
    int y = 0;
    int w = 0;
    while (w) {
        y = x % 10;
    }
}

```



```

        w += x % 10;
        x /= 10;
    }
    if (w % y == 0) {
        return true;
    }
    else {
        return false;
    }
}

int main () {
    int x;
    cin >> x;
    if (check(x)) {
        cout << "Yes";
    }
    else
        cout << "No";
    return 0;
}

```

---

#### Problem 74865

---

```

#include <iostream>
using namespace std;

int get_cnt_equals(int n, int a[], int b[]) {
    int x[101]; // max znachenye a[i]
    int y[101]; // max znachenye b[i]
    int sum = 0;
    for (int i = 1; i <= n; ++ i)
        x[a[i]] ++;
    for (int i = 1; i <= n; ++ i)
        y[b[i]] ++;
    for (int i = 1; i <= 100; ++ i) {
        sum += min (x[i], y[i]);
    }
    return sum;
}

```

```

int main () {
    int n;
    cin >> n;
    int a[n + 1], b[n + 1];
    for (int i = 1; i <= n; ++ i) {
        cin >> a[i];
    }
    for (int j = 1; j <= n; ++ j) {
        cin >> b[j];
    }
    cout << get_cnt_equals (n, a, b);
    return 0;
}

```

---

#### Problem 74446

---

```

#include <iostream>
using namespace std;

int addition(int a, int b) { // functions gets two parameters its
    a and b
    return a + b; // return is like out of function
    // returns a + b
}

int main () {
    int a, b;
    cout << addition(a, b); // its sample how to call this function
    return 0;
}

```

---

#### Problem 74449

---

```

#include <iostream>
using namespace std;

bool findElement(int a[], int n, int x) { // boolean function
    for (int i = 0; i < n; ++ i) {
        if (a[i] == x)
            return true;
    }
    return false;
}

```

```

}

int main () {
    int n;
    cin >> n;
    int a[n];
    for (int i = 0; i < n; ++ i) {
        cin >> a[i];
    }
    int x;
    cin >> x;
    if (findElement(a, n, x)) {
        cout << "Yes";
    }
    else
        cout << "No";
    return 0;
}

```

---

### Problem 74630

---

```

#include <iostream>
#include <cmath>

using namespace std;

int maximum(int a, int b, int c, int d) {

    return max(a, max(b, max(c, d)));
}

int a, b, c, d;

int main() {

    cin>>a>>b>>c>>d;
    cout<<maximum(a, b, c, d);

    return 0;
}

```

---

### Problem 74633

---

```
#include <iostream>

using namespace std;

void reverse_print(int a[], int len) {
    for (int i = len - 1; i >= 0; i--) {
        cout<<a[i]<<" ";
    }
}

int n, arr[500500];

int main() {
    cin>>n;
    for (int i = 0; i < n; i++) {
        cin>>arr[i];
    }

    reverse_print(arr, n);

    return 0;
}
```

---

### Problem 74715

---

```
#include <iostream>

using namespace std;

string remove_consonants(string s) {
    string new_string = "";
    for (int i = 0; i < s.size(); i++) {
        char c = s[i];
        if (
            c == 'a' ||
            c == 'e' ||
            c == 'i' ||
            c == 'o' ||
            c == 'u' ||

```

```

        c == 'A' ||
        c == 'E' ||
        c == 'I' ||
        c == 'O' ||
        c == 'U') {
            continue;
        }
        new_string += c;
    }

    return new_string;
}

string s;

int main() {

    getline(cin, s);
    cout << remove_consonants(s);

    return 0;
}

```

---

### Problem 74784

---

```

#include <iostream>

using namespace std;

bool isValidString(string s, int n) {
    int counter = 0;
    for (int i = 0; i < s.size(); i++) {
        char c = s[i];
        if (c >= '0' && c <= '9') counter++;
        else counter = 0;
        if (counter == n) return true;
    }

    return false;
}

```

```

string s;
int n;

int main() {

    cin >> s >> n;
    if (isValidString(s, n)) {
        cout<<"Valid";
    } else {
        cout<<"Not valid";
    }
    return 0;
}

```

---

### Problem 74821

---

```

#include <iostream>
#include <cmath>
#include <iomanip>
using namespace std;

double hypotenuse(int a, int b) {

    return sqrt(a * a + b * b);
}

int a, b;

int main() {

    cin>>a>>b;
    cout<<setprecision(4)<<hypotenuse(a, b);

    return 0;
}

```

---

### Problem 74862

---

```

#include <iostream>
using namespace std;

```

```

int d[101010];
void diff(int n, int a[], int b[]) {
    for (int i = 1; i <= n; ++ i) {
        d[i] = a[i] - b[i];
    }
}

int main () {
    int n;
    cin >> n;
    int a[n + 1], b[n + 1];
    for (int i = 1; i <= n; ++ i) {
        cin >> a[i];
    }
    for (int i = 1; i <= n; ++ i) {
        cin >> b[i];
    }
    diff(n, a, b);
    for (int i = 1; i <= n; ++ i) {
        cout << d[i] << ' ';
    }
    return 0;
}

```

---

### Problem 74867

---

```

#include <iostream>
using namespace std;

double persent_of_boys(int n, int m) {
    double x = m * 100;
    x = x / (n * 1.0);
    return 100 - x;
}

int main () {
    int n, m;
    cin >> n >> m;
    cout << persent_of_boys(n, m);
    return 0;
}

```

}

---

## 6 Additional tasks for this lab

You can solve problems in Informatics

<https://informatics.msk.ru/mod/statements/view.php?id=277>

*note: statements are in russian*