# C-Programming Lab Sheet I Year / I Part

**Faculty: Computer/Electrical** 

## Labsheet#6

#### Objectives:

- 1. To familiarized with different parts of function such as function prototype and function definition.
- 2. Passing arguments by value and return statement to return the value from callee to caller
- 3. Concept of local, global and static variable.
- 4. Recursive function

#### Objective#1

```
#inc1ude<stdio.h>
#include<conio.h>
                 /*function prototype*/
void Italy();
void brazil();
void main(){
       printf("\nI am in the main function\n");
       printf("I am finally back in the main function\n");
       getch();
}
void italy(){
       printf("I am in Italy function\n");
       brazil();
void brazil(){
         printf("I am in Brazil function\n");
}
```

**Assignment 1.1:** Using F8 to execute the program and see how the control is transferred from calling function to called function and return back to main function. Note down the output.

### Objective#2

2.1 Write a program to add two number using user defined type function with no return type and with argument.

```
#include<stdio.h>
#include<conio.h>
void sum(int x, int y); /* function prototype*/
void main(){
    int a, b;
    printf("Enter the number a, b: ");
    scanf("%d%d", &a, &b);
    sum(a, b);
    getch();
}
void sum(int x, int y){
    int c;
    c=x+y;
    printf("%d", c);
}
```

**Assignment 2.1:** Modify the above program with no return type no argument, with return type no argument, with return type and argument.

**Assignment 2.2:** WAP to find the factorial of a number using the function.

#### Objective#3

Concept of local, global and static variable

```
#inc1ude<stdio.h>
#include<conio.h>
void function();
int a, b=10;
void main(){
        a=20; /*local variable*/
        printf("%d\n",a);
        function();
        getch();
}
void function(){
        int c;
        c=a+b;
        printf("%d",c);
}
```

**Assignment 3.1:** Note down the output and discuss why the output is 20 and 30.

**Assignment 3.2:** In the above program replace the statement a=20 by int a=20 and note the output and compare with output of above program.

```
3.2
#include<stdio.h>
#include<conio.h>
void increment();
void main(){
       increment();
       increment();
       increment();
}
void increment(){
       int i=1;
       printf("%d\n", i);
       i=i+1;
}
3.3
#include<stdio.h>
#include<conio.h>
void increment();
void main(){
       increment();
       increment();
       increment();
}
void increment(){
       static int i=1;
       printf("%d\n",i);
       i=i+1;
}
```

**Assignment 3.2:** Run the program 3.2 and 3.3 and note down the output. Discuss what is the difference between them and why.

#### **Objective#4: Recursive Function**

```
#inc1ude<stdio.h>
#include<conio.h>
int fact(int n);
void main(){
       int i,n,y;
       printf("enter the number n");
       scanf("%d",&n);
       y=fact(n);
       printf("the fact is %d",y);
       getch();
int fact(int a){
       int f=1;
       If(a < = 0)
       return(f);
       else
       f=a*fact(a-1);
       return(f);
}
```

**Assignment 4.1:** Run the above program and enter the number 15 and explain why the factorial of 15 is not correct and modify the program to correct this error.

**Assignment 4.2:** WAP to find the sum of the series sum=1+2+3+4.....+n using recursive function.

**Assignment 4.3:** WAP to find the fibonacii series up to given number using function.