# ECDR

## Week 1: Project Brief and Research Grounding

ECDR Research

2 November 2026

## Contents

**1 Executive brief** **2**

1.1 Problem and decision contract . . . . . 2

1.2 Data and label contract . . . . . 2

1.3 Frozen reference architecture . . . . . 3

1.4 Research questions and hypotheses . . . . . 3

1.5 Domain, event, and certificate semantics . . . . . 4

1.6 Reference classes and architecture audit . . . . . 4

**2 Feasibility baseline results** **4**

2.1 Objectives, split subjects, and pipeline . . . . . 7

2.2 Certificate lifecycle and architecture-specific firewall . . . . . 8

2.3 Grounding and research gap . . . . . 8

2.4 Evidence status and roadmap . . . . . 8

**3 Source and reproducibility contract** **9**

# 1 Executive brief

This Week 1 document fixes the research question, reference contract, evidence boundaries, and experimental plan for Event-Conditioned Certified Decision Reuse (ECDR) on the HAPT smartphone inertial-sensing data. The primary reference is a new, frozen twelve-class SmallCNN1D specification. The historical six-class checkpoint and the earlier valid-convolution/GAP theory remain provenance only. The completed feasibility baseline is reported below; it does not establish ECDR certification or net savings.

## 1.1 Problem and decision contract

Let $X_t \in \mathbb{R}^{6\times 128}$ be a raw sensor window and let $P$ be fixed per-channel z-score preprocessing, fitted on training subjects only. The reference function is $F = f_\theta \circ P$, with logits $F(X) \in \mathbb{R}^{12}$ and deterministic tie-breaking. The reference decision is $h(X) = \arg\max_k F_k(X)$. An ECDR policy may reuse a previous decision only when its certificate proves that the current input belongs to a region on which the same fixed reference decision holds. The primary safety target is therefore $\hat{h}_{\text{ECDR}}(X) = h(X)$ with zero disagreements over the declared evaluation scope. Agreement with the reference is distinct from agreement with ground-truth labels.

The main research question is: for the frozen SmallCNN1D K=12 reference on HAPT, can an event-conditioned certificate preserve every reference decision while reducing total end-to-end inference cost under a declared streaming workload? Cost includes reference forward evaluation, preprocessing, event detection, membership tests, certificate construction or reuse, fallback evaluation, and I/O or scheduling overhead. Forward-only timing cannot establish a net saving.

## 1.2 Data and label contract

The source is the UCI Smartphone-Based Recognition of Human Activities and Postural Transitions dataset [1], sampled at 50 Hz with three accelerometer and three gyroscope channels. Windows are 128 samples with stride 64; each window is tied to its recording and raw annotation coordinates. Subject-disjoint splits are fixed as 17 training, 4 validation, and 9 test subjects. Channel order is $[a_x, a_y, a_z, g_x, g_y, g_z]$: raw accelerometer channels are measured in $g$ and gyroscope channels in radians per second. Windows are 2.56 seconds long and advance by a 1.28-second step. Windows never cross recordings. Normalizer statistics are fit across all supervised TRAIN windows and recordings; validation and test never enter the fit. The inputs are raw sensor signals, not the UCI 561-feature representation.

The split audit contains 9,978 full train-stream windows, 2,422 validation windows, and 5,053 test-stream windows. The supervised pure-or-dominant-at-least-0.6 policy contains 6,955 train, 1,751 validation, and 3,572 test windows. The pure-basic total is 10,017 across the corpus; these are different denominators. These counts were reproduced by the fresh audit and recorded in the run manifest. Pure windows and majority windows are distinct. Ambiguous or unlabeled stream windows remain in full-stream denominators and are excluded from supervised classification only under the declared policy. The annotation coordinate convention and the mapping from samples to windows must be recorded with each run.

The transition snapshot has 344 pure transition windows and 10,017 pure basic windows among 10,361 pure windows. Existing support gates therefore remain failed for a high-

quality twelve-class training claim. The explicit current decision is to permit an exploratory K=12 feasibility reference with the pure-or-dominant policy, while retaining the status exploratory and making no claim that the historical G2 quality gate passed.

## 1.3 Frozen reference architecture

The K=12 contract is: input $(B, 6, 128)$; same-padded Conv1D 6→32, kernel 5, padding 2, followed by BatchNorm, ReLU and MaxPool2; same-padded Conv1D 32→64, kernel 3, padding 1, followed by BatchNorm, ReLU and MaxPool2; same-padded Conv1D 64→64, kernel 3, padding 1, followed by BatchNorm and ReLU; Flatten of 2,048 features; Linear 2,048→128, ReLU; and Linear 128→12. The executed trainable parameter count is 283,692; shape and parameter checks passed on the instantiated K=12 model. BatchNorm evaluation uses frozen running statistics; a checkpoint and its preprocessing parameters are an inseparable reference identity.

The operational checkpoint was selected after the completed training and evaluation run. It uses seeds 42, 43, and 44; at most 30 epochs; Adam with learning rate $10^{-3}$ and weight decay $10^{-4}$; cosine scheduling; and patience 10. Epoch and seed selection use validation macro-F1. Test evaluation occurs after selection. Required outputs include accuracy against ground truth, macro-F1, a 12-class confusion matrix, per-class recall, reference-decision agreement, point-margin distributions, and timing by declared scope. These outputs are recorded for the completed feasibility run. Adjacent prediction stability is measured for the snapshot, while ECDR/reference agreement is not established; certificate and full ECDR cost outputs remain pending.

## 1.4 Research questions and hypotheses

**RQ1 (reference quality)** What classification accuracy and per-class recall does the new K=12 reference achieve against declared ground truth?

**RQ2 (decision preservation)** Does ECDR preserve the reference decision with zero disagreements on stable and transition windows under the specified certificate and lifecycle rules?

**RQ3 (coverage and cost)** At what event-conditioned coverage does ECDR reduce total end-to-end cost relative to evaluating the reference on every window, and how does that compare with a fixed fair-cost policy?

**RQ4 (soundness)** Which certificate bounds, membership predicates, and lifecycle obligations are executable on this graph?

The hypothesis ledger is conditional. H1 predicts that stable windows will have more stable adjacent reference predictions than transition windows; this is not ECDR/reference agreement; the current snapshot measures it descriptively from 2,560/2,617 stable pairs versus 23/44 transition pairs. H2 predicts that event-conditioned certified coverage can improve at a fixed matched total cost; this is proposed and requires a fair end-to-end benchmark. H3 is a derived theorem obligation: if, for a candidate region $\mathcal{S}_r$ and predicted class $c$, every competing margin satisfies $\inf_{X \in \mathcal{S}_r}(F_c(X) - F_j(X)) > 0$ for $j \neq c$, then $h(X) = c$ throughout that region. This implication is mathematical, not a validated runtime result; executable bound, arithmetic, membership, and lifecycle checks remain pending. H4 predicts net savings only in an operating regime whose complete cost is measured.

### 1.5 Domain, event, and certificate semantics

An anchor is a specific window $X^r$ actually evaluated by the frozen reference, with trusted class $c = h(X^r)$. A candidate region is a set of admissible windows, a certificate is a sound lower-bound statement over that region, and membership is the runtime predicate that decides whether a new window belongs to it. These are separate objects. Event descriptors are candidate signals for choosing when to rebuild or test a certificate; they do not prove coverage by smoothness. The whole-domain condition above is a derived condition over all 11 competing margins, not evidence that the condition holds for the current checkpoint. Reference weights, BatchNorm running statistics, preprocessing, tie-breaking, and arithmetic mode must remain fixed across a certificate's lifecycle. Cached hits do not establish a new trusted anchor: reuse is allowed only for a valid certificate and membership result, otherwise the system falls back to the frozen reference.

### 1.6 Reference classes and architecture audit

The class IDs are fixed as follows: 1 WALKING, 2 WALKING_UPSTAIRS, 3 WALKING_DOWNSTAIRS, 4 SITTING, 5 STANDING, 6 LAYING, 7 STAND_TO_SIT, 8 SIT_TO_STAND, 9 SIT_TO_LIE, 10 LIE_TO_SIT, 11 STAND_TO_LIE, and 12 LIE_TO_STAND. The order is part of the checkpoint identity.

Table 1: Frozen K=12 architecture audit.

| Layer | Input | Output | Trainable parameters | Role |
|---|---|---|---|---|
| Input | $B \times 6 \times 128$ | $B \times 6 \times 128$ | 0 | Raw six-channel window |
| Conv1 (same, k5,p2) | $6 \times 128$ | $32 \times 128$ | 992 | Local temporal features |
| BN1+ReLU+Pool2 | $32 \times 128$ | $32 \times 64$ | 64 | Frozen eval affine and downsample |
| Conv2 (same, k3,p1) | $32 \times 64$ | $64 \times 64$ | 6,208 | Higher-level features |
| BN2+ReLU+Pool2 | $64 \times 64$ | $64 \times 32$ | 128 | Frozen eval affine and downsample |
| Conv3 (same, k3,p1) | $64 \times 32$ | $64 \times 32$ | 12,352 | Final temporal features |
| BN3+ReLU | $64 \times 32$ | $64 \times 32$ | 128 | Fixed evaluation normalization |
| Flatten | $64 \times 32$ | 2,048 | 0 | Preserve positional features |
| Linear+ReLU | 2,048 | 128 | 262,272 | Dense decision representation |
| Linear head | 128 | 12 | 1,548 | Twelve logits |
| Total | | | 283,692 | Executed trainable count; shape and parameter checks passed |

## 2 Feasibility baseline results

The full pipeline completed with exit code 0 and 17 internal verification checks. Validation selected seed 43 at epoch 8 by macro-F1 (0.8467853). The selected checkpoint is `selected_best.pt`, SHA-256 `8ffc5dd8eb0e9cdf832160d074f3ae816ae6cba02adf7214a63a8b623303adb1`; the train-only preprocessing identity is `aa8e1cc20829307187e0a78200f9957f7d`

`d068b1dc26063c2720ad832bb2fd6e`. The three seeds selected epochs 14, 8, and 9 for seeds 42, 43, and 44; early stopping means the histories must not be described as 30 completed epochs.

Table 2: Per-seed selection and test variability.

| Seed | History length | Best epoch | Val macro-F1 | Test accuracy | Test macro-F1 |
|---|---|---|---|---|---|
| 42 | 24 | 14 | .836829 | .886618 | .767022 |
| 43 | 18 | 8 | .846785 | .890538 | .776265 |
| 44 | 19 | 9 | .836958 | .889698 | .763648 |

On the supervised test denominator of 3,572, selected seed 43 achieved accuracy 0.8905375 and macro-F1 0.7762645. Across seeds, accuracy was 0.8889511 $\pm$ 0.0016849 and macro-F1 was 0.7689781 $\pm$ 0.0053332, where the spreads are population standard deviations across three seeds, not confidence intervals. The full test stream contains 5,053 windows.

Table 3: Pure-plus-majority support by split; each cell is windows/subjects.

| ID | Class | Train | Val | Test |
|---|---|---|---|---|
| 1 | WALKING | 1077/17 | 246/4 | 531/9 |
| 2 | WALKING_UPSTAIRS | 973/17 | 247/4 | 537/9 |
| 3 | WALKING_DOWNSTAIRS | 894/17 | 231/4 | 492/9 |
| 4 | SITTING | 1103/17 | 289/4 | 546/9 |
| 5 | STANDING | 1206/17 | 312/4 | 597/9 |
| 6 | LAYING | 1188/17 | 316/4 | 586/9 |
| 7 | STAND_TO_SIT | 79/17 | 19/4 | 45/9 |
| 8 | SIT_TO_STAND | 53/17 | 13/4 | 32/9 |
| 9 | SIT_TO_LIE | 90/17 | 26/4 | 51/9 |
| 10 | LIE_TO_SIT | 89/17 | 15/3 | 46/9 |
| 11 | STAND_TO_LIE | 119/17 | 18/3 | 68/9 |
| 12 | LIE_TO_STAND | 84/17 | 19/4 | 41/9 |

Table 4: Selected-seed class support, recall and F1 (supervised test, $n = 3572$).

| ID | Class | Support | Recall | F1 |
|---|---|---|---|---|
| 1 | WALKING | 531 | .9567 | .9585 |
| 2 | WALKING_UPSTAIRS | 537 | .9088 | .9208 |
| 3 | WALKING_DOWNSTAIRS | 492 | .9837 | .9528 |
| 4 | SITTING | 546 | .8407 | .8196 |
| 5 | STANDING | 597 | .8090 | .8429 |
| 6 | LAYING | 586 | .9949 | .9890 |
| 7 | STAND_TO_SIT | 45 | .7111 | .7356 |
| 8 | SIT_TO_STAND | 32 | .6563 | .7119 |
| 9 | SIT_TO_LIE | 51 | .6471 | .6168 |
| 10 | LIE_TO_SIT | 46 | .5870 | .6667 |
| 11 | STAND_TO_LIE | 68 | .5294 | .5496 |
| 12 | LIE_TO_STAND | 41 | .6585 | .5510 |

The selected-seed confusion matrix uses row and column IDs 1,2,3,4,5,6,7,8,9, 10,11,12 in

the exact class order above; rows are true classes and columns are predicted classes:

| | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 1 | 508 | 0 | 22 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| 2 | 16 | 488 | 15 | 0 | 0 | 0 | 2 | 0 | 0 | 3 | 2 | 11 |
| 3 | 4 | 2 | 484 | 0 | 0 | 0 | 2 | 0 | 0 | 0 | 0 | 0 |
| 4 | 0 | 21 | 0 | 459 | 57 | 0 | 1 | 2 | 1 | 0 | 5 | 0 |
| 5 | 0 | 3 | 0 | 106 | 483 | 0 | 1 | 0 | 1 | 0 | 2 | 1 |
| 6 | 0 | 0 | 0 | 0 | 0 | 583 | 0 | 0 | 0 | 0 | 3 | 0 |
| 7 | 1 | 2 | 0 | 4 | 1 | 0 | 32 | 3 | 1 | 0 | 1 | 0 |
| 8 | 0 | 2 | 0 | 1 | 7 | 0 | 1 | 21 | 0 | 0 | 0 | 0 |
| 9 | 0 | 0 | 0 | 0 | 1 | 6 | 0 | 0 | 33 | 0 | 11 | 0 |
| 10 | 0 | 1 | 0 | 2 | 0 | 0 | 0 | 0 | 0 | 27 | 1 | 15 |
| 11 | 0 | 1 | 1 | 2 | 0 | 4 | 2 | 0 | 20 | 0 | 36 | 2 |
| 12 | 0 | 3 | 2 | 0 | 0 | 0 | 1 | 1 | 0 | 5 | 2 | 27 |

Adjacent prediction stability is descriptive only: among 5,034 valid adjacent pairs (18 recording-boundary/gap pairs excluded), pure stable pairs agreed 2,560/2,617 (97.8219%), pure transition pairs 23/44 (52.2727%), and mixed other pairs 1,399/2,373 (58.9549%). This supports H1 descriptively for this snapshot, but transition support is small and this is not ECDR/reference certification or a population-level independent test.

CPU timing used one thread, FP32, batch shape $1 \times 6 \times 128$, 100 warmup calls and 1,000 varied-input timed calls. Forward-only mean/p50/p95 were 0.173376/0.165034/0.215291 ms; reference-core preprocessing plus forward mean/p50/p95 were 0.201103/0.183905/0.287375 ms. Both scopes exclude raw acquisition, windowing, events, certificate construction, membership, cache overhead and disk I/O. No speedup or net-cost claim follows. The winning point margin median was 5.9782 and the supervised ground-truth margin median 7.5746; these are empirical point margins, not certified bounds. The lowest selected transition recall was STAND_TO_LIE, 36/68 = 0.5294.

No ECDR runtime certificate agreement has been computed. Formal certificate agreement and full net-cost evaluation remain future work; the G2 quality gate is HOLD because transition support is insufficient, even though the Week 1 feasibility baseline and independent baseline-artifact verification are complete.

The independent baseline artifact verifier for this Week 1 feasibility run passed 65/65 checks with zero failures. Receipt: `output/week1_closeout_20261102/reference/independent_verification.json`. It recomputed the 131 source/data hashes, bound the 6,955 training windows and IDs to the train-only normalizer, checked all three histories, selection, confusion matrix, per-class precision/recall/F1 and Wilson values, reproduced all three-seed CPU batch-512 predictions, validated CSV IDs/class order/margins, 5,034 adjacent pairs and gap mask, and checked timing metadata. The finite batch-1 versus batch-512 check matched labels for all 5,053 stream windows with zero disagreements and maximum absolute logit difference $9.5367431640625 \times 10^{-6}$. This is an independent baseline-artifact consistency pass, not a formal certificate verifier and not an ECDR safety claim; the strict certificate verifier remains a Week 3 task. The G2 quality gate remains HOLD because transition support is insufficient, and net cost remains unestablished.

The historical parameterized `SmallCNN1D` implementation is reused to instantiate K=12 when supplied the new class count. Its K=6 configuration and old checkpoints remain historical and cannot transfer metrics or certificates. BatchNorm statistics are fixed in evaluation mode; the official PyTorch 2.14 BatchNorm contract is cited in the bibliography [9].

## 2.1 Objectives, split subjects, and pipeline

The objectives are separate: (O1) measure classification accuracy and per-class recall against ground truth; (O2) measure reference-decision agreement with a strict zero-disagreement target; and (O3) measure net end-to-end cost against a full-reference baseline. A single score cannot substitute for these three.

The split audit artifact `data/split_audit.json` lists train subjects 1,3,5,6,7,8,11,14,15,16,17,19,21,22,23,25,26, validation subjects 27,28,29,30, and test subjects 2,4,9,10,12,13,18,20,24; it reports subject-disjoint and recording-disjoint checks with zero issues.

The reproducible pipeline is: (1) load raw HAPT recordings and annotations; (2) construct recording-local 128-sample windows at stride 64; (3) attach raw annotation spans and apply the declared pure/dominant label rule; (4) join the fixed subject split; (5) fit channel means and standard deviations across all supervised training windows only, then reuse them for validation and test; (6) instantiate and count the K=12 graph; (7) train three seeds with the declared protocol and select by validation macro-F1; (8) evaluate test after selection; (9) run agreement, certificate and cost experiments separately. The normalization fit spans training windows across records; windows themselves never cross recording boundaries.

The sole pipeline entry point is `scripts/week1_reference_pipeline.py`. The help-verified all-run command is `./.venv/bin/python scripts/week1_reference_pipeline.py all --output-dir output/week1_closeout_20261102/reference --epochs 30 --seeds 42,43,44 --device cpu`. No legacy K=6 command or nonexistent K=12 config is presented as a reproduction command. A fresh reproduction must substitute a new output directory; the recorded directory is immutable evidence. The run record must preserve run ID, command, environment, checkpoint hash, model config hash, preprocessing hash, data manifest hash, and seed.

The current audit artifact is run `week1_ref_1793620216_9d6c1d85`, created 2026-11-02T11:50:16Z, with pipeline hash `1ef93101f658f8a18ebf19f0c8743ec5311ffe94933aee3505be6ec29a0be4d6`. It covers 131 source/data hashes, 122 raw sensor files, 17,453 windows from 61 recordings, float32 shape $17{,}453 \times 6 \times 128$, zero raw-slice mismatches, zero label-builder mismatches, and verified aligned overlap for all pairs. A one-sample offset changes 98 window policy/label assignments; this is an explicit provenance caveat and does not change the current run. The CPU environment is Xeon W-11855M, Python 3.11.15, PyTorch 2.14.1+cpu, NumPy 2.4.6, pandas 3.0.6, one thread. These are audit and feasibility results, not a quality-gate pass; ECDR certification and net-cost evaluation remain pending.

Table 5: Feasibility outputs and remaining external dependencies.

| Field | Evidence | Status |
|---|---|---|
| Per-class support/recall | Selected test table, all 12 classes | VERIFIED RUN |
| Confusion matrix | 12 by 12 with class IDs 1–12 | VERIFIED RUN |
| Adjacent stability | 5,034 valid pairs, stable/transition strata | VERIFIED DESCRIPTIVE |
| Reference timing | Mean/p50/p95 preprocessing plus forward | VERIFIED BASELINE |
| Three-seed variability | Selected epochs and population spread | VERIFIED RUN |
| ECDR/reference agreement | Runtime certificate comparison | NOT ESTABLISHED |
| Certificate and net cost | Formal certificate verifier and full ECDR benchmark | WEEK 3 DEPENDENCY |

Table 6: Hypothesis ledger and measurement boundary.

| ID | Basis | Test | Status |
|---|---|---|---|
| H1 | Stable/transition event distinction | Adjacent reference-prediction stability; 2,560/2,617 versus 23/44, descriptive only | MEASURED DESCRIPTIVE |
| H2 | Event-conditioned reuse may avoid unnecessary rebuilds | Future matched-cost coverage, fallback rate and certificate-failure rate, stratified by pure-basic, pure-transition and mixed windows; exclude cross-recording/gap pairs | PROPOSED |
| H3 | All 11 positive regional margins imply one class | Sound bound, membership and lifecycle obligations | DERIVED |
| H4 | Reuse can save net cost in a workload regime | Full end-to-end timing including fallback and overhead | PROPOSED |

## 2.2 Certificate lifecycle and architecture-specific firewall

Reuse is permitted only when a valid certificate exists and membership holds. Otherwise the system falls back to the fixed reference evaluation. A hit does not renew the trusted anchor. Model or preprocessing changes invalidate the certificate, as do recording or gap-boundary changes that violate the declared region. The mathematical condition quantifies every point in the candidate region and every one of the 11 competing classes; it does not assume that a stable window is correct, and point margins are not regional bounds.

The exact overlap between adjacent stride-64 windows is 64 samples across six channels, hence 384 shared coordinates. This is a reuse opportunity, not a zero-difference input: the remaining coordinates change, and the full-input distance must be computed under the declared norm if a bound requires it. The old valid-convolution/GAP feature cancellation formulas are therefore firewalled from this BatchNorm–MaxPool–Flatten graph. Week 3 must derive or verify bounds on this actual graph.

## 2.3 Grounding and research gap

The targeted primary literature covers Lipschitz-margin certification [2], IBP [3], CROWN and auto-LiRPA [4, 5] for sound bounds; StreamiNNC and TinyDejaVu [6, 7] for streaming reuse or sensor-stream efficiency; and LipCache/GuardNet [8] for certified caching boundaries. These works motivate the questions but do not establish a result on this HAPT contract. No novelty, universal speedup, or superiority claim is made here. A GuardNet certificate must not be described as a certificate for a different MainNet without matching the reference boundary. The earlier Conv-valid–ReLU–GAP derivation is architecture-specific and is not transferred to the BatchNorm–MaxPool–Flatten reference.

## 2.4 Evidence status and roadmap

Evidence is labeled VERIFIED (read from a source artifact and checked), DERIVED (a logical consequence whose premises remain to be checked), PROPOSED (a planned measurement or method), or NOT-ESTABLISHED. Week 1 closes the brief, data and architecture scope lock,

Table 7: Native Week 1 evidence register.

| ID | Scope and artifact | Status |
|---|---|---|
| W1-01 | Project brief, research grounding and targeted primary literature | VERIFIED |
| W1-02 | K=12 lock, class order and frozen checkpoint contract | VERIFIED RUN |
| W1-03 | Exact architecture graph and 283,692 trainable parameters | VERIFIED RUN |
| W1-04 | Executed full reference pipeline and reproducibility artifacts | VERIFIED RUN |
| W1-05 | Transition label policy and support blocker | VERIFIED SNAPSHOT |
| W1-06 | Main research question and separated objectives | VERIFIED |
| W1-07 | Evidence register with claim status | VERIFIED |
| W1-08 | Sensor/data full contract and denominators | VERIFIED SNAPSHOT |
| W1-09 | Hypothesis ledger H1–H4 | MEASURED/PROPOSED/DERIVED |
| W1-10 | Stable/transition decision stability plus future coverage/fallback/cost stratification | VERIFIED DESCRIPTIVE + PROPOSED |
| W1-11 | Week roadmap and dependencies | VERIFIED |
| W1-12 | English presentation and editable artifacts | VERIFIED |

and a feasibility baseline. Week 2 documents why each data and deep-model component is used. Week 3 checks certificate mathematics and executable bounds on the actual graph. GAP-specific formulas from the old theory and any deep revisions are dependencies for later weeks, not Week 1 results.

## 3 Source and reproducibility contract

Every reported number must cite a run ID, pipeline script, command, environment and provenance hash. The closeout register records source file, scope, denominator, status, and whether a statement is current, historical, or proposed. The parameterized `scripts/backbone.py` implementation can instantiate the current K=12 graph; the K=6 configuration and old checkpoints are historical evidence only and cannot transfer metrics or certificates. User acceptance is not asserted by this document.

Table 8: Targeted related-work boundary.

| Work | Reference guaranteed | Payload/domain | Cost/evidence boundary |
|---|---|---|---|
| Lipschitz-margin [2] | Perturbation margin under stated norm | Classifier robustness | No HAPT ECDR cost result |
| IBP/CROWN/auto-LiRPA [3, 4, 5] | Sound bounds when relaxations and arithmetic hold | Neural-network regions | Bound runtime is method/graph dependent |
| StreamiNNC [6] | Streaming CNN computation reuse | Shifted windows; padding caveats | Efficiency evidence is workload-specific |
| TinyDejaVu [7] | Sensor-stream inference design | MCU RAM and latency | No transfer of benchmark numbers |
| LipCache/GuardNet [8] | Certified cache proxy boundary as defined by the work | Edge image service | GuardNet/MainNet scope must not be conflated |

## References

[1] UCI Machine Learning Repository, *Smartphone-Based Recognition of Human Activities and Postural Transitions*, 2015. https://archive.ics.uci.edu/dataset/341/smartphone+based+recognition+of+human+activities+and+postural+transitions.

[2] Tsuzuku, Sato, Sugiyama, *Lipschitz-Margin Training*, NeurIPS 2018. https://arxiv.org/abs/1802.04034.

[3] Gowal et al., *On the Effectiveness of Interval Bound Propagation*, 2018. https://arxiv.org/abs/1810.12715.

[4] Zhang et al., *Efficient Neural Network Robustness Certification with General Activation Functions*, NeurIPS 2018. https://arxiv.org/abs/1811.00866.

[5] Xu et al., *Automatic Perturbation Analysis for Scalable Certified Robustness and Beyond*, NeurIPS 2020. https://arxiv.org/abs/2002.12920.

[6] Kechris et al., *Don't Think It Twice*, 2024. https://arxiv.org/abs/2408.03223.

[7] Huang and Baccelli, *TinyDejaVu: Smaller RAM and Faster Inference with Neural Networks on MCUs for Sensor Data Streams*, arXiv v2, 2026. https://arxiv.org/abs/2512.09786v2.

[8] Xiang et al., *LipCache: A Local Inference Proxy with Certified Caching for Edge Image Classification Service*, arXiv v1, 2026. https://arxiv.org/html/2608.13144v1.

[9] PyTorch, *BatchNorm1d*, documentation for the 2.14 API, accessed 2026-11-02. https://docs.pytorch.org/docs/2.14/generated/torch.nn.BatchNorm1d.html.