Finite-size corrections to the classical cost of a verifiable decoded-quantum-interferometry advantage

Tyler Duic
Independent researcher, New York, NY
ORCID 0009-0005-4675-3045
https://github.com/tduic

October 2026

Abstract

Khattar et al. propose decoded quantum interferometry (DQI) on a structured polynomial-intersection problem over $\mathbb{F}_{2^{12}}$ as a verifiable demonstration of quantum advantage, with a headline instance that requires about 10^{23} trials of the best known classical attack. That classical cost is evaluated at a target score set by the asymptotic semicircle law for the DQI expected score. At the sizes in question a single DQI run falls short of this target by a predictable amount: at the headline instance the expected score is 2,359.7 against a target of 2,393, and one run reaches the target only 6.0% of the time even with the enhancing polynomial optimized for the tail. Measured as classical trials per quantum run, every entry of the paper's resource table overstates the classical gap by a factor of 14.0–18.5 (16.8 at the headline instance). The shortfall is described to within 4.3% by a law built on the Airy edge asymptotic of the underlying Jacobi spectrum, and a moderately larger instance ($n = 96$, about 9.1 million Toffoli gates per run) restores the claimed margin. The asymptotic results of the original paper are unaffected.

1 Introduction

Decoded quantum interferometry [1] reduces approximate optimization to decoding: for a max-LINSAT problem with m constraints, a DQI run with an enhancing polynomial of degree ℓ outputs an assignment whose number of satisfied constraints (its *score*) is, in expectation, given by a semicircle law in the limit of large m. Khattar et al. [2] use this to design a verifiable advantage experiment: a twisted "bent target" optimal polynomial intersection problem with $m = q - 1$ constraints over $\mathbb{F}_q$, $q = 2^b$, and an unknown polynomial of degree at most $n - 1$. They compile DQI circuits for several instances and compare against an extended form of Prange's information-set attack [3], which they call XP [2, Sec. III.B], in their Table VI. At the headline instance $(m, n, b) = (4095, 70, 12)$ they report about 5.7 million Toffoli gates and 1.97×10^{23} XP trials.

The classical cost in Table VI is computed at the target score t obtained by plugging the instance into the asymptotic semicircle law. This note makes two observations. First, at these sizes the score of a single DQI run falls well short of that target, so the fair classical cost to compare with one quantum run is smaller by the number of runs DQI needs to reach t (Section 3). Second, the shortfall is predictable from a simple finite-size law (Section 4), which shows how to size an instance that does reach the claimed margin (Section 5). All numbers below are reproduced by code and tests in the accompanying repository.

2 The finite-size score distribution

Let $p = r/q$ be the density of each constraint's target set ($r = 2016$ for $b = 12$), and let $e_0, e_1, \ldots$ be the Krawtchouk polynomials orthonormal with respect to the binomial distribution $\mathrm{Binom}(m, p)$. Jordan et al. show that the expected DQI score with enhancing-polynomial weights $w = (w_0, \ldots, w_\ell)$, $\|w\| = 1$, is the quadratic form of w in an $(\ell+1) \times (\ell+1)$ tridiagonal (Jacobi) matrix [1, Lemma 9.2 of the arXiv version], so the mean-optimal weights are its top eigenvector and the optimal expected score is its top eigenvalue. That lemma is stated for prime fields; Khattar et al. apply the same analysis over $\mathbb{F}_{2^b}$, and so do I. The derivation uses that the constraint indicators of a uniformly random assignment have the joint moments of independent Bernoulli(p) variables up to the order the computation needs, which holds when $2\ell + 1$ is below the dual distance $n + 1$ of the underlying Reed–Solomon code. The same reasoning gives the model score law

$$\pi_w(s) \;=\; \mathrm{Binom}(m, p)(s) \Big(\sum_{k=0}^{\ell} w_k \, e_k(s) \Big)^2, \qquad s = 0, \ldots, m. \tag{1}$$

Its mean is exact under the condition above, but its tail probabilities are not exact for an individual instance, whose score histogram is binomial only in its low moments. They do describe the instance ensemble of [2]: averaging over the random twist of the target sets, the score histogram of a random assignment is a mixture of binomials over the number of roots of the candidate polynomial (treated as binomially distributed), and at the Table VI instances the resulting DQI tail probabilities agree with (1) to within 10^{-14}. On small instances ($b = 4$, $n = 5$, $\ell = 2$), where every assignment can be enumerated, the mean agrees exactly and the probability of reaching score 11 ranges over 0.181–0.184 across eight random instances, against 0.182 for the model.

The paper's choice $\ell = n/2$ sits exactly at the boundary $2\ell + 1 = n + 1$, where the mean picks up a correction term. I have not bounded it at the Table VI sizes; on small instances ($b = 4$ and 6) exhaustive enumeration puts it within 0.016 in score. The expected scores below are the values of the Jacobi-matrix formula, subject to this caveat. For a target t, the tail-optimal weights maximizing $\Pr_w[s \geq t]$ under (1) are the top eigenvector of the Gram matrix $M_{jk}(t) = \sum_{s \geq t} \mathrm{Binom}(m, p)(s) \, e_j(s) \, e_k(s)$.

I computed these quantities three ways: from the expected-score formula directly, from an independent re-derivation of (1) in 60-digit arithmetic, and from a float64 implementation with a log-scaled three-term recurrence used for large m. They agree to numerical precision on every instance tested.

At the headline instance ($m = 4095$, $n = 70$, $\ell = 35$) the semicircle target is $t = 2{,}393$. The score distribution (1) with mean-optimal weights has mean 2,359.7, median 2,362 and standard deviation 31.8. A mean-optimal run reaches t with probability 2.8%; with tail-optimal weights the probability is 6.0%, so on average 16.8 runs are needed.

3 Classical trials per quantum run

I reproduced the XP and plain Prange trial counts of all 10 rows of Table VI to the three significant figures printed (1.966×10^{23} XP trials at the headline instance). Those counts are the expected number of classical trials needed to find an assignment of score at least t. A quantum experimentalist running DQI must also repeat until a run reaches t, which takes $1/\Pr_w[s \geq t]$ runs on average. The classical cost to compare with *one* quantum run is therefore the XP count multiplied by $\Pr_w[s \geq t]$, and the published figure overstates it by the factor $1/\Pr_w[s \geq t]$. Table 1 lists this factor for every row, using the tail-optimal weights, which favour DQI.

m	n	t (paper)	expected score	paper's classical trials	overstatement
1023	60	669	652.5	1.92×10^{15}	15.4
1023	70	682	666.3	4.64×10^{16}	14.0
1023	80	695	679.1	1.22×10^{18}	16.1
1023	90	707	691.0	2.08×10^{19}	17.9
1023	100	718	702.2	2.56×10^{20}	18.5
4095	60	2365	2331.4	4.02×10^{20}	16.0
4095	70	2393	2359.7	1.97×10^{23}	**16.8**
4095	80	2419	2386.0	7.99×10^{25}	17.5
4095	90	2443	2410.7	2.27×10^{28}	17.3
4095	100	2466	2434.0	5.91×10^{30}	17.8

Table 1: Instances of Table VI of [2] ($b = 10$ for $m = 1023$, $b = 12$ for $m = 4095$, $\ell = n/2$). "Overstatement" is the number of tail-optimal DQI runs needed, on average, to reach the paper's target score t; dividing the paper's classical trial count by it gives the classical cost per quantum run. The headline instance is in bold.

The overstatement ranges from 14.0 to 18.5 across the table and is 16.8 at the headline instance, so the headline classical gap is about 1.2×10^{22} trials per quantum run rather than 1.966×10^{23}. The advantage survives, and the asymptotic analysis of [2] is unaffected; only the concrete figures shift.

4 A finite-size law for the shortfall

Write a_k and b_k for the diagonal and off-diagonal entries of the Jacobi matrix. The semicircle value equals the local band edge $a_\ell + 2b_\ell$ at index ℓ; truncating the enhancing polynomial at degree ℓ imposes a hard wall there, and the top eigenvalue of the truncated matrix sits an Airy distance below that edge. This is the standard edge behaviour of extreme zeros of classical orthogonal polynomials (compare the Hermite case in [4, §6.32]); I do not claim novelty for the leading term. Let D be the semicircle value minus the top eigenvalue, and set

$$\beta = \sqrt{p(1-p)\,\ell(m-\ell)}, \qquad g = (1-2p) + \sqrt{p(1-p)}\,\frac{m-2\ell}{\sqrt{\ell(m-\ell)}}, \qquad X = (\beta/g)^{1/3}.$$

I find that

$$D \;\approx\; g\left(|a_1|\,X + c_0 + \frac{c_1}{X}\right), \qquad |a_1| = 2.3381, \quad c_0 = -1.46, \quad c_1 = 0.137, \tag{2}$$

where a_1 is the first zero of the Airy function and c_0, c_1 are fitted. Over a grid of 588 instances with $m = 2^7, \ldots, 2^{14}$, $\ell \geq 3$, ℓ/m from 0.001 to 0.3 and p from 0.05 to 0.5, (2) is within 4.3% of the exact value (1.2% rms). On a fresh grid with $m = 2^{15}, \ldots, 2^{18}$, outside the fitting range but with the same ranges of ℓ/m and p, it is within 1.1%. The leading term alone is off by up to 82% at small ℓ, so the corrections matter. At the headline instance (2) gives $D = 33.4$ against the exact 33.2. Equation (2) is an empirical law; I have not proved an error bound for it.

For small ℓ/m the shortfall is of the order of one binomial standard deviation of the score, so any concrete hardness figure that evaluates a classical attack at the semicircle value overstates the classical cost per quantum run.

5 Restoring the claimed margin

The cheapest fix is a larger instance rather than repetition. Along the $b = 12$ rows of Table VI, each increase of n by 10 multiplies the classical trial count by 260–490 while the Toffoli count grows by a factor of about 1.20. I searched over n (with $\ell = \lfloor n/2 \rfloor$), the target t and tail-optimal weights for the design minimizing Toffoli gates per quantum success subject to at least 10^{23} classical trials per quantum run, interpolating the paper's Toffoli and qubit counts across $n = 60$–100. For speed this search uses a simplified XP allocation, which agrees with the paper's counts to within 10% on the Table VI rows. The optimum is $n = 96$ with a target reached in 90% of runs: about 9.1 million Toffoli gates per run (10.2 million per success), 2,510 logical qubits and 1.06×10^{23} classical trials per quantum run. Re-priced with the paper's own XP allocation the margin is thinner but still sufficient: 1.04×10^{23} classical trials per quantum run. Keeping $n = 70$ and raising the target instead needs about 67 runs per success and is about 38 times more expensive in Toffoli gates.

6 Discussion

The comparison here assumes that the relevant classical task is to match the score that the quantum device actually achieves, run by run; other operational definitions of advantage shift the factor but not the conclusion that the asymptotic target is too generous at this size. Resource counts for the redesigned instance are interpolated from the original paper rather than compiled. The same check applies to any concrete DQI resource estimate: compute the finite-size score distribution, or use (2), before pricing the classical attack.

Data and code availability. Code, data and regression tests reproducing every number in this note are at `https://github.com/tduic/research-results/tree/main/dqi-finite-size`.

Acknowledgments. I carried out the analysis, code and an independent re-derivation with substantial assistance from AI models (Anthropic's Claude), working under my direction. I checked every claim and reference in this note and take full responsibility for its content.

References

[1] Stephen P. Jordan, Noah Shutty, Mary Wootters, Adam Zalcman, Alexander Schmidhuber, Robbie King, Sergei V. Isakov, Tanuj Khattar, and Ryan Babbush. Optimization by decoded quantum interferometry. *Nature*, 646(8086):831–836, 2025. doi: 10.1038/s41586-025-09527-5. arXiv:2408.08292.

[2] Tanuj Khattar, Noah Shutty, Craig Gidney, Adam Zalcman, Noureldin Yosri, Dmitri Maslov, Ryan Babbush, and Stephen P. Jordan. Verifiable quantum advantage via optimized DQI circuits, 2025. arXiv:2510.10967v1.

[3] Eugene Prange. The use of information sets in decoding cyclic codes. *IRE Transactions on Information Theory*, 8(5):5–9, 1962. doi: 10.1109/TIT.1962.1057777.

[4] Gábor Szegő. *Orthogonal Polynomials*, volume 23 of *American Mathematical Society Colloquium Publications*. American Mathematical Society, Providence, RI, 4th edition, 1975.