Welcome to TIPS

Technical Interview Preperation System

Username

Enter your username

Password

Enter your password

Login

Create Account

Hello, JohnGamecock! 👋

Ready to sharpen your coding skills today?

5 Days

Current Streak - Keep it up!

View Questions

Browse and solve coding problems from various courses

Explore Questions

Daily Challenge

Take on today's challenge and maintain your streak

Start Challenge

Your Progress

Problems Solved
24

Courses Active
3

Achievements
7

Daily Challenge

Friday, April 3, 2026

Maximum Subarray

Medium C++ • CSCE 350

Problem Description

Given an integer array nums, find the subarray with the largest sum, and return its sum.

Example 1:
Input: nums = [-2,1,-3,4,-1,2,1,-5,4]
Output: 6
Explanation: The subarray [4,-1,2,1] has the largest sum 6.

Example 2:
Input: nums = [1]
Output: 1
Explanation: The subarray [1] has the largest sum 1.

Hint

Try Kadane's algorithm. Keep track of the maximum sum ending at the current position and the overall maximum sum.

Test Cases

Input: [-2,1,-3,4,-1,2,1,-5,4]
Expected Output: 6

Input: [1]
Expected Output: 1

Start Solving

Your Streak

5
Days

Complete today's challenge to increase your streak!

Challenge Stats

Completed
12 / 30

Success Rate
92%

Leaderboard

1.	EmmaWilson	28
2.	JohnGamecock	24
3.	AlexTech	21
4.	SarahCoder	18

Questions

Search questions...

All Courses

All Difficulties

All Languages

Two Sum Easy

Language: Java • Course: CSCE 146

Solve

Valid Parentheses Easy

Language: Java • Course: CSCE 146

Solve

Merge Two Sorted Lists Easy

Language: Java • Course: CSCE 146

Solve

Binary Search Tree Validation Medium

Language: C++ • Course: CSCE 350

Solve

Longest Palindromic Substring Medium

Language: C++ • Course: CSCE 350

Solve

Graph Cycle Detection Hard

Language: C++ • Course: CSCE 350

Solve

Back to Questions

Valid Parentheses

Easy Java • CSCE 146

Problem Description

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:
1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

Example 1:
Input: s = "()"
Output: true

Example 2:
Input: s = "()[]{}"
Output: true

Example 3:
Input: s = "(]"
Output: false

Hint

Test Cases

Input: "()"

Expected Output: true

Input: "()[]{}"

Expected Output: true

Input: "(]"

Expected Output: false

Write Code

View Solution

Discussion

Problem Stats

Acceptance Rate	68.5%
Total Submissions	1,247
Total Accepted	854

Back to Problem

Valid Parentheses

Easy

Given a string s containing just the characters '(', ')', '{', '}', '[' and ']', determine if the input string is valid.

An input string is valid if:
1. Open brackets must be closed by the same type of brackets.
2. Open brackets must be closed in the correct order.
3. Every close bracket has a corresponding open bracket of the same type.

Example 1:
Input: s = "()"
Output: true

Example 2:
Input: s = "()[]{}"
Output: true

Example 3:
Input: s = "(]"
Output: false

Test Cases

Input: "()"
Output: true

Input: "()[]{}"
Output: true

Input: "(]"
Output: false

Code Editor

Java

Write your code here...

Run Code

Submit