

TP Docker

Boris Teabe

boris.teabe@inp-toulouse.fr

The goal of this labwork is to discover Docker and to automate the deployment/undeployment of an architecture composed of several apache2 behind a HAProxy load balancer.

1. Connection

You must be connected to N7 with the VPN and be connected to a N7 machine with your studentID. Use the following commands to access your server :

```
ssh <your enseeiht user name>@<an enseeiht machine>.enseeiht.fr
```

Type your enseeiht password.

```
ssh ubuntu@147.127.121.11 -p 130XX
```

Where XX=01-40. This will give you access to a VM with IP address 192.168.27.(XX+10) and the password is "toto"

```
sudo bash
```

2. Installation

Docker installation with a simple command

```
# Run once when preparing the VM

apt-get update
apt-get install -y ca-certificates curl uidmap dbus-user-session \
    slirp4netns fuse-overlayfs

install -m 0755 -d /etc/apt/keyrings

curl -fsSL https://download.docker.com/linux/ubuntu/gpg \
    | sudo tee /etc/apt/keyrings/docker.asc > /dev/null

chmod a+r /etc/apt/keyrings/docker.asc

echo \
    "deb [arch=$(dpkg --print-architecture) signed-by=/etc/apt/keyrings/docker.asc]
https://download.docker.com/linux/ubuntu \
    $(. /etc/os-release && echo "${UBUNTU_CODENAME:-$VERSION_CODENAME}") stable" \
    | sudo tee /etc/apt/sources.list.d/docker.list > /dev/null

apt-get update
```

```
apt-get install -y \
    docker-ce \
    docker-ce-cli \
    containerd.io \
    docker-buildx-plugin \
    docker-compose-plugin \
    docker-ce-rootless-extras

systemctl disable --now docker.service docker.socket

exit

dockerd-rootless-setup tool.sh install
```

Test your installation

```
systemctl --user status docker

docker run hello-world
```

Change docker repository due to hub limitations

```
cat << EOF > /etc/docker/daemon.json
{
    "registry-mirrors": ["http://192.168.0.1:5000"]
}
EOF

systemctl restart docker
```

3. Using docker

Download a Ubuntu image from the hub

```
docker pull ubuntu
```

We will use this image in the following.

List the images you have locally, each image has a name, tag and ID

```
docker images
```

You can remove an image with

```
docker rmi -f hello-world
```

you can start a container with

```
docker run -it --name mycontainer ubuntu /bin/bash
```

To get the container IP address type

Type « **exit** » to exit from a container

you can list all your containers (from another terminal) with

```
docker ps -a
```

and get containerIDs. To restart a container use :

```
docker start <containerID or container name>
```

To connect back to a container console do

```
docker attach <containerID>
```

You can customize your container

```
apt-get update  
apt-get install apache2
```

Then, save an image of the container (from another terminal) with

```
docker commit mycontainer myimage
```

You can stop your container (from another terminal) with

```
docker stop mycontainer
```

You can remove your container (from another terminal) with

```
docker rm mycontainer
```

For all these commands, you can use names or IDs as well

Question1: Which user are you inside the container? How can you be `root` inside the container while Docker itself is running as a non-root user on the host?

Question 2: Compare the processes visible with `ps aux` inside the container and on the host. Why are they different?

Question 3: Does `exit` destroy the container? Use a Docker command to verify your answer.

Question 4: What is the difference between an **image** and a **container**? Can several containers be created from the same image?

4. Dockerfile

You can create a Docker image by describing it in a Dockerfile. In a directory "apache", create a file Dockerfile.

```
#Here we create a container image where apache2 is installed
FROM kiritigowda/ubuntu-16.04
RUN apt-get update
ARG DEBIAN_FRONTEND=noninteractive
RUN apt-get install -y apache2
RUN apt-get install -y php7.0
RUN apt-get install -y php7.0-intl
RUN apt-get install -y libapache2-mod-php7.0
COPY index.php /var/www/html/
COPY start-apache2.sh /tmp/
CMD /tmp/start-apache2.sh
EXPOSE 80
```

You have to download the Hello.war which is a little webapp

```
wget --no-check-certificate 'https://docs.google.com/uc?
export=download&id=1zpbjIhA6sBV0h8Y81wocGqTndnVtu-ZS' -O index.php
wget --no-check-certificate 'https://docs.google.com/uc?
export=download&id=1mDsUcMVphKWZpccapaGNLXJzG8PgQyT3' -O haproxy.cfg
```

start-apache2.sh is a script for starting apache2 .

```
#!/bin/bash
/etc/init.d/apache2 start
sleep infinity
```

Add index.php and start-apache2.sh in the apache directory.

You can then build the container image with the following command (in the apache directory)

```
chmod +x start-apache2.sh
docker build -t apache:v1 .
```

You can start an instance of this image.

```
docker run -d --name hello apache:v1
```

You can get the IP address from the container with: `docker inspect containerID`

You can access the webapp with the URL

```
wget <ip-address>:80/index.php
```

Question 5: What advantage does a Dockerfile provide compared with manually modifying a container and using `docker commit`?

5. Implementing an architecture

The figure presents the target architecture (final goal).

5.1 First step:

Create two containers

1. one for apache (as in Section 3)
2. one for HAProxy (the image is already available on the hub)

HAProxy is configured by a file `/usr/local/etc/haproxy/haproxy.cfg`

`haproxy.cfg` is a template of that file (given) where you can add lines

```
server server1 <ip-of-apache>:80 maxconn 32
```

you can test that it works with one HAProxy and one apache. You can implement a script which creates these two images

Start the Haproxy container

```
docker pull haproxy
docker run -v <local absolute path to haproxy.cfg>:/usr/local/etc/haproxy/haproxy.cfg
haproxy
```

Test your configuration with

```
wget <Ip address of Haproxy container>:80/index.php
```

5.2 Second step:

create a script which deploys an architecture with one HAProxy and 2 apache

You can create a network (bridge) for your instances

```
docker network create mynet
```

You can start your apache instances in that network with

```
docker run -d --rm --net mynet --hostname ap1 --name ap1 apache:v1
```

You can add you apache instances in the HAProxy configuration file with

```
echo "server server1 ap1:80 maxconn 32" >> haproxy.cfg
```

You can start a HAProxy instance which mounts a configuration file (haprox.cfg) which is local to the host system.

```
docker run -d --rm --net mynet --name hp -v <local absolute path of
haproxy.cfg>:/usr/local/etc/haproxy/haproxy.cfg haprox
```

6. Docker compose

Reproduce the previous architecture using docker compose

Install docker-compose

```
sudo curl -L "https://github.com/docker/compose/releases/download/1.27.4/docker-  
compose-$(uname -s)-$(uname -m)" -o /usr/local/bin/docker-compose  
sudo chmod +x /usr/local/bin/docker-compose
```

Create the docker-compose.yml file (you can start from this content)

```
version: '3'  
services:  
  tc1:  
    image: apache:v1  
    hostname: ap1  
    ports:  
      - 80  
    networks:  
      - mynet  
  myhaproxy:  
    image: haproxy  
    depends_on:  
      - ap1  
    volumes:  
      - <local path to haproxy.cfg>:/usr/local/etc/haproxy/haproxy.cfg  
    ports:  
      - 80:80  
    networks:  
      - mynet  
networks:  
  mynet:  
    driver: bridge
```

```
docker-compose up
```