

Tuning Machine Learning Algorithms with mlr3

mlr3tuning

Department of Statistics – LMU Munich



Intro

TUNING

- Behavior of most methods depends on *hyperparameters*

TUNING

- Behavior of most methods depends on *hyperparameters*
- We want to choose them so our algorithm performs well

TUNING

- Behavior of most methods depends on *hyperparameters*
- We want to choose them so our algorithm performs well
- Good hyperparameters are data-dependent

TUNING

- Behavior of most methods depends on *hyperparameters*
 - We want to choose them so our algorithm performs well
 - Good hyperparameters are data-dependent
- ⇒ We do *black box optimization* (“Try stuff and see what works”)

TUNING


- Behavior of most methods depends on *hyperparameters*
 - We want to choose them so our algorithm performs well
 - Good hyperparameters are data-dependent
- ⇒ We do *black box optimization* (“Try stuff and see what works”)

Tuning toolbox for mlr3:


```
library("bbotk")  
library("mlr3tuning")
```

Tuning

TUNING





TUNING




Start



TUNING




TUNING




TUNING





TUNING




TUNING




TUNING




TUNING




TUNING





TUNING




TUNING




TUNING




TUNING





TUNING




Batch evaluation




TUNING




TUNING



TUNING




TUNING




Tuning in mlr3


OBJECTS IN TUNING




OBJECTS IN TUNING



SEARCH SPACE




SEARCH SPACE



```
ParamSet$new(list(param1, param2, ...))
```


SEARCH SPACE



```
ParamSet$new(list(param1, param2, ...))
```

Numerical parameter

```
ParamDbl$new(id, lower, upper)
```

Integer parameter

```
ParamInt$new(id, lower, upper)
```

Discrete parameter

```
ParamFct$new(id, levels)
```


Logical parameter

```
ParamLgl$new(id)
```

Untyped parameter

```
ParamUty$new(id)
```

SEARCH SPACE



```
ParamSet$new(list(param1, param2, ...))
```

Numerical parameter ParamDbl\$new(id, lower, upper)

Integer parameter ParamInt\$new(id, lower, upper)

Discrete parameter ParamFct\$new(id, levels)

Logical parameter ParamLgl\$new(id)

Untyped parameter ParamUty\$new(id)

```
library("paradox")
searchspace_knn = ParamSet$new(list(
  ParamInt$new("k", 1, 20)
))
```

TERMINATION

- Tuning needs a *termination condition*: when to finish

TERMINATION

- Tuning needs a *termination condition*: when to finish
- Terminator class

TERMINATION

- Tuning needs a *termination condition*: when to finish
- Terminator class
- `mlr_terminators` dictionary, `trm()` short form

TERMINATION

- Tuning needs a *termination condition*: when to finish
- Terminator class
- `mlr_terminators` dictionary, `trm()` short form

- `as.data.table(mlr_terminators)`

```
#>               key
#> 1:      clock_time
#> 2:           combo
#> 3:           evals
#> 4:             none
#> 5:    perf_reached
#> 6:         run_time
#> 7:      stagnation
#> 8: stagnation_batch
```

TERMINATION

- Tuning needs a *termination condition*: when to finish
- Terminator class
- `mlr_terminators` dictionary, `trm()` short form

- `as.data.table(mlr_terminators)`

```
#>               key
#> 1:      clock_time
#> 2:           combo
#> 3:           evals
#> 4:           none
#> 5:    perf_reached
#> 6:       run_time
#> 7:      stagnation
#> 8: stagnation_batch
```

- `trm("evals", n_evals = 20)`

```
#> <TerminatorEvals>
#> * Parameters: n_evals=20
```

TUNING METHOD

- need to choose a *tuning method*

TUNING METHOD

- need to choose a *tuning method*
- Tuner class

TUNING METHOD

- need to choose a *tuning method*
- Tuner class
- `mlr_tuners` dictionary, `tnr()` short form

TUNING METHOD

- need to choose a *tuning method*
- Tuner class
- `mlr_tuners` dictionary, `tnr()` short form

- `as.data.table(mlr_tuners)`

```
#>           key
#> 1: design_points
#> 2:          gensa
#> 3:   grid_search
#> 4:         nloptr
#> 5: random_search
```

TUNING METHOD

- load Tuner with `tnr()`, set parameters

TUNING METHOD

- load Tuner with `tnr()`, set parameters

- `gsearch = tnr("grid_search", resolution = 3)`

```
print(gsearch)
#> <TunerGridSearch>
#> * Parameters: resolution=3, batch_size=1
#> * Parameter classes: ParamLgl, ParamInt, ParamDbl, ParamFct
#> * Properties: dependencies, single-crit, multi-crit
#> * Packages: -
```

TUNING METHOD


- load Tuner with `tnr()`, set parameters

- `gsearch = tnr("grid_search", resolution = 3)`


```
print(gsearch)
#> <TunerGridSearch>
#> * Parameters: resolution=3, batch_size=1
#> * Parameter classes: ParamLgl, ParamInt, ParamDbl, ParamFct
#> * Properties: dependencies, single-crit, multi-crit
#> * Packages: -
```

- common parameter `batch_size` for parallelization

CALLING THE TUNER



CALLING THE TUNER



```
inst = TuningInstanceSingleCrit$new(  
  tsk("iris"), lrn("classif.kknn", kernel="rectangular"),  
  rsmp("holdout"), msr("classif.ce"),  
  searchspace_knn, trm("none")  
)
```


CALLING THE TUNER

```
gsearch$optimize(inst)
```

```
#>      k learner_param_vals  x_domain classif.ce
```

```
#> 1: 10          <list[2]> <list[1]>         0.04
```

TUNING RESULTS


```
gsearch = tnr("grid_search", resolution = 20)

inst = TuningInstanceSingleCrit$new(
  tsk("iris"), lrn("classif.kknn", kernel="rectangular"), rsmp("holdout"),
  msr("classif.ce"), searchspace_knn, trm("none"))

gsearch$optimize(inst)

#>      k learner_param_vals  x_domain classif.ce
#> 1: 14          <list[2]> <list[1]>         0.02

ggplot(inst$archive$data(),
  aes(x = k, y = classif.ce)) + geom_line() + geom_point()
```



RECAP

```
inst = TuningInstanceSingleCrit$new(  
  tsk("iris"), lrn("classif.kknn", kernel="rectangular"),  
  rsmp("holdout"), msr("classif.ce"),  
  searchspace_knn, trm("evals", n_evals = 2)  
)  
  
gsearch = tnr("grid_search", resolution = 3)  
  
gsearch$optimize(inst)  
  
#>    k learner_param_vals  x_domain classif.ce  
#> 1: 1                <list[2]> <list[1]>      0.06
```

Parameter Transformation

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

- Part of ParamSet

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

- Part of ParamSet

Example:

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

- Part of `ParamSet`

Example:

- 1 optimize from $\log(1) \dots \log(100)$ (`k_before_trafo`)

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

- Part of `ParamSet`

Example:

- 1 optimize from $\log(1) \dots \log(100)$ (`k_before_trafo`)
- 2 transform by $\exp()$ in `trafo` function

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

- Part of ParamSet

Example:

- 1 optimize from $\log(1) \dots \log(100)$ (`k_before_trafo`)
- 2 transform by $\exp()$ in `trafo` function
- 3 don't forget to round (k must be integer)

PARAMETER TRANSFORMATION

- Sometimes we do not want to optimize over an evenly spaced range
- $k = 1$ vs. $k = 2$ probably more interesting than $k = 101$ vs. $k = 102$

⇒ Transformations

- Part of ParamSet

Example:

- 1 optimize from $\log(1) \dots \log(100)$ (`k_before_trafo`)
- 2 transform by $\exp()$ in `trafo` function
- 3 don't forget to round (k must be integer)

```
searchspace_knn_trafo = ParamSet$new(list(  
  ParamDbl$new("k_before_trafo", log(1), log(50))  
))  
searchspace_knn_trafo$trafo = function(x, param_set) {  
  return(list(k = round(exp(x$k_before_trafo))))  
}
```

PARAMETER TRANSFORMATION

What is our transformation doing?





PARAMETER TRANSFORMATION

What is our transformation doing?




PARAMETER TRANSFORMATION

What is our transformation doing?



PARAMETER TRANSFORMATION

What is our transformation doing?



PARAMETER TRANSFORMATION

Tuning again...

PARAMETER TRANSFORMATION

Tuning again...

```
inst$result


#>      k_before_trafo learner_param_vals  x_domain classif.ce
#> 1:                0.98                <list[2]> <list[1]>      0

inst$result$x_domain


#> [[1]]
#> [[1]]$k
#> [1] 3
```

PARAMETER TRANSFORMATION

```
ggplot(inst$archive$data(),  
  aes(x = k_before_trafo, y = classif.ce)) + geom_line() + geom_point()
```




```
ggplot(inst$archive$data(unnest = "x_domain"),  
  aes(x = x_domain_k, y = classif.ce)) + geom_line() + geom_point()
```



Nested Resampling

NESTED RESAMPLING

- Need to perform nested resampling to estimate tuned learner performance
- ⇒ Treat tuning as if it were a Learner!
- Training:
 - 1 Tune model using (inner) resampling
 - 2 Train final model with best parameters on all (i.e. outer resampling) data
 - Predicting: Just use final model



NESTED RESAMPLING

```
optlrn = AutoTuner$new(lrn("classif.kknn", kernel="rectangular"),  
  rsmp("holdout"), msr("classif.ce"), searchspace_knn,  
  trm("none"), tnr("grid_search", resolution = 10))
```


```
optlrn$train(tsk("iris"))
```

```
optlrn$model$learner
```

```
#> <LearnerClassifKKNN:classif.kknn>  
#> * Model: list  
#> * Parameters: kernel=rectangular, k=5  
#> * Packages: kknn  
#> * Predict Type: response  
#> * Feature types: logical, integer, numeric, factor, ordered  
#> * Properties: multiclass, twoclass
```

NESTED RESAMPLING

```
ggplot(optltn$model$tuning_instance$archive$data(),  
  aes(x = k, y = classif.ce)) + geom_line() + geom_point() + xlab("")
```



NESTED RESAMPLING

```
result = resample(tsk("iris"), optlrn, rsmp("holdout"),  
  store_models = TRUE)  
ggplot(result$learners[[1]]$  
  model$tuning_instance$archive$data(),  
  aes(x = k, y = classif.ce)) + geom_line() + geom_point() + xlab("")
```

