

Namespace Aplib.Core

Classes

[Combinators](#)

Convenience class containing static methods for creating goal structures and tactics.

[LiftingExtensionMethods](#)

Contains extension methods for lifting BDI cycle components into higher-order components.

[Metadata](#)

Data structure to store information about a component which may be useful for debugging or logging.

Interfaces

[ICompletable](#)

Defines an object that can be completed.

[IDocumented](#)

Represents an object that contains general information on an instance, such as [IMetadata](#).

[IMetadata](#)

A collection of generic metadata for unique instances which should help visualise the instance with human-readable information.

Enums

[CompletionStatus](#)

Represents the state of a completable object.

Class Combinators

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll

Convenience class containing static methods for creating goal structures and tactics.

```
public static class Combinators
```

Inheritance

[object](#)  ← Combinators

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Methods

AnyOf<TBeliefSet>(IMetadata, params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified sub-tactics and an optional guard condition.

```
public static AnyOfTactic<TBeliefSet> AnyOf<TBeliefSet>(IMetadata metadata, params  
ITactic<TBeliefSet>[] subTactics) where TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Returns

[AnyOfTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

AnyOf<TBeliefSet>(IMetadata, Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified sub-tactics and an optional guard condition.

```
public static AnyOfTactic<TBeliefSet> AnyOf<TBeliefSet>(IMetadata metadata,
Func<TBeliefSet, bool> guard, params ITactic<TBeliefSet>[] subTactics) where
TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Returns

[AnyOfTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

AnyOf<TBeliefSet>(params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified sub-tactics and an optional guard condition.

```
public static AnyOfTactic<TBeliefSet> AnyOf<TBeliefSet>(params ITactic<TBeliefSet>[]  
subTactics) where TBeliefSet : IBeliefSet
```

Parameters

subTactics [ITactic](#)<TBeliefSet>[]

The list of sub-tactics.

Returns

[AnyOfTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

AnyOf<TBeliefSet>(Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified sub-tactics and an optional guard condition.

```
public static AnyOfTactic<TBeliefSet> AnyOf<TBeliefSet>(Func<TBeliefSet, bool>  
guard, params ITactic<TBeliefSet>[] subTactics) where TBeliefSet : IBeliefSet
```

Parameters

guard [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

subTactics [ITactic](#)<TBeliefSet>[]

The list of sub-tactics.

Returns

[AnyOfTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

FirstOf<TBeliefSet>(params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [FirstOfGoalStructure<TBeliefSet>](#) class.

```
public static FirstOfGoalStructure<TBeliefSet> FirstOf<TBeliefSet>(params  
IGoalStructure<TBeliefSet>[] children) where TBeliefSet : IBeliefSet
```

Parameters

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

Returns

[FirstOfGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

FirstOf<TBeliefSet>(IMetadata, params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [FirstOfGoalStructure<TBeliefSet>](#) class.

```
public static FirstOfGoalStructure<TBeliefSet> FirstOf<TBeliefSet>(IMetadata  
metadata, params IGoalStructure<TBeliefSet>[] children) where TBeliefSet  
: IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

Returns

[FirstOfGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

FirstOf<TBeliefSet>(IMetadata, params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified sub-tactics and guard condition.

```
public static FirstOfTactic<TBeliefSet> FirstOf<TBeliefSet>(IMetadata metadata,  
params ITactic<TBeliefSet>[] subTactics) where TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Returns

[FirstOfTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

FirstOf<TBeliefSet>(IMetadata, Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified sub-tactics and guard condition.

```
public static FirstOfTactic<TBeliefSet> FirstOf<TBeliefSet>(IMetadata metadata,
Func<TBeliefSet, bool> guard, params ITactic<TBeliefSet>[] subTactics) where
TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

guard [Func](#) <TBeliefSet, [bool](#)>

The guard condition.

subTactics [ITactic](#) <TBeliefSet>[]

The list of subtactics.

Returns

[FirstOfTactic](#) <TBeliefSet>

Type Parameters

TBeliefSet

FirstOf<TBeliefSet>(params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified sub-tactics and guard condition.

```
public static FirstOfTactic<TBeliefSet> FirstOf<TBeliefSet>(params  
ITactic<TBeliefSet>[] subTactics) where TBeliefSet : IBeliefSet
```

Parameters

`subTactics` [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Returns

[FirstOfTactic](#)<TBeliefSet>

Type Parameters

`TBeliefSet`

FirstOf<TBeliefSet>(Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified subtactics and guard condition.

```
public static FirstOfTactic<TBeliefSet> FirstOf<TBeliefSet>(Func<TBeliefSet, bool>  
guard, params ITactic<TBeliefSet>[] subTactics) where TBeliefSet : IBeliefSet
```

Parameters

`guard` [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

`subTactics` [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Returns

[FirstOfTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IGoal<TBeliefSet>)

Initializes a new instance of the [PrimitiveGoalStructure<TBeliefSet>](#) class.

```
public static PrimitiveGoalStructure<TBeliefSet> Primitive<TBeliefSet>  
(IGoal<TBeliefSet> goal) where TBeliefSet : IBeliefSet
```

Parameters

goal [IGoal](#)<TBeliefSet>

The goal to fulfill.

Returns

[PrimitiveGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IMetadata, IGoal<TBeliefSet>)

Initializes a new instance of the [PrimitiveGoalStructure<TBeliefSet>](#) class.

```
public static PrimitiveGoalStructure<TBeliefSet> Primitive<TBeliefSet>(IMetadata  
metadata, IGoal<TBeliefSet> goal) where TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

goal [IGoal](#)<TBeliefSet>

The goal to fulfill.

Returns

[PrimitiveGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IMetadata, IAction<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>(IMetadata metadata,
    IAction<TBeliefSet> action) where TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IMetadata, IAction<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>(IMetadata metadata,  
    IAction<TBeliefSet> action, Func<TBeliefSet, bool> guard) where TBeliefSet  
    : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IMetadata, IQueryable<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>(IMetadata metadata,  
    IQueryable<TBeliefSet> query) where TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

query [IQueryable](#)<TBeliefSet>

Returns

[PrimitiveTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IMetadata, IQueryable<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>(IMetadata metadata,
    IQueryable<TBeliefSet> query, Func<TBeliefSet, bool> guard) where TBeliefSet
    : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

query [IQueryable](#)<TBeliefSet>

guard [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IAction<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>(IAction<TBeliefSet>  
action) where TBeliefSet : IBeliefSet
```

Parameters

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IAction<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>(IAction<TBeliefSet>  
action, Func<TBeliefSet, bool> guard) where TBeliefSet : IBeliefSet
```

Parameters

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

guard [Func](#) <TBeliefSet, [bool](#)>

The guard of the primitive tactic.

Returns

[PrimitiveTactic](#) <TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IQueryable<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>  
(IQueryable<TBeliefSet> query) where TBeliefSet : IBeliefSet
```

Parameters

query [IQueryable](#) <TBeliefSet>

Returns

[PrimitiveTactic](#) <TBeliefSet>

Type Parameters

TBeliefSet

Primitive<TBeliefSet>(IQueryable<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public static PrimitiveTactic<TBeliefSet> Primitive<TBeliefSet>  
(IQueryable<TBeliefSet> query, Func<TBeliefSet, bool> guard) where TBeliefSet  
: IBeliefSet
```

Parameters

`query` [IQueryable](#)<TBeliefSet>

`guard` [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

Type Parameters

TBeliefSet

Repeat<TBeliefSet>(IGoalStructure<TBeliefSet>)

Initializes a new instance of the [RepeatGoalStructure<TBeliefSet>](#) class.

```
public static RepeatGoalStructure<TBeliefSet> Repeat<TBeliefSet>  
(IGoalStructure<TBeliefSet> goalStructure) where TBeliefSet : IBeliefSet
```

Parameters

`goalStructure` [IGoalStructure](#)<TBeliefSet>

The GoalStructure to repeat.

Returns

[RepeatGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

Repeat<TBeliefSet>(IMetadata, IGoalStructure<TBeliefSet>)

Initializes a new instance of the [RepeatGoalStructure<TBeliefSet>](#) class.

```
public static RepeatGoalStructure<TBeliefSet> Repeat<TBeliefSet>(IMetadata metadata,
    IGoalStructure<TBeliefSet> goalStructure) where TBeliefSet : IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this goal, used to quickly display the goal in several contexts.

goalStructure [IGoalStructure](#)<TBeliefSet>

The GoalStructure to repeat.

Returns

[RepeatGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

Seq<TBeliefSet>(params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [SequentialGoalStructure<TBeliefSet>](#) class.

```
public static SequentialGoalStructure<TBeliefSet> Seq<TBeliefSet>(params
    IGoalStructure<TBeliefSet>[] children) where TBeliefSet : IBeliefSet
```

Parameters

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

Returns

[SequentialGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

Seq<TBeliefSet>(IMetadata, params
IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [SequentialGoalStructure](#)<TBeliefSet> class.

```
public static SequentialGoalStructure<TBeliefSet> Seq<TBeliefSet>(IMetadata  
metadata, params IGoalStructure<TBeliefSet>[] children) where TBeliefSet  
: IBeliefSet
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

Returns

[SequentialGoalStructure](#)<TBeliefSet>

Type Parameters

TBeliefSet

Enum CompletionStatus

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll

Represents the state of a completable object.

```
public enum CompletionStatus
```

Fields

Failure = 2

Represents the status of a completable object that has failed to complete.

Success = 1

Represents the status of a completable object that has been successfully completed.

Unfinished = 0

Represents the status of a completable object that is not yet completed.

Interface ICompletable

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll

Defines an object that can be completed.

```
public interface ICompletable
```

Properties

Status

Gets the completion status of the object.

```
CompletionStatus Status { get; }
```

Property Value

[CompletionStatus](#)

Interface IDocumented

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll

Represents an object that contains general information on an instance, such as [IMetadata](#).

```
public interface IDocumented
```

Properties

Metadata

Gets the metadata of the instance.

```
IMetadata Metadata { get; }
```

Property Value

[IMetadata](#)

Interface IMetadata

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll

A collection of generic metadata for unique instances which should help visualise the instance with human-readable information.

```
public interface IMetadata
```

Properties

Description

Gets the description used to describe the instance.

```
string? Description { get; }
```

Property Value

[string](#)

Id

Gets the unique identifier of the instance.

```
Guid Id { get; }
```

Property Value

[Guid](#)

Name

Gets the name used to display the instance.

```
string? Name { get; }
```

Property Value

[string](#)

Class LiftingExtensionMethods

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll








Contains extension methods for lifting BDI cycle components into higher-order components.

```
public static class LiftingExtensionMethods
```

Inheritance

[object](#)  ← LiftingExtensionMethods

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Methods

Lift<TBeliefSet>(IGoalStructure<TBeliefSet>)

Wraps a goal structure into a desire set.

```
public static DesireSet<TBeliefSet> Lift<TBeliefSet>(this IGoalStructure<TBeliefSet>  
goalStructure) where TBeliefSet : IBeliefSet
```

Parameters

goalStructure [IGoalStructure](#)<TBeliefSet>

The goal structure which on its own can function as a desire set. Meaning, the desire set consists of just a single goal structure.

Returns

[DesireSet](#)<TBeliefSet>

A desire set.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IGoalStructure<TBeliefSet>, IMetadata)

Wraps a goal structure into a desire set.

```
public static DesireSet<TBeliefSet> Lift<TBeliefSet>(<this IGoalStructure<TBeliefSet>  
goalStructure, IMetadata metadata) where TBeliefSet : IBeliefSet
```

Parameters

goalStructure [IGoalStructure](#)<TBeliefSet>

The goal structure which on its own can function as a desire set. Meaning, the desire set consists of just a single goal structure.

metadata [IMetadata](#)

Optional metadata to be assigned to the desire set.

Returns

[DesireSet](#)<TBeliefSet>

A desire set.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IGoal<TBeliefSet>)

Wraps a goal into a goal structure.

```
public static PrimitiveGoalStructure<TBeliefSet> Lift<TBeliefSet>(<this  
IGoal<TBeliefSet> goal) where TBeliefSet : IBeliefSet
```


Parameters

goal [IGoal](#)<TBeliefSet>

The goal which on its own can function as a goal structure. Meaning, the goal structure consists of just a single goal.

Returns

[PrimitiveGoalStructure](#)<TBeliefSet>

A primitive goal structure.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IGoal<TBeliefSet>, IMetadata)

Wraps a goal into a goal structure.

```
public static PrimitiveGoalStructure<TBeliefSet> Lift<TBeliefSet>(this  
    IGoal<TBeliefSet> goal, IMetadata metadata) where TBeliefSet : IBeliefSet
```

Parameters

goal [IGoal](#)<TBeliefSet>

The goal which on its own can function as a goal structure. Meaning, the goal structure consists of just a single goal.

metadata [IMetadata](#)

Optional metadata to be assigned to the goal structure.

Returns

[PrimitiveGoalStructure](#)<TBeliefSet>

A primitive goal structure.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IAction<TBeliefSet>)

Wraps a normal action into a tactic.

```
public static PrimitiveTactic<TBeliefSet> Lift<TBeliefSet>(this IAction<TBeliefSet>  
action) where TBeliefSet : IBeliefSet
```

Parameters

action [IAction](#)<TBeliefSet>

The action which on its own can function as a tactic. Meaning, the tactic consists of just a single action.

Returns

[PrimitiveTactic](#)<TBeliefSet>

A primitive tactic, whose guard always returns true.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IAction<TBeliefSet>, IMetadata)

Wraps a normal action into a tactic.

```
public static PrimitiveTactic<TBeliefSet> Lift<TBeliefSet>(this IAction<TBeliefSet>  
action, IMetadata metadata) where TBeliefSet : IBeliefSet
```

Parameters

action [IAction](#)<TBeliefSet>

The action which on its own can function as a tactic. Meaning, the tactic consists of just a single action.

metadata [IMetadata](#)

Optional metadata to be assigned to the tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

A primitive tactic, whose guard always returns true.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IQueryable<TBeliefSet>)

Wraps a queryable action into a tactic.

```
public static PrimitiveTactic<TBeliefSet> Lift<TBeliefSet>(this  
IQueryable<TBeliefSet> action) where TBeliefSet : IBeliefSet
```

Parameters

action [IQueryable](#)<TBeliefSet>

The action which on its own can function as a tactic. Meaning, the tactic consists of just a single action.

Returns

[PrimitiveTactic](#)<TBeliefSet>

A primitive tactic, whose guard always returns true.

Type Parameters

TBeliefSet

Lift<TBeliefSet>(IQueryable<TBeliefSet>, IMetadata)

Wraps a queryable action into a tactic.

```
public static PrimitiveTactic<TBeliefSet> Lift<TBeliefSet>(this  
IQueryable<TBeliefSet> action, IMetadata metadata) where TBeliefSet : IBeliefSet
```

Parameters

action [IQueryable](#)<TBeliefSet>

The action which on its own can function as a tactic. Meaning, the tactic consists of just a single action.

metadata [IMetadata](#)

Optional metadata to be assigned to the tactic.

Returns

[PrimitiveTactic](#)<TBeliefSet>

A primitive tactic, whose guard always returns true.

Type Parameters

TBeliefSet

Class Metadata

Namespace: [Aplib.Core](#)

Assembly: Aplib.Core.dll

Data structure to store information about a component which may be useful for debugging or logging.

```
public class Metadata : IMetadata
```








Inheritance

[object](#)  ← Metadata

Implements

[IMetadata](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Constructors

Metadata(string?, string?)


Store information about a BDI cycle component which may be useful for debugging or logging or general overviews.

```
public Metadata(string? name = null, string? description = null)
```

Parameters

name [string](#) 

The name used to display the component.

description [string](#) 

The description used to describe the component.

Properties

Description

Gets the description used to describe the instance.

```
public string? Description { get; }
```

Property Value

[string](#)

Id

Gets the unique identifier of the instance.

```
public Guid Id { get; }
```

Property Value

[Guid](#)

Name

Gets the name used to display the instance.

```
public string? Name { get; }
```

Property Value

[string](#)

Namespace Aplib.Core.Agents

Classes

[BdiAgent<TBeliefSet>](#)

Represents an agent that performs actions based on goals and beliefs.

Interfaces

[IAgent](#)

Defines an agent that can play a game.

Class BdiAgent<TBeliefSet>

Namespace: [Aplib.Core.Agents](#)

Assembly: Aplib.Core.dll

Represents an agent that performs actions based on goals and beliefs.

```
public class BdiAgent<TBeliefSet> : IAgent, ICompletable where TBeliefSet
    : IBeliefSet
```

Type Parameters

TBeliefSet








Inheritance

[object](#)  ← BdiAgent<TBeliefSet>

Implements

[IAgent](#), [ICompletable](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Constructors

BdiAgent(TBeliefSet, IDesireSet<TBeliefSet>)

Initializes a new instance of the [BdiAgent<TBeliefSet>](#) class.

```
public BdiAgent(TBeliefSet beliefSet, IDesireSet<TBeliefSet> desireSet)
```

Parameters

beliefSet TBeliefSet

The beliefset of the agent.

desireSet [IDesireSet](#)<TBeliefSet>

Properties

Status

Gets the completion status of the object.

```
public CompletionStatus Status { get; }
```

Property Value

[CompletionStatus](#)

Methods

Update()

Performs a single BDI cycle, in which the agent updates its beliefs, selects a concrete goal, chooses a concrete action to achieve the selected goal, and executes the chosen action.

```
public void Update()
```

Remarks

This method will get called every frame of the game.

Interface IAgent

Namespace: [Aplib.Core.Agents](#)

Assembly: Aplib.Core.dll

Defines an agent that can play a game.

```
public interface IAgent : ICompletable
```

Inherited Members

[ICompletable.Status](#)

Methods

Update()

Updates the agent's state and goals.

```
void Update()
```

Remarks

This method will get called every frame of the game.

Namespace Aplib.Core.Belief.BeliefSets

Classes

[BeliefSet](#)

The [BeliefSet](#) class can be inherited to define a set of beliefs for an agent. All *public fields* of type [IBelief](#) that are defined in the inheriting class are automatically updated when calling [UpdateBeliefs\(\)](#).

Interfaces

[IBeliefSet](#)

A belief set defines beliefs for an agent.

Class BeliefSet


Namespace: [Aplib.Core.Belief.BeliefSets](#)

Assembly: Aplib.Core.dll

The [BeliefSet](#) class can be inherited to define a set of beliefs for an agent. All *public fields* of type [IBelief](#) that are defined in the inheriting class are automatically updated when calling [UpdateBeliefs\(\)](#).

```
public abstract class BeliefSet : IBeliefSet
```








Inheritance

[object](#)  ← BeliefSet

Implements

[IBeliefSet](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Constructors

BeliefSet()

Initializes a new instance of the [BeliefSet](#) class, and stores all *public fields* of type [IBelief](#) (that have been defined in the inheriting class) in an array. All public [IBelief](#) fields are then automatically updated when calling [UpdateBeliefs\(\)](#).

```
protected BeliefSet()
```

Methods

UpdateBeliefs()

Updates all objects of type [IBelief](#) that are defined as *public fields* in the inheriting class.

```
public void UpdateBeliefs()
```

Interface IBeliefSet

Namespace: [Aplib.Core.Belief.BeliefSets](#)

Assembly: Aplib.Core.dll

A belief set defines beliefs for an agent.

```
public interface IBeliefSet
```

Methods

UpdateBeliefs()

Updates all beliefs in the belief set.

```
void UpdateBeliefs()
```

Namespace Aplib.Core.Belief.Beliefs

Classes

[Belief<TReference, TObservation>](#)

The [Belief<TReference, TObservation>](#) class represents the agent's belief of a single object. Some *object reference* is used to generate/update an *observation* (i.e., some piece of information of the game state as perceived by an agent).

[ListBelief<TReference, TObservation>](#)

A convenience variant of [Belief<TReference, TObservation>](#) to track multiple references in one belief. Both the collection storing the references and the references themselves can be changed after the [ListBelief<TReference, TObservation>](#) has been created.

[MemoryBelief<TReference, TObservation>](#)

The [MemoryBelief<TReference, TObservation>](#) class represents the agent's belief of a single object, but with additional "memory" of previous observations. Some *object reference* is used to generate/update an *observation* (i.e., some piece of information on the game state as perceived by an agent). This belief also stores a limited amount of previous observations in memory.

[SampledMemoryBelief<TReference, TObservation>](#)

The [SampledMemoryBelief<TReference, TObservation>](#) class represents the agent's belief of a single object, but with additional "memory" of previous observations. These observations are sampled at a fixed rate. Some *object reference* is used to generate/update an *observation* (i.e., some piece of information on the game state as perceived by an agent). This belief also stores a limited amount of previous observation samples in memory. Optionally, the belief can always store the most recent observation, regardless of the sample rate.

Interfaces

[IBelief](#)

A belief represents/encapsulates an observation (i.e., piece of information of the game state as perceived by an agent).

Enums

[UpdateMode](#)

Specifies the update mode of a sampled memory belief.

Class Belief<TReference, TObservation>

Namespace: [Aplib.Core.Belief.Beliefs](#)

Assembly: Aplib.Core.dll

The [Belief<TReference, TObservation>](#) class represents the agent's belief of a single object. Some *object reference* is used to generate/update an *observation* (i.e., some piece of information of the game state as perceived by an agent).

```
public class Belief<TReference, TObservation> : IBelief where TReference : class
```

Type Parameters

TReference

The type of the object reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if **TReference** is an interface.

TObservation

The type of the observation that the belief represents.

Inheritance

[object](#)  ← [Belief<TReference, TObservation>](#)








Implements

[IBelief](#)

Derived

[ListBelief<TReference, TObservation>](#), [MemoryBelief<TReference, TObservation>](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Remarks

It supports implicit conversion to **TObservation**.

Constructors

Belief(Metadata, TReference, Func<TReference, TObservation>)

Initializes a new instance of the [Belief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated.

```
public Belief(Metadata metadata, TReference reference, Func<TReference, TObservation> getObservationFromReference)
```

Parameters

metadata [Metadata](#)

Metadata about this Belief, used to quickly display the goal in several contexts.

reference TReference

The object reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if TReference is an interface.

getObservationFromReference [Func](#)<TReference, TObservation>

A function that takes an object reference and generates/updates an observation.

Exceptions

[ArgumentException](#)

Thrown when **reference** is not a reference type.

Belief(Metadata, TReference, Func<TReference, TObservation>, Func<bool>)

Initializes a new instance of the [Belief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated.

```
public Belief(Metadata metadata, TReference reference, Func<TReference,
TObservation> getObservationFromReference, Func<bool> shouldUpdate)
```

Parameters

metadata [Metadata](#)

Metadata about this Belief, used to quickly display the goal in several contexts.

reference TReference

The object reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if TReference is an interface.

getObservationFromReference [Func](#) <TReference, TObservation>

A function that takes an object reference and generates/updates an observation.

shouldUpdate [Func](#) <[bool](#)>

A condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when **reference** is not a reference type.

Belief(TReference, Func<TReference, TObservation>)

Initializes a new instance of the [Belief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated.

```
public Belief(TReference reference, Func<TReference, TObservation>
getObservationFromReference)
```

Parameters

reference TReference

The object reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if `TReference` is an interface.

`getObservationFromReference` [Func](#) <TReference, TObservation>

A function that takes an object reference and generates/updates an observation.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

Belief(TReference, Func<TReference, TObservation>, Func<bool>)

Initializes a new instance of the [Belief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated.

```
public Belief(TReference reference, Func<TReference, TObservation>  
getObservationFromReference, Func<bool> shouldUpdate)
```

Parameters

`reference` TReference

The object reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if `TReference` is an interface.

`getObservationFromReference` [Func](#) <TReference, TObservation>

A function that takes an object reference and generates/updates an observation.

`shouldUpdate` [Func](#) <[bool](#)>

A condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

Fields

`_getObservationFromReference`

A function that takes an object reference and generates/updates an observation.

```
protected readonly Func<TReference, TObservation> _getObservationFromReference
```

Field Value

[Func](#)  <TReference, TObservation>

`_reference`

The object reference used to generate/update the observation.

```
protected readonly TReference _reference
```

Field Value

TReference

`_shouldUpdate`

A condition on when the observation should be updated.

```
protected readonly Func<bool> _shouldUpdate
```

Field Value

[Func](#)  <[bool](#)  >

Properties

Metadata

Gets the metadata of the Belief.

```
public Metadata Metadata { get; }
```

Property Value

[Metadata](#)

Observation

The observation represented by the belief (i.e., some piece of information of the game state as perceived by an agent).

```
public TObservation Observation { get; protected set; }
```

Property Value

TObservation

Methods

UpdateBelief()

Generates/updates the observation if the shouldUpdate condition is satisfied. The observation is then updated by calling the getObservationFromReference function.

```
public virtual void UpdateBelief()
```

UpdateObservation()

Generates/updates the observation.

```
protected void UpdateObservation()
```

Operators

implicit operator TObservation(Belief<TReference, TObservation>)

Implicit conversion operator to allow a [Belief<TReference, TObservation>](#) object to be used where a `TObservation` is expected.

```
public static implicit operator TObservation(Belief<TReference,  
TObservation> belief)
```

Parameters

`belief` [Belief](#)<TReference, TObservation>

The [Belief<TReference, TObservation>](#) object to convert.

Returns

`TObservation`

Interface IBelief

Namespace: [Aplib.Core.Belief.Beliefs](#)

Assembly: Aplib.Core.dll

A belief represents/encapsulates an observation (i.e., piece of information of the game state as perceived by an agent).

```
public interface IBelief
```

Methods

UpdateBelief()

Updates the belief based on information of the game state.

```
void UpdateBelief()
```

Class ListBelief<TReference, TObservation>

Namespace: [Aplib.Core.Belief.Beliefs](#)

Assembly: Aplib.Core.dll

A convenience variant of [Belief<TReference, TObservation>](#) to track multiple references in one belief. Both the collection storing the references and the references themselves can be changed after the [ListBelief<TReference, TObservation>](#) has been created.

```
public class ListBelief<TReference, TObservation> : Belief<IEnumerable<TReference>,
List<TObservation>>, IBelief
```

Type Parameters





TReference

The type of the object references used to generate/update the observation.

TObservation

The type of the observations that the belief represents.

Inheritance

[object](#)  ← [Belief](#)  [IEnumerable](#)  [TReference](#)>, [List](#)  [TObservation](#)>> ← [ListBelief](#)<[TReference](#), [TObservation](#)>

Implements

[IBelief](#)

Inherited Members

[Belief<IEnumerable<TReference>, List<TObservation>>._reference](#) ,
[Belief<IEnumerable<TReference>, List<TObservation>>._getObservationFromReference](#) ,
[Belief<IEnumerable<TReference>, List<TObservation>>._shouldUpdate](#) ,
[Belief<IEnumerable<TReference>, List<TObservation>>.Metadata](#) ,
[Belief<IEnumerable<TReference>, List<TObservation>>.Observation](#) ,
[Belief<IEnumerable<TReference>, List<TObservation>>.UpdateBelief\(\)](#) ,
[Belief<IEnumerable<TReference>, List<TObservation>>.UpdateObservation\(\)](#) ,
[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,

[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Remarks

A [ListBelief<TReference, TObservation>](#) can be implicitly converted to a [List<T>](#), which will have the same size as the reference collection the last time that [UpdateBelief\(\)](#) was called, and contain the observation results for each element in the collection.

Constructors

ListBelief(Metadata, IEnumerable<TReference>, Func<TReference, TObservation>)

Initializes a new instance of the [ListBelief<TReference, TObservation>](#) class from an object reference collection, a function to generate an observation from an object reference, and optionally an update guard.

```
public ListBelief(Metadata metadata, IEnumerable<TReference> references,
    Func<TReference, TObservation> getObservationFromReference)
```

Parameters

metadata [Metadata](#)

Metadata about this Belief, used to quickly display the goal in several contexts.

references [IEnumerable](#) <TReference>

The collection of reference objects. The underlying type implementing [IEnumerable<T>](#) *must* be a reference type, note that this is not enforced by C#.

getObservationFromReference [Func](#) <TReference, TObservation>

A function that takes an object reference and generates an observation.

Exceptions

[ArgumentException](#)

Thrown when **references** is not a reference type.

ListBelief(Metadata, IEnumerable<TReference>, Func<TReference, TObservation>, Func<bool>)

Initializes a new instance of the [ListBelief<TReference, TObservation>](#) class from an object reference collection, a function to generate an observation from an object reference, and optionally an update guard.

```
public ListBelief(Metadata metadata, IEnumerable<TReference> references,
    Func<TReference, TObservation> getObservationFromReference, Func<bool> shouldUpdate)
```

Parameters

metadata [Metadata](#)

Metadata about this Belief, used to quickly display the goal in several contexts.

references [IEnumerable](#)<TReference>

The collection of reference objects. The underlying type implementing [IEnumerable<T>](#) *must* be a reference type, note that this is not enforced by C#.

getObservationFromReference [Func](#)<TReference, TObservation>

A function that takes an object reference and generates an observation.

shouldUpdate [Func](#)<[bool](#)>

A condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when **references** is not a reference type.

ListBelief(IEnumerable<TReference>, Func<TReference, TObservation>)

Initializes a new instance of the [ListBelief<TReference, TObservation>](#) class from an object reference collection, a function to generate an observation from an object reference, and optionally an update guard.

```
public ListBelief(IEnumerable<TReference> references, Func<TReference,
TObservation> getObservationFromReference)
```

Parameters

references [IEnumerable](#) <TReference>

The collection of reference objects. The underlying type implementing [IEnumerable<T>](#) *must* be a reference type, note that this is not enforced by C#.

getObservationFromReference [Func](#) <TReference, TObservation>

A function that takes an object reference and generates an observation.

Exceptions

[ArgumentException](#)

Thrown when **references** is not a reference type.

ListBelief(IEnumerable<TReference>, Func<TReference, TObservation>, Func<bool>)

Initializes a new instance of the [ListBelief<TReference, TObservation>](#) class from an object reference collection, a function to generate an observation from an object reference, and optionally an update guard.

```
public ListBelief(IEnumerable<TReference> references, Func<TReference, TObservation>
getObservationFromReference, Func<bool> shouldUpdate)
```

Parameters

references [IEnumerable](#) <TReference>

The collection of reference objects. The underlying type implementing [IEnumerable<T>](#) *must* be a reference type, note that this is not enforced by C#.

getObservationFromReference [Func](#) <TReference, TObservation>

A function that takes an object reference and generates an observation.

shouldUpdate [Func](#) <[bool](#)>

A condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when `references` is not a reference type.

Class MemoryBelief<TReference, TObservation>

Namespace: [Aplib.Core.Belief.Beliefs](#)

Assembly: Aplib.Core.dll

The [MemoryBelief<TReference, TObservation>](#) class represents the agent's belief of a single object, but with additional "memory" of previous observations. Some *object reference* is used to generate/update an *observation* (i.e., some piece of information on the game state as perceived by an agent). This belief also stores a limited amount of previous observations in memory.

```
public class MemoryBelief<TReference, TObservation> : Belief<TReference, TObservation>, IBelief where TReference : class
```

Type Parameters

TReference

The type of the reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if **TReference** is an interface.

TObservation

The type of the observation the belief represents.

Inheritance

[object](#)  [Belief](#)<TReference, TObservation>  MemoryBelief<TReference, TObservation>

Implements

[IBelief](#)

Derived

[SampledMemoryBelief<TReference, TObservation>](#)

Inherited Members

[Belief<TReference, TObservation>._reference](#) ,
[Belief<TReference, TObservation>._getObservationFromReference](#) ,
[Belief<TReference, TObservation>._shouldUpdate](#) ,
[Belief<TReference, TObservation>.Metadata](#) ,

[Belief<TReference, TObservation>.Observation](#) ,
[Belief<TReference, TObservation>.UpdateBelief\(\)](#) ,
[Belief<TReference, TObservation>.UpdateObservation\(\)](#) , [object.Equals\(object\)](#) ,
[object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#)

Remarks

It supports implicit conversion to `TObservation`.

Constructors

MemoryBelief(Metadata, TReference, Func<TReference, TObservation>, int)

Initializes a new instance of the [MemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. Also initializes the memory array with a specified number of slots.

```
public MemoryBelief(Metadata metadata, TReference reference, Func<TReference,  
TObservation> getObservationFromReference, int framesToRemember)
```

Parameters

`metadata` [Metadata](#)

Metadata about this Belief, used to quickly display the goal in several contexts.

`reference` `TReference`

The reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if `TReference` is an interface.

`getObservationFromReference` [Func](#) <TReference, TObservation>

A function that takes a reference and generates/updates a observation.

`framesToRemember` [int](#)

The number of frames to remember back.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

MemoryBelief(Metadata, TReference, Func<TReference, TObservation>, int, Func<bool>)

Initializes a new instance of the [MemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. Also initializes the memory array with a specified number of slots.

```
public MemoryBelief(Metadata metadata, TReference reference, Func<TReference, TObservation> getObservationFromReference, int framesToRemember, Func<bool> shouldUpdate)
```

Parameters

`metadata` [Metadata](#)

Metadata about this Belief, used to quickly display the goal in several contexts.

`reference` TReference

The reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if TReference is an interface.

`getObservationFromReference` [Func](#) <TReference, TObservation>

A function that takes a reference and generates/updates a observation.

`framesToRemember` [int](#)

The number of frames to remember back.

`shouldUpdate` [Func](#) <[bool](#)>

A function that sets a condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

MemoryBelief(TReference, Func<TReference, TObservation>, int)

Initializes a new instance of the [MemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. Also initializes the memory array with a specified number of slots.

```
public MemoryBelief(TReference reference, Func<TReference, TObservation>
getObservationFromReference, int framesToRemember)
```

Parameters

`reference` TReference

The reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if TReference is an interface.

`getObservationFromReference` [Func](#)<TReference, TObservation>

A function that takes a reference and generates/updates a observation.

`framesToRemember` [int](#)

The number of frames to remember back.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

MemoryBelief(TReference, Func<TReference, TObservation>, int, Func<bool>)

Initializes a new instance of the [MemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. Also initializes the memory array with a specified number of slots.

```
public MemoryBelief(TReference reference, Func<TReference, TObservation>  
getObservationFromReference, int framesToRemember, Func<bool> shouldUpdate)
```

Parameters

reference [TReference](#)

The reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if [TReference](#) is an interface.

getObservationFromReference [Func](#)<[TReference](#), [TObservation](#)>

A function that takes a reference and generates/updates a observation.

framesToRemember [int](#)

The number of frames to remember back.

shouldUpdate [Func](#)<[bool](#)>

A function that sets a condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when [reference](#) is not a reference type.

Fields

[_memorizedObservations](#)

A "memorized" resource, from the last time the belief was updated.

```
protected readonly ExposedQueue<TObservation> _memorizedObservations
```

Field Value

[ExposedQueue](#)<TObservation>

Methods

GetAllMemories()

Gets all the memorized observations. The first element is the newest memory.

```
public TObservation[] GetAllMemories()
```

Returns

TObservation[]

An array of all the memorized observations.

GetMemoryAt(int, bool)

Gets the memorized observation at a specific index. A higher index means a memory further back in time.

```
public TObservation GetMemoryAt(int index, bool clamp = false)
```

Parameters

index [int](#)

The index of the memory to get.

clamp [bool](#)

If true, the index will be clamped between 0 and the last memory index.

Returns

TObservation

The memory of the observation at the specified index.

GetMostRecentMemory()

Gets the most recently memorized observation.

```
public TObservation GetMostRecentMemory()
```

Returns

TObservation

The most recent memory of the observation.

UpdateBelief()

Generates/updates the observation. Also stores the previous observation in memory.

```
public override void UpdateBelief()
```

Class SampledMemoryBelief<TReference, TObservation>

Namespace: [Aplib.Core.Belief.Beliefs](#)

Assembly: Aplib.Core.dll

The [SampledMemoryBelief<TReference, TObservation>](#) class represents the agent's belief of a single object, but with additional "memory" of previous observations. These observations are sampled at a fixed rate. Some *object reference* is used to generate/update an *observation* (i.e., some piece of information on the game state as perceived by an agent). This belief also stores a limited amount of previous observation samples in memory. Optionally, the belief can always store the most recent observation, regardless of the sample rate.

```
public class SampledMemoryBelief<TReference, TObservation> :  
    MemoryBelief<TReference, TObservation>, IBelief where TReference : class
```

Type Parameters


TReference

The type of the reference used to generate/update the observation. This *must* be a reference type, be aware that this is not enforced by C# if **TReference** is an interface.

TObservation

The type of the observation the belief represents.

Inheritance

[object](#)  ← [Belief](#)<TReference, TObservation> ←
[MemoryBelief](#)<TReference, TObservation> ←
SampledMemoryBelief<TReference, TObservation>

Implements

[IBelief](#)

Inherited Members

[MemoryBelief<TReference, TObservation>._memorizedObservations](#) ,
[MemoryBelief<TReference, TObservation>.UpdateBelief\(\)](#) ,
[MemoryBelief<TReference, TObservation>.GetMostRecentMemory\(\)](#) ,

[MemoryBelief<TReference, TObservation>.GetMemoryAt\(int, bool\)](#) ,
[MemoryBelief<TReference, TObservation>.GetAllMemories\(\)](#) ,
[Belief<TReference, TObservation>._reference](#) ,
[Belief<TReference, TObservation>._getObservationFromReference](#) ,
[Belief<TReference, TObservation>._shouldUpdate](#) ,
[Belief<TReference, TObservation>.Metadata](#) ,
[Belief<TReference, TObservation>.Observation](#) ,
[Belief<TReference, TObservation>.UpdateBelief\(\)](#) ,
[Belief<TReference, TObservation>.UpdateObservation\(\)](#) , [object.Equals\(object\)](#)[↗] ,
[object.Equals\(object, object\)](#)[↗] , [object.GetHashCode\(\)](#)[↗] , [object.GetType\(\)](#)[↗] ,
[object.MemberwiseClone\(\)](#)[↗] , [object.ReferenceEquals\(object, object\)](#)[↗] , [object.ToString\(\)](#)[↗]

Remarks

It supports implicit conversion to `TObservation`.

Constructors

SampledMemoryBelief(Metadata, TReference, Func<TReference, TObservation>, int, UpdateMode, int)

Initializes a new instance of the [SampledMemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. This belief also stores a limited amount of previous observation samples in memory. Optionally, the belief can always store the most recent observation, regardless of the sample rate.

```
public SampledMemoryBelief(Metadata metadata, TReference reference, Func<TReference, TObservation> getObservationFromReference, int sampleInterval, UpdateMode updateMode, int framesToRemember)
```

Parameters

`metadata` [Metadata](#)

Metadata about this goal, used to quickly display the goal in several contexts.

`reference` `TReference`

The reference used to generate/update the observation. This *must* be a reference type.

`getObservationFromReference` [Func](#) <TReference, TObservation>

A function that takes a reference and generates/updates an observation.

`sampleInterval` [int](#)

The sample interval of the memory. One observation memory (i.e., snapshot) is stored every `sampleInterval`-th cycle.

`updateMode` [UpdateMode](#)

Specifies how this sampled memory belief should be updated.

`framesToRemember` [int](#)

The number of frames to remember back.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

SampledMemoryBelief(Metadata, TReference, Func<TReference, TObservation>, int, UpdateMode, int, Func<bool>)

Initializes a new instance of the [SampledMemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. This belief also stores a limited amount of previous observation samples in memory. Optionally, the belief can always store the most recent observation, regardless of the sample rate.

```
public SampledMemoryBelief(Metadata metadata, TReference reference, Func<TReference, TObservation> getObservationFromReference, int sampleInterval, UpdateMode updateMode, int framesToRemember, Func<bool> shouldUpdate)
```

Parameters

`metadata` [Metadata](#)

Metadata about this goal, used to quickly display the goal in several contexts.

`reference` [TReference](#)

The reference used to generate/update the observation. This *must* be a reference type.

`getObservationFromReference` [Func](#) [<TReference, TObservation>](#)

A function that takes a reference and generates/updates an observation.

`sampleInterval` [int](#)

The sample interval of the memory. One observation memory (i.e., snapshot) is stored every `sampleInterval`-th cycle.

`updateMode` [UpdateMode](#)

Specifies how this sampled memory belief should be updated.

`framesToRemember` [int](#)

The number of frames to remember back.

`shouldUpdate` [Func](#) [<bool>](#)

A function that sets a condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

SampledMemoryBelief(TReference, Func<TReference, TObservation>, int, UpdateMode, int)

Initializes a new instance of the [SampledMemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. This belief also stores a limited amount of previous observation samples in memory. Optionally, the belief can always store the most recent observation, regardless of the sample rate.

```
public SampledMemoryBelief(TReference reference, Func<TReference, TObservation>
getObservationFromReference, int sampleInterval, UpdateMode updateMode,
int framesToRemember)
```

Parameters

`reference` [TReference](#)

The reference used to generate/update the observation. This *must* be a reference type.

`getObservationFromReference` [Func](#) <[TReference](#), [TObservation](#)>

A function that takes a reference and generates/updates an observation.

`sampleInterval` [int](#)

The sample interval of the memory. One observation memory (i.e., snapshot) is stored every `sampleInterval`-th cycle.

`updateMode` [UpdateMode](#)

Specifies how this sampled memory belief should be updated.

`framesToRemember` [int](#)

The number of frames to remember back.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

SampledMemoryBelief(TReference, Func<TReference, TObservation>, int, UpdateMode, int, Func<bool>)

Initializes a new instance of the [SampledMemoryBelief<TReference, TObservation>](#) class with an object reference, a function to generate/update the observation using the object reference, and a condition on when the observation should be updated. This belief also stores a limited amount of previous observation samples in memory. Optionally, the belief can always store the most recent observation, regardless of the sample rate.

```
public SampledMemoryBelief(TReference reference, Func<TReference, TObservation>
getObservationFromReference, int sampleInterval, UpdateMode updateMode, int
framesToRemember, Func<bool> shouldUpdate)
```


Parameters

`reference` [TReference](#)

The reference used to generate/update the observation. This *must* be a reference type.

`getObservationFromReference` [Func](#) <[TReference](#), [TObservation](#)>

A function that takes a reference and generates/updates an observation.

`sampleInterval` [int](#)

The sample interval of the memory. One observation memory (i.e., snapshot) is stored every `sampleInterval`-th cycle.

`updateMode` [UpdateMode](#)

Specifies how this sampled memory belief should be updated.

`framesToRemember` [int](#)

The number of frames to remember back.

`shouldUpdate` [Func](#) <[bool](#)>

A function that sets a condition on when the observation should be updated.

Exceptions

[ArgumentException](#)

Thrown when `reference` is not a reference type.

Methods

UpdateBelief()

Generates/updates the observation if applicable. Also stores the previous observation in memory every `sampleInterval`-th cycle.

```
public override void UpdateBelief()
```

Enum UpdateMode

Namespace: [Aplib.Core.Belief.Beliefs](#)

Assembly: Aplib.Core.dll

Specifies the update mode of a sampled memory belief.

```
public enum UpdateMode
```

Fields

`AlwaysUpdate = 0`

Update the observation every cycle.

`UpdateWhenSampled = 1`

Update the observation whenever a memory sample is stored.

Namespace Aplib.Core.Collections

Classes

[CircularArray<T>](#)

An array that wraps around when it reaches its end. Functionally works like a queue with indexing.

[ExposedQueue<T>](#)

A queue with all elements exposed. Functionally works like a queue with indexing. It has a MaxCount and Count. MaxCount being the maximal length of the queue, and Count being the actual number of elements in the queue.

[OptimizedActivationStack<T>](#)

A stack that has a predefined set of items that can be *activated* (i.e., pushed on top of the stack). When an item that is already on the stack is activated, it is *reactivated* (i.e., moved to the top of the stack).

[OptimizedActivationStack<T>.StackItem](#)

Represents (i.e., encapsulates) an item on the activation stack.

Class CircularArray<T>

Namespace: [Aplib.Core.Collections](#)

Assembly: Aplib.Core.dll

An array that wraps around when it reaches its end. Functionally works like a queue with indexing.

```
public class CircularArray<T>
```

Type Parameters

T

Inheritance

[object](#)  ← CircularArray<T>

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Constructors

CircularArray(int)

Initializes a new instance of the [CircularArray<T>](#) class.

```
public CircularArray(int size)
```

Parameters

size [int](#) 

The size of the array.

CircularArray(T[])

Initializes a new instance of the [CircularArray<T>](#) class.

```
public CircularArray(T[] array)
```

Parameters

array T[]

An array to use as the circular array.

Properties

this[int]

Gets the element at the specified index.

```
public T this[int index] { get; set; }
```

Parameters

index [int](#)

The index of the element to get.

Property Value

T

The element at the specified index.

Length

The length of the array.

```
public int Length { get; }
```

Property Value

Methods

GetFirst()

Gets the first element of the array.

```
public T GetFirst()
```

Returns

T

The last element of the array

GetHead()

Gets the element at the head of the array.

```
public T GetHead()
```

Returns

T

The element at the head of the array

Put(T)

Puts an element at the start of the array.

```
public void Put(T value)
```

Parameters

value T

The element to add to the array

ToArray(int, int)

Converts the circular array to an array. The head should be the last element of the array. Copies from start to end inclusive.

```
public T[] ToArray(int start = 0, int end = -1)
```

Parameters

start [int](#)

The start index of the range to copy.

end [int](#)

The end index of the range to copy.

Returns

T[]

The circular array as a normal array

Class ExposedQueue<T>

Namespace: [Aplib.Core.Collections](#)

Assembly: Aplib.Core.dll


A queue with all elements exposed. Functionally works like a queue with indexing. It has a MaxCount and Count. MaxCount being the maximal length of the queue, and Count being the actual number of elements in the queue.

```
public class ExposedQueue<T> : ICollection<T>, IEnumerable<T>, IEnumerable
```

Type Parameters

T








Inheritance

[object](#)  ← ExposedQueue<T>

Implements

[ICollection](#)  <T>, [IEnumerable](#)  <T>, [IEnumerable](#) 

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Remarks

When adding an element to a full queue, all other elements are shifted one place like so:
[4, 3, 2, 1], Put(5) => [5, 4, 3, 2]

Constructors

ExposedQueue(int)

Initializes a new empty instance of the [ExposedQueue<T>](#) class.

```
public ExposedQueue(int size)
```


Parameters

size [int](#)

The maximum size of the queue.

ExposedQueue(T[])

Initializes a new instance of the [ExposedQueue<T>](#) class with an array to use as basis for the queue. By default, assumes the array is filled.

```
public ExposedQueue(T[] array)
```

Parameters

array T[]

An array to use as the circular array.

Remarks

The MaxCount of the queue will be set to the length of the array. If the array is not fully filled, the Count should be specified.

ExposedQueue(T[], int)

Initializes a new instance of the [ExposedQueue<T>](#) class with an array to use as basis for the queue. By default, assumes the array is filled.

```
public ExposedQueue(T[] array, int count)
```

Parameters

array T[]

An array to use as the circular array.

count [int](#)

The number of actual elements in the array.

Remarks

The MaxCount of the queue will be set to the length of the array. If the array is not fully filled, the Count should be specified.

Properties

Count


Actual number of elements in the array.

```
public int Count { get; }
```

Property Value

[int](#)




IsReadOnly

Gets a value indicating whether the [ICollection<T>](#) is read-only.

```
public bool IsReadOnly { get; }
```

Property Value

[bool](#)

[true](#) if the [ICollection<T>](#) is read-only; otherwise, [false](#).

this[int]

Gets the element at the specified index. Throws an exception if the index is out of bounds.

```
public T this[int index] { get; }
```

Parameters

index [int](#)

The index of the element to get.

Property Value

T

The element at the specified index.

Exceptions

[ArgumentOutOfRangeException](#)

Thrown when the index is out of range.

MaxCount

The length of the array.

```
public int MaxCount { get; }
```

Property Value

[int](#)

Methods

Add(T)

Adds an item to the [ICollection<T>](#).

```
public void Add(T item)
```

Parameters

item T

The object to add to the [ICollection<T>](#).

Exceptions

[NotSupportedException](#)

The [ICollection<T>](#) is read-only.

Clear()

Removes all items from the [ICollection<T>](#).

```
public void Clear()
```

Exceptions

[NotSupportedException](#)

The [ICollection<T>](#) is read-only.

Contains(T)

Determines whether the [ICollection<T>](#) contains a specific value.

```
public bool Contains(T item)
```

Parameters

item T

The object to locate in the [ICollection<T>](#).

Returns

[bool](#)

[true](#) if **item** is found in the [ICollection<T>](#); otherwise, [false](#).

CopyTo(T[], int)

Copies the elements of the [ICollection<T>](#) to an [Array](#), starting at a particular [Array](#) index.

```
public void CopyTo(T[] array, int arrayIndex)
```

Parameters

array [T\[\]](#)

The one-dimensional [Array](#) that is the destination of the elements copied from [ICollection<T>](#). The [Array](#) must have zero-based indexing.

arrayIndex [int](#)

The zero-based index in **array** at which copying begins.

Exceptions

[ArgumentNullException](#)

array is [null](#).

[ArgumentOutOfRangeException](#)

arrayIndex is less than 0.

[ArgumentException](#)

The number of elements in the source [ICollection<T>](#) is greater than the available space from **arrayIndex** to the end of the destination **array**.

CopyTo(T[], int, int)

Copies the ExposedQueue to an array. The head should be the last element of the array. Copies from start to end inclusive.

```
public void CopyTo(T[] array, int arrayIndex, int endIndex)
```

Parameters

array [T\[\]](#)

The array to copy to."

`arrayIndex` [int](#)

The start index of the range to copy.

`endIndex` [int](#)

The end index of the range to copy.

GetEnumerator()

Returns an enumerator that iterates through the collection.

```
public IEnumerator<T> GetEnumerator()
```

Returns

[IEnumerator](#) <T>

An enumerator that can be used to iterate through the collection.

GetFirst()

Gets the first element of the queue.

```
public T GetFirst()
```

Returns

T

The first element of the queue.

GetLast()

Gets the element at the end of the queue.

```
public T GetLast()
```

Returns

T

The element at the end of the queue.

Put(T)

Puts an element at the start of the queue.

```
public void Put(T value)
```

Parameters

value T

The element to add to the queue.

Remove(T)

Removes the specified item from the queue and shifts remaining elements to the left. For example, given the queue [4, 3, 2, 1], if you call Remove(3), the resulting queue will be [4, 2, 1].

```
public bool Remove(T item)
```

Parameters

item T

The item to remove.

Returns

[bool](#) 

True if the item was successfully removed; otherwise, false.

Remarks

The MaxCount will not change, but the Count will decrease by one.

ToArray()

Converts the ExposedQueue to an array. Only returns the used slots.

```
public T[] ToArray()
```

Returns

T[]

An array containing the elements within the specified range.

ToArray(int, int)

Converts the ExposedQueue to an array.

```
public T[] ToArray(int start, int end)
```

Parameters

start [int](#)

The start index of the range to convert.

end [int](#)

The end index of the range to convert.

Returns

T[]

An array containing the elements within the specified range.

Class OptimizedActivationStack<T>

Namespace: [Aplib.Core.Collections](#)

Assembly: Aplib.Core.dll

A stack that has a predefined set of items that can be *activated* (i.e., pushed on top of the stack). When an item that is already on the stack is activated, it is *reactivated* (i.e., moved to the top of the stack).

```
public class OptimizedActivationStack<T>
```

Type Parameters








T

The type of the items that are put on the stack.

Inheritance

[object](#)  ← OptimizedActivationStack<T>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Remarks

The [OptimizedActivationStack<T>](#) allows for O(1) activation and reactivation of an arbitrary stack item.

Constructors

OptimizedActivationStack(T[])

Initializes an optimized activation stack with a set of activatable data.

```
public OptimizedActivationStack(T[] activatables)
```

Parameters

activatables T[]

A set of activatable items that could be pushed on the stack.

Properties

ActivatableStackItems

Gets the activatable stack items.

```
public IEnumerable<OptimizedActivationStack<T>.StackItem> ActivatableStackItems {  
    get; }
```

Property Value

[IEnumerable](#)  <[OptimizedActivationStack](#)<T>.[StackItem](#)>

Remarks

The stack items are exposed, since they should be accessible from the outside to provide O(1) activation of a stack item with [Activate\(StackItem\)](#).

Count

Gets the number of items that are currently activated (i.e., on the stack).

```
public int Count { get; }
```

Property Value

[int](#) 

Exceptions

[InvalidOperationException](#) 

Thrown when the stack count is negative.

Methods

Activate(StackItem)

Activates an item (i.e., pushes an item on top of the stack). If the pushed item is already on the stack, it is extracted from the stack before it is put on top again.

```
public void Activate(OptimizedActivationStack<T>.StackItem item)
```

Parameters

item [OptimizedActivationStack<T>.StackItem](#)

The stack item that is pushed on top of the stack (i.e., it is activated).

Exceptions

[ArgumentException](#) 

Thrown when an item is pushed that belongs to a different stack.

Peek()

Peeks the top item from the stack.

```
public T Peek()
```

Returns

T

The top item.

Exceptions

[InvalidOperationException](#) 

Thrown when the stack is empty.

Pop()

Pops the top item from the stack.

```
public T Pop()
```

Returns

T

The popped item.

Exceptions

[InvalidOperationException](#)

Thrown when the stack is empty.

Class

OptimizedActivationStack<T>.StackItem

Namespace: [Aplib.Core.Collections](#)

Assembly: Aplib.Core.dll







Represents (i.e., encapsulates) an item on the activation stack.

```
public sealed class OptimizedActivationStack<T>.StackItem
```

Inheritance

[object](#)  ← OptimizedActivationStack<T>.StackItem

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Remarks

This class is public, because the whole stack item should be accessible from the outside to provide O(1) activation of a stack item with [Activate\(StackItem\)](#).

Constructors

StackItem(T, OptimizedActivationStack<T>)

Creates a stack item for the [OptimizedActivationStack<T>](#) class.

```
public StackItem(T data, OptimizedActivationStack<T> activationStack)
```

Parameters

data T

The data to put on the stack.

activationStack [OptimizedActivationStack<T>](#)

The activation stack instance that this stack item belongs to.

Properties

ActivationStack

Gets the activation stack instance that this stack item belongs to.

```
public OptimizedActivationStack<T> ActivationStack { get; }
```

Property Value

[OptimizedActivationStack<T>](#)

Data

Gets the data that this stack item represents.

```
public T Data { get; }
```

Property Value

T

IsActive

Gets or sets a value indicating whether the item is currently on the stack.

```
public bool IsActive { get; set; }
```

Property Value

[bool](#)

Next

Gets or sets the next (above) item on the stack.

```
public OptimizedActivationStack<T>.StackItem? Next { get; set; }
```

Property Value

[OptimizedActivationStack<T>.StackItem](#)

Previous

Gets or sets the previous (below) item on the stack.

```
public OptimizedActivationStack<T>.StackItem? Previous { get; set; }
```

Property Value

[OptimizedActivationStack<T>.StackItem](#)

Methods

PushOnStackAfter(StackItem)

Pushes an item that is not on the stack yet after another item that is already on the stack.

```
public void PushOnStackAfter(OptimizedActivationStack<T>.StackItem item)
```

Parameters

item [OptimizedActivationStack<T>.StackItem](#)

An item that is already on the stack.

Exceptions

[ArgumentException](#)

Thrown when an item is pushed after an item that is not on the same stack, when an item is already on the stack, or when an item is pushed after an item that is not on the stack.

RemoveFromStack()

Safely remove the item from the stack.

```
public void RemoveFromStack()
```


Namespace Aplib.Core.Desire.DesireSets

Classes

[DesireSet<TBeliefSet>](#)

Interfaces

[IDesireSet<TBeliefSet>](#)

Represents a set of goals that the agent has. This is the main structure that the agent will use to determine what it should do next.

Class DesireSet<TBeliefSet>

Namespace: [Aplib.Core.Desire.DesireSets](#)

Assembly: Aplib.Core.dll

```
public class DesireSet<TBeliefSet> : IDesireSet<TBeliefSet>, ICompletable,
IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet








Inheritance

[object](#)  ← DesireSet<TBeliefSet>

Implements

[IDesireSet](#)<TBeliefSet>, [ICompletable](#), [IDocumented](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Constructors

DesireSet(IGoalStructure<TBeliefSet>, params
(IGoalStructure<TBeliefSet> goalStructure,
Func<TBeliefSet, bool> guard)[])

```
public DesireSet(IGoalStructure<TBeliefSet> mainGoal, params
(IGoalStructure<TBeliefSet> goalStructure, Func<TBeliefSet, bool> guard)
[] sideGoals)
```

Parameters

mainGoal [IGoalStructure](#)<TBeliefSet>

```
sideGoals (IGoalStructure<TBeliefSet> goalStructure, Func<TBeliefSet, bool> guard)[]
```

DesireSet(IMetadata, IGoalStructure<TBeliefSet>, params (IGoalStructure<TBeliefSet> goalStructure, Func<TBeliefSet, bool> guard)[])

Initializes a new instance of the [DesireSet<TBeliefSet>](#) class.

```
public DesireSet(IMetadata metadata, IGoalStructure<TBeliefSet> mainGoal,
params (IGoalStructure<TBeliefSet> goalStructure, Func<TBeliefSet, bool> guard)
[] sideGoals)
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

mainGoal [IGoalStructure](#)<TBeliefSet>

The main goal structure that the agent needs to complete.

```
sideGoals (IGoalStructure<TBeliefSet> goalStructure, Func<TBeliefSet, bool> guard)[]
```

The side goal structures that could be activated during the agent playthrough.

Properties

Metadata

Gets the metadata of the instance.

```
public IMetadata Metadata { get; }
```

Property Value

[IMetadata](#)

Status

If there are no goal structures left to be completed, the status of this desire set is set to the main goal status.

```
public CompletionStatus Status { get; }
```

Property Value

[CompletionStatus](#)

Methods

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
public IGoal<TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[IGoal](#)<TBeliefSet>

The current goal to be fulfilled.

Update(TBeliefSet)

Activates side goal structures when their guard is satisfied, and updates the activation stack by popping goal structures from the top of the stack when they are finished.

```
public void Update(TBeliefSet beliefSet)
```

Parameters

beliefSet `TBeliefSet`

The belief set of the agent.

Operators

implicit operator `DesireSet<TBeliefSet>` `(GoalStructure<TBeliefSet>)`

Implicitly lifts a goal structure a desire set.

```
public static implicit operator DesireSet<TBeliefSet>(GoalStructure<TBeliefSet>  
goalStructure)
```

Parameters

goalStructure `GoalStructure<TBeliefSet>`

The goal structure which on its own can function as a desire set. Meaning, the desire set consists of just a single goal structure.

Returns

`DesireSet<TBeliefSet>`

The most logically matching desire set, wrapping around `goalStructure`.

implicit operator `DesireSet<TBeliefSet>` `(Goal<TBeliefSet>)`

Implicitly lifts a goal into a desire set.

```
public static implicit operator DesireSet<TBeliefSet>(Goal<TBeliefSet> goal)
```

Parameters

`goal` [Goal](#)<TBeliefSet>

The goal which on its own can function as a goal structure. Meaning, the goal structure consists of just a single goal.

Returns

[DesireSet](#)<TBeliefSet>

The most logically matching desire set, wrapping around `goal`.

Interface IDesireSet<TBeliefSet>

Namespace: [Aplib.Core.Desire.DesireSets](#)

Assembly: Aplib.Core.dll

Represents a set of goals that the agent has. This is the main structure that the agent will use to determine what it should do next.

```
public interface IDesireSet<in TBeliefSet> : ICompletable where TBeliefSet
: IBeliefSet
```

Type Parameters

TBeliefSet

Inherited Members

[ICompletable.Status](#)

Methods

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
IGoal<in TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[IGoal](#)<TBeliefSet>

The current goal to be fulfilled.

Update(TBeliefSet)

Updates the status of this [IDesireSet<TBeliefSet>](#).

```
void Update(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Namespace Aplib.Core.Desire.Goal Structures

Classes

[FirstOfGoalStructure<TBeliefSet>](#)

Represents a goal structure that will complete if any of its children complete.

[GoalStructure<TBeliefSet>](#)

Describes a structure of goals that need to be fulfilled.

[PrimitiveGoalStructure<TBeliefSet>](#)

Represents a goal structure that will complete if any of its children complete.

[RepeatGoalStructure<TBeliefSet>](#)

Represents a goal structure that will complete if any of its children complete.

[SequentialGoalStructure<TBeliefSet>](#)

Represents a sequential goal structure.

Interfaces

[IGoalStructure<TBeliefSet>](#)

Represents a goal structure.

Class FirstOfGoalStructure<TBeliefSet>

Namespace: [Aplib.Core.Desire.GoalStructures](#)

Assembly: Aplib.Core.dll

Represents a goal structure that will complete if any of its children complete.

```
public class FirstOfGoalStructure<TBeliefSet> : GoalStructure<TBeliefSet>,
    IGoalStructure<TBeliefSet>, ICompletable, IDocumented, IDisposable where TBeliefSet
    : IBeliefSet
```

Type Parameters

TBeliefSet

The beliefset of the agent.








Inheritance

[object](#)  ← [GoalStructure](#)<TBeliefSet> ← FirstOfGoalStructure<TBeliefSet>

Implements

[IGoalStructure](#)<TBeliefSet>, [ICompletable](#), [IDocumented](#), [IDisposable](#) 

Inherited Members

[GoalStructure<TBeliefSet>.Metadata](#), [GoalStructure<TBeliefSet>._children](#),
[GoalStructure<TBeliefSet>.Status](#), [GoalStructure<TBeliefSet>._currentGoalStructure](#),
[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>\)](#),
[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>, IMetadata\)](#)

Remarks

The children of this goal structure will be executed in the order they are given.

Constructors

FirstOfGoalStructure(params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [FirstOfGoalStructure<TBeliefSet>](#) class.

```
public FirstOfGoalStructure(params IGoalStructure<TBeliefSet>[] children)
```

Parameters

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

FirstOfGoalStructure(IMetadata, params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [FirstOfGoalStructure<TBeliefSet>](#) class.

```
public FirstOfGoalStructure(IMetadata metadata, params IGoalStructure<TBeliefSet>[] children)
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

Methods

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.


```
public void Dispose()
```

Dispose(bool)

Disposes of the goal structure.

```
protected virtual void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

Whether we are actually disposing.

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
public override IGoal<TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet [TBeliefSet](#)

The belief set of the agent.

Returns

[IGoal](#)<[TBeliefSet](#)>

The current goal to be fulfilled.

UpdateStatus(TBeliefSet)

Updates the state of the goal structure.

```
public override void UpdateStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet `TBeliefSet`

The belief set of the agent.

Class GoalStructure<TBeliefSet>

Namespace: [Aplib.Core.Desire.GoalStructures](#)

Assembly: Aplib.Core.dll


Describes a structure of goals that need to be fulfilled.

```
public abstract class GoalStructure<TBeliefSet> : IGoalStructure<TBeliefSet>,
    ICompletable, IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

Inheritance

[object](#)  ← GoalStructure<TBeliefSet>








Implements

[IGoalStructure](#)<TBeliefSet>, [ICompletable](#), [IDocumented](#)

Derived

[FirstOfGoalStructure](#)<TBeliefSet>, [PrimitiveGoalStructure](#)<TBeliefSet>, [RepeatGoalStructure](#)<TBeliefSet>, [SequentialGoalStructure](#)<TBeliefSet>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift](#)<TBeliefSet>(IGoalStructure<TBeliefSet>), [LiftingExtensionMethods.Lift](#)<TBeliefSet>(IGoalStructure<TBeliefSet>, IMetadata)

Constructors

GoalStructure(IMetadata,
IEnumerable<IGoalStructure<TBeliefSet>>)

Initializes a new instance of the [GoalStructure<TBeliefSet>](#) class.

```
protected GoalStructure(IMetadata metadata, IEnumerable<IGoalStructure<TBeliefSet>>
children)
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

children [IEnumerable](#) [IGoalStructure](#)<TBeliefSet>>

The children of the goal structure.

GoalStructure(IEnumerable<IGoalStructure<TBeliefSet>>)

Initializes a new instance of the [GoalStructure<TBeliefSet>](#) class.

```
protected GoalStructure(IEnumerable<IGoalStructure<TBeliefSet>> children)
```

Parameters

children [IEnumerable](#) [IGoalStructure](#)<TBeliefSet>>

The children of the goal structure.

Fields

_children

The children of the goal structure.

```
protected readonly IEnumerable<IGoalStructure<TBeliefSet>> _children
```

Field Value

[IEnumerable](#) [IGoalStructure](#)<TBeliefSet>>

_currentGoalStructure

The goal structure that is currently being fulfilled.

```
protected IGoalStructure<TBeliefSet>? _currentGoalStructure
```

Field Value

[IGoalStructure](#)<TBeliefSet>

Properties

Metadata

Gets the metadata of the instance.

```
public IMetadata Metadata { get; }
```

Property Value

[IMetadata](#)

Status

Gets the completion status of the object.

```
public CompletionStatus Status { get; protected set; }
```

Property Value

[CompletionStatus](#)

Methods

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
public abstract IGoal<TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[IGoal](#)<TBeliefSet>

The current goal to be fulfilled.

UpdateStatus(TBeliefSet)

Updates the state of the goal structure.

```
public abstract void UpdateStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Operators

implicit operator GoalStructure<TBeliefSet>
(Goal<TBeliefSet>)

Implicitly lifts a goal into a goal structure.

```
public static implicit operator GoalStructure<TBeliefSet>(Goal<TBeliefSet> goal)
```

Parameters

`goal` [Goal](#)<TBeliefSet>

The goal which on its own can function as a goal structure. Meaning, the goal structure consists of just a single goal.

Returns

[GoalStructure](#)<TBeliefSet>

The most logically matching goal structure, wrapping around `goal`.

Interface IGoalStructure<TBeliefSet>

Namespace: [Aplib.Core.Desire.GoalStructures](#)

Assembly: Aplib.Core.dll

Represents a goal structure.

```
public interface IGoalStructure<in TBeliefSet> : ICompletable where TBeliefSet
: IBeliefSet
```

Type Parameters

TBeliefSet

The belief set of the agent.

Inherited Members

[ICompletable.Status](#)

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>, IMetadata\)](#)

Remarks

A goal structure is a structure of predicates that must be fulfilled in order to complete a test.

Methods

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
IGoal<in TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[IGoal](#)<TBeliefSet>

The current goal to be fulfilled.

UpdateStatus(TBeliefSet)

Updates the state of the goal structure.

```
void UpdateStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Class PrimitiveGoalStructure<TBeliefSet>

Namespace: [Aplib.Core.Desire.GoalStructures](#)

Assembly: Aplib.Core.dll

Represents a goal structure that will complete if any of its children complete.

```
public class PrimitiveGoalStructure<TBeliefSet> : GoalStructure<TBeliefSet>,
    IGoalStructure<TBeliefSet>, ICompletable, IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The beliefset of the agent.








Inheritance

[object](#)  ← [GoalStructure](#)<TBeliefSet> ← PrimitiveGoalStructure<TBeliefSet>

Implements

[IGoalStructure](#)<TBeliefSet>, [ICompletable](#), [IDocumented](#)

Inherited Members

[GoalStructure<TBeliefSet>.Metadata](#) , [GoalStructure<TBeliefSet>._children](#) ,
[GoalStructure<TBeliefSet>.Status](#) , [GoalStructure<TBeliefSet>._currentGoalStructure](#) ,
[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>, IMetadata\)](#)

Remarks

This is the most primitive goal structure. It is used to represent a single goal that is not part of a larger structure. This goal structure will only return the goal it was created with if the goal is not yet finished.

Constructors

PrimitiveGoalStructure(IGoal<TBeliefSet>)

Initializes a new instance of the [PrimitiveGoalStructure<TBeliefSet>](#) class.

```
public PrimitiveGoalStructure(IGoal<TBeliefSet> goal)
```

Parameters

goal [IGoal](#)<TBeliefSet>

The goal to fulfill.

PrimitiveGoalStructure(IMetadata, IGoal<TBeliefSet>)

Initializes a new instance of the [PrimitiveGoalStructure<TBeliefSet>](#) class.

```
public PrimitiveGoalStructure(IMetadata metadata, IGoal<TBeliefSet> goal)
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

goal [IGoal](#)<TBeliefSet>

The goal to fulfill.

Methods

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
public override IGoal<TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[IGoal](#)<TBeliefSet>

The current goal to be fulfilled.

UpdateStatus(TBeliefSet)

Updates the state of the goal structure.

```
public override void UpdateStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Class RepeatGoalStructure<TBeliefSet>

Namespace: [Aplib.Core.Desire.GoalStructures](#)

Assembly: Aplib.Core.dll

Represents a goal structure that will complete if any of its children complete.

```
public class RepeatGoalStructure<TBeliefSet> : GoalStructure<TBeliefSet>,
IGoalStructure<TBeliefSet>, ICompletable, IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The beliefset of the agent.








Inheritance

[object](#)  ← [GoalStructure](#)<TBeliefSet> ← RepeatGoalStructure<TBeliefSet>

Implements

[IGoalStructure](#)<TBeliefSet>, [ICompletable](#), [IDocumented](#)

Inherited Members

[GoalStructure<TBeliefSet>.Metadata](#) , [GoalStructure<TBeliefSet>._children](#) ,
[GoalStructure<TBeliefSet>.Status](#) , [GoalStructure<TBeliefSet>._currentGoalStructure](#) ,
[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoalStructure<TBeliefSet>, IMetadata\)](#)

Remarks

This structure will repeatedly execute the goal it was created with until the goal is finished.

Constructors

RepeatGoalStructure(IGoalStructure<TBeliefSet>)

Initializes a new instance of the [RepeatGoalStructure<TBeliefSet>](#) class.

```
public RepeatGoalStructure(IGoalStructure<TBeliefSet> goalStructure)
```

Parameters

goalStructure [IGoalStructure](#)<TBeliefSet>

The GoalStructure to repeat.

RepeatGoalStructure(IMetadata, IGoalStructure<TBeliefSet>)

Initializes a new instance of the [RepeatGoalStructure<TBeliefSet>](#) class.

```
public RepeatGoalStructure(IMetadata metadata, IGoalStructure<TBeliefSet>  
goalStructure)
```

Parameters

metadata [IMetadata](#)

Metadata about this goal, used to quickly display the goal in several contexts.

goalStructure [IGoalStructure](#)<TBeliefSet>

The GoalStructure to repeat.

Methods

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
public override IGoal<TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[IGoal](#)<TBeliefSet>

The current goal to be fulfilled.

UpdateStatus(TBeliefSet)

Updates the state of the goal structure.

```
public override void UpdateStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Class

SequentialGoalStructure<TBeliefSet>

Namespace: [Aplib.Core.Desire.GoalStructures](#)

Assembly: Aplib.Core.dll

Represents a sequential goal structure.

```
public class SequentialGoalStructure<TBeliefSet> : GoalStructure<TBeliefSet>,
    IGoalStructure<TBeliefSet>, ICompletable, IDocumented, IDisposable where TBeliefSet
    : IBeliefSet
```

Type Parameters

TBeliefSet

The type of belief set that this goal structure operates on.








Inheritance

[object](#)  ← [GoalStructure](#)[<TBeliefSet>](#) ← [SequentialGoalStructure](#)[<TBeliefSet>](#)

Implements

[IGoalStructure](#)[<TBeliefSet>](#), [ICompletable](#), [IDocumented](#), [IDisposable](#) 

Inherited Members

[GoalStructure](#)[<TBeliefSet>.Metadata](#) , [GoalStructure](#)[<TBeliefSet>._children](#) ,
[GoalStructure](#)[<TBeliefSet>.Status](#) , [GoalStructure](#)[<TBeliefSet>._currentGoalStructure](#) ,
[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift](#)[<TBeliefSet>\(IGoalStructure<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift](#)[<TBeliefSet>\(IGoalStructure<TBeliefSet>, IMetadata\)](#)

Remarks

This class is a specific type of goal structure where goals are processed sequentially. All goals must be completed in order for the goal structure to be completed.

Constructors

SequentialGoalStructure(params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [SequentialGoalStructure<TBeliefSet>](#) class.

```
public SequentialGoalStructure(params IGoalStructure<TBeliefSet>[] children)
```

Parameters

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

SequentialGoalStructure(IMetadata, params IGoalStructure<TBeliefSet>[])

Initializes a new instance of the [SequentialGoalStructure<TBeliefSet>](#) class.

```
public SequentialGoalStructure(IMetadata metadata, params IGoalStructure<TBeliefSet>[] children)
```

Parameters

metadata [IMetadata](#)

Metadata about this GoalStructure, used to quickly display the goal in several contexts.

children [IGoalStructure](#)<TBeliefSet>[]

The children of the goal structure.

Methods

Dispose()

Performs application-defined tasks associated with freeing, releasing, or resetting unmanaged resources.


```
public void Dispose()
```

Dispose(bool)

Disposes the enumerator.

```
protected virtual void Dispose(bool disposing)
```

Parameters

disposing [bool](#)

Whether the object is being disposed.

GetCurrentGoal(TBeliefSet)

Gets the current goal using the given [IBeliefSet](#).

```
public override IGoal<TBeliefSet> GetCurrentGoal(TBeliefSet beliefSet)
```

Parameters

beliefSet [TBeliefSet](#)

The belief set of the agent.

Returns

[IGoal](#)<[TBeliefSet](#)>

The current goal to be fulfilled.

UpdateStatus(TBeliefSet)

Updates the state of the goal structure.

```
public override void UpdateStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Namespace Aplib.Core.Desire.Goals

Classes

[CommonHeuristicFunctions<TBeliefSet>](#)

Contains helper methods to generate commonly used heuristic functions.

[Goal<TBeliefSet>](#)

A goal effectively combines a heuristic function with a tactic, and aims to meet the heuristic function by applying the tactic. Goals are combined in a

[GoalStructure<TBeliefSet>](#), and are used to prepare tests or do the testing.

[Heuristics](#)

Contains all information on how close the associated state is to its goal. Can be used to optimise search algorithms.

Interfaces

[IGoal<TBeliefSet>](#)

Defines a goal that can be achieved by a [Tactic<TBeliefSet>](#).

Delegates

[Goal<TBeliefSet>.HeuristicFunction](#)

The abstract definition of what it means to test the Goal's heuristic function. Returns [Heuristics](#), as they represent how close we are to matching the heuristic function, and if the goal is completed.

Class

CommonHeuristicFunctions<TBeliefSet>

Namespace: [Aplib.Core.Desire.Goals](#)

Assembly: Aplib.Core.dll

Contains helper methods to generate commonly used heuristic functions.

```
public static class CommonHeuristicFunctions<TBeliefSet> where TBeliefSet
: IBeliefSet
```

Type Parameters

TBeliefSet

Inheritance

[object](#)  ← CommonHeuristicFunctions<TBeliefSet>

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Methods

Boolean(Func<TBeliefSet, bool>)

Converts a boolean-based heuristic function to a [Goal<TBeliefSet>.HeuristicFunction](#).

```
public static Goal<TBeliefSet>.HeuristicFunction Boolean(Func<TBeliefSet,
bool> heuristicFunction)
```

Parameters

heuristicFunction [Func](#)  <TBeliefSet, [bool](#)  >

A heuristic function which returns true only when the state is considered completed.

Returns

[Goal<TBeliefSet>.HeuristicFunction](#)

A heuristic function which wraps around the boolean-based heuristic function.

Completed()

Returns a heuristic function which always, at all times, and forever, returns a value indicating the state can be seen as completed.

```
public static Goal<TBeliefSet>.HeuristicFunction Completed()
```

Returns

[Goal<TBeliefSet>.HeuristicFunction](#)

Said heuristic function.

Constant(float)

A [Goal<TBeliefSet>.HeuristicFunction](#) which always returns [Heuristics](#) with the same distance.

```
public static Goal<TBeliefSet>.HeuristicFunction Constant(float distance)
```

Parameters

distance [float](#)

The distance which the heuristic function must always return.

Returns

[Goal<TBeliefSet>.HeuristicFunction](#)

Uncompleted()

Returns a heuristic function which always, at all times, and forever, returns a value indicating the state can be seen as NOT completed.

```
public static Goal<TBeliefSet>.HeuristicFunction Uncompleted()
```

Returns

[Goal](#)<TBeliefSet>.[HeuristicFunction](#)

Said heuristic function.

Class Goal<TBeliefSet>

Namespace: [Aplib.Core.Desire.Goals](#)

Assembly: Aplib.Core.dll

A goal effectively combines a heuristic function with a tactic, and aims to meet the heuristic function by applying the tactic. Goals are combined in a [GoalStructure<TBeliefSet>](#), and are used to prepare tests or do the testing.

```
public class Goal<TBeliefSet> : IGoal<TBeliefSet>, ICompletable, IDocumented where
    TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The belief set of the agent.








Inheritance

[object](#)  ← Goal<TBeliefSet>

Implements

[IGoal](#)<TBeliefSet>, [ICompletable](#), [IDocumented](#)

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoal<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoal<TBeliefSet>, IMetadata\)](#)

Constructors

Goal(IMetadata, ITactic<TBeliefSet>, HeuristicFunction, double)

Creates a new goal which works with [Heuristics](#).

```
public Goal(IMetadata metadata, ITactic<TBeliefSet> tactic,  
Goal<TBeliefSet>.HeuristicFunction heuristicFunction, double epsilon = 0.005)
```

Parameters

metadata [IMetadata](#)

Metadata about this goal, used to quickly display the goal in several contexts.

tactic [ITactic](#)<TBeliefSet>

The tactic used to approach this goal.

heuristicFunction [Goal](#)<TBeliefSet>.[HeuristicFunction](#)

The heuristic function which defines whether a goal is reached.

epsilon [double](#) 

The goal is considered to be completed, when the distance of the [DetermineCurrentHeuristics\(TBeliefSet\)](#) is below this value.

Goal(IMetadata, ITactic<TBeliefSet>, Func<TBeliefSet, bool>, double)

Creates a new goal which works with boolean-based [Heuristics](#).

```
public Goal(IMetadata metadata, ITactic<TBeliefSet> tactic, Func<TBeliefSet, bool>  
predicate, double epsilon = 0.005)
```

Parameters

metadata [IMetadata](#)

Metadata about this goal, used to quickly display the goal in several contexts.

tactic [ITactic](#)<TBeliefSet>

The tactic used to approach this goal.

predicate [Func](#)  <TBeliefSet, [bool](#)  >

The heuristic function (or specifically predicate) which defines whether a goal is reached.

`epsilon` [double](#)

The goal is considered to be completed, when the distance of the [DetermineCurrentHeuristics\(TBeliefSet\)](#) is below this value.

Goal(ITactic<TBeliefSet>, HeuristicFunction, double)

Creates a new goal which works with [Heuristics](#).

```
public Goal(ITactic<TBeliefSet> tactic, Goal<TBeliefSet>.HeuristicFunction  
heuristicFunction, double epsilon = 0.005)
```

Parameters

`tactic` [ITactic](#)<TBeliefSet>

The tactic used to approach this goal.

`heuristicFunction` [Goal](#)<TBeliefSet>.[HeuristicFunction](#)

The heuristic function which defines whether a goal is reached.

`epsilon` [double](#)

The goal is considered to be completed, when the distance of the [DetermineCurrentHeuristics\(TBeliefSet\)](#) is below this value.

Goal(ITactic<TBeliefSet>, Func<TBeliefSet, bool>, double)

Creates a new goal which works with boolean-based [Heuristics](#).

```
public Goal(ITactic<TBeliefSet> tactic, Func<TBeliefSet, bool> predicate, double  
epsilon = 0.005)
```

Parameters

`tactic` [ITactic](#)<TBeliefSet>

The tactic used to approach this goal.

`predicate Func <TBeliefSet, bool>`

The heuristic function (or specifically predicate) which defines whether a goal is reached.

`epsilon double`

The goal is considered to be completed, when the distance of the [DetermineCurrentHeuristics\(TBeliefSet\)](#) is below this value.

Fields

DefaultEpsilon

The default value for the epsilon parameter in the Goal constructors. The epsilon parameter defines the threshold distance for a goal to be considered completed.

```
protected const double DefaultEpsilon = 0.005
```

Field Value

[double](#)

_epsilon

The goal is considered to be completed, when the distance of the [DetermineCurrentHeuristics\(TBeliefSet\)](#) is below this value.

```
protected readonly double _epsilon
```

Field Value

[double](#)

_heuristicFunction

The concrete implementation of this Goal's [Goal<TBeliefSet>.HeuristicFunction](#). Used to test whether this goal is completed.

```
protected readonly Goal<TBeliefSet>.HeuristicFunction _heuristicFunction
```

Field Value

[Goal<TBeliefSet>.HeuristicFunction](#)

See Also

[GetStatus\(TBeliefSet\)](#)

Properties

Metadata

Gets the metadata of the instance.

```
public IMetadata Metadata { get; }
```

Property Value

[IMetadata](#)

Status

Gets the completion status of the object.

```
public CompletionStatus Status { get; protected set; }
```

Property Value

[CompletionStatus](#)

Tactic

The [Tactic<TBeliefSet>](#) used to achieve this [Goal<TBeliefSet>](#), which is executed during every iteration of the BDI cycle.

```
public ITactic<TBeliefSet> Tactic { get; }
```

Property Value

[ITactic<TBeliefSet>](#)

Methods

DetermineCurrentHeuristics(TBeliefSet)

Gets the [Heuristics](#) of the current state of the game.

```
public virtual Heuristics DetermineCurrentHeuristics(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

Returns

[Heuristics](#)

Remarks

If no heuristics have been calculated yet, they will be calculated first.

GetStatus(TBeliefSet)

Tests whether the goal has been achieved, bases on the [_heuristicFunction](#) and the [DetermineCurrentHeuristics\(TBeliefSet\)](#). When the distance of the heuristics is smaller than [_epsilon](#), the goal is considered to be completed.

```
public virtual CompletionStatus GetStatus(TBeliefSet beliefSet)
```


Parameters

`beliefSet` TBeliefSet

Returns

[CompletionStatus](#)

An enum representing whether the goal is complete and if so, with what result.

See Also

[_epsilon](#)

See Also

[GoalStructure](#)<TBeliefSet>

Delegate Goal<TBeliefSet>.HeuristicFunction

Namespace: [Aplib.Core.Desire.Goals](#)

Assembly: Aplib.Core.dll

The abstract definition of what is means to test the Goal's heuristic function. Returns [Heuristics](#), as they represent how close we are to matching the heuristic function, and if the goal is completed.

```
public delegate Heuristics Goal<TBeliefSet>.HeuristicFunction(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The abstract definition of what is means to test the Goal's heuristic function. Returns , as they represent how close we are to matching the heuristic function, and if the goal is completed.

Returns

[Heuristics](#)

The abstract definition of what is means to test the Goal's heuristic function. Returns , as they represent how close we are to matching the heuristic function, and if the goal is completed.

See Also

[GetStatus](#)(TBeliefSet)

Class Heuristics


Namespace: [Aplib.Core.Desire.Goals](#)

Assembly: Aplib.Core.dll








Contains all information on how close the associated state is to its goal. Can be used to optimise search algorithms.

```
public class Heuristics
```

Inheritance

[object](#)  ← Heuristics

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Properties

Distance

The logical distance the current state is to its goal.

```
public float Distance { get; set; }
```

Property Value

[float](#) 

Methods

Boolean(bool)

Creates a heuristic value representing just a boolean. The heuristic value is considered '0' or 'done' when the boolean is true. Non-zero otherwise.

```
public static Heuristics Boolean(bool value)
```

Parameters

value [bool](#)

True if completed, False if not completed.

Returns

[Heuristics](#)

Interface IGoal<TBeliefSet>

Namespace: [Aplib.Core.Desire.Goals](#)

Assembly: Aplib.Core.dll

Defines a goal that can be achieved by a [Tactic<TBeliefSet>](#).

```
public interface IGoal<in TBeliefSet> : ICompletable where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The belief set of the agent.

Inherited Members

[ICompletable.Status](#)

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoal<TBeliefSet>\)](#) ,

[LiftingExtensionMethods.Lift<TBeliefSet>\(IGoal<TBeliefSet>, IMetadata\)](#)

Properties

Tactic

The [Tactic<TBeliefSet>](#) used to achieve this [Goal<TBeliefSet>](#), which is executed during every iteration of the BDI cycle.

```
ITactic<in TBeliefSet> Tactic { get; }
```

Property Value

[ITactic<TBeliefSet>](#)

Methods

DetermineCurrentHeuristics(TBeliefSet)

Gets the [Heuristics](#) of the current state of the game.

```
Heuristics DetermineCurrentHeuristics(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

Returns

[Heuristics](#)

Remarks

If no heuristics have been calculated yet, they will be calculated first.

GetStatus(TBeliefSet)

Tests whether the goal has been achieved, based on the [_heuristicFunction](#) and the [DetermineCurrentHeuristics\(TBeliefSet\)](#). When the distance of the heuristics is smaller than [_epsilon](#) , the goal is considered to be completed.

```
CompletionStatus GetStatus(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

Returns

[CompletionStatus](#)

An enum representing whether the goal is complete and if so, with what result.

See Also

[_epsilon](#)

Namespace Aplib.Core.Intent.Actions

Classes

[Action<TBeliefSet>](#)

Describes an action that can be executed and guarded.

[QueryAction<TBeliefSet, TQuery>](#)

Describes an action that can be executed and guarded with a query that stores a result. The result can be used in the effect.

Interfaces

[IAction<TBeliefSet>](#)

Represents an action that can be executed on a belief set.

[IQueryable<TBeliefSet>](#)

Represents an interface for executing queries on a belief set.

Class Action<TBeliefSet>

Namespace: [Aplib.Core.Intent.Actions](#)

Assembly: Aplib.Core.dll

Describes an action that can be executed and guarded.


```
public class Action<TBeliefSet> : IAction<TBeliefSet>, IDocumented where TBeliefSet
: IBeliefSet
```

Type Parameters

TBeliefSet

The belief set of the agent.

Inheritance

[object](#)  ← Action<TBeliefSet>








Implements

[IAction](#)<TBeliefSet>, [IDocumented](#)

Derived

[QueryAction](#)<TBeliefSet, TQuery>

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>, IMetadata\)](#)

Constructors

Action(IMetadata, Action<TBeliefSet>)

Initializes a new instance of the [Action<TBeliefSet>](#) class.


```
public Action(IMetadata metadata, Action<TBeliefSet> effect)
```

Parameters

metadata [IMetadata](#)

Metadata about this action, used to quickly display the action in several contexts.

effect [Action](#) <TBeliefSet>

The effect of the action.

Action(Action<TBeliefSet>)

Initializes a new instance of the [Action<TBeliefSet>](#) class.

```
public Action(Action<TBeliefSet> effect)
```

Parameters

effect [Action](#) <TBeliefSet>

The effect of the action.

Fields

_effect

Gets or sets the effect of the action.

```
protected readonly Action<TBeliefSet> _effect
```

Field Value

[Action](#) <TBeliefSet>

Properties

Metadata

Gets the metadata of the instance.

```
public IMetadata Metadata { get; }
```

Property Value

[IMetadata](#)

Methods

Execute(TBeliefSet)

Executes the action on the specified belief set.

```
public virtual void Execute(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set on which the action is executed.

Interface IAction<TBeliefSet>

Namespace: [Aplib.Core.Intent.Actions](#)

Assembly: Aplib.Core.dll

Represents an action that can be executed on a belief set.

```
public interface IAction<in TBeliefSet> where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The type of the belief set that the action uses.

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>, IMetadata\)](#)

Methods

Execute(TBeliefSet)

Executes the action on the specified belief set.

```
void Execute(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set on which the action is executed.

Interface IQueryable<TBeliefSet>

Namespace: [Aplib.Core.Intent.Actions](#)

Assembly: Aplib.Core.dll

Represents an interface for executing queries on a belief set.

```
public interface IQueryable<in TBeliefSet> : IAction<TBeliefSet> where TBeliefSet
    : IBeliefSet
```

Type Parameters

TBeliefSet

The type of the query object.

Inherited Members

[IAction<TBeliefSet>.Execute\(TBeliefSet\)](#)

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>, IMetadata\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IQueryable<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IQueryable<TBeliefSet>, IMetadata\)](#)

Methods

Query(TBeliefSet)

Executes a query on the specified belief set.

```
bool Query(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set to query.

Returns

[bool](#) 

A boolean value indicating whether the query executed successfully or not.

Class QueryAction<TBeliefSet, TQuery>

Namespace: [Aplib.Core.Intent.Actions](#)

Assembly: Aplib.Core.dll

Describes an action that can be executed and guarded with a query that stores a result. The result can be used in the effect.

```
public class QueryAction<TBeliefSet, TQuery> : Action<TBeliefSet>, IDocumented,
    IQueryable<TBeliefSet>, IAction<TBeliefSet> where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The belief set of the agent.

TQuery

The type of the query of the action








Inheritance

[object](#)  ← [Action](#)<TBeliefSet> ← QueryAction<TBeliefSet, TQuery>

Implements

[IDocumented](#), [IQueryable](#)<TBeliefSet>, [IAction](#)<TBeliefSet>

Inherited Members

[Action<TBeliefSet>.Metadata](#) , [object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Extension Methods

[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IAction<TBeliefSet>, IMetadata\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IQueryable<TBeliefSet>\)](#) ,
[LiftingExtensionMethods.Lift<TBeliefSet>\(IQueryable<TBeliefSet>, IMetadata\)](#)

Constructors

QueryAction(IMetadata, Action<TBeliefSet, TQuery>, Func<TBeliefSet, TQuery?>)

Initializes a new instance of the [QueryAction<TBeliefSet, TQuery>](#) class.

```
public QueryAction(IMetadata metadata, Action<TBeliefSet, TQuery> effect,
    Func<TBeliefSet, TQuery?> query)
```

Parameters

metadata [IMetadata](#)

Metadata about this action, used to quickly display the action in several contexts.

effect [Action](#) <TBeliefSet, TQuery>

The effect of the action.

query [Func](#) <TBeliefSet, TQuery>

The query of the action.

QueryAction(Action<TBeliefSet, TQuery>, Func<TBeliefSet, TQuery?>)

Initializes a new instance of the [QueryAction<TBeliefSet, TQuery>](#) class.

```
public QueryAction(Action<TBeliefSet, TQuery> effect, Func<TBeliefSet, TQuery?>
    > query)
```

Parameters

effect [Action](#) <TBeliefSet, TQuery>

The effect of the action.

query [Func](#) <TBeliefSet, TQuery>

The query of the action.

Fields

`_effect`

Gets or sets the effect of the action.

```
protected readonly Action<TBeliefSet, TQuery> _effect
```

Field Value

[Action](#)  <TBeliefSet, TQuery>

`_query`

Gets or sets the query of the action.

```
protected readonly Func<TBeliefSet, TQuery?> _query
```

Field Value

[Func](#)  <TBeliefSet, TQuery>

`_storedQueryResult`

Gets or sets the result of the query.

```
protected TQuery? _storedQueryResult
```

Field Value

TQuery

Methods

`Execute(TBeliefSet)`

Executes the action on the specified belief set.

```
public override void Execute(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set on which the action is executed.

Query(TBeliefSet)

Queries the environment for the queried item and returns whether the query is not null.

```
public bool Query(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

The belief set of the agent.

Returns

[bool](#) 

True if the query is not null; otherwise, false.

Namespace Aplib.Core.Intent.Tactics

Classes

[AnyOfTactic<TBeliefSet>](#)

Represents a tactic that executes any of the provided sub-tactics.

[FirstOfTactic<TBeliefSet>](#)

Represents a tactic that executes the first enabled action from a list of sub-tactics.

[PrimitiveTactic<TBeliefSet>](#)

Represents a primitive tactic

[Tactic<TBeliefSet>](#)

Tactics are the real meat of [Goal<TBeliefSet>](#)s, as they define how the agent can approach the goal in hopes of finding a solution which makes the Goal's heuristic function evaluate to being completed. A tactic represents a smart combination of [Action<TBeliefSet>](#)s, which are executed in a Belief Desire Intent Cycle.

Interfaces

[ITactic<TBeliefSet>](#)

Represents a tactic that an agent can use to achieve its goals. A tactic is a strategy for achieving a particular goal.

Class AnyOfTactic<TBeliefSet>

Namespace: [Aplib.Core.Intent.Tactics](#)

Assembly: Aplib.Core.dll

Represents a tactic that executes any of the provided sub-tactics.

```
public class AnyOfTactic<TBeliefSet> : Tactic<TBeliefSet>, ITactic<TBeliefSet>,
IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

Inheritance

[object](#)  ← [Tactic](#)<TBeliefSet> ← AnyOfTactic<TBeliefSet>








Implements

[ITactic](#)<TBeliefSet>, [IDocumented](#)

Derived

[FirstOfTactic](#)<TBeliefSet>

Inherited Members

[Tactic](#)<TBeliefSet>._guard, [Tactic](#)<TBeliefSet>.Metadata, [Tactic](#)<TBeliefSet>.IsActionable(TBeliefSet), [object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Constructors

AnyOfTactic(IMetadata, params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified sub-tactics and an optional guard condition.

```
public AnyOfTactic(IMetadata metadata, params ITactic<TBeliefSet>[] subTactics)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

AnyOfTactic(IMetadata, Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified subtactics and an optional guard condition.

```
public AnyOfTactic(IMetadata metadata, Func<TBeliefSet, bool> guard, params
ITactic<TBeliefSet>[] subTactics)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

AnyOfTactic(params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified subtactics and an optional guard condition.

```
public AnyOfTactic(params ITactic<TBeliefSet>[] subTactics)
```

Parameters

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

AnyOfTactic(Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [AnyOfTactic<TBeliefSet>](#) class with the specified subtactics and an optional guard condition.

```
public AnyOfTactic(Func<TBeliefSet, bool> guard, params ITactic<TBeliefSet>[] subTactics)
```

Parameters

guard [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Fields

_subTactics

Gets or sets the sub-tactics of the tactic.

```
protected readonly LinkedList<ITactic<TBeliefSet>> _subTactics
```

Field Value

[LinkedList](#)<[ITactic](#)<TBeliefSet>>

Methods

GetAction(TBeliefSet)

Gets the first enabled action of the tactic.

```
public override IAction<TBeliefSet>? GetAction(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

Returns

[IAction](#)<TBeliefSet>

A concrete [IAction<TBeliefSet>](#) that the tactic can perform, or null if no actions are enabled.

Class FirstOfTactic<TBeliefSet>

Namespace: [Aplib.Core.Intent.Tactics](#)

Assembly: Aplib.Core.dll

Represents a tactic that executes the first enabled action from a list of sub-tactics.

```
public class FirstOfTactic<TBeliefSet> : AnyOfTactic<TBeliefSet>,
ITactic<TBeliefSet>, IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

[TBeliefSet](#)








Inheritance

[object](#)  ← [Tactic](#)<TBeliefSet> ← [AnyOfTactic](#)<TBeliefSet> ← FirstOfTactic<TBeliefSet>

Implements

[ITactic](#)<TBeliefSet>, [IDocumented](#)

Inherited Members

[AnyOfTactic<TBeliefSet>._subTactics](#) , [Tactic<TBeliefSet>._guard](#) ,
[Tactic<TBeliefSet>.Metadata](#) , [Tactic<TBeliefSet>.IsActionable\(TBeliefSet\)](#) ,
[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  ,
[object.GetType\(\)](#)  , [object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  ,
[object.ToString\(\)](#) 

Constructors

FirstOfTactic(IMetadata, params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified sub-tactics and guard condition.

```
public FirstOfTactic(IMetadata metadata, params ITactic<TBeliefSet>[] subTactics)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

FirstOfTactic(IMetadata, Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified subtactics and guard condition.

```
public FirstOfTactic(IMetadata metadata, Func<TBeliefSet, bool> guard, params ITactic<TBeliefSet>[] subTactics)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

subTactics [ITactic](#)<TBeliefSet>[]

The list of subtactics.

FirstOfTactic(params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified subtactics and guard condition.

```
public FirstOfTactic(params ITactic<TBeliefSet>[] subTactics)
```

Parameters

`subTactics` [ITactic](#)<TBeliefSet>[]

The list of subtactics.

FirstOfTactic(Func<TBeliefSet, bool>, params ITactic<TBeliefSet>[])

Initializes a new instance of the [FirstOfTactic<TBeliefSet>](#) class with the specified subtactics and guard condition.

```
public FirstOfTactic(Func<TBeliefSet, bool> guard, params ITactic<TBeliefSet>[] subTactics)
```

Parameters

`guard` [Func](#)<TBeliefSet, [bool](#)>

The guard condition.

`subTactics` [ITactic](#)<TBeliefSet>[]

The list of subtactics.

Methods

GetAction(TBeliefSet)

Gets the first enabled action of the tactic.

```
public override IAction<TBeliefSet>? GetAction(TBeliefSet beliefSet)
```

Parameters

`beliefSet` TBeliefSet

Returns

[IAction](#)<TBeliefSet>

A concrete [IAction<TBeliefSet>](#) that the tactic can perform, or null if no actions are enabled.

Interface ITactic<TBeliefSet>

Namespace: [Aplib.Core.Intent.Tactics](#)

Assembly: Aplib.Core.dll

Represents a tactic that an agent can use to achieve its goals. A tactic is a strategy for achieving a particular goal.

```
public interface ITactic<in TBeliefSet> where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The type of the belief set that the tactic uses.

Methods

GetAction(TBeliefSet)

Gets the first enabled action of the tactic.

```
IAction<in TBeliefSet>? GetAction(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

Returns

[IAction](#)<TBeliefSet>

A concrete [IAction](#)<TBeliefSet> that the tactic can perform, or null if no actions are enabled.

IsActionable(TBeliefSet)

Determines whether the tactic is actionable.

```
bool IsActionable(TBeliefSet beliefSet)
```

Parameters

beliefSet TBeliefSet

Returns

[bool](#) 

True if the tactic is actionable, false otherwise.

Class PrimitiveTactic<TBeliefSet>

Namespace: [Aplib.Core.Intent.Tactics](#)

Assembly: Aplib.Core.dll

Represents a primitive tactic

```
public class PrimitiveTactic<TBeliefSet> : Tactic<TBeliefSet>, ITactic<TBeliefSet>,
IDocumented where TBeliefSet : IBeliefSet
```

Type Parameters

TBeliefSet

The belief set of the agent.








Inheritance

[object](#)  ← [Tactic](#) <TBeliefSet> ← PrimitiveTactic <TBeliefSet>

Implements

[ITactic](#) <TBeliefSet>, [IDocumented](#)

Inherited Members

[Tactic<TBeliefSet>._guard](#) , [Tactic<TBeliefSet>.Metadata](#) ,
[Tactic<TBeliefSet>.IsActionable\(TBeliefSet\)](#) , [object.Equals\(object\)](#)  ,
[object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  ,
[object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Constructors

PrimitiveTactic(IMetadata, IAction<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IMetadata metadata, IAction<TBeliefSet> action)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

PrimitiveTactic(IMetadata, IAction<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IMetadata metadata, IAction<TBeliefSet> action,
    Func<TBeliefSet, bool> guard)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

PrimitiveTactic(IMetadata, IQueryable<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IMetadata metadata, IQueryable<TBeliefSet> queryAction)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

queryAction [IQueryable](#)<TBeliefSet>

The queryable action of the primitive tactic.

PrimitiveTactic(IMetadata, IQueryable<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IMetadata metadata, IQueryable<TBeliefSet> queryAction,
    Func<TBeliefSet, bool> guard)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

queryAction [IQueryable](#)<TBeliefSet>

The queryable action of the primitive tactic.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

PrimitiveTactic(IAction<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IAction<TBeliefSet> action)
```

Parameters

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

PrimitiveTactic(IAction<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IAction<TBeliefSet> action, Func<TBeliefSet, bool> guard)
```

Parameters

action [IAction](#)<TBeliefSet>

The action of the primitive tactic.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

PrimitiveTactic(IQueryable<TBeliefSet>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IQueryable<TBeliefSet> queryAction)
```

Parameters

queryAction [IQueryable](#)<TBeliefSet>

The queryable action of the primitive tactic.

PrimitiveTactic(IQueryable<TBeliefSet>, Func<TBeliefSet, bool>)

Initializes a new instance of the [PrimitiveTactic<TBeliefSet>](#) class with the specified action and guard.

```
public PrimitiveTactic(IQueryable<TBeliefSet> queryAction, Func<TBeliefSet, bool> guard)
```

Parameters

queryAction [IQueryable](#)<TBeliefSet>

The queryable action of the primitive tactic.

guard [Func](#)<TBeliefSet, [bool](#)>

The guard of the primitive tactic.

Fields

_action

Gets the action of the primitive tactic.

```
protected readonly IAction<TBeliefSet> _action
```

Field Value

[IAction](#)<TBeliefSet>

Methods

GetAction(TBeliefSet)

Gets the first enabled action of the tactic.

```
public override IAction<TBeliefSet>? GetAction(TBeliefSet beliefSet)
```

Parameters

`beliefSet` TBeliefSet

Returns

[IAction](#)<TBeliefSet>

A concrete [IAction<TBeliefSet>](#) that the tactic can perform, or null if no actions are enabled.

Class `Tactic<TBeliefSet>`

Namespace: [Aplib.Core.Intent.Tactics](#)

Assembly: Aplib.Core.dll

Tactics are the real meat of [Goal<TBeliefSet>](#)s, as they define how the agent can approach the goal in hopes of finding a solution which makes the Goal's heuristic function evaluate to being completed. A tactic represents a smart combination of [Action<TBeliefSet>](#)s, which are executed in a Belief Desire Intent Cycle.


```
public abstract class Tactic<TBeliefSet> : ITactic<TBeliefSet>, IDocumented where
    TBeliefSet : IBeliefSet
```

Type Parameters

`TBeliefSet`

The belief set of the agent.

Inheritance

[object](#)  ← `Tactic<TBeliefSet>`








Implements

[ITactic](#)<TBeliefSet>, [IDocumented](#)

Derived

[AnyOfTactic<TBeliefSet>](#), [PrimitiveTactic<TBeliefSet>](#)

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) ,
[object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) ,
[object.ToString\(\)](#) 

Constructors

`Tactic()`

Initializes a new instance of the [object](#)  class.

```
protected Tactic()
```

Tactic(IMetadata)

```
protected Tactic(IMetadata metadata)
```

Parameters

metadata [IMetadata](#)

Tactic(IMetadata, Func<TBeliefSet, bool>)

Initializes a new instance of the [Tactic<TBeliefSet>](#) class with a specified guard.

```
protected Tactic(IMetadata metadata, Func<TBeliefSet, bool> guard)
```

Parameters

metadata [IMetadata](#)

Metadata about this tactic, used to quickly display the tactic in several contexts.

guard [Func](#) <TBeliefSet, [bool](#)>

The guard of the tactic.

Tactic(Func<TBeliefSet, bool>)

Initializes a new instance of the [Tactic<TBeliefSet>](#) class with a specified guard.

```
protected Tactic(Func<TBeliefSet, bool> guard)
```

Parameters

guard [Func](#) <TBeliefSet, [bool](#)>

The guard of the tactic.

Fields

`_guard`

Gets or sets the guard of the tactic.

```
protected Func<TBeliefSet, bool> _guard
```

Field Value

[Func](#) <[TBeliefSet](#), [bool](#)>

Properties

Metadata

Gets the metadata of the instance.

```
public IMetadata Metadata { get; }
```

Property Value

[IMetadata](#)

Methods

GetAction(TBeliefSet)

Gets the first enabled action of the tactic.

```
public abstract IAction<TBeliefSet>? GetAction(TBeliefSet beliefSet)
```

Parameters

`beliefSet` TBeliefSet

Returns

[IAction](#)<TBeliefSet>

A concrete [IAction<TBeliefSet>](#) that the tactic can perform, or null if no actions are enabled.

IsActionable(TBeliefSet)

Determines whether the tactic is actionable.

```
public virtual bool IsActionable(TBeliefSet beliefSet)
```

Parameters

`beliefSet` TBeliefSet

Returns

[bool](#) 

True if the tactic is actionable, false otherwise.

Operators

implicit operator Tactic<TBeliefSet>
(Action<TBeliefSet>)

Implicitly lifts an action into a tactic.

```
public static implicit operator Tactic<TBeliefSet>(Action<TBeliefSet> action)
```

Parameters

`action` [Action](#)<TBeliefSet>

The action which on its own can function as a tactic. Meaning, the tactic consists of just a single action.

Returns

[Tactic](#)<TBeliefSet>

The most logically matching tactic, wrapping around [action](#).

See Also

[Goal](#)<TBeliefSet>

[Action](#)<TBeliefSet>