

1. RUN CONFIGURATION

Frames Processed	Duration	Processing FPS	Avg Processing	Max Processing
1104	83.86 s	154.7	6.46 ms	7.34 ms

2. TRACKING PERFORMANCE

Acquisition Time	Average Tracking Error	Maximum Tracking Error
0.60 s	2.92 px	67.07 px
<= 2 s		<= 10 px
RMSE Tracking Error	Centroid Error Avg/Max	Lock Retention
4.51 px	0.75 / 5.16 px	98.90 %
	ground truth only	
Target Loss	Re-acquisition Avg/Max	Successful Re-acq.
0.92 %	0.17 / — s	2
< 5 %	<= 1 s	2 loss events

3. PS REQUIREMENT CHECK

Parameter	Measured	Requirement	Status
Acquisition Time	0.60	<= 2.0 s	PASS
Tracking Error (Max)	67.07	<= 10 px	FAIL
Center Error (Final)	67.07	<= 10 px	FAIL
Target Loss	0.92 %	< 5%	PASS
Re-acquisition Time	0.17	<= 1.0 s	PASS
Processing Speed	154.7 FPS	>= 20 FPS	PASS

Ground truth was available: centroid accuracy is measured.

OVERALL: FAIL

Source: live simulation | Frames: 1104 | FPS: 154.7