

1. RUN CONFIGURATION

Frames Processed	Duration	Processing FPS	Avg Processing	Max Processing
3416	191.90 s	179.7	5.56 ms	6.87 ms

2. TRACKING PERFORMANCE

Acquisition Time	Average Tracking Error	Maximum Tracking Error
0.17 s	2.18 px	60.01 px
<= 2 s		<= 10 px
RMSE Tracking Error	Centroid Error Avg/Max	Lock Retention
2.56 px	0.40 / 3.22 px	99.82 %
	ground truth only	
Target Loss	Re-acquisition Avg/Max	Successful Re-acq.
0.15 %	0.17 / — s	1
< 5 %	<= 1 s	1 loss events

3. PS REQUIREMENT CHECK

Parameter	Measured	Requirement	Status
Acquisition Time	0.17	<= 2.0 s	PASS
Tracking Error (Max)	60.01	<= 10 px	FAIL
Center Error (Final)	60.01	<= 10 px	FAIL
Target Loss	0.15 %	< 5%	PASS
Re-acquisition Time	0.17	<= 1.0 s	PASS
Processing Speed	179.7 FPS	>= 20 FPS	PASS

Ground truth was available: centroid accuracy is measured.

OVERALL: FAIL

Source: live simulation | Frames: 3416 | FPS: 179.7