

TapTapUp API Integration Guide (Third-Party)

This document describes how to integrate with the TapTapUp payment API

Overview

The TapTapUp API provides a secure payment flow for third-party merchants:

1. Merchant calls `initiate-payment` with HMAC authentication.
2. API returns a hosted payment link (redirect URL).
3. Customer completes payment on TapTapUp.
4. TapTapUp sends a webhook to merchant (optional).
5. TapTapUp redirects customer to merchant return URL.
6. Merchant can check status via token endpoints.

Base URLs

- `/api/v1`

Authentication (HMAC)

All API endpoints require HMAC headers.

Required headers

- `X-Merchant-ID` : Your merchant ID
- `X-Timestamp` : Current unix timestamp (seconds)
- `X-Signature` : HMAC signature

Signature generation

Signature is HMAC-SHA256 of:

```
{timestamp}{raw_body}
```

- Key: your `shared_secret`
- Body: exact raw JSON body (no whitespace changes)

Example (pseudo)

```
data_to_sign = timestamp + raw_json_body
signature = hmac_sha256(data_to_sign, shared_secret)
```

Endpoint: Initiate Payment

URL

- `POST /api/v1/initiate-payment`

Request JSON

```
{
  "product_id": 123,
  "amount": 19.99,
  "email": "customer@example.com",
  "merchant_reference": "INV-1001",
  "return_url": "https://merchant.example/return",
  "webhook_url": "https://merchant.example/webhook"
}
```

Response (success)

```
{
  "success": true,
  "redirect_url": "https://taptapup.xyz/cashme/product-slug/?api_token=...",
  "token": "api_token_here",
  "expires_in": 3600,
  "message": "Payment form ready",
  "requested_amount": 19.99,
  "final_amount": 19.99
}
```

Notes

- `merchant_reference` must be unique per merchant.
- `webhook_url` is optional.
- Token expires after 1 hour.

Endpoint: Verify Token

URL

- `POST /api/v1/verify-token`

Request JSON

```
{
  "token": "api_token_here"
}
```

Response (success)

```
{
  "success": true,
  "token": "api_token_here",
  "status": "processing",
  "order_id": 160948,
  "amount": 19.99,
  "email": "customer@example.com"
}
```

Status values

- pending
- processing
- completed
- expired

Endpoint: Status Check

URL

- GET /api/v1/status/{token}

Response (success)

```
{
  "success": true,
  "status": "completed",
  "order_id": 160948
}
```

Webhook Delivery (Optional)

If `webhook_url` is provided during initiation, TapTapUp will POST a webhook after payment completion.

Webhook headers

- Content-Type: application/json
- X-TapTapUp-Event: payment.completed
- X-Merchant-Reference: {merchant_reference}

Webhook payload

```
{
  "event": "payment.completed",
  "merchant_reference": "INV-1001",
  "order_id": 160948,
  "status": "completed",
  "amount": 19.99,
  "email": "customer@example.com",
  "product_id": 123,
  "transaction_id": "",
  "completed_at": "2026-02-19 12:34:56",
  "order_number": "160948"
}
```

Webhook behavior

- Webhook is sent only for API-created orders.
- A successful webhook response is any 2xx status.
- After successful webhook send, the API record status is updated to completed.

Return URL

- Customer is redirected to return_url after payment.
- TapTapUp appends order_id as query param.

Example:

```
https://merchant.example/return?order_id=160948
```

Security Notes

- Only server-side notify callbacks should change order status.
- Return URL should be used for user navigation only.
- Treat token as sensitive; do not expose it publicly.
- Validate all webhook requests on your side if required.

Error Responses

All errors follow this format:

```
{
  "success": false,
  "error": "error_code",
  "message": "Human readable message",
  "code": 422
}
```

Common Error Codes

- `unauthorized` (401)
- `invalid_request` (422)
- `conflict` (409)
- `not_found` (404)
- `expired` (410)
- `server_error` (500)

Support

If you need credentials or endpoint access, contact TanTanIn support.