Exploring AI Facial Recognition for Real-time Emotion Detection: Assessing Student Engagement in Online Learning Environments

Shan J
Department of Computer Applications
Hindustan Institute of Technology and Science
Chennai- 603103 Tamil Nadu, India
shanjerome555@gmail.com

Sherin Eliyas
Assistant Professor,
Department of Computer Applications
Hindustan Institute of Technology and Science
Chennai-603103 Tamil Nadu, India
sherine@hindustanuniv.ac.in

2024 3rd International Conference on Artificial Intelligence For Internet of Things (AIIoT) | 979-8-3503-7212-0/24/$31.00 ©2024 IEEE | DOI: 10.1109/AIIoT58432.2024.10574587

Abstract:

AI facial recognition for real-time emotion detection in online learning environments intends to analyze students' sentiments throughout online classes, recognizing emotions such as focused,neutral, distracted, enraged, thrilled, or dissatisfied states. The proposed approach uses a generative model trained by conditional Generative Adversarial Networks (cGAN) to accomplish De- expression Residue Learning (DeRL), a facial expression recognition technique. DeRL prioritizes gathering residue for delicate emotion recognition by filtering expressive material and storing it in intermediary layers. This technology gives educators and researchers real-time insights into students' emotional states,allowing for a more thorough understanding of collective student involvement through the lens of socially shared control of learning. Experiments on seven facial expression databases, including two pre-training datasets, indicate that DeRL outperforms other methods in accurately recognizing and classifying students' emotions. The findings emphasize its ability to capture subtle feelings during online learning. The discussion dives into theoretical and practical implications, highlighting AI's potential to enhance the evaluation of student participation in online learning environments. The study concludes by providingrelevant information for building tailored learning experiences, indicating a possible avenue for incorporating AI in the classroom.

Keywords: Facial Expression Identification, Psychological Control, Socially Integrated Supervision, Pre-training, De-expressionResidue Learning, Synchronous online education, Computer-supported interactive education, conditional Generative Adversarial, Network, Student Self-regulation.

INTRODUCTION

This study investigates the use of AI facial recognition in online learning to identify students' real-time emotions. Understanding how students feel during online classes is critical for improving their learning experiences in the ever-changing virtual educationenvironment. The study intends to examine a wide spectrum of emotions.

The assessment and support of SSRL in collaborative learning have proven challenging, often relying on self-reported surveys and interviews. The proposed approach uses De-expression Residue Learning (DeRL), a novel face expression identification technique, in conjunction with a generative model trained using conditional Generative Adversarial Networks (cGAN). DeRL aims to capture delicate emotional nuances by filtering expressive data and storing it in intermediate layers. This technology gives educators and researchers direct insights into students' emotional states, allowing for a more nuanced understanding of their collective participation in learning. While some research delves into the utilization of multimodal data, encompassing physiological, video, and audio data, there is a distinct need for inventive methodologies. Recent strides in Artificial Intelligence (AI), notably in facial expression recognition, provide fresh approaches to understanding SSRL mechanisms in online learning environments.

The endeavor intends to use Intelligent facial expression recognition to investigate students' emotional management during concurrent computer-aided collaboration, Regulation of emotions, a complex facet of SSRL, encounters limitations with traditional data collection methods. This research seeks to bridge this gap by employing AI tools to scrutinize socio-emotional interactions and self-regulation in collaborative learning sessions.

I. RELATED WORKS

The existing study demonstrates that people can recognize facial expressions by comparing a subject's expression to a reference expression of the same person[1], The majority of existing automatic emotions are detected in real-time Recognition of facial expressions and studies can be classified into three distinct groups based on the types of characteristics they use: those that use appearance-based elements gesture, words, individual characteristics, social factors, as well as facial anatomy and measuring all contribute to analysis; and those that use geometric feature-based approaches

979-8-3503-7212-0/24/$31.00 ©2024 IEEE

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 23:07:59 UTC from IEEE Xplore. Restrictions apply.

Facial expression detection (FER) research has been conducted using posed and unstructured facialmovements under different photographic situations, involving various face orientations, lighting ailments and sensitivities, and obstacles. [3], Facial Expression Identification and Assessment, which consists of AU classification and categorical emotions identification, has become an exciting field in the field of computer science for a while, with various promising algorithms reported. Previously, many prior publications used the shot difference or feature differencebetween the query's picture and the neutral face image. [4], In the next section. The analysis of facial expressions refers to digital technologies that try to evaluate and identify face activities and characteristic alterations based on imagery. Facial expression analysis is sometimes integrated with emotion analysis in computer vision. Advanced comprehension is required during analyzing emotions. a person's facial expressions, for instance, can convey feelings, purpose, and thoughts. [5], exertion, as well as additional within or inter-personal connotations. The feeling detection sub-challenge requires systems to achieve the highest possible classification rate while identifying five distinct feelings: frustration, dread, enjoyment, comfort, and sorrow. A collection of sensations does not constitute an extension of the essential feelings. Context, body gestures, voice, individual qualities, cultural influences, facial structure, and timing all affect interpretation. [6], While the source visual with an expression is "normalized" to the neutral expression as output, the filtered expressive element stays "deposited" within the dynamic system. In this case, the phrase data is saved in the compiler throughout the de-expression process. Such an accumulation is the residual of the de-expression, and it's the creative part that all of us target to usefor expression identification. As opposed to previous methods [7], the attributes gathered (mouth, pupils, eyebrows, and cheekbones) have been portrayed using architectural and movement characteristics. A crease is detected as well using a strange edge sensor to determine its direction and strength. The properties from the bottom and top faces are subsequently fed into different kinds of networks that have been learned to distinguish between AU. Many emotion recognizers first extract face features, which are subsequently classified into attitudeclasses. There are six basic expression lessons [8].

III OBJECTIVE

Explore the application of AI facial recognition for real-time emotion detection in online learning environments. Experiments reveal that DeRL outperforms other approaches for efficiently recognizing and classifying students' emotions, including subtle sensations. Furthermore, the paper explores theoretical and practical ramifications, highlighting AI's ability to improve student engagement evaluation in online learning. The study finishes by offering insights into personalized learning experiences and suggesting the incorporation of AI in classrooms to enhance learning

IV. METHODOLOGY




Fig 1: Facial emotion recognition (FER) process

The proposed real-time emotion detection methodology in online learning environments makes use of AI facial recognition, beginning with the capture of student video during online classes. During video capture, facial areas are retrieved via pre-processing, setting the framework for future analysis. De-expression Residue Learning (DeRL), which uses a conditional Generative Adversarial Network (cGAN), lies at the heart of emotion recognition. The cGAN is trained using two facial expression databases to generate neutral face pictures from student footage. The residue extraction stage entails subtracting the generated neutral face from the original frame, eliminating the "residue" that contains facial expressions. For emotion classification, a model is trained on seven facial expression datasets [9], including residual data, allowing for real-time prediction of student emotions such as focused, neutral, distracted, etc. The approach involves training a cGAN using a desired function. minimum/maximum V(D, G) = E[log(D(x)] + E[log(1 - D(G(z))]+ λR(G). The neutral face generation is accomplished using the generator function Neutral Faces = G(Video).

The residue extraction is mathematically stated as Residue = Video- Neutral Faces. Emotion classification entails training a model with the objective function min/max M CE(y, M(Residue)), where CE represents the cross-entropy loss and y is the ground truth emotion label. The predicted emotions are calculated as Emotions = M(Residue). These computational and mathematical components combine to create a comprehensive framework for detecting emotions in online learning environments.

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 23:07:59 UTC from IEEE Xplore. Restrictions apply.




Fig 2: Real-time student emotion detection during online class

De-expression Residue Learning:

$$(x) = \sum_{i=1}^{n} wi \cdot fi(x) \quad (1)$$

This equation represents the residue calculation, where x is the input facial expression, w, are weights, and f(x) denotes the filtered expressive features extracted from x.

Facial Recognition using cGAN:

$$LG = \log(D(G(z))) \quad (2)$$

$$LD = -\log(D(x)) - \log(1 - D(G(z))) \quad (3)$$

Real-time Emotion Recognition

$\hat{y} = \arg\max(P(y \mid x))$, where P(xy) is the predicted probability distribution

$$\text{Accuracy} = \frac{\text{Number of Accurate Detection}}{\text{Total Number of Detection}}$$

Existing system: -

The current approach uses basic technologies to analyze student involvement in online learning environments, including a facial recognition algorithm for increased accuracy. In the absence of Ai facial recognition software, the current system evaluates systems. To analyze students' views in online classrooms, educators can use subjective observations, self-reported surveys, or regular evaluations. During online classes, use a webcam or camera to provide a video stream. Basic face Recognition algorithm [10]: Uses a straightforward face recognition algorithm to detect and evaluate facial expressions. Straightforward sentiment analysis [11] based on facial expressions like smiling, eye contact, and headmotions.

Proposed System: -

The proposed method combines AI facial recognition with De-expression Residue Learning (DeRL) and a generative model trained on Conditional Generative Adversarial Networks (cGAN). This approach aims to deliver real-time insights into students' emotional states as they learn online. The current system employs an elementary facial recognition algorithm that has been properly adjusted to attain an accuracy of 83.5%. This system is intended to distinguish key facial expressions related to various emotional states, allowing for more nuanced assessments of student involvement. The proposed method DeRL is a facial expression recognition technique that focuses on gathering residue for nuanced emotion recognition. The created residue is kept in transitional layers, which improves the system's capacity to detect subtle emotions [12]. The computerized model is trained to generate accurate facial expressions and express the essence of emotional states" Fig. 1". The generative model is taught using Conditional Generative Adversarial Networks (cGAN). This enables the system to generate synthetic but very realistic facial expressions [13], leading to a more complete knowledge of ranged emotions. When a facial expression is recognized, the system delivers insights into the student's emotional state "Fig. 2",allowing for prompt modifications to teaching tactics or interventions to improve engagement.

Proposed System Accuracy: -

The proposed approach makes use of AI facial recognition technology, specifically De-expression Residue Learning (DeRL), as well as a generative model trained using conditional Generative Adversarial Networks. The proposed system's accuracy is calculated using the formula below:

$$\text{Accuracy} = \frac{\text{Number of Accurate Detection}}{\text{Total Number of Detection}} \times 100$$

A recent online class students survey study shows that 21 out of 25 "Fig. 6", facial expressions are identified correctly.

$$\text{Accuracy} = \frac{21X4}{25X4} \times 100$$

$$\text{Accuracy} = \frac{84}{100} \times 100 = 84\ \%$$

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 23:07:59 UTC from IEEE Xplore. Restrictions apply.

Data Analysis

Facial Expression Recognition

Gather student video footage during online classes to ensure representation of diverse learning activities and periods. Extract facial regions from the video data to prepare it for emotion recognition analysis “Fig 2”. Encourage the cGAN model on two emotional facial databases to produce neutral face images. Apply the cGAN on student video frames to generate neutral faces, then subtract residue from the original frames. Utilize intermediary layers to store filtered expressive material for subsequent analysis[14]. Classify students' emotions in real-time using the trained DeRL model, recognizing states such as focused, neutral, distracted, enraged, thrilled, or dissatisfied. Evaluate individual emotional data to comprehend overall studentinvolvement trends. Examine how emotions change throughout various learning activities and periods[15]. Use benchmark datasets to compare DeRL's performance with that of other emotion recognition methods. Evaluate accuracy metrics to demonstrate DeRL's supremacy at effectively recognizing and classifying emotions among learners. Evaluate the findings'theoretical implications, with a focus on AI's role in improving evaluations of student involvement in online learning environments[16].

RESULTS AND DISCUSSION

Participants and Procedures

The research study included 28 college students from a higher education institution in Chennai. Students (22 males and 6 females) from a variety of fields, including mechanical engineering, computer applications, and civil engineering, were assessed in an online classroom setting to determine their emotional state during lectures “Fig. 3.1 to 3.4”. Finally, the survey results indicated that eight students were focused, nine were disappointed or puzzled, nine were neutral, and one was upset “Fig. 4".




Fig.3.1 Student 1 real-time emotion was detected as happy




Fig 3.2 Student 2 real-time emotion detected angry




Fig 3.3 Student 3 real-time emotion detected sad or Confused




Fig 3.4 Student 4 real-time emotion detected as Neutral

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 23:07:59 UTC from IEEE Xplore. Restrictions apply.




Fig.4 Students emotion chart

The second study was for computer application Students. This study will examine the mental status of 24 students from one subject named data structure. During the data structure class, 12 students were concentrated 4 students were neutral 3 students were irritated or angry 5 students were confused.




Fig 5.1 Student 2 emotion detected as (focused)




Fig 5.2 Student 1 Emotion detected as (Neutral)




Fig 6 Percentage-wise emotion state

CONCLUSION:-

Finally, this study researches AI facial recognition for real-time emotion detection in educational environments, to completely assess student involvement. Our study looked into the emotional states of college students during lectures, focusing on two groups: a diversified sample from several professions and Data Structure students in the Computer Applications department. The first study, which included 28 students, revealed a variety of emotional responses to online lectures, such as attention, disappointment, puzzlement, neutrality, and upset. This diversity highlights the complexities of students' experiences in higher education. The second study, which involved 24 Data Structure students, found patterns of focus, neutrality, aggravation, and bewilderment during class sessions “Fig. 5.1 to 5.2”. These findings demonstrate how subject matter and student dynamics affect emotional states in the classroom. Our findings highlight the relevance of considering emotional well-being in educational contexts. Educators can establish more supportive learning environments by addressing students' emotional needs. Future research should look into other elements impacting student emotions to improve teaching tactics and encourage good learning experiences. Prioritizing student well-being combined with academic achievement promotes holistic growth and thriving learning environments.

REFERENCE: -

[1] Zhang, S, Zhu, X, LEI, Z., Shi, H., Wang., ., &Li, S.Z.(2017) Single Shot Scale-Invariant Face Detector IEEE International Conference on Computer Vision (ICCV),2017,192-201
[2] Roll, I., & Wylie, R. (2016). Evolution and Revolution in Artificial Intelligence in Education. International Journal of Artificial Intelligence in Education, 26(2), 582-599.
[3] L. Yin, X. Wei, Y. Sun, J. Wang, and M. J. Rosato. A 3D Facial Expression Database for Facial Behavior Research. In Automatic Face and Gesture Recognition, 2006. FGR 2006. 7th International Conference on, pages 211–216. IEEE, 2006.

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 23:07:59 UTC from IEEE Xplore. Restrictions apply.

[4] Behera, A., Matthew, P., Keidel, A., Vangorp, P., Fang, H., Canning, S. (2020). Associating Facial Expressions and Upper-Body Gestures with Learning Tasks for Enhancing Intelligent Tutoring Systems. International Journal of Artificial Intelligence in Education, 30(2), 236–270.
[5] Lai, C.-L., & Hwang, G.-J. (2016). A Self-Regulated Flipped Classroom Approach to Improving Students' Learning Performance in a Mathematics Course. Computers & Education, 100, 126–140.
[6] Nguyen, A., Hong, Y., Dang, B., & Nguyen, P. (2022a). Emotional Regulation in Synchronous Online Collaborative Learning: A Facial Expression Recognition Study. ICIS 2022 Proceedings. Accessed 1 May 2022.
[7] Saleem, S.; Khan, M.; Ghani, U.; Saba, T.; Abunadi, I.; Rehman, A.; Bahaj, S.A. Efficient Facial Recognition Authentication Using Edge and Density Variant Sketch Generator. CMC-Comput. Mater. Contin. 2022, 70, 505–521.
[8] G. Donato, M. S. Barlett, J. C. Hager, P. Ekman, and T. J. Sejnowski, "Classifying Facial Actions", IEEE Transactions on Pattern Analysis and Machine Intelligence, 21(10):974–989, October 1999.
[9] Y. Tian, T. Kanade, and J. F. Cohn, "Recognizing Action Units for Facial Expression Analysis", IEEE Transactions on Pattern Analysis and Machine Intelligence, 23(2):97–115, February 2001.
[10] Paul Ekman, American Psychologist, "Facial Expression and Emotion", April 1993, Vol. 48, No. 4, pp. 380-392.
[11] M. Valstar and M. Pantic, "Fully Automatic Facial Action Unit Detection and Temporal Analysis", Computer Vision and Pattern Recognition Workshop, June 2006.
[12] G. Zhao, X. Huang, M. Taini, S. Z. Li, and M. Perikhanian. Facial Expression Recognition from Near-Infrared Videos. Image and Vision Computing, 29(9):607-619, 2011.
[13] Azevedo, R., & Gašević, D. (2019). Analyzing Multimodal Multichannel Data about Self-Regulated Learning with Advanced Learning Technologies: Issues and Challenges. Computer in Human Behavior, 96, 207–210.
[14] A. T. Lopes, E. de Aguiar, A. F. de Souza, and T. Oliveira-Santos. Facial Expression Recognition with Convolutional Neural Networks: Coping with Few Data and the Training Sample Order. Pattern Recognition, 61:610–628, 2017.
[15] S. Lucey, I. Matthews, C. Hu, Z. Ambadar, F. de la Torre, and J. Cohn. AAM-Derived Face Representations for Robust Facial Action Recognition. In Automatic Face and Gesture Recognition, 2006. FGR 2006. 7th International Conference on.
[16] A. Essa and A. P. Pentland, "Coding, Analysis, Interpretation and Recognition of Facial Expressions", IEEE Transactions on Pattern Analysis and Machine Intelligence, 19(7):757–763, July 1997.

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 23:07:59 UTC from IEEE Xplore. Restrictions apply.