2024 International Conference on Communication, Computing and Energy Efficient Technologies (I3CEET) | 979-8-3315-4158-3/24/$31.00 ©2024 IEEE | DOI: 10.1109/I3CEET61722.2024.10993939

Facial Emotion Recognition

A Holistic Review

Aryan Mandal
Electical and Electronics Engineering
Galgotias College of Engineering & Technology
Greater Noida, India
aryanmandal0233@gmail.com

Anurag Yadav
Electical and Electronics Engineering
Galgotias College of Engineering & Technology
Greater Noida, India
anuragyadav220902@gmail.com

Aryan Kumar Latiyan
Electical and Electronics Engineering
Galgotias College of Engineering & Technology
Greater Noida, India
latiyanaryan10@gmail.com

DR. GAURI KATIYAR, MEMBER IEEE
Electical and Electronics Engineering
Galgotias College of Engineering & Technology
Greater Noida, India
gaurikatiyar0208@yahoo.com

ABSTRACT- Facial emotion recognition is a field having rapid enhancement with every day passing, exploring and advancing the field of surveillance, security, healthcare and numerous other critical infrastructures. Its underlying mechanism, application, and burgeoning prominence in contemporary society are highly valuable. The state of the art in the field of emotional detection and recognition is succinctly summarized in this paper as well as the necessity of appropriate facial recognition deployment in the digital era going forward.

KEYWORDS- CONVOLUTIONAL NEURAL NETWORK(CNN), Facial emotion recognition (FER), ADA boost, Haar Cascades, Artificial Neural Network (ANN), Facial animation parameter (FAPs).

1. INTRODUCTION

In an increasingly interconnected world driven by technological innovation, the ability to accurately perceive and interpret human emotions plays a pivotal role in humancomputer interaction, psychology, and various other domains. Within the domains of artificial intelligence and computer vision, facial emotion identification has become a vital topic of research with many applications. It holds the promise of enhancing human-machine communication, revolutionizing marketing strategies, improving mental health diagnosis, and even contributing to the development of emotionally intelligent robots.

Facial emotion recognition involves the automated detection and interpretation of emotional states from facial expressions, providing valuable insights into an individual's emotional well-being and intentions. The potential of this technology to close gaps in communication, promote compassionate connections, and provide hitherto unattainable insights into human behavior highlight its significance.

This research paper embarks on a journey through the landscape of facial emotion recognition, seeking to provide a comprehensive overview of its evolution, methodologies, challenges, and promising applications. In order to shed light on the quick advancement and interdisciplinary nature of face emotion recognition research, this presentation will examine the historical background, contemporary state-of-the-art methodologies, and future directions in this subject.

We begin by exploring the Historical Evaluation underlying human facial expressions and emotions, recognizing the role they play in human social interaction and communication. After that, we go into the history of face emotion identification, covering everything from the first manual techniques to the modern Deep learning and machine learning approaches have revolutionized the sector.

Next, we delve into the methodologies and technologies that enable the automatic recognition of emotions from facial expressions. This section will encompass the various data sources, feature extraction techniques, and machine learning algorithms that are commonly employed to achieve high levels of accuracy in emotion detection.

However, the journey of facial emotion recognition is not without its challenges. Ethical concerns surrounding privacy, bias, and the responsible use of this technology loom large. We will explore these ethical considerations and discuss the measures taken to address them. Section 2 of the study outlines the historical assessment in the area of recognition of faces. In Section 3, it is discussed about development of facial expression recognition meanwhile Section 4 mentions the methodologies used whereas Section 5 depicts the result of the research paper.

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 22:58:59 UTC from IEEE Xplore. Restrictions apply.

2. HISTORICAL EVALUATION

There is a long history behind facial expression recognition research and popular interest. These early studies established the idea that emotions may be regarded as reflex behaviors with biological bases that serve adaptive purposes, and they emphasized the importance of facial expressions in emotional life. Emotions being seen as catalysts for physiological action served as the foundation for the Darwinian idea, which held that emotions help with survival and that intentions are communicated through facial expressions and other physiological responses.

Newer theories "have started to methodically link particular emotions to social functions" [1]. Lazarus, for instance, focused his theory of emotion on how the experience of emotion is influenced by individual assessment, or how an event is assessed in terms of relationships and one's own selfconcept. One "prominent recurrent question" has been how emotions are distinguished [2]. According to Izard's differentiated emotions theory, different facial shapes and neurological substrates correspond to different emotions[3].

Academic publications have published special issues on facial expression recognition [4], one of which is Behavior Modification. Multiple publications that included study data on the FER abilities of people with various clinical situations were offered by Singh and Ellis theory. According to Singh and Ellis' theory, it is essential to comprehend the reasons behind certain people's inability to precisely identify the essential basic emotion-related expressions at a publically accepted standard to help students develop the ability to interpret facial expressions correctly. The ultimate goal is, naturally, to improve people's quality of life by enabling them to fully participate in the human experience, in addition to treating the underlying clinical disorders [5].

After decades of studying facial expressions and emotions, the Ekman theory has been used to support the presence of basic emotions that can be identified in facial expressions, such as fear, joy, sadness, anger, contempt, and surprise. multiple mainstream publications, including Time Magazine, have featured Ekman's work, and he is now publishing multiple books in popular culture. As a result, there appears to be a parallel interest in research into the anatomical operational characteristics of expressions, as well as in individuals' tenancy to acknowledge them, which will be supported by popular culture[6].

3. DEVELOPMENT OF FACIAL EXPRESSION RECOGNITION

It makes sense to begin with the studies on the theory of how face recognition evolves during from early infancy and throughout adulthood to look more closely at this topic that is becoming more and more well-known. It's also critical to revisit How FER is influenced by culture, class, gender, and cognitive ability.

An overview of the literature on these subjects can be found in the sections that follow. The capacity to recognize facial expressions usually follows a developmental trajectory, becoming more accurate as one gains experience with others and develops cognitively. Most children learn to classify basic emotions by the time they are 18 months old, however Early childhood is when the capacity to infer emotions from facial expressions begins. Crosssectional study results indicate that by the age of five, children's ability to recognize specific emotions such as happiness, sadness, and anger improves to a level approaching that of an adult. The majority of children can recognize and classify the basic emotions of pleased and furious by the time they reach the age of three, even yet it appears that the capacity to recognize more nuanced emotions (such disgust and surprise) comes later in life [3].

Much research needs to be done to determine the specific processes and mechanisms behind the development of facial expression recognition ability. Nonetheless, there is proof that the formation of emotion-processing brain networks [9] and early life experiences [7, 8, 9] are crucial for the improvement of face expression recognition abilities. Since the turn of the century, there has been an increase in curiosity in learning more about how people decipher nonverbal emotional cues and the potential effects of this interpretation behavior and social interactions [9][10].

Control access CNNs are the most widely used is an approach for data extracting. CNNs differ from multilayer perceptrons (MLPs) in that they have hidden layers called convolutional layers. The proposed method is based on a two-level CNN structure. Background removal is the first level that is advised since it is employed to draw emotions out of an image. In this case, The CNN network module in its standard form is used to extract the primary expressional vector (EV). By identifying relevant facial spots of interest, the expressional vector (EV) is generated. EV and expression alterations are directly correlated.

The EV is gained by requisitioning a simple perceptron unit to the facial image after obstacles has been removed. In the planned FERC blueprint, a non-convolutional perceptron layer is also a part of the final level. Each CNN layer gets the image input and filter before forwading it to next step[11].

All of the convolutional layers that are used have the ability to recognize patterns. Every convolutional layer had four filters in it. Most of the time, the input data provided to the first level of CNN including the face as well (which removes the backdrop) contains of forms, edges, textures, and objects. The edge detector, circle detector, and corner detector filters are used at the beginning of the convolution level. Once the object has been identified, the second level of the CNN filter record features like the nose, cheeks, lips, eyes, ears. Layers using a 3

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 22:58:59 UTC from IEEE Xplore. Restrictions apply.

× 3 kernel matrix, the second level of CNN is made of [0.25, 0.17, 0.9; 0.89, 0.36, 0.63; 0.7, 0.24, 0.82]. These numbers are initially selected between 0 and 1. Using our ground truth, these parameters are optimized for EV identification in the supervised training dataset. Using minimal error decrypting to maximize the filter values. The supervisory learning process tunes the filter, applying to the face with the obstacle removed which is an image of first level of CNN. To identify different facial components. Different facial traits are extracted from each of the 24 in order for the EV matrix to be created. The normalized Euclidian distance values between each facial segment are used to create the EV feature vector [12].

4. METHODOLOGY

Convolutional neural networks are the process frequently employed for data evaluation. CNNs differ from multi-layer perceptrons (MLPs) as they contain hidden convolutional layers. The suggested method is drew on a two-level CNN structure. Background removal is the first level that is advised since it is employed to draw emotions out of an image. The typical CNN network module is employed in this case to extract the primary expressional vector (EV) [13].

The process of creating the expressional vector (EV) is done via identification of pertinent face points of interest. EV and expression alterations are directly correlated. The EV is gained by requisitioning a simple perceptron unit to a face image after the obstacles has been eliminated. In this process, the input image is received and delivered the findings to the last level that receives after it in the convolution layer. Every convolutional layer had four filters in it. In addition to the face, the test image given to the first part CNN, which does the removal of the backdrop, usually containing shapes, edges, textures, and objects [18].



Fig. 1 Face Recognition Algorithm [11]

After image processing the second-level CNN filter records facial features like the nose, cheeks, lips, eyes, and ears. Edge detection filters are used in this layer. The integers were initially selected binary terms. Using our ground truth, these parameters are optimized for EV identification in the supervised training dataset. Here, we optimized the filter values using minimal error decoding.

The supervisory learning process tunes the filter, which is then applied to the facial features with obstacle removal. The result data of the first part of CNN to identify different facial features (e.g., eye, mouth, nose, ears, etc.).




Fig. 2 Block diagram for Face recognition system [14]

Different facial traits are extracted from each of the 24 in order to create the EV matrix. All that the EV feature vector consists of are normalized Euclidian distance between each face component is used in 3D face recognition testing and training. Richer geometric information seen in 3D faces as opposed to 2D photos can offer additional distinct qualities, aiding the software in subduing basic flaws as well as limitations of the software [15].

Numerous applications, like lie detection and predictive learning, could make use of FERC.

If the input to FERC is a video, the frame with the highest aggregated sum of white pixels after Canny edge detection is selected as the input since it includes the most detail.

The skin tone detection approach is used to extract the human body components for the input image. The kind of input image determines the skin tone detection algorithm. The Hough transform is if the image is grayscale being put to use. The

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 22:58:59 UTC from IEEE Xplore. Restrictions apply.

elimination of the background CNN makes use of two input features (first-part CNN).




Fig. 3 Taxonomy of 3D Face recognition methods

FERC is a unique two-part CNN technique for facial expression identification. FERC produced good results on a larger dataset of 750,000 photos and an accuracy of 96% on a collection of 10,000 photographs.

The convolutional neural networks, or CNNs, Proposed method will be on a two-level CNN structure. As a starting point, background removal is advocated since it is employed to draw emotions out of an image. In this case, the conventional CNN network module extracts the primary expressional vector (EV). The background-removed face (i.e., the first part CNN's output image) receives the filter, after being fine- tuned by supervised learning in order to recognize various facial components, such as the eye, mouth, nose, ears, etc. [12].

In recent years, 3D face recognition has gained popularity as a study topic due to its higher recognition accuracy and durability than 2D face recognition.Testing for 3D-based software uses 3D facial data and development. Richer geometric information seen in 3D faces as opposed to 2D photos can offer more distinct qualities hence aiding software in subduing the flaws and limitations of 2D face identification. Acquiring 3D training photos are the primary obstacle to the software [16].

Regular face recognition technology is really good at recognizing faces in well-lit places where everything is stable. But it struggles when things change, like when the lighting is different, or when a person's face is in a different position or making a different expression. The problems can be solved using Infrared Sensing.

Unlike computers, our brains are amazing at recognizing faces even when things change a little bit. We're great at recognizing faces even after a long time or if the face looks a bit different. In summary, infrared images possess unique characteristics that facilitate facial recognition even in the presence of changing illumination or expressions. We sought to determine whether the loss of certain visual characteristics such as edges, skin patterns, and texture might be made up for by infrared (IR) facial photographs, which are less influenced by variables such as face direction and expression. We employed a classification system based on Eigenfaces to accomplish this [17][18].

Using a database including 40 distinct faces in a range of poses and expressions, we evaluated this. This is depicted in Figure 4. There were two to four training images (96 total) and five to ten test images (250 total) for each face. Setting a threshold of 99% allowed us to choose the most important Eigenfaces, giving us a collection of 78 Eigenfaces [19].



FIG.4. EXAMPLE OF IR SHOWING FACIAL EXPRESSION VARIATION

The main conclusions of this study show that variations in posture or expression have less of an impact on IR face images. They also make it possible to identify face traits in an easy way. The study investigates a number of face recognition techniques with infrared images [20].

4. RESULT

This study presents a thorough analysis of the state of face emotion identification today, emphasizing developments, difficulties, and potential paths forward. The findings contribute to the ongoing dialogue on the evolution of FER technology, offering insights for researchers, practitioners, and policymakers. The continued development of accurate and reliable FER systems holds immense potential for enhancing human-machine interactions and applications in various domains.

5. CONCLUSIONS

The essential contributing factors in the field of Facial Expression Recognition during the past decade, its current whereabouts, and its prospects have been surveyed in this paper. Various processes discussed are CNN (convolutional neural networks), FERC (facial emotional recognition), 3D Face recognition and IR (infrared imaging) which contribute towards recognition more or less being dependent on each other or in some case independently. The crucial emphasis

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 22:58:59 UTC from IEEE Xplore. Restrictions apply.

lies in refining these techniques to align with the standards of a precise science, rather than relying solely on the accumulation of empirical knowledge.

Real-time Processing, facial changes due to long span or makeup, and Lighting Conditions are the problems that are faced currently in Facial Expression Recognition but are solvable using Infrared technique and to overcome other problems, combining other modalities like speech and body language can enhance accuracy but also introduces additional complexity. Therefore, we hope that our research helps future researchers in this field.

6. REFERENCES

[1] Keltner, D., & Haidt, J. (2001). Social functions of emotions. In T. Mayne & G. A. Bonanno (Eds.)

[2] Frida, N. H. (2004). The psychologists' point of view. In M. Lewis & J. M. Haviland-Jones (Eds.)

[3] Izard, C. E., & Harris, P. (1995). Emotional development and developmental psychopathology. In Cicchetti & D. J. Cohen (Eds.), Developmental psychopathology, Vol. 1: Theory and method (pp.467 503). New York: John Wiley & Sons.

[4] Happe', F. (2004). Editorial: Introduction to special section on pace processing. Journal of Child Psychology and Psychiatry

[5] Singh and Ellis, Facial Expressions of Emotion First, published April 1998, https://journals.sagepub.com/doi/abs/10.1177/0 1454455980222001 Virginia commonwealth university

[6] Ekman, P. (1993). Facial expression and emotion. American Psychologist, 48(4), 384- 392.https://doi.org/10.1037/0003- 066X.48.4.38 [7] Gibb, B. E., Schofield, C. A., & Coles, M. E. (2009). Reported history of childhood abuse and young adults' information processing biases for facial display of emotion, Child Maltreatment, 14, 148 156.

[8] Pollak, S. D., & Sinha, P. (2002). Effects of early experience on children's recognition of facial displays of emotion. Developmental Psychology, 38, 784 791.

[9] Herba, C. M., Landau, S., Russell, T., Ecker, C., & Phillips, M. L. (2006). The development of emotion processing in children: Effects of age, emotion, and intensity. Journal of Child Psychology and Psychiatry, 47, 1098 210

[10] Crick, N. R., & Dodge, K. A. (1994). A review and reformulation of social information- processing mechanisms and children social adjustment. Psychological Bulletin, 115, 74-101

[11] P. Phillips, H. Wechsler, J. Huang, and P. Rauss (1998). The FERET database and evaluation procedure for face recognition algorithms, Image and Vision Computing.

[12] Yann Lecum," Face Recognition", Institute for Computer Science University of Tromso, Norway.

[13] J. Wilder, P.J. Phillips, C. Jiang, and S. Wiener. Comparison of Visible and Infra-Red Imagery for Face Recognition, Proceedings of the 2nd International Conference on Automatic Face and Gesture Recognition, Killington.

[14] Yaping Jing1, Xuequan Lu, and Shang Goa, "3D- FaceRecognition".

[15] Huibin Li, Di Huang, Jean Merie Morvan, Yunhong Wang, Liming Chen.

[16] M. Turk and A. Pentland (1990). Eigenfaces for recognition, J. Cog. Neuroscience.

[17] M. Kirby and L. Sirovich (1990) Application of the karhunen-loeve procedure for the Characterization of human faces, IEEE Pattern Analysis and Machine Intelligence.

[18] R. Cutler (1996). Face recognition using infrared images and eigenfaces. http://research.microsoft.com/~rcutler/face/fac e.html

[19] Huibin Li, Di Huang, Jean Merie Morvan, Yunhong Wang, Liming Chen.

Authorized licensed use limited to: UNIVERSITAS GADJAH MADA. Downloaded on June 15,2025 at 22:58:59 UTC from IEEE Xplore. Restrictions apply.