

```
1: #include<stdio.h>
2:
3: int get_median(int a, int b, int c, int med);
4:
5: int main(void)
6: {
7:     int a, b, c, med;
8:     printf("i\204, ê\234i\235\230 i \225i\210\230ë¥%
i\236\205ë ¥í\225\230i\204,i\232\224: ");
9:     scanf("%d %d %d", &a, &b, &c);
10:    med = get_median(a, b, c, med);
11:    printf("%d", med);
12:    return 0;
13: }
14: int get_median(int a, int b, int c, int med)
15: {
16:     if(a>b && a<c || a>c && a<b)
17:         return a;
18:     if(b>a && b<c || b>c && b<a)
19:         return b;
20:     if(c>a && c<b || c>b && c<a)
21:         return c;
22: }
```

```
1: #include<stdio.h>
2:
3: int is_leap_year(int year)
4: {
5:     if(year % 4 == 0 && year % 100 != 0)
6:         return 1;
7:     if(year % 400 == 0)
8:         return 1;
9:     else
10:        return 0;
11: }
12:
13: int main(void)
14: {
15:     int year, result;
16:     printf("i\227°ë\217\204ë¥% i\236\205ë ¥i\225\230i\204,i\232\224: ");
17:     scanf("%d", &year);
18:     result = is_leap_year(year);
19:     if(result == 1)
20:         printf("%dë\205\204i\235\200 i\234¤ë\205\204i\236\205ë\213\210ë\213¤.",
year);
21:     if(result == 0)
22:         printf("%dë\205\204i\235\200 i\234¤ë\205\204i\235´
i\225\204ë\213\231ë\213\210ë\213¤.", year);
23: }
```

```
1: #include<stdio.h>
2: int abs_compare(int a, int b);
3:
4: int main(void)
5: {
6:     int i, j;
7:     printf("ë\221\220 ì \225ì\210\230ë¥%
ì\236\205ë ¥ì\225\230ì\204,ì\232\224: ");
8:     scanf("%d %d", &i, &j);
9:     printf("ì \210ë\214\223ë°\222ì\235´ ë\215\224 í\201° ì\210\230ë\212\224
%d ì\236\205ë\213\210ë\213¤.", abs_compare(i, j));
10:    return 0;
11:
12: }
13:
14: int abs_compare(int a, int b)
15: {
16:     if(a<0)
17:         a=-a;
18:     if(b<0)
19:         b=-b;
20:     if(a>b)
21:         return a;
22:     if(b>a)
23:         return b;
24: }
```

```
1: #include<stdio.h>
2: int main(void)
3: {
4:     int a;
5:
6:     printf("ì \220ì\210\230ë¼¼ ì\236\205ë ¥í\225\230ì\204,ì\232\224: ");
7:     scanf("%d", &a);
8:
9:     if(a>=90)
10:         printf("ë\213¹ì\213 ì\235\230 í\225\231ì \220ì\235\200 A
ì\236\205ë\213\210ë\213¤");
11:     else if(a>=80 && a<=89)
12:         printf("ë\213¹ì\213 ì\235\230 í\225\231ì \220ì\235\200 B
ì\236\205ë\213\210ë\213¤");
13:     else if(a>=70 && a<=79)
14:         printf("ë\213¹ì\213 ì\235\230 í\225\231ì \220ì\235\200 C
ì\236\205ë\213\210ë\213¤");
15:     else if(a>=60 && a<=69)
16:         printf("ë\213¹ì\213 ì\235\230 í\225\231ì \220ì\235\200 D
ì\236\205ë\213\210ë\213¤");
17:     else
18:         printf("ë\213¹ì\213 ì\235\230 í\225\231ì \220ì\235\200 F
ì\236\205ë\213\210ë\213¤");
19:
20:     return 0;
21: }
```

```
1: #include<stdio.h>
2: int main(void)
3: {
4:     int a, b, c;
5:
6:     printf("i\204, ê°\234i\235\230 i \225i\210\230ë¥%
i\236\205ë ¥i\225\230i\204,i\232\224: ");
7:     scanf("%d %d %d", &a, &b, &c);
8:
9:     if(a<b && a<c)
10:    {
11:        if(a % 2 == 1)
12:            printf("ê°\200i\236¥ i\236\221i\235\200
i\210\230ë\212\224 %di\235'ê³ , í\231\200i\210\230i\236\205ë\213\210ë\213¤.", a);
13:        if(a % 2 == 0)
14:            printf("ê°\200i\236¥ i\236\221i\235\200
i\210\230ë\212\224 %di\235'ê³ , is\235i\210\230i\236\205ë\213\210ë\213¤.", a);
15:    }
16:    if(b<a && b<c)
17:    {
18:        if(b % 2 == 1)
19:            printf("ê°\200i\236¥ i\236\221i\235\200
i\210\230ë\212\224 %di\235'ê³ , í\231\200i\210\230i\236\205ë\213\210ë\213¤.", b);
20:        if(b % 2 == 0)
21:            printf("ê°\200i\236¥ i\236\221i\235\200
i\210\230ë\212\224 %di\235'ê³ , í\231\200i\210\230i\236\205ë\213\210ë\213¤.", b);
22:    }
23:    if(c<a && c<b)
24:    {
25:        if(c % 2 == 1)
26:            printf("ê°\200i\236¥ i\236\221i\235\200
i\210\230ë\212\224 %di\235'ê³ , í\231\200i\210\230i\236\205ë\213\210ë\213¤.", c);
27:        if(c % 2 == 0)
28:            printf("ê°\200i\236¥ i\236\221i\235\200
i\210\230ë\212\224 %di\235'ê³ , í\231\200i\210\230i\236\205ë\213\210ë\213¤.", c);
29:    }
30:    return 0;
}
```

```
1: #include<stdio.h>
2:
3: int reverse_number(int num);
4: int is_palindrome(int num);
5:
6: int main(void)
7: {
8:     int a, b;
9:     printf("i\204, i\236\220ë;¬ i \225i\210\230ë¥%
i\236\205ë ¥i\225\230i\204,i\232\224: ");
10:     scanf("%d", &a);
11:
12:     b = reverse_number(a);
13:     printf("è\222mi§\221i\235\200 i\210\230ë\212\224
%di\236\205ë\213\210ë\213¤.", b);
14:
15: }
16:
17: int reverse_number(int num)
18: {
19:     int reverse=0, remain;
20:     while(num != 0)
21:     {
22:         remain = num % 10;
23:         reverse = reverse * 10 + remain;
24:         num = num / 10;
25:         //num = 123, reverse = 321, remain = 3
26:         //reverse * 10 = 3210+3 = 3213
27:     }
28:     return reverse;
29: }
30:
31: int is_palindrome(int num)
32: {
33:     int reverse, remain;
34:     while(num != 0)
35:     {
36:         remain = num % 10;
37:         reverse = reverse * 10 + remain;
38:         num = num / 10;
39:     }
40:     if(num == reverse)
41:         printf("i\232\214ë¬,i\236\205ë\213\210ë\213¤.");
42:     else
43:         printf("i\232\214ë¬,i\235´ i\225\204ë\213\231ë\213\210ë\213¤.");
44:
45:     if(num / 100 <= 1)
46:         printf("i\204, i\236\220ë;¬ i \225i\210\230ë°\200
i\225\204ë\213\231ë\213\210ë\213¤.");
47:     return num;
48: }
49:
```

```
1: #include<stdio.h>
2: //int is_triangle(void);
3: //int triangle_type(void);
4:
5: int main(void)
6: {
7:     int a, b, c;
8:     printf("i\204, ë³\200i\235\230 ê, i\235'ë¥%
i\236\205ë ¥í\225\230i\204,i\232\224: ");
9:     scanf("%d %d %d", &a, &b, &c);
10:    if(a+b<c || a+c<b || b+c<a)
11:        printf("i\202%ê°\201í\230\225i\235\204 ë§\214ë\223¤ i\210\230
i\227\206i\212pë\213\210ë\213¤.");
12:    else
13:    {
14:        if(a==b && b==c && a==c)
15:            printf("i\202%ê°\201í\230\225 ê°\200ë\212¥:
i \225i\202%ê°\201í\230\225");
16:        if(a==b && a!=c)
17:            printf("i\202%ê°\201í\230\225 ê°\200ë\212¥:
i\235'ë\223±ë³\200 i\202%ê°\201í\230\225");
18:        if(a==c && a!=b)
19:            printf("i\202%ê°\201í\230\225 ê°\200ë\212¥:
i\235'ë\223±ë³\200 i\202%ê°\201í\230\225");
20:        if(b==c && b!=a)
21:            printf("i\202%ê°\201í\230\225 ê°\200ë\212¥:
i\235'ë\223±ë³\200 i\202%ê°\201í\230\225");
22:        if(a!=b && b!=c && c!=a)
23:            printf("i\202%ê°\201í\230\225 ê°\200ë\212¥:
i\202%ê°\201í\230\225");
24:    }
25:    return 0;
26: }
```

```
1: #include<stdio.h>
2:
3: int is_valid_date(int year, int month, int day);
4: int is_leap_year(int year);
5:
6: int main(void)
7: {
8:     int year, month, day;
9:     printf("i\227°è\217\204ë¥% i\236\205ë ¥i\225\230i\204,i\232\224: ");
10:    scanf("%d", &year);
11:    printf("i\233\224i\235\204 i\236\205ë ¥i\225\230i\204,i\232\224: ");
12:    scanf("%d", &month);
13:    printf("i\235%i\235\204 i\236\205ë ¥i\225\230i\204,i\232\224: ");
14:    scanf("%d", &day);
15:
16:    if(is_valid_date(year, month, day) == 1 && is_leap_year(year) == 1)
17:        printf("i\234 i\232"i\225\234
ë\202 i§\234i\236\205ë\213\210ë\213¤.");
18:    else
19:        printf("i\234 i\232"i\225\230i§\200 i\225\212i\235\200
ë\202 i§\234i\236\205ë\213\210ë\213¤.");
20:
21:    return 0;
22: }
23:
24: int is_valid_date(int year, int month, int day)
25: {
26:     if(year<2027 && month<13)
27:     {
28:         if(month == 1 || month == 3 || month == 5 || month == 7 || month
== 8 || month == 10 || month == 12)
29:             if(day<=31)
30:                 return 1;
31:             else if(month == 4 || month == 6 || month == 9 || month == 11)
32:                 if(day<=30)
33:                     return 1;
34:             else if(month == 2)
35:                 if(day<=29)
36:                     return 1;
37:             else
38:                 return 0;
39:
40:     }
41: }
42:
43: int is_leap_year(int year)
44: {
45:     if((year % 4 == 0 && year % 100 != 0) || (year % 400 == 0))
46:         return 1;
47:     else
48:         return 0;
49: }
50:
```