

```
1: //êµ¬êµ¬ë\213¨í\224\204ë;\234ê•,ë\236¨
2:
3: #include<stdio.h>
4: int main(void)
5: {
6:     int a=1;
7:     int b=1;
8:     int c=1;
9:     printf("Insert Start Number: ");
10:    scanf("%d", &a);
11:    printf("Insert End Number: ");
12:    scanf("%d", &b);
13:
14:    while(a<=b)
15:    {
16:        c = 1;
17:        while(c<=9)
18:        {
19:            printf("%d x %d: %d      ", a, c, a*c);
20:            c++;
21:        }
22:        a++;
23:    }
24:    return 0;
25: }
26:
```

```
1: //ë°°ì\210\230ì\235\230ë°\234ì\210\230
2:
3: #include<stdio.h>
4: int main(void)
5: {
6:     int a, i=1;
7:     printf("Insert number: ");
8:     scanf("%d", &a);
9:     printf("Multiple of %d: ", a);
10:
11:     while(i<=100)
12:     {
13:         if(i % a ==0)
14:             printf(" %d ", i);
15:         i++;
16:     }
17:     printf("\nThe number of multiple of %d: %d", a, 100/a);
18:     return 0;
19: }
```

```
1: //ë³\204i°\215ê,°í\224\204ë;\234ê•,ë\236°
2:
3: #include<stdio.h>
4: int main(void)
5: {
6:     int n, b=1, s;
7:     printf("Insert the number of lines: ");
8:     scanf("%d", &n);
9:     printf("[START]\n");
10:    while(n>=b)
11:    {
12:        s = 1;
13:        while(s<=n-b)
14:        {
15:            printf(" ");
16:            s++;
17:        }
18:        while(s<=n)
19:        {
20:            printf("*");
21:            s++;
22:        }
23:        printf("\n");
24:        b++;
25:    }
26:
27:    printf("[CHANGE]\n");
28:    b = 1;
29:    while(n>=b)
30:    {
31:        s = 1;
32:        while(s<=n-b)
33:        {
34:            printf(" ");
35:            s++;
36:        }
37:        s = 1;
38:        while(s<= ((2*b)-1))
39:        {
40:            printf("*");
41:            s++;
42:        }
43:        printf("\n");
44:        b++;
45:    }
46:    printf("[END] ");
47:
48:    return 0;
49: }
```

```
1: //ë¹\204í\212,ì\227°ì\202°
2:
3: #include<stdio.h>
4: int main(void)
5: {
6:     int num1, bit, num2, oldnum, newnum, i=0;
7:     //num1 = i\236\204i\235\230i\235\230 i \225i\210\230, bit = ë¹\204í\212,
i\234\204i¹\230 i \225i\210\230, num2 = i\203\210ë;\234
i¶\234ë ¥ë\220\230ë\212\224i \225i\210\230
8:     //oldnum = i\236\205ë ¥i\225\234 i\236\204i\235\230i\235\230
i \225i\210\230i\235\230 ë¹\204í\212, 1i\235\230 ë°\234i\210\230
9:     //newnum = i\203\210ë;\234 i¶\234ë ¥ë\220\230ë\212\224
i \225i\210\230i\235\230 ë¹\204í\212, 1i\235\230 ë°\234i\210\230
10:    int count1 = 0, count2 = 0;
11:
12:    printf("Insert number and location: ");
13:    scanf("%d %d", &num1, &bit);
14:
15:    num2 = num1 | (1 << bit);
16:    printf("OLD: %d\t NEW: %d\n", num1, num2);
17:
18:    while(i<32)
19:    {
20:        count1 = (num1 & (1<<i)) ? count1 + 1 : count1;
21:        count2 = (num2 & (1<<i)) ? count2 + 1 : count2;
22:        i++;
23:    }
24:    printf("NEW COUNT: %d\t OLD COUNT: %d", count1, count2);
25:
26:    return 0;
27: }
28:
29:
```