NoteNest: a MERN notes application deployed on AWS


CEA SE-490 · Technical report · Syed Muhammad Hussain · Repository: https://github.com/tech-Hussain/Notes-App-for-AWS-Deployment

1. Cloud provider and justification

The application runs on Amazon Web Services in the Asia Pacific (Sydney) region, `ap-southeast-2`. AWS was chosen for the maturity of the managed building blocks this design needs (a managed Application Load Balancer, Auto Scaling, private networking, a container registry, a secret store, and monitoring), because a new account includes credits and a budget service for cost control, and because GitHub Actions can authenticate to AWS with short-lived OIDC credentials instead of stored keys. Sydney is the region offered by the account's organization and is also one of the three regions its policy allows; the Mumbai region originally planned for latency from Pakistan was not available, so all latency figures in this report include the long path from Pakistan to Sydney.

2. Architecture and design decisions

The app is a React single-page front end and an Express/Node API backed by MongoDB. It runs as two containers per server (Nginx web and Node API) on EC2 instances in private subnets behind a public load balancer, with MongoDB on a separate private instance. Request path: Browser → Application Load Balancer (public subnets, 2 zones) → EC2 instance in a private app subnet → Nginx container (serves the React build and proxies `/api/*`) → API container on the same Docker network (no published port) → MongoDB instance in a private DB subnet (port 27017, app security group only). Deploys are driven by `git push` through GitHub Actions.



Decision	Choice	Why

Compute	EC2 + Auto Scaling Group, Docker Compose on each instance	Matches the brief's "same host with docker-compose" path; simpler than ECS or Kubernetes for a student project.
Database	MongoDB 7 in Docker on a private EC2 with a separate encrypted EBS volume	Keeps the MERN code unchanged; a properly secured self-managed database is allowed; the EBS volume satisfies an enhancement option.
Registry	Amazon ECR, immutable tags, scan on push	IAM-controlled; every image is tagged with the git commit SHA so every deploy is traceable and rollback is just an older tag.
Secrets	SSM Parameter Store SecureString	Encrypted, IAM-scoped, free for standard parameters; values never enter Terraform state or git.
Deploy	SSM Run Command, one instance at a time	No SSH keys and no port 22 anywhere.
Infrastructure	Terraform (59+ resources)	Repeatable, reviewable, and allows nightly teardown to save money.

3. Services used per tier

Tier	AWS services
Network	VPC 10.0.0.0/16; 2 public, 2 private-app and 2 private-DB subnets across two zones; Internet Gateway; one NAT Gateway; public and private route tables; free S3 gateway endpoint.
Web	Application Load Balancer, target group with health check on `/api/health`, Auto Scaling Group (2–4 t3.micro) with target tracking at 50% CPU; Nginx container.
App	Node/Express container on the same instances, reachable only through Nginx.
Database	t3.small EC2 running MongoDB 7 with authentication and a least-privilege application user; encrypted gp3 EBS volume.
Registry / CI-CD	ECR (two repositories); GitHub Actions authenticating with an OIDC role.
Monitoring / backup	CloudWatch log groups, dashboard and 6 alarms, SNS email topic; S3 bucket for nightly MongoDB dumps (private, versioned, encrypted, lifecycle rules).
Admin / secrets	SSM Session Manager and Run Command; SSM Parameter Store; IAM roles per tier.

4. Containerization and CI/CD

Containers. The web image is a two-stage build (Node builds the Vite app, then `nginx:alpine` serves it with gzip, long cache for hashed assets, a SPA fallback and a reverse proxy to the API). The API image is a two-stage build too: TypeScript is compiled in the first stage, and the final stage installs production dependencies only and runs as the non-root `node` user with a container health check. Locally, `docker compose` uses two networks so the web container cannot reach MongoDB, and only Nginx publishes a port (8080). On AWS the production compose file publishes only port 80 on the host, which the security group allows from the load balancer alone.

Pipeline. On every push to `main`: (1) *test*: backend unit and integration tests against a real MongoDB service container, type-check, front-end tests and build; (2) *build-push*: images are built for linux/amd64 and pushed to ECR tagged with the short commit SHA; (3) *deploy*: the new tag is written to an SSM parameter, a rolling SSM Run Command (one instance at a time, stop on first error) runs the deploy script on each server, and a smoke test calls `/api/health` through the load balancer until it reports the new version. Pull requests run only the test job. If any deploy step fails, a final step restores the previous tag and redeploys it. AWS access uses an OIDC role restricted to this repository's `main` branch; the only secret stored in GitHub is the role's address.

5. Security

- **Segmentation:** security groups chain by reference (internet → ALB group → app group → DB group); the database accepts port 27017 only from the app group; no group opens port 22; no instance has a public IP.
- **Administration:** only SSM Session Manager and Run Command; instance metadata requires IMDSv2 with hop limit 1 so containers cannot read instance credentials.
- **Least-privilege IAM:** separate roles for app servers, the database and the pipeline. *A test found a gap:* the app role could read the database root password because the AWS-managed SSM policy grants broader read access than my inline policy. I fixed it with explicit deny statements (app role denied the DB credentials; DB role denied the JWT secret and URI) and re-tested: the root password read now returns AccessDenied while the app's own secrets still work.
- **Secrets:** generated random values stored as SecureString parameters, read at deploy time into a mode-600 file; never committed (secret scans of the repository were clean).
- **Encryption and images:** EBS volumes and the backup bucket are encrypted; the bucket blocks all public access and denies non-TLS requests; ECR scans on push and tags are immutable.

6. Testing results

Test	Result
Automated tests	Backend: 78 tests (including 8 integration tests against real MongoDB); front end: 108 tests; both run in CI.
Pipeline	Full run green (test, build-push, deploy); `/api/health` reported the new commit as `version`; both targets healthy.
Pull request with a failing test	Check turned red, only the test job ran, nothing deployed.
Automatic rollback	A release whose API container crashed on start failed the rolling deploy; the rollback step restored the previous version. One sampled 502 (about 20 seconds) while the first server was switched; the other server stayed healthy.

Scaling out and in	The initial load test (autocannon, 200 connections, 8 minutes, from a laptop in Pakistan to Sydney) did not raise CPU above about 14%, so it could not trigger scaling. Using the plan's fallback (CPU burn on the app servers through SSM), CPU reached 100% and the group scaled from 2 to 4 instances in about 6 minutes; after the load stopped it scaled back to 2 within about 15 minutes.
Load test numbers	63,000 requests in 481 s (about 116 requests/s average), 55,400 successful, about 7,000 timeouts (11%), median latency 293 ms, p99 7.5 s. These reflect the single-laptop client and the long network path, not the servers' capacity; they should be read as a smoke test, not a benchmark.
Server failure	One app instance terminated: the application kept answering (one 502 in the first seconds), and the group launched a healthy replacement in about 4.5 minutes.
Database reboot	API health returned 503 for about 35 seconds, then recovered by itself; data was intact. This is the known single point of failure.
Backup and restore	A dump was written to S3 and restored into a separate database; document counts matched (1 user, 1 note in each).
Security checks	Private addresses and port 5000 unreachable from the internet; `/.env` returns the web app's index page; API without a token returns 401; no public IPs and no rule for port 22; least-privilege test passed after the fix above.

Evidence. AWS console screenshots (VPC, subnets, route tables, gateways, security groups, instances, load balancer, target group, Auto Scaling group, EBS, ECR, CloudWatch, S3, IAM, Parameter Store, the GitHub Actions runs and the live application) are collected with captions in the separate *Evidence appendix* (docs/Evidence-Appendix.pdf); command-line outputs for every test above are saved in docs/evidence/.

7. Non-functional requirements, justification and limitations

NFR	Supporting decisions	Limitation / improvement
Scalability	Stateless containers with JWT; load-balanced; Auto Scaling 2–4 (demonstrated 2→4→2).	The database scales only vertically; move to a replica set or DocumentDB.
Availability / reliability	Two zones; ELB health checks replace bad instances (tested); Docker restart policy; nightly backups with a tested restore.	One MongoDB instance and one NAT Gateway (one zone) are single points of failure (database outage of about 35 s on reboot); use a 3-node replica set and a NAT per zone.
Elasticity	Target tracking at 50% CPU with automatic scale-in.	Reaction takes minutes; the database is not elastic.
Security	See section 5.	HTTP only because no domain was available; add a domain, an ACM certificate and HTTPS, plus AWS WAF. Web and API share hosts.
Maintainability / deployability	Dockerfiles, compose, Terraform, CI/CD with tests, SHA-tagged images, automatic rollback.	No staging environment; Terraform state is local and must be backed up.
Performance / latency	Nginx gzip and long-lived asset caching; health-checked routing.	Measured median 293 ms from Pakistan to Sydney is mostly network distance; a CDN such as CloudFront and a cache such as Redis would help.
Cost efficiency	Burstable t3 instances, scale-in, free S3 gateway endpoint, log retention of 14 days, S3 lifecycle, teardown when idle.	NAT Gateway is the largest cost; see section 8.
Portability	OCI images run anywhere; compose; configuration through environment variables; MongoDB image is not AWS-specific.	Terraform, SSM and the ALB are AWS-specific; Kubernetes and Helm would improve portability.

Other honest limitations: the stack was built and tested in a single sitting from a student account with one organization-level restriction that temporarily blocked the GitHub OIDC connection until the organization owner lifted it; ECR vulnerability scan results were not captured for the images built locally with attestation manifests (the CI builds disable them); and the load test used one laptop.

8. Cost

Estimated at about **US$127 per month** if always on in Sydney (730 hours, on-demand, 2 app servers): NAT Gateway about US$43, EC2 about US$39, Application Load Balancer about US$24, public IPv4 addresses about US$11, EBS about US$5, other services about US$5 (prices from the AWS Price List API; see `docs/COST-ESTIMATE.md`). Because the environment runs only while building and testing, actual spend is a few US dollars per day. Two optimizations: replacing the NAT Gateway with a small NAT instance saves about US$39 per month (a managed-service trade-off), and moving to Graviton (arm64) instances saves about US$7.6 per month; running only about 8 hours per working day cuts the hourly-billed items by about US$84 per month.